



Technical Service Bulletin

Technical Service Bulletin: tsb101540

Released Date: 08-Dec-2004

Drilled and Non-Drilled Connecting Rods

Drilled and Non-Drilled Connecting Rods

Warranty Statement

The information in this document has no effect on present warranty coverage or repair practices, nor does it authorize TRP or Campaign actions.

Contents

This Service/Parts Topic addresses the difference between the drilled and non-drilled connecting rod applications for the ISX EGR and Non-EGR series engines.

Note : This is a product improvement, not subject to campaign.

This topic includes the following:

- Engine serial number first
- Parts table
- General information
- Repair guidelines.

The engine serial number first for the single piece pistons and drilled connecting rods is 14042852. The build date is October 18, 2002

ISX Drilled Connecting Rod Parts List

Description	Part Number
ISX Drilled Connecting Rod	4059429 NX
ISX Drilled Connecting Rod Bearing Set of 1 Bearing Set	4089405

ISX Non-Drilled Connecting Rod Parts List

Description	Part Number
ISX Non-Drilled Connecting Rod	3681343 NX/RX
ISX Non-Drilled Connecting Rod Bearing Set of 1 Bearing Set	4089139

Parts Supercession		
Description	Old Part Number	New Part Number
ISX Non-Drilled Connecting Rod	3681343 NX/RX	4059429 NX

With the introduction of the single piece (Monotherm) piston, the ISX engine went through several cylinder kit component changes. Engines equipped with single piece pistons require redesigned piston pins, drilled connecting rods, drilled upper rod bearings, and updated ring sets. This piston pin joint **must** be lubricated, which is provided by the drilled connecting rod and matching drilled upper rod bearing. Single piece pistons are lighter than the two piece articulated pistons and are **not** to be mixed within the same engine. However, drilled and non-drilled connecting rods can be mixed within the same engine provided the two piece articulated piston is used. Rod bearings **must** be matched with the connecting rods; drilled connecting rods **must** use drilled rod bearings and non-drilled rods **must** use non-drilled rod bearings.

⚠ CAUTION ⚠

Single piece pistons cannot be mixed with two piece pistons within the same engine. Mixing single piece with two piece pistons within the same engine will cause engine damage.

- Non-drilled and drilled connecting rods can be mixed in the same engine.
- Rod bearings **must** match the connecting rod design.
- Single piece pistons can **not** be mixed with two piece pistons within the same engine.
- Drilled connecting rods **must** be fitted with drilled rod bearings.
- Single piece pistons can **not** be mixed with two piece pistons within the same engine.

Related Procedures

10-001-005 (/qs3/pubsys2/xml/en/procedures/10/10-001-005.html)	Bearings, Connecting Rod (/qs3/pubsys2/xml/en/procedures/10/10-001-005.html)
---	---