

Trainings ▾

Specifications

General Information

Cummins Inc. recommends the use of fully-formulated antifreeze or coolant containing a precharge of supplemental coolant additive (SCA). The antifreeze or coolant **must** meet the specifications outlined in The Maintenance Council (TMC) Recommended Practice (RP) 329 (ethylene glycol) or RP 330 (propylene glycol). The use of fully-formulated antifreeze or coolant significantly simplifies cooling system maintenance.

Copies of TMC specifications can be obtained through Cummins Inc., or by contacting:

The Maintenance Council
American Trucking Association
2200 Mill Road
Alexandria, VA 33314-5388
Phone: (703) 838-1763
Fax (703) 836-6070

Fully-formulated antifreeze contains balanced amounts of antifreeze, SCA, and buffering compounds, but does **not** contain 50 percent water. Fully-formulated coolant contains balanced amounts of antifreeze, SCA, and buffering compounds already premixed 50/50 with deionized water.

The following pages explain water, antifreeze, and SCA's and how to test antifreeze and SCA levels.

This section also contains information on cooling system maintenance and a coolant treatment chart that is used to determine the correct SCA service filter.

Alternative maintenance practices for cooling systems can be found in Cummins Coolant Requirements and Maintenance, Bulletin 3666132.

