

**Engine Set up for Dyno with recommended Cummins® Electronic Service Tool? (Circle one)
Yes / No**

Oil Level (Circle one) Low / High / OK

Fuel Quality (Circle one) OK / Not OK

EGR
Valve
Positi
on (if
equipp
ed)

Turbo
charg
er
Contro
l Valve
Comm
and

Fuel
Rate
(lb/hr)
3

Rail
Fuel
Press
ure
(psi)

Fuel
Temp
eratur
e

Intake
Manif
old Air
Temp
eratur
e

Intake
Manif
old
Press
ure (in
Hg)

**Engine Set up for Dyno with recommended Cummins® Electronic Service Tool? (Circle one)
Yes / No**

Oil Level (Circle one) Low / High / OK

Fuel Quality (Circle one) OK / Not OK

Coolant
Temperature

Coolant
Pressure
(psi)

Engine
Oil
Pressure
(psi)

1. Be sure that the fuel rate is corrected for temperature, see table below.

Fuel Temperature

Correction for Flow Rate

Less than 7°C [45°F]

Flow meter is **not** accurate

7 to 13°C [45 to 55° F]

Subtract 2 percent from flow rate reading

13 to 20°C [55 to 68°F]

Subtract 1 percent from flow rate reading

20 to 29°C [68 to 85°F]

No Correction

29 to 42°C [85 to 108°F]

Add 1 percent to flow rate reading

42 to 56°C [108 to 132°F]

Add 2 percent to flow rate reading

56°C [132°F] above

Flowmeter **not** accurate

Pressure Conversions

1 in H₂O = 0.074 in Hg = 0.036 psi

1 in Hg = 13.600 in H₂O = 0.491 psi

1 psi = 2.036 in Hg = 27.680 in H₂O

This Page Can Be Copied for Your Convenience.

