

Trainings ▾

General Information

Severe operating conditions can reduce the maintenance interval. Regular oil sample testing is recommended to determine the optimal engine maintenance schedule.

For information on lubricating oil analysis, see Fluids for Cummins® Products Service Manual, Bulletin 5411406.

During each oil drain interval, add oil to bring the level up to the H (high) mark on the dipstick if the lubricating oil level is found to L (low) mark on the dipstick.

Use the following steps to determine the maximum lubricating oil drain and filter change intervals.

1. Select appropriate application lubricating oil drain interval table.
2. Determine oil type used.
3. Determine lubricating oil pan capability. Refer to Procedure 018-017 in Section V.
(/qs3/pubsys2/xml/en/procedures/1016/1016-018-017.html)
4. Determine the duty cycle severity. Refer to Procedure 359-013 in Section 3.
(/qs3/pubsys2/xml/en/procedures/1016/1016-359-013.html)
5. Determine the appropriate oil drain and filter change intervals.
6. Determine the lubricating oil filter to be installed on the engine. Refer to Procedure 018-024 in Section V. (/qs3/pubsys2/xml/en/procedures/1016/1016-018-024.html)
7. Perform maintenance at whichever interval occurs first.

Table 1, Tractor Application Lubricating Oil Drain and Filter Change Intervals

Oil Used	Duty Cycle	Kilometers	Hours	Months
Valvoline™ genuine gas engine oil Premium Blue™ 9200ES, 50 Liter Oil Pan	Normal	100,000	1600	12
	Severe	50,000	800	6
	Extreme	20,000	400	3
Cummins® Engineering Standard (CES) 20092, 44 Liter Oil Pan	Normal	60,000	1000	12
	Severe	30,000	500	6
	Extreme	10,000	200	2

Table 2, Dangerous Goods Transport Vehicle Application Lubricating Oil Drain and Filter Change Intervals

Oil Used	Duty Cycle	Kilometers	Hours	Months
CES 20092, 37 Liter Oil Pan	Normal	30,000	500	6
	Severe	15,000	250	3

Do **not** use lubricating oil that is **not** registered with the appropriate CES in a Cummins® engine. Refer to Procedure 018-003 in Section V. (</qs3/pubsys2/xml/en/procedures/1016/1016-018-003.html>)

Lubricating oil drain interval **must** be reduced by 50 percent if the maximum gas sulfur level exceeds 10 ppm.

Last Modified: 19-Nov-2024
