

Trainings ▾

Specifications

Fleetguard® filters are manufactured by Cummins Filtration Inc., which is a subsidiary of Cummins Inc. Fleetguard® filters are developed through joint testing at Cummins Inc. and at Cummins Filtration Inc. Fleetguard® filters are standard on new Cummins® engines. Cummins Inc. recommends their use.

Fleetguard® products meet all Cummins Inc. Source Approval Test standards to provide the quality filtration necessary to achieve the engine's design life. If other brands are substituted, the purchaser **must** insist on products that the supplier has tested to meet Cummins Inc. high-quality standards.

Cummins Inc. can **not** be responsible for problems caused by non-genuine filters that do **not** meet Cummins Inc. performance or durability requirements.

Filter Type	
Lubricating Oil Filter	
Cummins® Part Number	4367100
Fleetguard® Part Number	LF14000NN
Spin-On Suction Fuel Filter	
Cummins® Part Number	3685711
Fleetguard® Part Number	FS19764
Spin-On Pressure Fuel Filter	
Cummins® Part Number	5599456
Fleetguard® Part Number	FF5825NN
Coolant Filter	
Fleetguard® Part Number	WF2126 ¹
	WF2127 ²
Diesel Exhaust Fluid Filter	
Cummins® Part Number	4388378

1. This filter is designed for extended service intervals up to 80,467 km [50,000 mi] when using TMC RP329/RP330 or American Society of Testing and Materials (ASTM) D6210 coolants that meet Cummins® Engineering Standard (CES) 14603. The filter is designed for cooling systems up to 49 liters [13 gal]. Refer to Cummins® Coolant Requirements and Maintenance, Bulletin 3666132 (/qs3/pubsys2/xml/en/bulletin/3666132.html).
2. This filter has been designed for extended service intervals of 80,467 to 241,402 km [50,000 to 150,000 mi]. It has no chemical additives, as it contains zero units of DCA4 and can be

used in the following systems:

- Cooling systems of any capacity
- See maintenance chart below.

When using WF2127 filter, the following volumes of liquid treatment **must** be added at the designated distances/intervals.

Cooling System Capacity	80,467 km [50,000 mi] Service Interval with RP329/330 Coolant or Treated Water (DCA2 or DCA4)	241,402 km [150,000 mi] Service Interval with ES Compleat™ Coolant (ES Extender Liquid)
0 to 57 liters [0 to 15 gal]	0.95 liters [1 qt]	0.95 liters [1 qt]
	10 units	15 units
58 to 114 liters [16 to 30 gal]	1.89 liters [2 qt]	1.89 liters [2 qt]
	20 units	30 units
115 to 170 liters [31 to 45 gal]	2.84 liters [3 qt]	2.84 liters [3 qt]
	30 units	45 units
171 to 227 liters [46 to 60 gal]	3.79 liters [4 qt]	3.79 liters [4 qt]
	40 units	60 units
228 to 284 liters [61 to 75 gal]	4.74 liters [5 qt]	4.74 liters [5 qt]
	50 units	75 units
285 to 341 liters [76 to 90 gal]	5.69 liters [6 qt]	5.69 liters [6 qt]
	60 units	90 units
342 to 397 liters [91 to 105 gal]	6.63 liters [7 qt]	6.63 liters [7 qt]
	70 units	105 units

Note : Filters must meet Cummins Inc. SAM 10,769. Fleetguard® filters meet Cummins Inc. SAM 10,769. The standard filter is Fleetguard® WF2126. For systems larger than 379 liters [100 gal], use 0.94 liters [1 qt] per 57 liters [15 gal]. Consult the vehicle manufacturer for total cooling system capacity information.