

Trainings ▾

Requirements

Utilize Table 1 to determine what Cummins® Engineering Standard (CES) oil your engine requires.

Use the following procedure for a list of the closest American Petroleum Institute (API) and International oil classification. Refer to Procedure 378-003 in Section 4 (</qs3/pubsys2/xml/en/procedures/00/00-378-003.html>).

Table 1: Global CES Oil Recommendation

CES	L10G, QSK19G, K19G, KTA38GC, G19, G38, G50, G28, G855, and G14	B5.9G, B5.9LPG, B Gas Plus, B LPG Plus, B Gas International , B6.7 G, G5.9, ISB5.9 G, B6.7 G, C8.3G, C Gas Plus, G8.3, ISC G, and L Gas Plus	ISL G, L9N, ISB6.7 G, and B6.7N	ISX12 G, ISG12 G, ISX12N and X15N	QSK60G, HSK78G, QSV81G and QSV91G
CES 14615	Not Permitted	Not Permitted	Not Permitted	Not Permitted	For a list of approved oils, see the appropriate engine Operation and Maintenance Manual or contact a Cummins® Authorized Repair Location
CES 20074	Not Permitted	Not Permitted	Not Permitted	Not Permitted	
CES 20076 CES 20077	Not Permitted	Not Permitted	Not Permitted	Not Permitted	
CES 20078	Not Permitted	Not Permitted	Not Permitted	Not Permitted	
CES 20085	Not Permitted	Not Permitted	Not Permitted	Not Permitted	
CES 20092	Recommend ed	Recommend ed	Recommend ed	Recommend ed	

A list of oils that meet the appropriate CES for your engine can be obtained from your local Cummins® distributor or can be found on QuickServe Online at:

https://quickserve.cummins.com/qs3/qsol/service/serviceproducts/oil_registration.html

Re-Refined Oils

New commercially available re-refined or recycled engine oils can be used **only** if the oil brand name and viscosity grade are found on the QuickServe™ oil registration list. Used reclaimed oils or new re-refined/recycled engine oils **not** found on the oil registration lists should **never** be used.

Friction Modifiers

Engine oil that contains friction modifiers should **not** be used unless the oil brand name and viscosity grade are found on the QuickServe™ oil registration list. Friction modifiers can compete with the anti-wear additives in your engine oil to compromise wear performance.

Break-In Oils

Special break-in oils are **not** recommended for use in any Cummins® engine. These oils are **not** designed to meet our wear standards and may negatively affect durability.

Top-Treat or Aftermarket Oil Additives

Cummins® neither approves or disapproves of any additives **not** manufactured or sold by Cummins Inc. or its subsidiaries. Engine malfunction or performance problems which result from the use of such additives are **not** warrantable by Cummins Inc.