

Trainings ▾

General Information

This section includes coolant testing supplies and services offered by Cummins® Filtration.

Coolant Testing

Recommended coolant test methods include:

- **Refractometer** - Provides a more accurate measure of freeze-point than test strips. This level of accuracy is typically **not** required for field measurements.
- **Test Strip** - Provides some indication of freeze protection in addition to additive levels. Less accurate than refractometers. Should **not** be used as a tool for maintaining a supplemental coolant additive (SCA) concentration on the low end of the recommended range. That practice historically results in cylinder liner cavitation pitting.
- **Coolant Analysis Program** - Performed in laboratories and offers additional, useful information, but require mailing coolant samples to a laboratory. Provide guidance in coolant treatment effectiveness, early warning detection, and further treatment actions. **Must not** be used as a method for minimizing treatment. Laboratory measurements typically include the following:
 - pH level
 - SCA level, if applicable
 - Freezing point protection
 - Buffer level
 - Dissolved solids
 - Silicate level
 - Metal corrosion products.

Cummins Inc. recommends using the following Fleetguard® products shown in Table 1 below. Contact Cummins® Filtration Technical Assistance at 800-223-4583 or www.cumminsfiltration.com for additional information.

Table 1 - Fleetguard® Coolant Testing Supplies and Services

Product	Part Number(s)	Glycol/Antifreeze Percent	SCA	Replacement Limits	pH	Chloride	Sulfate	Notes
Refractometer	CC2806	x						Not compatible with glycerin, non-aqueous, or organic acid technology (OAT) coolants
Refractometer	CC8998	x						Not compatible with glycerin, non-aqueous, or OAT coolants
3-Way™ SCA and Freeze Point Test Strips ¹	CC2602 CC2602A CC2602B CC2602M CC2602AM	x	x					Not compatible with OAT coolants

Table 1 - Fleetguard® Coolant Testing Supplies and Services

Product	Part Number(s)	Glycol/Antifreeze Percent	SCA	Replacement Limits	pH	Chloride	Sulfate	Notes
Quick-Chek™ Coolant Quality Test Strips ²	CC2718				x	x	x	Not compatible with red coolants, not compatible with ES Compleat™ OAT and PG platinum
4-Way™ ES Compleat™ OAT Test Strip	CC8997	x	x		x			Only for use with ES Compleat™ OAT
Monitor C Program	CC2700 CC2706	x	x	x	x	x	x	Laboratory analysis program for all Fleetguard® coolants, only available in North America

Table 1 - Fleetguard® Coolant Testing Supplies and Services

Product	Part Number(s)	Glycol/Antifreeze Percent	SCA	Replacement Limits	pH	Chloride	Sulfate	Notes
1. 3-Way™ heavy duty coolant field test kit is appropriate for coolants containing nitrite and/or molybdate for cylinder liner pitting protection. Because the kit measures nitrite and molybdate separately, kit can reliably measure both Fleetguard® SCA formulations as well as most competitive SCA formulations. 2. Quick-Chek™ Coolant Quality Test Strips provide an indication of coolant health, but do not measure all of the parameters required for the coolant replacement check.								

Last Modified: 18-Dec-2017
