

Trainings ▾

Specifications

Holset® SS191 A/C Model

Cylinders 1 Compressor Swept Volume at 1250 rpm 4.0 L per sec. [8.5 cfm] Piston Displacement 191 cc [11.66 C.I.D.] Bore 80 mm [3.15 in] Stroke 38.1 mm [1.5 in] Speed Engine Speed Cooling Air or Engine Coolant Lubrication Engine Lubricating Oil Plumbing Line Sizes: Coolant Inlet and Outlet (pipe fitting) 9.53 mm NPTF [0.375 in NPTF] Air Inlet (inside diameter) 15.875 mm [0.625 in] Air Outlet (minimum inside diameter) 12.7 mm [0.50 in] Height, Overall (approximate) 202.2 cm [7.96 in] Width, Overall (approximate) 124.7 cm [4.91 in] Length, Overall (approximate) 185.9 cm [7.32 in] Weight (approximate) 13.6 kg [30.0 lb]

Holset® QE230 A/C Model

Cylinders 1 Compressor Swept Volume at 1250 rpm 4.86 L per sec. [10.3 cfm] Piston Displacement 230 cc [14.04 C.I.D.] Bore 81.17 mm [3.20 in] Stroke 44.5 mm [1.75 in] Speed Engine Speed Cooling Engine Coolant Lubrication Engine Lubricating Oil Plumbing Line Sizes: Coolant Inlet and Outlet (pipe fitting) 9.53 mm NPTF [0.375-in NPTF] Air Inlet 22.22 mm [0.875 in] Air Outlet 12.7 mm [0.50 in] Height, Overall (approximate) 31.1 cm [12.25 in] Width, Overall (approximate) 14.6 cm [5.75 in] Length, Overall (approximate) 22.9 cm [9.00 in] Weight (approximate) 18 kg [40.0 lb]

Holset® QE230, QE296, and QE338 A/C Model

Cylinders 1 Compressor Swept Volume at 1250 RPM 6.2 L per sec. [13.20 CFM] Piston Displacement 296 cc [18.06 C.I.D.] Bore 92.08 mm [3.625 in] Stroke 44.45 mm [1.750 in] Speed Engine Speed Cooling Engine Coolant Lubrication Engine Lubricating Oil Plumbing Line Sizes: Coolant Inlet and Outlet (Pipe Fitting) 9.53 mm NPTF [0.375 in. NPTF] Air Inlet (Inside Diameter) 22.22 mm [0.875 in.] Air Outlet (Minimum Inside Diameter) 12.7 mm [0.50 in.] Height, Overall (Approximate) 31.1 cm [12.25 in.] Width, Overall (Approximate) 14.6 cm [5.75 in.] Length, Overall (Approximate) 22.9 cm [9.00 in.] Weight (Approximate) 18 kg [40.0 lbs.]

Holset® SS338/QE338 A/C Models

Cylinders 1 Compressor Swept Volume at 1250 RPM 7.1 L per sec. [15.0 CFM] Piston Displacement 338 cc [20.63 C.I.D.] Bore 98.40 mm [3.75 in] Stroke 44.45 mm [1.75 in] Speed Engine Speed Cooling Engine Coolant Lubrication Engine Lubricating Oil Plumbing Line Sizes: Coolant Inlet and Outlet (Pipe Fitting) 12.70 mm NPTF [0.50 in. NPTF] Air Inlet (Inside Diameter) 22.22 mm [0.875 in.] Air Outlet (Minimum Inside Diameter) 12.7 mm [0.50 in.] Height, Overall (Approximate) 31.1 cm [12.25 in.] Width, Overall (Approximate) 14.6 cm [5.75 in.] Length, Overall (Approximate) 22.9 cm [9.00 in.] Weight (Approximate) 18 kg [40.0 lbs.]

Holset® ST676 A/C Model

Cylinders 2 Compressor Swept Volume at 1250 RPM 14.2 L per sec. [30.00 CFM] Piston Displacement 676 cc [41.3 C.I.D.] Bore 92.08 mm [3.625 in] Stroke 50.8 mm [2.00 in] Speed Engine Speed Cooling Engine Coolant Lubrication Engine Lubricating Oil Plumbing Line Sizes: Coolant Inlet and Outlet (Pipe Fitting) 12.70 mm NPTF [0.50 in. NPTF] Air Inlet (Inside Diameter) 22.22 mm [0.875 in.] Air Outlet (Minimum Inside Diameter) 15.88 mm [0.625 in.] Height, Overall (Approximate) 34.3 cm [13.50 in.] Width, Overall (Approximate) 17.8 cm [7.00 in.] Length, Overall (Approximate) 28.7 cm [11.30 in.] Weight (Approximate) 33.5 kg [74.50 lbs.]

Holset® ST773 A/C Model

Cylinders 2 Compressor Swept Volume at 1250 RPM 16.0 L per sec. [34.00 CFM] Piston Displacement 773 cc [47.2 C.I.D.] Bore 92.14 mm [3.875 in] Stroke 50.8 mm [2.00 in] Speed Engine Speed Cooling Engine Coolant Lubrication Engine Lubricating Oil Plumbing Line Sizes: Coolant Inlet and Outlet (Pipe Fitting) 12.70 mm NPTF [0.50 in. NPTF] Air Inlet (Inside Diameter) 22.22 mm [0.875 in.] Air Outlet (Minimum Inside Diameter) 15.88 mm [0.625 in.] Height, Overall (Approximate) 24.3 cm [9.19 in.] Width, Overall (Approximate) 27.7 cm [10.9 in.] Length, Overall (Approximate) 28.7 cm [11.30 in.] Weight (Approximate) 36.3 kg [80.0 lbs.]

In applications where duty cycles average 10 percent or more, or air pressures are above 862 kPa [125 psi], use a discharge line with a minimum inside diameter of 19 mm [0.75 in] to prevent carbon buildup. Examples of these applications are as follows:

- Refuse trucks
- Pickup trucks
- Delivery trucks
- Transit buses
- Equipment with high accessory air usage.

Compressor Spring Force Specifications

	Load Required to Compress Spring to Measurement Length						
Spring Part Number	Type of Spring Use	Approximate Free Length mm [in]	Number of Coils	Wire Diameter mm [in]	Measurement Length mm [in]	Minimum kg [lb]	Maximum kg [lb]
128080	Exhaust Valve	17.02 [0.670]	3.0	2.03 [0.080]	7.11 [0.280]	3.6 [8.55]	4.7 [10.35]

190334	Intake Valve	12.70 [0.500]	2.8	1.58 [0.062]	7.11 [0.280]	0.35 [0.65]	0.5 [1.10]
150631	Unloading Valve (naturally aspirated) center unloading valve - twin	41.91 [1.650]	11.5	2.03 0.080	24.89 [0.980]	14.5 [32.00]	17.2 [38.00]
3023101	Unloading Valve (all turbocharged engines)	41.91 [1.650]	10.8	1.65 [0.065]	24.89 [0.980]	5.9 [13.00]	7.7 [17.00]
3049553	E-Type Unloader Valve	41.91 [1.650]	11.25	1.93 [0.076]	24.89 [0.980]	10.4 [23.00]	12.2 [27.00]
800399-XW	Unloader	17.02 [0.67]	6	1.04 [0.041]	6.60 [0.260]	N/A	2.54 [5.60]
					10.03 [3.95]	1.71 [3.78]	N/A
802000-FZ	Intake and Exhaust	10.16 [0.40]	4.25	0.79 [0.031]	4.57 [0.18]	N/A	0.36 [0.80]
					5.99 [0.275]	0.20 [0.45]	N/A
3054489	Exhaust Valve	21.49 [0.846]	4.5	2.54 [0.100]	15.21 [0.599]	3.88 [8.55]	4.74 [10.45]

Holset® QE230, QE296, and QE338 A/C Model

Crank shaft Dimensions									
Crank shaft Part Number	Rear Coupling Journal (A)			Connecting Rod Journal (B)	Front Support Journal (C)				
	mm		[in]	mm		[in]	mm		[in]

Crank shaft Dimensions									
Crank shaft Part Number	Rear Coupling Journal (A)			Connecting Rod Journal (B)	Front Support Journal (C)				
3000167	47.52	MIN	1.871	49.10	MIN	1.933	47.52	MIN	1.871
	47.57	MAX	1.873	48.16	MAX	1.936	47.57	MAX	1.873
3050368	47.52	MIN	1.871	49.10	MIN	1.933	47.52	MIN	1.871
	47.57	MAX	1.873	48.16	MAX	1.936	47.57	MAX	1.873

Holset® SS296/SS296E/QE296 A/C Models

Cranks haft Dimensions								
Cranks haft Part Number	Front Support Journal (C)		Connec ting Rod Journal (B)	Engine Gear Case Journal (D)	Rear Couplin g Journal (A)			
	MIN mm [in]	MAX mm [in]	MIN mm [in]	MAX mm [in]	MIN mm [in]	MAX mm [in]	MIN mm [in]	MAX mm [in]
163502	47.52 [1.871]	47.57 [1.873]	49.10 [1.933]	49.162 [1.936]	38.06 [1.499]	38.11 [1.501]	47.52 [1.871]	47.57 [1.873]
163120	47.52 [1.871]	47.57 [1.873]	49.10 [1.933]	49.162 [1.936]	31.70 [1.248]	31.78 [1.251]	N/A	N/A
163230	47.52 [1.871]	47.57 [1.873]	49.10 [1.933]	49.162 [1.936]	31.70 [1.248]	31.78 [1.251]	N/A	N/A
160130	47.52 [1.871]	47.57 [1.873]	49.10 [1.933]	49.162 [1.936]	32.03 [1.261]	32.06 [1.262]	N/A	N/A
156090	47.52 [1.871]	47.57 [1.873]	49.10 [1.933]	49.162 [1.936]	39.65 [1.561]	39.68 [1.562]	N/A	N/A
163844	47.52 [1.871]	47.57 [1.873]	49.10 [1.933]	49.162 [1.936]	39.65 [1.561]	39.68 [1.562]	N/A	N/A

Cranks haft Dimens ions								
Cranks haft Part Numbe r	Front Support Journal (C)		Connec ting Rod Journal (B)	Engine Gear Case Journal (D)	Rear Couplin g Journal (A)			
158360	47.52 [1.871]	47.57 [1.873]	49.10 [1.933]	49.162 [1.936]	39.65 [1.561]	39.68 [1.562]	N/A	N/A
156110	47.52 [1.871]	47.57 [1.873]	49.10 [1.933]	49.162 [1.936]	33.288 [1.311]	33.33 [1.312]	N/A	N/A
160380	47.52 [1.871]	47.57 [1.873]	49.10 [1.933]	49.162 [1.936]	31.65 [1.246]	31.70 [1.248]	47.52 [1.871]	47.57 [1.873]
163843	47.52 [1.871]	47.57 [1.873]	49.10 [1.933]	49.162 [1.936]	N/A	N/A	N/A	N/A
179290	47.52 [1.871]	47.57 [1.873]	49.10 [1.933]	49.162 [1.936]	38.06 [1.499]	38.11 [1.501]	47.52 [1.871]	47.57 [1.873]
176030	47.52 [1.871]	47.57 [1.873]	49.10 [1.933]	49.162 [1.936]	38.06 [1.499]	38.11 [1.501]	47.52 [1.871]	47.57 [1.873]
176040	47.52 [1.871]	47.57 [1.873]	49.10 [1.933]	49.162 [1.936]	31.70 [1.248]	31.78 [1.251]	N/A	N/A
176050	47.52 [1.871]	47.57 [1.873]	49.10 [1.933]	49.162 [1.936]	31.70 [1.248]	31.78 [1.251]	N/A	N/A
176060	47.52 [1.871]	47.57 [1.873]	49.10 [1.933]	49.162 [1.936]	39.65 [1.561]	39.68 [1.562]	N/A	N/A
176070	47.52 [1.871]	47.57 [1.873]	49.10 [1.933]	49.162 [1.936]	N/A	N/A	N/A	N/A
176080	47.52 [1.871]	47.57 [1.873]	49.10 [1.933]	49.162 [1.936]	39.65 [1.561]	39.68 [1.562]	N/A	N/A
176090	47.52 [1.871]	47.57 [1.873]	49.10 [1.933]	49.162 [1.936]	39.65 [1.561]	39.68 [1.562]	N/A	N/A
176100	47.52 [1.871]	47.57 [1.873]	49.10 [1.933]	49.162 [1.936]	32.03 [1.261]	32.06 [1.262]	N/A	N/A
176110	47.52 [1.871]	47.57 [1.873]	49.10 [1.933]	49.162 [1.936]	N/A	N/A	N/A	N/A
180300	47.52 [1.871]	47.57 [1.873]	49.10 [1.933]	49.162 [1.936]	38.06 [1.499]	38.11 [1.501]	47.52 [1.871]	47.57 [1.873]
190960	47.52 [1.871]	47.57 [1.873]	49.10 [1.933]	49.162 [1.936]	31.71 [1.249]	31.75 [1.250]	N/A	N/A

Cranks haft Dimens ions								
Cranks haft Part Numbe r	Front Support Journal (C)		Connec ting Rod Journal (B)	Engine Gear Case Journal (D)	Rear Couplin g Journal (A)			
215780	47.52 [1.871]	47.57 [1.873]	49.10 [1.933]	49.162 [1.936]	N/A	N/A	47.52 [1.871]	47.57 [1.873]
215790	47.52 [1.871]	47.57 [1.873]	49.10 [1.933]	49.162 [1.936]	N/A	N/A	47.52 [1.871]	47.57 [1.873]
218597	47.52 [1.871]	47.57 [1.873]	49.10 [1.933]	49.162 [1.936]	31.71 [1.249]	31.75 [1.250]	47.52 [1.871]	47.57 [1.873]
202780	47.52 [1.871]	47.57 [1.873]	49.10 [1.933]	49.162 [1.936]	N/A	N/A	47.52 [1.871]	47.57 [1.873]
300016 7	47.52 [1.871]	47.57 [1.873]	49.10 [1.933]	49.162 [1.936]	N/A	N/A	47.52 [1.871]	47.57 [1.873]
301366 6	47.52 [1.871]	47.57 [1.873]	49.10 [1.933]	49.162 [1.936]	N/A	N/A	47.52 [1.871]	47.57 [1.873]
303113 4	47.52 [1.871]	47.57 [1.873]	49.10 [1.933]	49.162 [1.936]	N/A	N/A	47.52 [1.871]	47.57 [1.873]
303113 5	47.52 [1.871]	47.57 [1.873]	49.10 [1.933]	49.162 [1.936]	N/A	N/A	47.52 [1.871]	47.57 [1.873]

Holset® SS338/QE338 A/C Models

Support Dimensions - Distance Between Thrust Faces				
	MIN		MAX	
Support Part Number	mm	[in]	mm	[in]
3005152	32.893	1.295	33.274	1.310
3005153	32.893	1.295	33.147	1.305
3050367	32.893	1.295	33.147	1.305

Holset® SS296/SS296E/QE296 A/C Models

Support Dimensions - Distance Between Thrust Faces				
	MIN		MAX	
Support Part Number	mm	[in]	mm	[in]
152105	42.52	1.674	43.08	1.696
156088	60.55	2.384	61.11	2.406
156097	127.86	5.034	128.42	5.056
159208	147.22	5.796	147.78	5.818
160111	147.22	5.796	147.78	5.818
160113	120.47	4.743	121.03	4.765
163032	34.87	1.373	35.59	1.401
163503	42.52	1.676	43.08	1.696
163832	147.22	5.796	147.78	5.818
163836	127.86	5.034	128.42	5.056
163838	147.22	5.796	147.78	5.818
163840	67.95	2.675	68.50	2.697
167994	42.52	1.674	43.08	1.696
169836	42.52	1.674	43.08	1.696
176026	42.52	1.674	43.08	1.696
176029	42.52	1.674	43.08	1.696
176037	147.22	5.796	147.78	5.818
176045	120.22	4.733	120.78	4.755
176046	120.22	4.733	120.78	4.755
176048	139.57	5.495	140.14	5.517
176049	139.57	5.495	140.14	5.517
176054	58.24	2.293	58.80	2.315
176057	115.14	4.533	115.70	4.555
176058	62.61	2.465	63.18	2.487
176064	42.52	1.674	43.08	1.696
186256	42.52	1.674	43.08	1.696
188039	137.49	5.413	138.05	5.435
188956	118.05	4.648	118.62	4.670
193836	137.49	5.413	138.05	4.435
199337	30.40	1.197	30.99	1.220

Support Dimensions - Distance Between Thrust Faces				
	MIN		MAX	
202273	42.52	1.674	43.08	1.696
215761	40.13	1.580	40.69	1.602
218598	42.52	1.674	43.08	1.696
3005152	32.69	1.287	33.27	1.310
3005153	32.69	1.287	33.27	1.310
650183	42.52	1.674	43.08	1.696

Holset® SS338/QE338 A/C Models

Support Dimensions - Crankshaft End Clearance				
	MIN		MAX	
Support Part Number	mm	[in]	mm	[in]
3005152	0.05	0.002	0.38	0.015
3005153	0.05	0.002	0.38	0.015
3050367	0.10	0.004	0.38	0.015

Holset® SS296/SS296E/QE296 A/C Models

Support Dimensions - Crankshaft End Clearance				
	MIN		MAX	
Support Part Number	mm	[in]	mm	[in]
152105	0.15	0.006	0.76	0.030
156088	0.18	0.007	0.79	0.031
156097	0.20	0.008	0.81	0.032
159208	0.25	0.010	0.86	0.034
160111	0.25	0.010	0.86	0.034

Support Dimensions - Crankshaft End Clearance				
	MIN		MAX	
160113	0.23	0.009	0.84	0.033
163032	0.15	0.006	0.76	0.030
163503	0.15	0.006	0.76	0.030
163832	0.25	0.010	0.86	0.034
163836	0.20	0.008	0.81	0.032
163838	0.25	0.010	0.86	0.034
163840	0.18	0.007	0.84	0.033
167994	0.15	0.006	0.76	0.030
169836	0.15	0.006	0.76	0.030
176026	0.15	0.006	0.76	0.030
176029	0.15	0.006	0.76	0.030
176037	0.25	0.010	0.86	0.034
176045	0.20	0.008	0.81	0.032
176046	0.20	0.008	0.81	0.032
176048	0.25	0.010	0.86	0.034
176049	0.25	0.010	0.86	0.034
176054	0.18	0.007	0.79	0.031
176057	0.23	0.009	0.84	0.033
176058	0.18	0.007	0.84	0.033
176064	0.15	0.006	0.76	0.030
186256	0.15	0.006	0.76	0.030
188039	0.05	0.002	0.61	0.024
188956	0.05	0.002	0.61	0.024
193836	0.05	0.002	0.61	0.024
199337	0.05	0.002	0.69	0.027
202273	0.15	0.006	0.76	0.030
215761	0.15	0.006	0.76	0.030
218598	0.15	0.006	0.76	0.030
3005152	0.05	0.002	0.69	0.027
3005153	0.05	0.002	0.69	0.027
650183	0.15	0.006	0.76	0.030

