

Trainings ▾

Specifications

⚠ CAUTION ⚠

Under NO circumstances must a customer exceed one oil change interval before adding chemicals (by filter or liquid) to the coolant. If the recommended service intervals are neglected, there is a high probability that cylinder liner corrosion will occur.

Cummins Filtration®/Fleetguard® filters are developed through joint testing at Cummins Inc. and Cummins Filtration®. Cummins Filtration®/Fleetguard® filters are standard on new Cummins® engines. Cummins Inc. recommends their use.

Cummins Filtration®/Fleetguard® products meet all Cummins Inc. Source Approval Test standards to provide the quality filtration necessary to achieve the engine's design life. If other brands are substituted, the purchaser **must** insist on products that the supplier has tested to meet Cummins Inc. high quality standards.

Cummins Inc. can **not** be responsible for problems caused by non-genuine filters that do **not** meet Cummins Inc. performance or durability requirements.

Note : Filters must meet Cummins Inc. Source Approval Method 10,769. Cummins Filtration®/Fleetguard® filters meet Cummins Inc. Source Approval Method 10,769.

Filter Type		
Lubricating Oil Filter		
Cummins® Part Number	3313279 (Full Flow), 3313283 (Bypass), and 3318853 (Combination)	
Cummins Filtration®/Fleetguard® Part Number	LF 670 (Full Flow), LF777 (Bypass) and LF3000 (Combination)	
Fuel-Water Separator		
Cummins® Part Number	3308638	
Cummins Filtration®/Fleetguard® Part Number	FS1212	
Coolant Filter - Standard Service		
Cummins® Part Number	Cummins Filtration®/Fleetguard® Part Number	DCA4 SCA Units*

Filter Type		
3100303	WF2070	2
3100304	WF2071	4
3100305	WF2072	6
4058964	WF2073	8
3100307	WF2074	12
3100308	WF2075	15
4058965	WF2076	23
3827423	WF2077	None
* See the maintenance charts below.		

Coolant Capacity Charts					
Precharge					
1.2 Units of DCA4 per Gallon of Coolant					
Gallons of Coolant		DCA4 Liquid Gallons	DCA4 Units		DCA4 Units per Gallon
5 - 7		2 pints	10		1.4 - 2.0
8 - 10		3 pints	15		1.3 - 1.9
11 - 15		4 pints	20		1.3 - 1.8
16 - 20		5 pints	25		1.2 - 1.6
21 - 30		1.00	40		1.3 - 1.9
31 - 50		1.50	60		1.2 - 1.9
51 - 75		2.25	90		1.2 - 1.8
76 - 100		3.00	120		1.2 - 1.6
101 - 150		4.50	180		1.2 - 1.8
151 - 200		6.00	240		1.2 - 1.6
201 - 250		7.50	300		1.2 - 1.5
251 - 300		9.00	360		1.2 - 1.4
301 - 350		10.50	420		1.2 - 1.4
351 - 400		12.00	480		1.2 - 1.4
Service					
Miles	Hours	Install a Service Filter with DCA4 Units Shown Below			
5,000	125		2	2	2
10,000	250	2	2	4	4
15,000	375	2	4	4	6
20,000	500	2	4	6	8
25,000	645	2	4	8	12
		5 - 7	8 - 10	11 - 15	16 - 20

Service		
Miles	Hours	Install a Service Filter with DCA4 Units Shown Below
		System Size in Gallons
Service		
Gallons of Coolant	Add DCA4	
	250 Hours	500 Hours
21 - 30	2	3
31 - 50	3	5
51 - 75	4	8
76 - 100	5	10
101 - 150	8	15
151 - 200	10	20
201 - 250	13	25
251 - 300	15	30
301 - 350	18	35
351 - 400	20	40
8 pints equals 1 gallon		
A. Consult the vehicle equipment manufacturer's maintenance information for total cooling system capacity. B. After draining and replacing the coolant, always pre-charge the cooling system to an SCA level of 1.5 units per gallon. This concentration level must never be allowed to fall below 1.2 units and must be controlled when the level is greater than 3 units. Action needed when the level falls below 1.2: a filter and liquid; above 1.2 to 3.0: filter only; above 3.0: test and add filter when 3.0 and below. Note : When performing service which requires draining the cooling system, take special precautions to collect it in a clean container, seal it to prevent contamination, and save for reuse. C. Change the coolant filters at each oil change to protect the cooling system. The service filter listed above is satisfactory for use with maintenance intervals from 16,000 to 24,000 km [10,000 to 15,000 mi] or 250 to 600 hours.		