

Trainings ▾

Specifications

The following specifications are for a upright two-cylinder air compressor (Holset® ST676 Air Compressor Model)

CylindersCompressor Capacity (at 1250 rpm)Piston DisplacementBoreStrokeSpeedCoolingLubrication	2 14.2 liter [30.00 cfm] per second 676 cc [41.3 C.I.D.] 92.08 mm [3.625 in] 50.8 mm [2 in] Engine speed Engine coolant Engine lubricating oil
--	--

Plumbing Line Sizes:

Coolant Inlet and Outlet (pipe fitting) 12.7 mm NPTF [0.50 in NPTF]Air Inlet (inside diameter) 22.22 mm [0.875 in]Air Outlet (minimum inside diameter) 15.88 mm [0.625 in]

Height, Overall (approximate)Width, Overall (approximate)Length, Overall (approximate)Weight (approximate)	34.3 cm [13.5 in] 17.8 cm [7 in] 28.7 cm [11.30 in] 33.5 kg [74.5 lb]
--	---

Note : In applications where duty cycles average 10 percent or more or air pressures are above 862 kPa [125 psi], use a discharge line with a minimum inside diameter of 15.9 mm [0.625 in] for single-cylinder compressors and 25.4 mm [1 in] for twin-cylinder compressors to prevent carbon buildup. Examples of these applications are as follows:

- Refuse trucks
- Pickup and delivery trucks
- Transit buses
- Equipment with high accessory air usage.

The following specifications are for a upright single-cylinder air compressor (Holset® HD850 Air Compressor Models)

CylindersCompressor Capacity (at 1250 rpm)Piston DisplacementBoreStrokeSpeedCoolingLubrication	1 7.1 liter [15.00 cfm] per second 338 cc [20.63 C.I.D.] 98.4 mm [3.875 in] 44.5 mm [1.75 in] Engine speed Engine coolant Engine lubricating oil
--	--

Plumbing Line Sizes:

Coolant Inlet and Outlet (pipe fitting) 9.53 mm NPTF [0.375 in NPTF]Air Inlet (inside diameter) 22.22 mm [0.875 in]Air Outlet (minimum inside diameter) 15.88 mm [0.625 in]

Height, Overall (approximate) Width, Overall (approximate) Length, Overall (approximate) Weight (approximate)	31.1 cm [12.25 in] 14.6 cm [5.75 in] 22.9 cm [9 in] 18 kg [40 lb]
--	---

Last Modified: 16-May-2007
