



Technical Service Bulletin

Technical Service Bulletin: tsb101611

Released Date: 07-Mar-2005

Cylinder Head Procedure Revision

Cylinder Head Procedure Revision

Warranty Statement

The information in this document has no effect on present warranty coverage or repair practices, nor does it authorize TRP or Campaign actions.

Contents

This Service/Parts Topic introduces a new Protective Plug Kit for all ISX Series engines. The plugs are to be used any time a lubrication port or drilling is exposed during a repair.

If a repair exposes a filtered oil passage, it is very important to seal the oil passage drillings with the recommended plugs. Failure to insert the oil passage plugs can result in main bearing and connecting rod bearing failures. The use of power tools combined with abrasive disc pads to clean gasket surfaces can also introduce abrasive pad residue into oil passage areas. Therefore, it is **not** recommended to use power tools when cleaning gasket surfaces that have intersecting oil passages. Clean the gasket sealing surfaces by hand, with a gasket scraper or cleaning pad, Part Number 3823258. If the residual gasket material can **not** be felt with a finger, the surface is ready to accept a new gasket.

The Protective Plug Kit part numbers and descriptions are shown in the table below.

Table 1, Protective Plug Kit Content

Kit Part Number 4918319

Part Number	Quantity	Part Description	Color
4918320	1	Front block oil passage rubber plug	Black
4918321	1	Rear block oil passage rubber plug	Black
4918322	1	Oil pump to oil cooler passage rubber plug (block side)	Black
4918323	1	Oil cooler housing oil passage rubber plug	White
4918340	1	Oil cooler oil passage rubber plug (block side)	Blue

Table 1, Protective Plug Kit Content			
Kit Part Number 4918319			
Part Number	Quantity	Part Description	Color
4089255	8	Block head deck and head oil passage rubber plugs	White

Related Procedures

10-002-004-topic (/qs3/pubsys2/xml/en/procedures/10/10-002-004-topic.html)	Cylinder Head (/qs3/pubsys2/xml/en/procedures/10/10-002-004-topic.html)
---	--