

Trainings ▾

Specifications

For performance and fuel rate values, refer to the Engine Data Sheet or the fuel pump code for the particular rating involved.

Engine Idle Speed	700 ± 25 rpm
-------------------	--------------

Fuel Inlet Maximum Restriction:

Clean Fuel Filter 100 mm Hg [4.0 in Hg] Dirty Fuel Filter 229 mm Hg [9.0 in Hg]

Fuel Drain Line Restriction:

With Check Valves 0 to 21 kPa [0 to 3 psi] With Check Valves Removed 14 to 34 kPa [2 to 5 psi]

Fuel Check Valve Between Fuel Pump and Cylinder Head (integral to fuel pump):

Opening Pressure 21 to 35 kPa [3 to 5 psi]

Engine Minimum Cranking Speed	130 rpm
-------------------------------	---------

Fuel Check Valve in Fuel Drain Line:

Opening Pressure 13 to 25 mm Hg [1/4 to 1/2 psi]

Derate Engine Fuel Rate for High Altitude Derate Engine Fuel Rate for Hot Weather Shutoff Valve Solenoid Coil Resistance in ohms 24 VDC Fuel Pump Cranking Pressure - Minimum	4 percent per 300 m [1000 ft] above 3600 m [12,000 ft] 2 percent per 11°C above 38°C [1 percent per 10°F above 100°F] 28 to 32 ohms 172 kPa [25 psi] @ 150 rpm
--	---

Fuel Pump Pressure - Minimum (on engine measurement):

1500 rpm 1779 kPa [258 psi] 1800 rpm 2117 kPa [307 psi] 2100 rpm 2344 kPa [340 psi]

Fuel Filter Specifications:

Efficiency 98.7 percent at 10 microns/96.0 percent at 8 microns/86.0 percent at 5 microns
Water Removal Free = 95 percent/Emulsified = 95 percent

