

Trainings ▾

Specifications

Oil Pressure (with 15W-40 oil at 107°C [225°F]):

At Idle (minimum allowable)	70 kPa [10 psi]
-----------------------------	-----------------

At Rated Speed (minimum allowable)	210 kPa [30 psi]
------------------------------------	------------------

Oil Temperature:

Maximum	120°C [250°F]
---------	---------------

Oil Filter Capacity:

Combination Filter (two LF9325 Fleetguard®)	5.3 liters [1.4 gal]
---	----------------------

Oil Sump Capacity:

Total lubricating oil system capacity can be determined by adding the high level of the oil in the oil pan, to the capacity of the two combination oil filters. See chart below.

Rated Sump Capacity	Application	Make	Sump Capacity at Low Level Mark on Dipstick in Liters [U.S. gal]	Sump Capacity at High Level Mark on Dipstick in Liters [U.S. gal]	Total System Capacity (Sump and Two Combo Oil Filters)
135 Liters [35.7 U.S. gal]	PG	Cast (Aluminum)	67 Liters [17.8 U.S. gal]	95 Liters [25 U.S. gal]	100 Liters [26.4 U.S. gal]
135 Liters [35.7 U.S. gal]	IND	Cast (Aluminum)	100 Liters [26.4 U.S. gal]	135 Liters [35.7 U.S. gal]	140 Liters [37 U.S. gal]
95 Liters [25 U.S. gal]	IND	FAB (Steel)	75 Liters [19.8 U.S. gal]	95 Liters [25 U.S. gal]	100 Liters [26.4 U.S. gal]
70 Liters [18.5 U.S. gal]	IND	FAB (Steel)	54 Liters [14.3 U.S. gal]	70 Liters [18.5 U.S. gal]	75 Liters [19.8 U.S. gal]

Rated Sump Capacity	Application	Make	Sump Capacity at Low Level Mark on Dipstick in Liters [U.S. gal]	Sump Capacity at High Level Mark on Dipstick in Liters [U.S. gal]	Total System Capacity (Sump and Two Combo Oil Filters)
52 Liters [13.7 U.S. gal]	IND	FAB (Steel)	38 Liters [10 U.S. gal]	52 Liters [13.7 U.S. gal]	57 Liters [15.1 U.S. gal]

Last Modified: 13-Aug-2020
