



Technical Service Bulletin

Technical Service Bulletin: tsb101579

Released Date: 07-Jan-2005

Plunger Lift Timing Procedure and Tool Addition

Plunger Lift Timing Procedure and Tool Addition

Warranty Statement

The information in this document has no effect on present warranty coverage or repair practices, nor does it authorize TRP or Campaign actions.

Contents

This Service/Parts Topic revises Procedure 005-013, Fuel Injection Pump, In-Line, Spill Port Timing.

Note : This is a product improvement and not subject to campaign.

The following is a part number list of Bosch® P7100 fuel injection pumps that use delivery valve gaskets. Pumps used in ratings developed after these will use delivery valves without gaskets. If the fuel injection pump was developed in North America and is **not** on this list, it will be without delivery valve gaskets. For assistance in identifying the fuel injection pump delivery valve type contact a Cummins® Authorized Repair Facility.

Injection Pump Part Number	
3913340	3921922
3916626	3922424
3916627	3921923
3916628	3921925
3916629	3921970
3917088	3922425
3917089	3922426
3918321	3922427
3919090	3922446
3921769	3922449
3921770	3922471
3921771	3924903
3921772	3925085
3921773	3925086

Injection Pump Part Number	
3921774	3926603
3921775	3927923
3921776	3927924
3921777	3928169
3921918	3928412
3921920	3928606

The following table supplies the lift specifications for the Bosch® P7100 fuel injection pumps **only**. The allowable tolerance range for timing is ± 0.1 mm [0.004 inch].

	CPLs	CPLs	CPLs	CPLs	CPLs	CPLs
Static Injection Timing (from engine dataplate, degrees BTDC)	987, 1126, 1262, 1263, 1406, 1422, 1582, 1618, 1850, 2118, 2196	1549, 1550, 1551, 1552, 1553, 1815, 1816, 1839, 1914, 1915, 1916, 1959	1863, 1968, 2022, 2174, 2265, 2268, 2308	2023, 2175	563, 1566, 1569, 1658, 1812, 1905, 1917, 1918, 1920, 1922, 1923, 1949, 1950, 1972, 2034, 2101, 2103, 2104, 2106, 2107, 2108, 2150	1564, 1919, 2011, 2102, 2105, 2158, 2169, 2191
	Lift Specificati on	Lift Specificati on	Lift Specificati on	Lift Specificati on	Lift Specificati on	Lift Specificati on
9.5	6.05 mm	5.15 mm	N/A	N/A	5.65 mm	5.6 mm
10	6.15 mm	5.25 mm	N/A	N/A	5.75 mm	5.7 mm
10.5	6.25 mm	5.35 mm	N/A	N/A	5.85 mm	5.8 mm
11	6.35 mm	5.45 mm	4.0 mm	N/A	5.95 mm	5.9 mm
11.5	6.4 mm	5.55 mm	4.05 mm	4.7 mm	6.05 mm	6 mm
12	6.5 mm	5.65 mm	4.15 mm	4.8 mm	6.15 mm	6.05 mm

12.5	6.6 mm	5.7 mm	4.2 mm	4.9 mm	6.25 mm	6.15 mm
13	6.7 mm	5.8 mm	4.3 mm	5 mm	6.35 mm	6.25 mm
13.5	6.8 mm	5.9 mm	4.4 mm	5.1 mm	6.45 mm	6.35 mm
14	N/A	6.0 mm	4.5 mm	5.2 mm	N/A	N/A
14.5	N/A	6.1 mm	4.6 mm	5.3 mm	N/A	N/A
15	N/A	N/A	4.7 mm	5.4 mm	N/A	N/A

The following table supplies the lift specifications for the Marine Midrange engines. The nominal value for control parts list (CPL) 1975 is 22 degrees and CPL 2172 and 2208 is 24 degrees. The allowable tolerance range for timing remains at ± 0.1 mm [0.004 inch].

	Control Parts List (CPL)	
Static Injection	Marine B Series	Marine C Series
Lift Value BTDC	CPLs 1975, 2208	CPL 2172
20.0	7.90 mm	7.29 mm
20.5	8.02 mm	7.40 mm
21.0	8.14 mm	7.52 mm
21.5	8.26 mm	7.63 mm
22.0	8.38 mm	7.75 mm
22.5	8.51 mm	7.87 mm
23.0	8.63 mm	7.98 mm
23.5	8.75 mm	8.10 mm
24.0	8.88 mm	8.22 mm
24.5	9.01 mm	8.34 mm
25.0	9.13 mm	8.47 mm
25.5	9.26 mm	8.59 mm
26.0	9.39 mm	8.71 mm

Related Procedures

41-005-013-topic (/qs3/pubsys2/xml/en/procedures/41/41-005-013-topic.html)	Fuel Injection Pump, In-Line, Spill Port Timing (/qs3/pubsys2/xml/en/procedures/41/41-005-013-topic.html)
---	--

