



Technical Service Bulletin

Technical Service Bulletin: TSB104262

Released Date: 15-Dec-2010

New Oil and Boost Pressure Sensors

New Oil and Boost Pressure Sensors

Warranty Statement

The information in this document has no effect on present warranty coverage or repair practices, nor does it authorize TRP or Campaign actions.

Contents

This service parts topic introduces the internal improvements of the oil and boost pressure sensors, designed to improve the prevention of water intrusion and increase the internal robustness of the sensor.

The new oil and boost pressure sensors can be identified by the 1-1/4 hex, 6-point and brass housing. The current pressure sensors use a 1-1/4 hex, round corner and carbon steel housing. The date code identifying these new parts will be J97 (October, 1997).

The changes went into production engines beginning:

Sensor	Engine	Engine Serial Number	Build Date
Oil Pressure	M11, ISM, QSM11	34876832	September 4, 1997
Oil Pressure	N14	11863064	September 26, 1997
Oil Pressure	K6, K19, QSK19	37178720	October 14, 1997
Boost Pressure	M11, ISM, QSM11	34877105	September 8, 1997
Boost Pressure	N14	11863179	September 29, 1997
Boost Pressure	QSK19	37178706	October 13, 1997

The current part numbers for the sensors will not change. Pressure sensors for production and service that are affected by this change are:

Part Number	Application
3080405	1991 Celect™ Boost Pressure
3084521	1994 Celect™, Celect™ Plus, AEM Boost Pressure
3085244	Quantum Boost Pressure (higher accuracy)
3080406	Celect™, Celect™ Plus, Quantum Oil Pressure
3080416	Centry Fuel Rail Pressure

Part Number	Application
3080407	Celect™ Ambient Air Pressure
3083787	M11 CNG Boost Pressure
3080408	CNG Boost Pressure
3085258	Quantum Fuel/Timing Rail Pressure

Note : This is a product improvement and is **not** subject to campaign.

Document History

Date	Details
2010-12-15	Module Created

Last Modified: 15-Dec-2010
