



Technical Service Bulletin

Technical Service Bulletin: TSB110114

Released Date: 30-Apr-2012

Warranty Statement

The information in this document has no effect on present warranty coverage or repair practices, nor does it authorize TRP or Campaign actions.

Contents

The purpose of this document is to increase the awareness of the nozzle opening pressure (NOP) specifications that should be seen on the new versus used injectors for B and C Series engines.

Most injectors for B and C Series engines have an NOP value stamped on the injector nozzle holder. This NOP value is given in units of bar. For new injectors that have **not** been run on an engine the actual NOP of the injector can be greater than the value as stamped on the injector, but should **not** be less than this value. Typically, the maximum acceptable value of the nozzle opening pressure is the NOP as stamped on the injector +8 bar.

This value can vary depending on the injector assembly. Reference the list below or the Injection Pumps And Injectors Midrange Engines Manual for the correct NOP range for specific injector assemblies.

As injectors accumulate hours their NOP can decay. Up to 10 percent of decay is normal for used injectors, and injectors that exhibit this decay should still be considered in specification. The maximum allowable decay in NOP is 10 percent of the value stamped on the injector nozzle holder. Refer to the table below for the upper and lower limits of the injector NOP on new and used injectors.

Cummins Injector Assembly Part No.	Lowest Acceptable NOP With Used Injectors (Bar)	Opening Pressure As Stamped on Injector - Lowest Acceptable Limit When Injector Is New (Bar)	Maximum Acceptable NOP New or Used (Bar)
3279242	202.5	225	233
3279243	202.5	225	233
3280567	214.5	238	246
3280787	220.5	245	253
3281825	270	300	308
3355015	220.5	245	253
3355043	207	230	238

Cummins Injector Assembly Part No.	Lowest Acceptable NOP With Used Injectors (Bar)	Opening Pressure As Stamped on Injector - Lowest Acceptable Limit When Injector Is New (Bar)	Maximum Acceptable NOP New or Used (Bar)
3902969	220.5	245	253
3902980	220.5	245	253
3903383	198	220	228
3904197	220.5	245	253
3905752	229.5	255	263
3907173	298	220	228
3908093	229.5	255	263
3908175	220.5	245	253
3908238	232	258	266
3908505	184.5	205	213
3908507	184.5	205	213
3908509	184.5	205	213
3908511	184.5	205	213
3908513	184.5	205	213
3909454	220.5	245	253
3909464	220.5	245	253
3909475	198	220	228
3909476	220.5	245	253
3909509	220.5	245	253
3909522	220.5	245	253
3910325	232	258	266
3910623	162	180	188
3911185	162	180	188
3911340	198	220	228
3911350	184.5	205	213
3912033	207	230	238
3912468	220.5	245	253
3912478	229.5	255	263
3913380	220.5	245	253
3913735	270	300	308
3913992	198	220	228
3914205	229.5	255	263
3914471	220.5	245	253

Cummins Injector Assembly Part No.	Lowest Acceptable NOP With Used Injectors (Bar)	Opening Pressure As Stamped on Injector - Lowest Acceptable Limit When Injector Is New (Bar)	Maximum Acceptable NOP New or Used (Bar)
3914472	198	220	228
3914473	220.5	245	253
3914474	198	220	228
3914491	236	262	270
3914710	223	248	256
3915568	198	220	228
3915790	220.5	245	253
3915792	220.5	245	253
3915806	220.5	245	253
3916232	270	300	308
3916495	198	220	228
3916730	229.5	255	263
3916735	229.5	255	263
3916737	229.5	255	263
3916740	234	260	268
3916742	220.5	245	253
3916745	229.5	255	263
3917040	162	180	188
3917100	235.5	262	270
3917102	162	180	188
3917567	198	220	228
3917601	270	300	308
3917603	270	300	308
3917661	220.5	245	253
3918554	198	220	228
3918965	225	250	260
3919010	225	250	260
3919058	270	300	308
3919091	270	300	308
3919092	270	300	308
3919298	220.5	245	253
3919300	198	220	228
3919302	220.5	245	253

Cummins Injector Assembly Part No.	Lowest Acceptable NOP With Used Injectors (Bar)	Opening Pressure As Stamped on Injector - Lowest Acceptable Limit When Injector Is New (Bar)	Maximum Acceptable NOP New or Used (Bar)
3919304	198	220	228
3919305	162	180	188
3919306	162	180	188
3919307	229.5	255	263
3919309	229.5	255	263
3919311	232	258	266
3919313	232	258	266
3919315	229.5	255	263
3919317	220.5	245	263
3919319	198	220	228
3919320	229.5	255	263
3919322	220.5	245	253
3919323	202.5	220	233
3919324	202.5	255	233
3919325	220.5	245	253
3919326	229.5	255	263
3919327	229.5	255	263
3919328	229.5	255	263
3919329	234	260	268
3919330	220.5	245	253
3919331	198	220	228
3919332	229.5	255	263
3919333	220.5	245	253
3919334	220.5	245	253
3919335	198	220	228
3919336	198	220	228
3919337	220.5	245	253
3919339	220.5	245	253
3919341	198	220	228
3919343	220.5	245	253
3919345	220.5	245	253
3919347	220.5	245	253
3919349	198	220	228

Cummins Injector Assembly Part No.	Lowest Acceptable NOP With Used Injectors (Bar)	Opening Pressure As Stamped on Injector - Lowest Acceptable Limit When Injector Is New (Bar)	Maximum Acceptable NOP New or Used (Bar)
3919350	220.5	245	253
3919353	162	180	188
3919355	162	180	188
3919356	235.8	262	270
3919582	220.5	245	253
3919602	184.5	205	213
3919631	270	300	308
3919744	220.5	245	253
3919760	198	220	228
3919956	235.8	262	270
3919957	220.5	245	253
3919977	220.5	245	253
3920012	220.5	245	253
3920140	270	300	308
3920334	198	220	228
3920526	198.9	221	231
3920527	198.9	221	231
3920529	229.5	255	265
3920531	288	320	328
3920532	162	180	188
3920628	319.5	355	363
3921359	184.5	205	213
3921365	319.5	355	363
3921421	220.5	245	253
3921703	198	220	228
3921835	270	300	308
3921910	198	220	228
3921913	220.5	245	253
3922162	220.5	245	253
3922509	232	258	270
3922515	232	258	270
3922518	232	258	270
3922521	232	258	270

Cummins Injector Assembly Part No.	Lowest Acceptable NOP With Used Injectors (Bar)	Opening Pressure As Stamped on Injector - Lowest Acceptable Limit When Injector Is New (Bar)	Maximum Acceptable NOP New or Used (Bar)
3922907	270	300	308
3922913	270	300	308
3924013	235.8	262	270
3924896	243	268	280
3926117	270	300	308
3926120	270	300	308
3926817	232	258	270
3926818	232	258	270
3926819	232	258	270
3926820	234	260	268
3927320	234	260	268

Document History

Date	Details
2011-4-13	Module Created
2012-4-30	Ticket No.: 36767 Reason: Spelling Error Notes: CA 4501

Last Modified: 30-Apr-2012
