



Technical Service Bulletin

Technical Service Bulletin: TSB170060

Released Date: 14-Jul-2017

New Stainless Steel Exhaust Manifold Capscrew and Spacer

New Stainless Steel Exhaust Manifold Capscrew and Spacer

Warranty Statement

The information in this document has no effect on present warranty coverage or repair practices, nor does it authorize TRP or Campaign actions.

Contents

Product Affected

- QSK45 (All Versions)
- QSK60 (All Versions)

Description of Change

- A new stainless steel exhaust manifold capscrew and mounting spacer have been released. The new capscrew has longer threads. The new spacer has an increased internal inner diameter chamfer to allow for more capscrew clearance.
- The existing steel capscrew design remains unchanged and has been released under a new part number.

Reason for Change

New components are more robust.

Service Instructions

New stainless steel capscrew **must** be used in conjunction with new spacers.

Service Parts Availability

Service parts are available. See Table 1 for part numbers.

Table 1, Service Parts

Part Description	Existing Part Number	Obsolete	Superseded	New Part Number
Screw, High Temperature (Stainless Steel)	4065866	Yes	No	5372426

Table 1, Service Parts				
Part Description	Existing Part Number	Obsolete	Superseded	New Part Number
Spacer, Mounting	3046287	Yes	Yes	5372868
Screw, Hex Flange Head Cap (Steel)	-	-	-	5374571

Part Compatibility

Never mix stainless steel and steel capscrews in same exhaust manifold section.

Part Identification

- Stainless steel capscrew will have part number etched into head of capscrew, and steel capscrew head will be stamped with a “V” or “Vimi”.
- New mounting spacer will have two grooves running around the circumference.

Part Inventory Action

- QSK60 construction engines are recommended to use new stainless steel capscrew.
- All other applications are recommend to use steel capscrew unless capscrew malfunctions are experienced.

Document History

Date	Details
2017-5-5	Module Created

Last Modified: 14-Jul-2017
