



Technical Service Bulletin

Technical Service Bulletin: TSB110245

Released Date: 19-Apr-2012

New Modular Common Rail System Fuel Pumps and Weep Hole Plugs

New Modular Common Rail System Fuel Pumps and Weep Hole Plugs

Warranty Statement

The information in this document has no effect on present warranty coverage or repair practices, nor does it authorize TRP or Campaign actions.

Contents

This document introduces new MCRS fuel pumps with the weep hole removed from the gerotor body and plugs that can be used to plug existing pumps with a weep hole. The weep hole was removed from the pump to prevent external leaks that were caused when debris was ingested into the seals.

Engines

- QSK19 CM850 and CM2150
- QSK38 CM850 and CM2150
- QSK50 CM850 and CM2150
- QSK60 CM850 and CM2150

The fuel pump weep hole can **only** be plugged if it has a slow oil leak or if it is **not** leaking. If a steady stream of oil is coming from it, the pump can **not** be plugged. A fuel leak of any amount can **not** be plugged.

A standard rivet gun with a 2 mm [0.078 in] shank adapter can be used to install the 3 mm [0.118 in] plug. Special tooling is needed to install the 7 mm [0.276 in] plug. Part Numbers KW-003 and HKW-003908 are needed, which can be purchased from www.kvt-koenig.com.

MCRS Fuel Pump Weep Hole Plugs

Plug Diameter	Part Number
3 mm [0.118 in]	2888710
7 mm [0.276 in]	2888711

New engines have had the fuel pump weep hole plugged starting with engine serial number first (ESN) 37247701 for QSK19 engines and 33184996 for QSK38/50/60 engines. See the table below for ESN first of new part number fuel pumps with the weep hole removed.

MCRS Fuel Pump Part Numbers				
Engine	Obsolete Part Number	New Part Number	ESN First	Implementation Date
QSK19 CM850 or QSK19 CM2150	2870938	2888712	37248634	27-Apr-2011
QSK38 CM850	2870939	2888748	33186400	12-Apr-2011
QSK38 CM2150	2881171	2888797	33188617	2-Sept-2011
QSK50 CM850 Industrial or QSK60 CM850 Marine	2870940	2888749	33186479	15-Apr-2011
QSK50/60 CM850 Power Generation	2886864	2888810	33186638	27-Apr-2011
QSK50/60 CM2150 Industrial or QSK50/60 CM2150 Marine	2881172	2888798	33186651	27-Apr-2011

All fuel pumps in stock at the Parts Distribution Centers were plugged as of April 2011. These parts will be used up and then superseded to the new part numbers.

Plug installation instructions:

- Make sure all fuel pump caps are installed in fuel pump ports to avoid contamination. Carefully remove and clean any dirt and debris from the gerotor assembly of the MCRS pump with a clean cloth. Make sure the weep hole bore is dry and clean. For off-engine installation, it is recommended to prop the pump up such that the weep hole is oriented slightly downwards, to prevent any debris or component pieces from falling into it.
- Place the plug into the tool shank end first. Make sure the expander plug body bottoms out against the tool and the shank is snug against the expander plug body.
- Activate the tool until the expander plug is successfully installed and the stem snaps off cleanly. Inspect the plug to confirm it is installed fully into the weep hole. Discard the shank section in an appropriate manner.

Document History

Date	Details
2011-8-22	Module Created

Date	Details
2012-3-28	Update ESN first information in table.

Last Modified: 19-Apr-2012
