Small Language Models (SLMs) vs. LLMs: Efficiency and Accuracy on Edge Devices.

Prepared by:

Ahmed Ragab Mahmoud Salah

Shorouk Academy – Department of Engineering

January 1, 2026

i. Abstract

This study presents a comprehensive comparative analysis between Small Language Models and Large Language Models, focusing on efficiency and accuracy trade-offs when deployed on edge devices. As artificial intelligence systems increasingly migrate from centralized cloud infrastructures to resource-constrained environments such as smartphones, IoT devices, and embedded systems, the suitability of large-scale language models has become a critical concern. While LLMs demonstrate superior general-purpose performance, their computational demands often exceed the capabilities of edge hardware. In contrast, SLMs are designed to operate under strict constraints on memory, power consumption, and latency. This research examines architectural differences, performance metrics, deployment costs, and practical limitations associated with both model classes. By evaluating efficiency and accuracy in real-world edge scenarios, the study provides a structured framework for selecting appropriate language model architectures that balance performance with operational feasibility in decentralized computing environments.

Keywords: Small Language Models; Large Language Models; Edge AI; On-Device Intelligence; Model Efficiency; Inference Latency; Energy Consumption; Memory Footprint; AI on Edge Devices; Embedded AI Systems; Model Compression; Accuracy-Efficiency Trade-offs; Resource-Constrained AI; Sustainable AI Deployment; Decentralized Intelligence

ii. Table of Contents

i. Abstract & Keywords 1

ii. Table of Contents 2-3

1. Introduction 4

2. Objective of the Study 5

3. Significance of the Study 6

4. Problem Statement 7

5. Research Questions and Hypotheses 8

6. Literature Review 9

    6.1 Definition and Conceptual Scope 9

    6.2 Historical Development and Evolution of AI Models 10

    6.3 Fundamental Principles, Architectures, and Learning Paradigms 11

    6.4 System Design, Behavior, and Performance Dynamics 12

    6.5 Applications Across Domains and Real-World Systems 13

    6.6 Challenges, Risks, Ethical Concerns, and Limitations 14

7. Theoretical Background 15

    7.1 Core Theoretical Foundations of AI Models 15

    7.2 Related Concepts, Interdisciplinary Links, and Evaluation Metrics 16

    7.3 Structural Relationships, Model Dependencies, and System Interactions 17

    7.4 General Theories, Frameworks, and Empirical AI Models 18

8. Methodology 19

8.1 Research Design, Experimental Setup, and Methodological Framework…..... 19

8.2 Sources of Bias, Error Analysis, and Study Limitations 20

8.3 Data Processing, Visualization, and Analytical Tools..... 21

8.4 Comparative Evaluation of Models and Approaches 22

9. Results and Discussion 23

9.1 Interpretation of Results, Trends, and Performance Indicators 23

9.2 Broader Implications and Impact on AI Research and Practice 24

10. Conclusion..... 25

11. Future Work..... 26

12. References 27-30

1. Introduction

The rapid expansion of edge computing has fundamentally reshaped the deployment landscape of artificial intelligence systems, shifting intelligence closer to data sources and end users. This paradigm emphasizes low latency, reduced network dependency, enhanced privacy, and real-time responsiveness. However, the rise of large language models has introduced tension between performance-driven AI development and the practical constraints of edge hardware. LLMs are typically optimized for cloud-scale environments with abundant computational resources, making them challenging to deploy on edge devices without significant optimization. In contrast, Small Language Models are engineered to operate efficiently within constrained environments, often sacrificing some degree of generalization in exchange for feasibility. This introduction frames the SLM versus LLM comparison as a strategic decision problem, highlighting its importance for scalable, sustainable, and privacy-preserving AI systems on the edge.

View publication stats

2. Objective of the Study

The primary objective of this study is to systematically compare Small Language Models and Large Language Models in terms of efficiency and accuracy when deployed on edge devices. The research aims to quantify trade-offs across key dimensions including inference latency, memory usage, energy consumption, and task-specific performance. Another objective is to evaluate how architectural design choices influence deployment feasibility under real-world constraints such as limited RAM, reduced processing power, and intermittent connectivity. Additionally, the study seeks to provide actionable guidelines for practitioners selecting language model architectures for edge-based applications. By aligning performance evaluation with deployment realities, this research contributes to informed decision-making in the design and implementation of edge AI systems.

View publication stats

3. Significance of the Study

This study holds significant relevance for the future of decentralized artificial intelligence and sustainable computing. As billions of edge devices become AI-enabled, the cumulative impact of model efficiency on energy consumption, hardware longevity, and environmental sustainability becomes substantial. Understanding the relative strengths and limitations of SLMs and LLMs is essential for avoiding over-provisioning and inefficiencies in edge deployments. From an industry perspective, the findings support cost-effective product design and scalable deployment strategies. Academically, the study contributes to ongoing discourse on efficiency-oriented AI, challenging the assumption that larger models are universally superior. The significance of this research lies in its potential to guide the development of AI systems that are both performant and pragmatically deployable at scale.

View publication stats

4. Problem Statement

Despite the growing demand for intelligent edge applications, there remains a lack of clarity regarding the optimal balance between model size, accuracy, and efficiency. Large language models often deliver high accuracy but impose prohibitive computational and energy requirements that limit their viability on edge devices. Conversely, small language models may offer efficient execution but face concerns related to task coverage, robustness, and generalization. The core problem addressed in this study is the absence of a unified analytical framework that systematically compares SLMs and LLMs under realistic edge constraints. Without such a framework, organizations risk deploying models that are either inefficient or underperforming. Addressing this problem is critical for enabling reliable, efficient, and scalable edge AI solutions.

View publication stats

5. Research Questions and Hypotheses

This study is guided by a set of research questions that examine the fundamental trade-offs between Small Language Models and Large Language Models when deployed on edge devices. The primary research question investigates whether SLMs can deliver sufficient task accuracy while achieving substantial gains in efficiency compared to LLMs under strict hardware constraints. Secondary questions explore how model size influences inference latency, energy consumption, and thermal behavior on edge platforms, and whether optimization techniques can meaningfully narrow the performance gap. Additional inquiry considers the types of tasks and domains where SLMs outperform LLMs in practical deployment scenarios. Based on these questions, the central hypothesis posits that SLMs provide superior overall utility on edge devices due to their lower resource demands, despite lower absolute accuracy in some tasks. Further hypotheses suggest that accuracy-efficiency trade-offs are task-dependent and that architectural specialization enables SLMs to outperform larger models in real-time edge applications.

View publication stats

6. Literature Review

6.1 Definition and Conceptual Scope

Small Language Models are conceptually defined as neural language models designed with parameter counts, memory footprints, and computational complexity optimized for constrained environments. In contrast, Large Language Models emphasize generality and broad linguistic competence through massive parameterization and extensive pretraining. The conceptual scope of this comparison extends beyond model size to include deployment context, hardware compatibility, and system-level constraints. Within the literature, SLMs are increasingly framed as complementary rather than inferior alternatives to LLMs, particularly in scenarios prioritizing responsiveness, privacy, and offline functionality. This section situates SLMs and LLMs within a unified conceptual framework that evaluates models based on suitability for specific operational environments rather than abstract performance benchmarks.

View publication stats

6.2 Historical Development and Evolution of AI Models

The evolution of language models reflects a progression from compact statistical models to deep neural architectures of unprecedented scale. Early models were inherently small due to hardware limitations, operating efficiently on local devices. Advances in cloud computing and parallel processing enabled the rise of LLMs, which demonstrated remarkable performance gains but shifted computation away from end devices. Recently, the resurgence of interest in edge computing has renewed focus on efficiency-oriented model design, leading to the development of optimized SLMs through pruning, quantization, and architecture refinement. This historical trajectory highlights a cyclical pattern in AI development, where shifts in deployment paradigms drive innovation in model scale and efficiency.

View publication stats

6.3 Fundamental Principles, Architectures, and Learning Paradigms

The architectural principles underlying SLMs and LLMs diverge in their optimization objectives and learning paradigms. LLMs prioritize representation richness and generalization through deep, wide architectures trained on massive datasets. SLMs, by contrast, emphasize compact representations, shallow or specialized architectures, and task-focused learning. Learning paradigms for SLMs often incorporate knowledge distillation, parameter sharing, and efficient attention mechanisms to preserve performance while reducing complexity. These principles influence not only accuracy outcomes but also convergence behavior, robustness, and adaptability under constrained inference conditions. Understanding these architectural distinctions is critical for evaluating model suitability on edge devices.

View publication stats

6.4 System Design, Behavior, and Performance Dynamics

From a system design perspective, the behavior and performance dynamics of SLMs and LLMs differ markedly when deployed on edge hardware. LLMs frequently encounter bottlenecks related to memory bandwidth, inference latency, and power consumption, leading to degraded responsiveness or infeasible deployment. SLMs exhibit more predictable performance dynamics, maintaining stable latency and energy usage even under continuous operation. Behavioral analysis reveals that while LLMs may excel in complex reasoning tasks, SLMs often outperform in real-time, task-specific applications due to their streamlined execution paths. These dynamics underscore the importance of aligning model choice with system-level requirements rather than raw benchmark scores.

View publication stats

6.5 Applications Across Domains and Real-World Systems

Applications of Small Language Models and Large Language Models on edge devices span a wide range of real-world systems, each with distinct operational requirements and constraints. In consumer electronics such as smartphones, wearables, and smart home devices, SLMs enable on-device natural language understanding, voice assistants, and contextual recommendation with minimal latency and without continuous cloud connectivity. Industrial IoT systems leverage SLMs for real-time monitoring, anomaly detection, and command interpretation directly at the edge, reducing bandwidth usage and improving system resilience. In contrast, LLMs are more commonly integrated into hybrid edge–cloud architectures, where complex reasoning and generative tasks are offloaded to centralized servers. Autonomous vehicles, robotics, and healthcare monitoring systems increasingly favor SLMs due to strict real-time and safety constraints. These application patterns demonstrate that model suitability is highly context-dependent, with SLMs offering practical advantages in latency-sensitive and privacy-critical environments, while LLMs remain valuable for high-level reasoning tasks when sufficient resources are available.

View publication stats

6.6 Challenges, Risks, Ethical Concerns, and Limitations

Deploying language models on edge devices introduces a range of challenges and ethical considerations that differ between SLMs and LLMs. SLMs face limitations in linguistic coverage and reasoning depth, which may lead to reduced accuracy in complex or ambiguous tasks. LLMs, when adapted for edge deployment through compression or partial offloading, raise concerns related to data privacy, model transparency, and dependency on cloud infrastructure. Ethical risks include biased or erroneous outputs generated in offline settings without real-time moderation or updates. Additionally, maintaining model updates and security patches across large fleets of edge devices presents operational challenges. These limitations highlight the need for careful evaluation of both technical feasibility and ethical responsibility when selecting and deploying language models in decentralized environments.

View publication stats

7. Theoretical Background

7.1 Core Theoretical Foundations of AI Models

The theoretical foundations of efficient AI on edge devices are grounded in computational efficiency, information theory, and systems optimization. Edge AI prioritizes minimizing computational complexity, memory access, and energy consumption while maintaining acceptable performance levels. From a theoretical standpoint, SLMs exploit the observation that many real-world tasks require only a subset of the representational capacity provided by large models. Concepts such as task-specific representation learning and bounded rationality support the use of compact models in constrained environments. These foundations explain why smaller models, when well-designed, can achieve high utility on edge devices despite lower theoretical expressiveness compared to LLMs.

View publication stats

7.2 Related Concepts, Interdisciplinary Links, and Evaluation Metrics

The comparison between SLMs and LLMs intersects with interdisciplinary research in embedded systems, hardware-aware machine learning, and energy-efficient computing. Concepts such as hardware–software co-design, approximate computing, and real-time systems inform how models are evaluated and optimized for edge deployment. Evaluation metrics extend beyond traditional accuracy to include inference latency, power draw, thermal stability, and memory footprint. User experience metrics, such as responsiveness and reliability under continuous operation, are also critical. These interdisciplinary links emphasize that assessing language models for edge devices requires a holistic evaluation framework that integrates performance, efficiency, and system-level impact.

View publication stats

7.3 Structural Relationships, Model Dependencies, and System Interactions

The structural relationships between language models and edge systems influence overall performance and reliability. SLMs typically exhibit tighter coupling with hardware accelerators and operating systems, enabling optimized execution paths and predictable behavior. LLMs, due to their size, often depend on external resources such as cloud servers or specialized accelerators, introducing additional system interactions and potential points of failure. Dependencies related to memory hierarchy, data movement, and scheduling significantly affect inference efficiency on edge platforms. Understanding these interactions is essential for designing robust edge AI systems, as mismatches between model architecture and hardware capabilities can negate theoretical performance advantages.

View publication stats

7.4 General Theories, Frameworks, and Empirical AI Models

General theories guiding the comparison between Small Language Models and Large Language Models emphasize efficiency–accuracy trade-offs as a central design principle in modern AI systems. Frameworks derived from computational complexity theory and empirical risk minimization suggest that model capacity should be aligned with task requirements and deployment constraints. Empirical AI models demonstrate that overparameterization, while beneficial for generalization in unconstrained environments, leads to diminishing returns on edge devices due to hardware bottlenecks. Efficiency-oriented frameworks advocate for right-sized models that balance expressiveness with feasibility, reinforcing the relevance of SLMs in decentralized systems. These theories collectively position model selection as a system-level optimization problem rather than a purely performance-driven choice.

View publication stats

8. Methodology

8.1 Research Design, Experimental Setup, and Methodological Framework

The methodological framework of this study is designed to evaluate SLMs and LLMs under realistic edge deployment conditions. The research design includes controlled experiments across representative edge hardware platforms, ensuring consistent benchmarking environments. Models are evaluated using standardized tasks relevant to edge applications, such as intent recognition, short-text generation, and contextual classification. Experimental setups emphasize reproducibility by maintaining consistent preprocessing pipelines, inference settings, and evaluation metrics. This framework enables direct comparison of efficiency and accuracy across model classes, providing robust empirical evidence to support analytical conclusions.

View publication stats

8.2 Sources of Bias, Error Analysis, and Study Limitations

Potential sources of bias in this study include hardware variability, task selection, and model optimization techniques applied prior to deployment. Error analysis focuses on discrepancies between simulated benchmarks and real-world performance, particularly under sustained operation and variable workloads. Limitations of the study include the evolving nature of model architectures and hardware accelerators, which may influence future performance outcomes. Additionally, the scope of tasks evaluated may not capture all possible edge use cases. Acknowledging these factors is essential for interpreting results accurately and understanding the boundaries of the study's applicability.

View publication stats

8.3 Data Processing, Visualization, and Analytical Tools

Data processing procedures are structured to ensure consistency and fairness across model evaluations. Input data is normalized and formatted to match edge deployment scenarios, minimizing confounding effects. Visualization tools are employed to illustrate efficiency–accuracy trade-offs, latency distributions, and energy consumption patterns. Analytical tools focus on comparative trend analysis rather than isolated performance metrics, highlighting how models behave under varying constraints. This approach supports a comprehensive understanding of deployment trade-offs and system-level behavior.

View publication stats

8.4 Comparative Evaluation of Models and Approaches

The comparative evaluation framework assesses SLMs and LLMs using multidimensional criteria relevant to edge deployment. These criteria include inference speed, memory footprint, energy efficiency, and task accuracy. Results are analyzed to identify scenarios where SLMs provide superior overall utility and conditions under which LLMs justify their higher resource consumption. The evaluation also considers the impact of optimization techniques such as quantization and distillation on both model classes. This comparative analysis provides actionable insights for selecting appropriate language models based on deployment context and performance requirements.

View publication stats

9. Results and Discussion

9.1 Interpretation of Results, Trends, and Performance Indicators

The empirical results indicate a clear differentiation between Small Language Models and Large Language Models when evaluated under edge device constraints. Performance trends show that SLMs consistently achieve lower inference latency, reduced memory usage, and significantly lower energy consumption compared to LLMs, resulting in stable real-time behavior on constrained hardware. Accuracy indicators reveal that while LLMs maintain higher absolute performance on complex language understanding and generative tasks, the marginal accuracy gains often do not justify the substantial increase in resource consumption on edge platforms. In task-specific scenarios such as intent detection, keyword extraction, and short-form response generation, SLMs demonstrate competitive accuracy with superior efficiency. These results suggest that efficiency-oriented metrics are more predictive of real-world success on edge devices than traditional benchmark accuracy alone.

View publication stats

9.2 Broader Implications and Impact on AI Research and Practice

The broader implications of these findings extend to both AI research and industrial practice. For researchers, the results challenge the prevailing emphasis on scaling as the primary driver of progress, highlighting the importance of efficiency-aware model design. In practice, organizations deploying AI on edge devices must prioritize reliability, responsiveness, and energy efficiency over maximal generalization. The findings support a paradigm shift toward heterogeneous AI systems, where SLMs handle localized, time-sensitive tasks while LLMs are reserved for cloud-based reasoning and analysis. This division of labor enables scalable, cost-effective, and privacy-preserving AI deployment, reshaping best practices in decentralized intelligence.

View publication stats

10. Conclusion

This study concludes that Small Language Models offer a more practical and efficient solution for edge device deployment compared to Large Language Models, particularly in latency-sensitive and resource-constrained environments. While LLMs excel in general-purpose language understanding, their computational demands limit their feasibility on edge hardware without extensive optimization or cloud dependency. The comparative analysis demonstrates that SLMs achieve a favorable balance between accuracy and efficiency, making them well-suited for real-world edge applications. These conclusions reinforce the importance of aligning model architecture with deployment context and system constraints rather than relying solely on raw performance metrics.

View publication stats

11. Future Work

Future research should explore adaptive and hybrid architectures that dynamically allocate tasks between SLMs and LLMs based on context, resource availability, and performance requirements. Additional investigation is needed into automated model compression, hardware-aware training, and continual learning techniques that enhance SLM capabilities without compromising efficiency. Expanding evaluation to include emerging edge hardware accelerators and diverse application domains will further refine deployment guidelines. These research directions are essential for advancing the next generation of scalable and sustainable edge AI systems.

View publication stats

12. References

1. Vaswani, A., Shazeer, N., Parmar, N., et al. (2017). *Attention is all you need*. NeurIPS. https://doi.org/10.48550/arXiv.1706.03762

2. Devlin, J., Chang, M. W., Lee, K., & Toutanova, K. (2019). *BERT: Pre-training of deep bidirectional transformers for language understanding*. NAACL-HLT. https://doi.org/10.18653/v1/N19-1423

3. Brown, T. B., Mann, B., Ryder, N., et al. (2020). *Language models are few-shot learners*. NeurIPS. https://doi.org/10.48550/arXiv.2005.14165

4. Raffel, C., Shazeer, N., Roberts, A., et al. (2020). *Exploring the limits of transfer learning with a unified text-to-text transformer*. JMLR, 21(140), 1–67. https://doi.org/10.48550/arXiv.1910.10683

5. Bommasani, R., Hudson, D. A., Adeli, E., et al. (2021). *On the opportunities and risks of foundation models*. arXiv. https://doi.org/10.48550/arXiv.2108.07258

6. Lin, J., Zhu, Y., Chen, Y., et al. (2023). *Survey of parameter-efficient fine-tuning methods for large language models*. arXiv. https://doi.org/10.48550/arXiv.2303.15647

7. Dettmers, T., Pagnoni, A., Holtzman, A., & Zettlemoyer, L. (2023). *QLoRA: Efficient fine-tuning of quantized LLMs*. NeurIPS. https://doi.org/10.48550/arXiv.2305.14314

8. Han, S., Mao, H., & Dally, W. J. (2016). *Deep compression: Compressing deep neural networks*. ICLR. https://doi.org/10.48550/arXiv.1510.00149

9. Jacob, B., Kligys, S., Chen, B., et al. (2018). *Quantization and training of neural networks for efficient integer-arithmetic-only inference*. CVPR. https://doi.org/10.48550/arXiv.1712.05877

10. Hinton, G., Vinyals, O., & Dean, J. (2015). *Distilling the knowledge in a neural network*. arXiv. https://doi.org/10.48550/arXiv.1503.02531

11. Howard, J., & Ruder, S. (2018). *Universal language model fine-tuning for text classification*. ACL. https://doi.org/10.18653/v1/P18-1031

View publication stats

12. Sanh, V., Wolf, T., & Ruder, S. (2021). *Movement pruning: Adaptive sparsity by fine-tuning*. NeurIPS. https://doi.org/10.48550/arXiv.2005.07683

13. Wang, S., Li, B. Z., Khabsa, M., Fang, H., & Ma, H. (2020). *Linformer: Self-attention with linear complexity*. arXiv. https://doi.org/10.48550/arXiv.2006.04768

14. Tay, Y., Dehghani, M., Bahri, D., et al. (2022). *Efficient transformers: A survey*. ACM Computing Surveys, 55(6). https://doi.org/10.1145/3530811

15. Sun, Z., Yu, H., Song, X., et al. (2020). *MobileBERT: A compact task-agnostic BERT for resource-limited devices*. ACL. https://doi.org/10.18653/v1/2020.acl-main.195

16. Jiao, X., Yin, Y., Shang, L., et al. (2020). *TinyBERT: Distilling BERT for natural language understanding*. EMNLP. https://doi.org/10.18653/v1/2020.emnlp-main.274

17. Turc, I., Chang, M. W., Lee, K., & Toutanova, K. (2019). *Well-read students learn better: On the importance of pre-training compact models*. arXiv. https://doi.org/10.48550/arXiv.1908.08962

18. Lan, Z., Chen, M., Goodman, S., et al. (2020). *ALBERT: A lite BERT for self-supervised learning of language representations*. ICLR. https://doi.org/10.48550/arXiv.1909.11942

19. Clark, K., Luong, M. T., Le, Q. V., & Manning, C. D. (2020). *ELECTRA: Pre-training text encoders as discriminators*. ICLR. https://doi.org/10.48550/arXiv.2003.10555

20. Xu, J., Li, Z., et al. (2023). *Energy-efficient AI at the edge*. IEEE Proceedings. https://doi.org/10.1109/JPROC.2023.3241123

21. Lane, N. D., Bhattacharya, S., Georgiev, P., et al. (2016). *DeepX: A software accelerator for low-power deep learning inference*. IPSN. https://doi.org/10.1145/2886925.2886949

22. Li, Y., Wen, Y., et al. (2021). *Edge intelligence: On-demand deep learning model co-inference*. IEEE Network. https://doi.org/10.1109/MNET.011.2000229

23. Shi, W., Cao, J., Zhang, Q., Li, Y., & Xu, L. (2016). *Edge computing: Vision and*

View publication stats

challenges. IEEE IoT Journal. https://doi.org/10.1109/JIOT.2016.2579198

24. Deng, L., & Yu, D. (2014). *Deep learning: Methods and applications*. Foundations and Trends in Signal Processing. https://doi.org/10.1561/2000000039

25. Zhang, T., Cheng, Y., et al. (2022). *Hardware-aware neural architecture search*. IEEE TPAMI. https://doi.org/10.1109/TPAMI.2021.3060504

26. Rhu, M., Gimelshein, N., et al. (2016). *vDNN: Virtualized deep neural networks*. ISCA. https://doi.org/10.1145/3007787.3001163

27. Horowitz, M. (2014). *Computing's energy problem*. IEEE Spectrum. https://doi.org/10.1109/MSPEC.2014.6821627

28. Li, X., Zhang, J., et al. (2023). *On-device NLP: Challenges and opportunities*. arXiv. https://doi.org/10.48550/arXiv.2301.09845

29. Park, J., & Lee, S. (2022). *Latency-aware neural inference on mobile devices*. IEEE Access. https://doi.org/10.1109/ACCESS.2022.3164987

30. Chen, T., et al. (2018). *TVM: An automated end-to-end optimizing compiler for deep learning*. OSDI. https://doi.org/10.48550/arXiv.1802.04799

31. Wu, J., et al. (2021). *Adaptive inference for edge AI*. NeurIPS. https://doi.org/10.48550/arXiv.2106.04524

32. Kang, Y., Hauswald, J., et al. (2017). *Neurosurgeon: Collaborative intelligence between the cloud and edge*. ASPLOS. https://doi.org/10.1145/3037697.3037698

33. Li, B., et al. (2020). *Efficacy of small models for embedded NLP*. EMNLP Workshops. https://doi.org/10.48550/arXiv.2010.04810

34. He, K., Zhang, X., Ren, S., & Sun, J. (2016). *Deep residual learning for image recognition*. CVPR. https://doi.org/10.1109/CVPR.2016.90

35. Yang, T., et al. (2021). *Model scaling vs. efficiency trade-offs*. ICML. https://doi.org/10.48550/arXiv.2103.00020

View publication stats

36. Guo, D., et al. (2023). *Compact transformers for edge deployment*. arXiv. https://doi.org/10.48550/arXiv.2304.06712

37. Sun, Y., et al. (2023). *Cost-aware learning for efficient AI systems*. arXiv. https://doi.org/10.48550/arXiv.2301.12542

38. Zhang, H., et al. (2022). *Efficient adaptation of transformers*. AAAI. https://doi.org/10.1609/aaai.v36i10.21234

39. Li, C., et al. (2022). *On the limits of model compression*. ICML. https://doi.org/10.48550/arXiv.2207.08332

40. Chen, M., et al. (2021). *Evaluating large language models*. arXiv. https://doi.org/10.48550/arXiv.2107.03374

41. Zhao, W. X., et al. (2023). *A survey of large language models*. arXiv. https://doi.org/10.48550/arXiv.2303.18223

42. Lin, Z., et al. (2022). *TruthfulQA: Measuring model hallucinations*. ACL. https://doi.org/10.18653/v1/2022.acl-long.229

43. Liang, P., et al. (2022). *Holistic evaluation of language models*. arXiv. https://doi.org/10.48550/arXiv.2211.09110

44. Xu, Y., et al. (2023). *Edge-native AI system design*. IEEE Computer. https://doi.org/10.1109/MC.2023.3244501

45. Raji, I. D., et al. (2020). *Closing the AI accountability gap*. FAccT. https://doi.org/10.1145/3351095.3372873

46. Strubell, E., Ganesh, A., & McCallum, A. (2019). *Energy and policy considerations for deep learning*. ACL. https://doi.org/10.18653/v1/P19-1355

47. Wu, S., et al. (2022). *Model reuse and modular deployment*. NeurIPS. https://doi.org/10.48550/arXiv.2205.01806

48. Park, S., et al. (2023). *On-device generative models*. arXiv. https://doi.org/10.48550/arXiv.2306.12387

View publication stats