

Class 4, Problem Set 2



UNIVERSITY OF
COPENHAGEN

Introduction to Programming and Numerical Analysis

Plan for today

1. Inaugural project
 - We will work on it next tuesday
 - Deadline March 21, 2021
2. Let's GIT it out of the way
 - Questionnaire
3. Work on PS2



UNIVERSITY OF
COPENHAGEN

The problem

Choose optimal housing and consumption:

$$c^*, h^* = \arg \max c^{(1-\phi)} h^\phi$$

s. t.

$$\tilde{p}_h = p_h \epsilon$$

$$m = \tau(p_h, \tilde{p}_h) + c$$

$$\tau(p_h, \tilde{p}_h) = r p_h + \tau^g \tilde{p}_h + \tau^p \max(\tilde{p}_h - \bar{p}, 0)$$



UNIVERSITY OF
COPENHAGEN

Utility is given by:

$$u = c^{(1-\phi)} h^{\phi}$$

Implement in python:



Utility is given by:

$$u = c^{(1-\phi)} h^{\phi}$$



Implement in python:

```
In [2]: # Exogenous variables as global variables
phi = 0.5

def utility_function(c, h, phi):
    return (c**(1-phi))*(h**phi)

# With dictionary of exogenous variables
param_dict = {'phi' : 0.5
              , 'parameter' : 1.5 # and so on
              }

def utility_function(c, h, param_dict):
    return (c**(1-param_dict['phi']))*(h**param_dict['phi'])
```

What about the constraints?

Do the same!



UNIVERSITY OF
COPENHAGEN

What about the constraints?

Do the same!



UNIVERSITY OF
COPENHAGEN

```
In [5]: def cost_of_housing(arguments, param_dict, r, tau_g): # Eq. (4)
        return param_dict['r']*p + param_dict['tau_g']*p_tilde #... and so on
```

How is the model solved?

As consumption, c is implicitly given by the constraints you only need the optimizer to find the optimal amount of housing, h .

This implies that your objective function calculates c given the constraints and returns the (negative) utility



UNIVERSITY OF
COPENHAGEN

How is the model solved?

As consumption, c is implicitly given by the constraints you only need the optimizer to find the optimal amount of housing, h .

This implies that your objective function calculates c given the constraints and returns the (negative) utility



UNIVERSITY OF
COPENHAGEN

In [4]:

```
def value_of_choice(arguments, param_dict):  
    # Calculate the choice of consumption using the constraints and the functions you have c  
    # Hint: Use constraints to implicitly find the choice of consumption, c  
    return -utility_function(h,choice of consumption goes here,param_dict) # '-' because we
```

Write a function that optimize

How is it done? - recall PS1/Lecture 3

- Create objective function
- Initial guess
- Call optimizer: `optimize.minimize()` or `optimize.minimize_scalar()`
- Create a print condition that prints out the results
- If you want return the values as well

Questions?



UNIVERSITY OF
COPENHAGEN

What's up with GitHub?

Let's try to resolve all the issues today

Please fill out the questionnaire



UNIVERSITY OF
COPENHAGEN

Pulling using VSCode



UNIVERSITY OF
COPENHAGEN

1. Important: always have a working folder and a folder that you pull changes to!
2. Click on 'Open folder' in the 'Welcome'-tab and open the local repository
3. (a) Press `control/command + shift + p` and enter `Git: Pull`
4. (b) Alternative: Press `Synchronize Changes` in the bottom left
5. Your folder is now up to date

Pulling using Terminal/Prompt



UNIVERSITY OF
COPENHAGEN

1. Important: always have a working folder and a folder that you pull changes to!
2. Open Terminal/Prompt
3. Change directory to the Git folder by entering `cd User/Desktop/Git_folder`
4. Enter `git pull`
5. Your folder is now up to date

Getting help



UNIVERSITY OF
COPENHAGEN

- Go into the main meeting and tell me to join your channel
- If im not there, leave a @Victor comment in the main meeting such that i get a notification

Working on PS2

Focus on

- 2.3 (interactive figure)
- 2.5 (creating modules)
- 2.6 (git)
- 3 (exchange economy)



UNIVERSITY OF
COPENHAGEN