

clustering_primary

October 22, 2024

```
[2]: import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
from minisom import MiniSom
from sklearn.preprocessing import MinMaxScaler
from sklearn.preprocessing import StandardScaler
from sklearn.metrics import silhouette_score
from sklearn.cluster import KMeans
```

1 Clustering Algorithms for Primary Dataset

```
[3]: dataset = 'primary'
data = pd.read_csv(f'../dataset/mapped_{dataset}.csv', sep=',')
data = data.drop(columns=['uuid'])
variable_names = data.columns.tolist()

# need to normalize data from SOMs
scaler = MinMaxScaler()
norm_data = pd.DataFrame(scaler.fit_transform(data), columns=data.columns)

print(norm_data)
```

	price	artist	cardFinish	colorIdentity	colors	edhrecRank	\
0	0.002581	0.773243	1.0	0.766667	0.766667	0.760212	
1	0.063226	0.773243	0.5	0.766667	0.766667	0.760212	
2	0.167742	0.773243	1.0	0.766667	0.766667	0.760212	
3	0.018065	0.773243	1.0	0.766667	0.766667	0.760212	
4	0.126452	0.773243	1.0	0.766667	0.766667	0.760212	
...	
15209	0.056774	0.621315	1.0	0.533333	0.533333	0.200869	
15210	0.024516	0.621315	0.5	0.533333	0.533333	0.200869	
15211	0.229677	0.621315	1.0	0.533333	0.533333	0.200869	
15212	0.126452	0.621315	0.5	0.533333	0.533333	0.200869	
15213	0.218065	0.621315	1.0	0.533333	0.533333	0.200869	
	edhrecSaltiness	gameAvailability	isReprint	layout	...	\	
0	0.027668	0.0	0.0	0.8	...		

1	0.027668		0.0	0.0	0.8	...
2	0.027668		1.0	0.0	0.8	...
3	0.027668		1.0	0.0	0.8	...
4	0.027668		1.0	0.0	0.8	...
...
15209	0.169960		1.0	1.0	0.8	...
15210	0.169960		1.0	1.0	0.8	...
15211	0.169960		1.0	1.0	0.8	...
15212	0.169960		1.0	1.0	0.8	...
15213	0.169960		1.0	1.0	0.8	...

	originalType	power	priceProvider	providerListing	rarity	\
0	1.000000	0.461538	0.000000	0.0	0.5	
1	1.000000	0.461538	0.000000	0.0	0.5	
2	1.000000	0.461538	1.000000	0.0	0.5	
3	1.000000	0.461538	0.333333	1.0	0.5	
4	1.000000	0.461538	0.333333	0.0	0.5	
...
15209	0.238754	0.461538	0.333333	1.0	0.5	
15210	0.238754	0.461538	0.333333	1.0	0.5	
15211	0.238754	0.461538	0.333333	0.0	0.5	
15212	0.238754	0.461538	0.333333	0.0	0.5	
15213	0.238754	0.461538	0.666667	0.0	0.5	

	setCode	supertypes	toughness	type	types
0	0.621053	0.0	0.500000	0.463466	0.666667
1	0.621053	0.0	0.500000	0.463466	0.666667
2	0.621053	0.0	0.500000	0.463466	0.666667
3	0.621053	0.0	0.500000	0.463466	0.666667
4	0.621053	0.0	0.500000	0.463466	0.666667
...
15209	0.768421	0.0	0.416667	0.062630	0.666667
15210	0.768421	0.0	0.416667	0.062630	0.666667
15211	0.768421	0.0	0.416667	0.062630	0.666667
15212	0.768421	0.0	0.416667	0.062630	0.666667
15213	0.768421	0.0	0.416667	0.062630	0.666667


[15214 rows x 24 columns]

```
[4]: som_size = 10
som = MiniSom(som_size, som_size, norm_data.shape[1], sigma=1.0,
↳ learning_rate=0.5)

som.train(norm_data.values, num_iteration=1000)

plt.figure(figsize=(8, 8))
plt.pcolor(som.get_weights()[:, :, 0], cmap='coolwarm', alpha=0.5)
```

```
plt.colorbar()
plt.title('Self-Organizing Map')
plt.show()
```



```
[5]: win_map = som.win_map(norm_data.values)
      cluster_characteristics = {}
```

```
[6]: def plt_som(win_map,col):

      cluster_characteristics = {}
```

```

# Loop through the win map to calculate mean prices for each cluster
for (x, y), indices in win_map.items():
    for i in indices:
        values = data.iloc[i][col].values

        # Calculate mean price for the cluster
        mean_col = np.mean(values) if len(values) > 0 else 0
        median_col = np.median(values) if len(values) > 0 else 0
        std_col = np.std(values) if len(values) > 0 else 0

        # Store in the dictionary
        cluster_characteristics[(x, y)] = {f'mean_{col}': mean_col,
        ↪ f'median_{col}': median_col, f'std_{col}': std_col}

mean_values = np.zeros((10, 10))

for (x, y), values in cluster_characteristics.items():
    mean_values[x, y] = values[f'mean_{col}']

# Plotting the heatmap
plt.figure(figsize=(8, 6))
plt.imshow(mean_values, cmap='coolwarm', interpolation='nearest')
plt.colorbar(label='Mean Values')
plt.title(f'{col} Heatmap of Cluster Means')
plt.xlabel('X-axis')
plt.ylabel('Y-axis')

# Optionally, add grid lines and labels
plt.xticks(ticks=np.arange(10), labels=np.arange(10))
plt.yticks(ticks=np.arange(10), labels=np.arange(10))
plt.grid(color='white', linestyle='-', linewidth=1)

plt.show()


```


```
[7]: print(len(data.columns))
```


24


```
[8]: for i in data.columns:
      plt_som(win_map, i)
```




































































```
[10]: scaler = StandardScaler()
scaled_data = scaler.fit_transform(data)

inertia = []
silhouette_scores = []
k_values = range(2,11)

for k in k_values:
    kmeans = KMeans(n_clusters=k, random_state=42)
    kmeans.fit(scaled_data)
    inertia.append(kmeans.inertia_)
    silhouette_scores.append(silhouette_score(scaled_data, kmeans.labels_))

# Step 4: Plot the Elbow Method results
plt.figure(figsize=(12, 5))

# Inertia Plot
```

```

plt.subplot(1, 2, 1)
plt.plot(k_values, inertia, marker='o')
plt.title('Elbow Method')
plt.xlabel('Number of Clusters (k)')
plt.ylabel('Inertia')

# Silhouette Score Plot
plt.subplot(1, 2, 2)
plt.plot(k_values, silhouette_scores, marker='o')
plt.title('Silhouette Scores')
plt.xlabel('Number of Clusters (k)')
plt.ylabel('Silhouette Score')

plt.tight_layout()
plt.show()

# Step 5: Fit the K-Means model with the chosen k (e.g., k=3)
optimal_k = 3 # Choose based on the Elbow method or Silhouette score
kmeans = KMeans(n_clusters=optimal_k, random_state=42)
kmeans.fit(scaled_data)

# Step 6: Add cluster labels to the original DataFrame
data['cluster'] = kmeans.labels_

# Step 7: Visualize the clusters
plt.figure(figsize=(8, 6))
plt.scatter(data['price'], data['cardFinish'], c=data['cluster'],
            cmap='viridis', marker='o')
plt.scatter(kmeans.cluster_centers_[ :, 0], kmeans.cluster_centers_[ :, 1],
            s=300, c='red', marker='X') # Cluster centers
plt.title('K-Means Clustering')
plt.xlabel('Feature 1')
plt.ylabel('Feature 2')
plt.grid()
plt.show()

```

