

**Json server instalation:** npm install -g json-server

**Run:** json-server db.json

**db.json update (create own data)**

```
{
  "posts": [
    {
      "id": 1,
      "title": "first post",
      "author": "Bartek"
    },
    {
      "title": "Ogniem i mieczem",
      "author": "Jagoda",
      "id": 2
    },
    {
      "id": 3,
      "title": "actualization",
      "author": "Miczi"
    },
    {
      "title": "Czwarty post 426 Adele Island",
      "author": "Brennan Kerluke",
      "id": 5
    },
    {
      "title": "Czwarty post 081 Claire Crest",
      "author": "Ramiro Stracke",
      "id": 6
    },
    {
      "title": "Czwarty post 65219 Luettgen Plain",
      "author": "Agustin DuBuque",
      "id": 7
    }
  ],
  "comments": [
    {
      "id": 1,
      "body": "some comment1",
      "postId": 1
    },
    {
      "id": 2,
      "body": "some comment2",
      "postId": 2
    }
  ]
}
```

```

{
  "id": 3,
  "body": "some comment3",
  "postId": 3
}
],
"profile": {
  "name": "typicode"
}
}

```

### Creating two collections with requests



**Test creating** (with Postman documentation and snippets using), samples (can be other than in Postman's files):

- 1) Checking response (is 200?)

```

pm.test("status code is 200"), function() {
  pm.response.to.have.status(200);
});

```

- 2) Checking string in field ('fir' in 'title' at post id=1)

```

pm.test("Post contain specific title", function () {

```

```
pm.expect(pm.response.text()).to.include("fir");
});
```

### 3) Checking value in field ('first' in 'title' and 'Bartek' in 'author' in post id=1)

```
pm.test("Check title and author", function () {
    var jsonData = pm.response.json();
    pm.expect(jsonData.title).to.eql("first post");
    pm.expect(jsonData.author).to.eql("Bartek");
});
```

### 4) Adding test on collections level. Checking response (is 200, 201 or maybe 202?)

```
pm.test("Successful POST request", function () {
    pm.expect(pm.response.code).to.be.oneOf([200, 201, 202]);
});
```

## Variables adding

	VARIABLE	INITIAL VALUE ⓘ	CURRENT VALUE ⓘ
<input checked="" type="checkbox"/>	host	localhost:3000	localhost:3000
<input checked="" type="checkbox"/>	id	1	1

## Pre-request Script

Change to the id value (in environment variable id = 1, we want to change to 7). In card „Pre-request Script:

```
console.log("Before change variable id")
console.log(pm.environment.get("id"));
pm.environment.set("id", "7");
console.log("After change variable id")
console.log(pm.environment.get("id"));
```

## Displayed result by Tests

### 1) Displayed in console

```
var postId = pm.response.json().id;
pm.environment.set("postId", postId);
console.log("Post with id " + postId + " was created")
```