

Logic and lambda calculus

Simon Dobnik
CLASP & FloV
University of Gothenburg

CS VT-2023: March 27, 2023

Model theoretic semantics

- linguistic expressions \rightsquigarrow logic expressions
- logic expressions \rightsquigarrow objects in a model
- the model provides
 - a set of basic objects
 - an assignment of objects to the basic expressions of the (logic) language
- for each rule combining expressions in the natural language there is a rule in the logic language for which there is a corresponding rule operating on the model-theoretic objects

Model theoretic semantics

- linguistic expressions \rightsquigarrow logic expressions
- logic expressions \rightsquigarrow objects in a model
- the model provides
 - a set of basic objects
 - an assignment of objects to the basic expressions of the (logic) language
- for each rule combining expressions in the natural language there is a rule in the logic language for which there is a corresponding rule operating on the model-theoretic objects
- Formal languages:
 - Propositional logic
 - First order logic
 - Lambda calculus

Propositional logic



propositional-logic.ipynb

...predicate logic or predicate calculus

first-order-logic.ipynb


From linguistic structure to logic representations

- a turtle runs
- $\exists x[\text{turtle}(x) \wedge \text{run}(x)]$
- **a**: $\exists x[?(x) \wedge ?(x)]$


From linguistic structure to logic representations

- a turtle runs
- $\exists x[\text{turtle}(x) \wedge \text{run}(x)]$
- **a**: $\exists x[?(x) \wedge ?(x)]$
- every turtle runs
- $\forall x[\text{turtle}(x) \rightarrow \text{run}(x)]$
- **every**: $\forall x[?(x) \rightarrow ?(x)]$


A mismatch in structure




A mismatch in structure




A mismatch in structure




A mismatch in structure



A mismatch in structure



A mismatch in structure



Solution: typed functions and lambda calculus

- $f(x) = 2x$

Solution: typed functions and lambda calculus

- $f(x) = 2x$
- $\lambda x[2x]$
 $\lambda x.(2x)$
 $\lambda x.2x$

Solution: typed functions and lambda calculus

- $f(x) = 2x$
- $\lambda x[2x]$
 $\lambda x.(2x)$
 $\lambda x.2x$
- Applying arguments and β -equivalence/conversion:
 $\lambda x[2 \times x](3)$

Solution: typed functions and lambda calculus

- $f(x) = 2x$
- $\lambda x[2x]$
 $\lambda x.(2x)$
 $\lambda x.2x$
- Applying arguments and β -equivalence/conversion:
 $\lambda x[2 \times x](3)$
 2×3
 6

Solution: typed functions and lambda calculus

- $f(x) = 2x$
- $\lambda x[2x]$
 $\lambda x.(2x)$
 $\lambda x.2x$
- Applying arguments and β -equivalence/conversion:
 $\lambda x[2 \times x](3)$
 2×3
 6
- Arguments can be assigned (basic) types:
 $x : r$ where r is the type of real numbers

Solution: typed functions and lambda calculus

- $f(x) = 2x$
- $\lambda x[2x]$
 $\lambda x.(2x)$
 $\lambda x.2x$
- Applying arguments and β -equivalence/conversion:
 $\lambda x[2 \times x](3)$
 2×3
 6
- Arguments can be assigned (basic) types:
 $x : r$ where r is the type of real numbers
- Functions are also typed: $\langle r, r \rangle$
- Functions can have other functions as domains and targets:
 $\lambda y[\lambda x[2x + y]](3)$


Solution: typed functions and lambda calculus

- $f(x) = 2x$
- $\lambda x[2x]$
 $\lambda x.(2x)$
 $\lambda x.2x$
- Applying arguments and β -equivalence/conversion:
 $\lambda x[2 \times x](3)$
 2×3
 6
- Arguments can be assigned (basic) types:
 $x : r$ where r is the type of real numbers
- Functions are also typed: $\langle r, r \rangle$
- Functions can have other functions as domains and targets:
 $\lambda y[\lambda x[2x + y]](3)$
 $\lambda x[2x + 3](4)$


Solution: typed functions and lambda calculus

- $f(x) = 2x$
- $\lambda x[2x]$
 $\lambda x.(2x)$
 $\lambda x.2x$
- Applying arguments and β -equivalence/conversion:
 $\lambda x[2 \times x](3)$
 2×3
 6
- Arguments can be assigned (basic) types:
 $x : r$ where r is the type of real numbers
- Functions are also typed: $\langle r, r \rangle$
- Functions can have other functions as domains and targets:
 $\lambda y[\lambda x[2x + y]](3)$
 $\lambda x[2x + 3](4)$
 $2 \times 4 + 3$
 11


Solution for ? in the linguistic example




Solution for ? in the linguistic example




Solution for ? in the linguistic example




Solution for ? in the linguistic example




Solution for ? in the linguistic example




Solution for ? in the linguistic example




Solution for ? in the linguistic example




Solution for ? in the linguistic example




Solution for ? in the linguistic example



Solution for ? in the linguistic example



Balance correct composition AND semantic interpretation



Grammar with first-order logic + lambda calculus



lambda-calculus.ipynb

simple-sem.fcfg

CLASP

centre for
linguistic theory
and studies in probability

- Logic-based computational semantics can use model theory to evaluate natural language in a database

- Logic-based computational semantics can use model theory to evaluate natural language in a database
- This is done by translating natural language into an extension of first order logic employing the λ -calculus

- Logic-based computational semantics can use model theory to evaluate natural language in a database
- This is done by translating natural language into an extension of first order logic employing the λ -calculus
- These expressions can be then evaluated in the database

- Logic-based computational semantics can use model theory to evaluate natural language in a database
- This is done by translating natural language into an extension of first order logic employing the λ -calculus
- These expressions can be then evaluated in the database
- Translations to logic and lambda calculus can be done for a significant part of natural language

- Logic-based computational semantics can use model theory to evaluate natural language in a database
- This is done by translating natural language into an extension of first order logic employing the λ -calculus
- These expressions can be then evaluated in the database
- Translations to logic and lambda calculus can be done for a significant part of natural language
- There are, however, important constructions of natural language which go beyond first order logic

Further reading

- Bird et al. (2009), Chapter 10: Analyzing the meaning of sentences
- Manning (2005)
- Eisenstein (2019), Chapter 13: Logical Semantics
- Jurafsky and Martin (2000): Chapter 17: Representing meaning and Chapter 18: Computational semantics

Advanced

- Blackburn and Bos (2005): Chapter 1: First-order logic and Chapter 2: Lambda calculus
- Eijck and Unger (2010)

Acknowledgement



Some slides based on the slides by Robin Cooper.

References I

- Steven Bird, Ewan Klein, and Edward Loper. 2009. *Natural language processing with Python*. O'Reilly.
- Patrick Blackburn and Johan Bos. 2005. *Representation and inference for natural language. A first course in computational semantics*. CSLI Publications.
- J. van Eijck and Christina Unger. 2010. *Computational semantics with functional programming*. Cambridge University Press, Cambridge.
- Jacob Eisenstein. 2019. *Introduction to natural language processing*. Adaptive computation and machine learning. The MIT Press: Cambridge, MA and London, England.
- Dan Jurafsky and James H. Martin. 2000. *Speech and language processing: an introduction to natural language processing, computational linguistics, and speech recognition*. Prentice Hall, Upper Saddle River, N.J.
- Christopher D. Manning. 2005. *An introduction to formal computational semantics*. Lecture notes for CS224N/Ling 280.