Chapter 25

Defining the Risk Level for Exceptions

In specific situations, FT PharmaSuite records exceptions automatically based on the user interaction. The risk level of an exception controls the related signature privilege. It is defined with a separate configuration key for each situation:

Production Management Client

- Unlock and unregister an operation with the **Remove Object Locks** task: **LibraryHolder/apps-ebr-impl.jar/OperationUnlockedByAdminExcRisk** configuration key
- Append a workflow to a batch-specific order step or remove a workflow from a batch-specific order step with the **Manage Orders** use case: **LibraryHolder/services-S88-impl.jar/OrdersAssignedByAdminExcRisk** configuration key
- Reactivate a non-Dispense order step with the **Manage Orders** use case: **LibraryHolder/services-order-ifc.jar/UnitProcedureReactivatedByAdminExcRisk** configuration key
- Abort a non-Dispense order step with the **Manage Orders** use case: **LibraryHolder/services-order-ifc.jar/UnitProcedureAbortByAdminExcRisk** configuration key
- Abort an order step (unit procedure) with the **Manage Orders** use case: **LibraryHolder/services-order-ifc.jar/UnitProcedureFinalAbortByAdminExcRisk** configuration key
- Cancel an order/workflow or abort a unit procedure with the **Manage Orders/Workflows** use cases: **LibraryHolder/apps-ebr-impl.jar/OSCanceledWhilePhaseActiveExcRisk** configuration key
- Finish an order with aborted order steps with the **Manage Orders** use case: **LibraryHolder/services-order-ifc.jar/UnitProcedureFinishWithAbortedByAdminExcRisk** configuration key
- Force the execution transition of an order/workflow with the **Manage Orders/Workflows** use cases: **LibraryHolder/services-order-ifc.jar/ForceTransitionExecutionOrderExcRisk** configuration key

- Increase the quantity of an order step input with the **Manage Orders** use case: **LibraryHolder/services-order-ifc.jar/IncreaseOSIQuantityExcRisk** configuration key
- Add a new additional order step input with the **Manage Orders** use case: **LibraryHolder/services-order-ifc.jar/NewCorrectiveOSIExcRisk** configuration key
- Reactivate an aborted order step input with the **Manage Orders** use case: **LibraryHolder/services-order-ifc.jar/ReactivateOSIExcRisk** configuration key
- Replace a target sublot with the **Manage Orders** use case: **LibraryHolder/services-order-ifc.jar/ReplaceTargetSublotExcRisk** configuration key
- Order or workflow changes have been tracked with the **Manage Orders/Workflows** use cases: **LibraryHolder/services-order-ifc.jar/OrderChangesExceptionRisk** configuration key
- Manually release an order step input lock with the **Manage Orders** use case: **LibraryHolder/services-order-ifc.jar/ReleaseOSILockExcRisk** configuration key

Production Execution Client

- Append a workflow to a batch-specific order step: **LibraryHolder/services-S88-impl.jar/AppendWorkflowsToOrderInPECExcRisk** configuration key
- Append a workflow from a unit procedure context menu to an order step. **LibraryHolder/services-S88-impl.jar/AppendWorkflowsFromRtUnitProcedureInPECExcRisk** configuration key
- Cancel an exception: **LibraryHolder/apps-ebr-impl.jar/CanceledExceptionRisk** configuration key
- Cancel a workflow: **LibraryHolder/services-S88-impl.jar/CancelWorkflowInPECExcRisk** configuration key
- Creation of a new run of an ETO template failed since the TOM is not available: **LibraryHolder/services-eto-impl.jar/AutomaticExceptionOnFailureAtCreationOfRunOfETOExcRisk** configuration key

- Applies to the recovery capabilities within the Production Execution Client.
  - Abort an active phase: **LibraryHolder/apps-ebr-ifc.jar/PhaseExecutionSkippedExcRisk** configuration key
  - Start the repair mode of a phase and edit process parameters in the repair mode of a phase: **LibraryHolder/apps-ebr-ifc.jar/PhaseRepairModeExcRisk** configuration key
- Restart an operation that runs on an OE server: **LibraryHolder/apps-ebr-impl.jar/AutomaticExceptionOnResumeOfServerRunOperationExcRisk** configuration key
- Restart of an ETO template that runs on the TOM server: **LibraryHolder/services-eto-impl.jar/AutomaticExceptionOnResumeOfTemplateExcRisk** configuration key
- Abort a (non-ETO-related) operation: **LibraryHolder/apps-ebr-impl.jar/AbortOperationExcRisk** configuration key
- The user who signs for a sequential phase completion signature has already signed for a previous phase completion within the operation: **LibraryHolder/apps-ebr-impl.jar/SequentialPhaseCompletionUserAlreadySignedExcRisk** configuration key
- A room-specific status transition fails. Applies to system phase building blocks of the Dispense package that do not hold the **Status transition failed** process parameter.
  LibraryHolder/apps-ebr-impl.jar/RoomTriggerStatusTransitionFailureExcRisk configuration key
  The exception text is taken from the **pec_ExceptionMessage** message pack and the **roomTriggerStatusTransitionFailureException_Msg** message ID.
- Identify a source sublot that is associated with a container entity that is not in the **Approved** status with the **D Identify material** phase
  Libraries/apps-ebr-impl.jar/ContainerStatusFailureExcRisk configuration key
  The exception text is taken from the **wd_MaterialIdentification<version>** message pack and the **containerStatusFailureException_Msg** message ID.

Data Manager

- Force unbinding of an equipment entity:
  LibraryHolder/apps-masterdata-impl.jar/ForceUnbindEquipmentExcRisk configuration key
  The exception text is taken from the **srv_s88equipment.exceptions** message pack and the **ForceUnbindEquipmentException_Msg** message ID.
- Save changes of runtime data, such as runtime properties, graph-related data (e.g. status, expiry date), and grouping situations, of a bound equipment entity in read-only status:
  LibraryHolder/services-s88equipment-impl.jar/SaveReadOnlyEquipmentExcRisk configuration key
  The exception text is taken from the **srv_s88equipment.exceptions** message pack and the **SaveReadOnlyEquipmentException_Msg**, **SaveReadOnlyEquipmentChanges_Title**, **SaveReadOnlyEquipmentDetail_Label**, **SaveReadOnlyEquipmentGroupingDetailAddedToParent_Label**, **SaveReadOnlyEquipmentGroupingDetailChildAdded_Label**, **SaveReadOnlyEquipmentGroupingDetailChildRemoved_Label**, and **SaveReadOnlyEquipmentGroupingDetailRemovedFromParent_Label** message IDs.

FT PharmaSuite Administrator Console

- Hold or resume an active runtime operation:
  LibraryHolder/apps-ebr-impl.jar/HoldOrResumeOESOperationExcRisk configuration key
- Unload or reload running procedures (order, workflow):
  LibraryHolder/apps-ebr-impl.jar/UnloadOrderFromEBRExcRisk configuration key

For details, see "Configuration Keys of FT PharmaSuite" in Volume 4 of the "Technical Guide Configuration and Extension" [A5] (page 501).