



EQUIPO 3

Estudiante:

Víctor de Jesús Ramírez Marte

Matrícula:

2025-1594

Asignatura:

Conmutación y Enrutamiento

Tema:

Producto 1: Implementación de Red Empresarial

Profesor:

Onel Luis Pelegrino

Fecha:

25/6/2026

R1-core

Last configuration change at 05:22:07 UTC Thu Jun 11 2026

version 15.4

service timestamps debug datetime msec

service timestamps log datetime msec

no service password-encryption

hostname R1-CORE

boot-start-marker

boot-end-marker

no aaa new-model

mmi polling-interval 60

no mmi auto-configure

no mmi pvc

mmi snmp-timeout 180

ip cef

no ipv6 cef

multilink bundle-name authenticated

redundancy

interface Ethernet0/0

no shutdown

ip address 172.20.11.1 255.255.255.252

interface Ethernet0/1

no shutdown

ip address 172.20.11.5 255.255.255.252

interface Ethernet0/2

no shutdown

no ip address

shutdown

interface Ethernet0/3

no shutdown

no ip address

shutdown

interface Serial1/0

no shutdown

ip address 172.20.10.145 255.255.255.252

serial restart-delay 0

clock rate 64000

interface Serial1/1

no shutdown

no ip address

shutdown

serial restart-delay 0

```
interface Serial1/2
no shutdown
no ip address
shutdown
serial restart-delay 0
interface Serial1/3
no shutdown
no ip address
shutdown
serial restart-delay 0
router ospf 1
router-id 10.10.10.10
network 172.20.10.144 0.0.0.3 area 0
network 172.20.11.0 0.0.0.3 area 0
network 172.20.11.4 0.0.0.3 area 0
ip forward-protocol nd
no ip http server
no ip http secure-server
control-plane
line con 0
logging synchronous
line aux 0
line vty 0 4
login
transport input none
end
```

R2

```
Last configuration change at 05:46:12 UTC Thu Jun 11 2026
version 15.4
service timestamps debug datetime msec
service timestamps log datetime msec
no service password-encryption
hostname R2
boot-start-marker
boot-end-marker
no aaa new-model
mmi polling-interval 60
no mmi auto-configure
no mmi pvc
mmi snmp-timeout 180
```

```
ip cef
no ipv6 cef
multilink bundle-name authenticated
redundancy
interface Ethernet0/0
  no shutdown
  no ip address
interface Ethernet0/0.60
  no shutdown
  encapsulation dot1Q 60
  ip address 172.20.9.129 255.255.255.128
interface Ethernet0/0.70
  no shutdown
  encapsulation dot1Q 70
  ip address 172.20.9.1 255.255.255.128
interface Ethernet0/1
  no shutdown
  no ip address
interface Ethernet0/1.80
  no shutdown
  encapsulation dot1Q 80
  ip address 172.20.10.1 255.255.255.192
interface Ethernet0/2
  no shutdown
  no ip address
  shutdown
interface Ethernet0/3
  no shutdown
  no ip address
  shutdown
interface Serial1/0
  no shutdown
  ip address 172.20.10.146 255.255.255.252
  serial restart-delay 0
interface Serial1/1
  no shutdown
  no ip address
  shutdown
  serial restart-delay 0
interface Serial1/2
  no shutdown
  no ip address
  shutdown
  serial restart-delay 0
```

```
interface Serial1/3
no shutdown
no ip address
shutdown
serial restart-delay 0
router ospf 1
router-id 20.20.20.20
network 172.20.9.0 0.0.0.127 area 1
network 172.20.9.128 0.0.0.127 area 1
network 172.20.10.0 0.0.0.63 area 1
network 172.20.10.144 0.0.0.3 area 0
ip forward-protocol nd
no ip http server
no ip http secure-server
control-plane
line con 0
logging synchronous
line aux 0
line vty 0 4
login
transport input none
end
```

SW

```
Last configuration change at 05:45:29 UTC Thu Jun 11 2026
version 15.2
service timestamps debug datetime msec
service timestamps log datetime msec
no service password-encryption
service compress-config
hostname SW-DATACENTER
boot-start-marker
boot-end-marker
no aaa new-model
vtp domain EMPRESA
vtp mode transparent
ip cef
no ipv6 cef
spanning-tree mode rapid-pvst
spanning-tree extend system-id
vlan internal allocation policy ascending
vlan 80
name DATACENTER
interface Ethernet0/0
```

```
no shutdown
switchport trunk encapsulation dot1q
switchport mode trunk
interface Ethernet0/1
no shutdown
switchport access vlan 80
switchport mode access
spanning-tree portfast edge
interface Ethernet0/2
no shutdown
interface Ethernet0/3
no shutdown
ip forward-protocol nd
no ip http server
no ip http secure-server
control-plane
line con 0
logging synchronous
line aux 0
line vty 0 4
end
```

SWA13

```
Last configuration change at 05:44:46 UTC Thu Jun 11 2026
version 15.2
service timestamps debug datetime msec
service timestamps log datetime msec
no service password-encryption
service compress-config
hostname SWA13
boot-start-marker
boot-end-marker
no aaa new-model
vtp domain EMPRESA
vtp mode transparent
ip cef
no ipv6 cef
spanning-tree mode rapid-pvst
spanning-tree extend system-id
vlan internal allocation policy ascending
vlan 60
name FINANZAS
vlan 70
name ACADEMICOS
```

```
interface Ethernet0/0
  no shutdown
  switchport trunk encapsulation dot1q
  switchport mode trunk
interface Ethernet0/1
  no shutdown
interface Ethernet0/2
  no shutdown
interface Ethernet0/3
  no shutdown
interface Ethernet1/0
  no shutdown
  switchport access vlan 70
  switchport mode access
  spanning-tree portfast edge
interface Ethernet1/1
  no shutdown
interface Ethernet1/2
  no shutdown
interface Ethernet1/3
  no shutdown
interface Ethernet2/0
  no shutdown
  switchport access vlan 60
  switchport mode access
  spanning-tree portfast edge
interface Ethernet2/1
  no shutdown
interface Ethernet2/2
  no shutdown
interface Ethernet2/3
  no shutdown
ip forward-protocol nd
no ip http server
no ip http secure-server
control-plane
line con 0
  logging synchronous
line aux 0
line vty 0 4
end
```

SWM1

Last configuration change at 08:00:28 UTC Thu Jun 11 2026
version 15.2
service timestamps debug datetime msec
service timestamps log datetime msec
no service password-encryption
service compress-config
hostname SWM1
boot-start-marker
boot-end-marker
no aaa new-model
ip cef
no ipv6 cef
spanning-tree mode rapid-pvst
spanning-tree extend system-id
spanning-tree vlan 1,10,20,30,40,50,60,70,80 priority 24576
vlan internal allocation policy ascending
interface Port-channel1
no shutdown
switchport trunk encapsulation dot1q
switchport mode trunk
interface Ethernet0/0
no shutdown
no switchport
ip address 172.20.11.2 255.255.255.252
duplex auto
interface Ethernet0/1
no shutdown
switchport trunk encapsulation dot1q
switchport mode trunk
channel-group 1 mode active
interface Ethernet0/2
no shutdown
switchport trunk encapsulation dot1q
switchport mode trunk
channel-group 1 mode active
interface Ethernet0/3
no shutdown
switchport trunk encapsulation dot1q
switchport mode trunk
channel-group 1 mode active
interface Ethernet1/0
no shutdown
switchport trunk encapsulation dot1q

```
switchport mode trunk
interface Ethernet1/1
no shutdown
switchport trunk encapsulation dot1q
switchport mode trunk
interface Ethernet1/2
no shutdown
switchport trunk encapsulation dot1q
switchport mode trunk
interface Ethernet1/3
no shutdown
interface Vlan10
no shutdown
ip address 172.20.8.2 255.255.255.0
standby 10 ip 172.20.8.1
standby 10 priority 110
standby 10 preempt
interface Vlan20
no shutdown
ip address 172.20.0.2 255.255.248.0
standby 20 ip 172.20.0.1
standby 20 priority 110
standby 20 preempt
interface Vlan30
no shutdown
ip address 172.20.10.66 255.255.255.224
standby 30 ip 172.20.10.65
standby 30 priority 110
standby 30 preempt
interface Vlan40
no shutdown
ip address 172.20.10.98 255.255.255.224
standby 40 ip 172.20.10.97
standby 40 priority 110
standby 40 preempt
interface Vlan50
no shutdown
ip address 172.20.10.130 255.255.255.240
standby 50 ip 172.20.10.129
standby 50 priority 110
standby 50 preempt
router ospf 1
router-id 1.1.1.1
passive-interface Vlan10
```

```
passive-interface Vlan20
passive-interface Vlan30
passive-interface Vlan40
passive-interface Vlan50
network 172.20.0.0 0.0.7.255 area 0
network 172.20.8.0 0.0.0.255 area 0
network 172.20.10.64 0.0.0.31 area 0
network 172.20.10.96 0.0.0.31 area 0
network 172.20.10.128 0.0.0.15 area 0
network 172.20.11.0 0.0.0.3 area 0
ip forward-protocol nd
no ip http server
no ip http secure-server
control-plane
line con 0
  logging synchronous
line aux 0
line vty 0 4
end
```

SWM2

```
Last configuration change at 21:22:50 UTC Tue Jun 16 2026
version 15.2
service timestamps debug datetime msec
service timestamps log datetime msec
no service password-encryption
service compress-config
hostname SWM2
boot-start-marker
boot-end-marker
no aaa new-model
ip cef
ipv6 unicast-routing
ipv6 cef
spanning-tree mode rapid-pvst
spanning-tree extend system-id
spanning-tree vlan 1,10,20,30,40,50,60,70,80 priority 28672
vlan internal allocation policy ascending
interface Port-channel1
  no shutdown
  switchport trunk encapsulation dot1q
  switchport mode trunk
interface Ethernet0/0
  no shutdown
```

```
no switchport
ip address 172.20.11.6 255.255.255.252
duplex auto
interface Ethernet0/1
no shutdown
switchport trunk encapsulation dot1q
switchport mode trunk
channel-group 1 mode active
interface Ethernet0/2
no shutdown
switchport trunk encapsulation dot1q
switchport mode trunk
channel-group 1 mode active
interface Ethernet0/3
no shutdown
switchport trunk encapsulation dot1q
switchport mode trunk
channel-group 1 mode active
interface Ethernet1/0
no shutdown
switchport trunk encapsulation dot1q
switchport mode trunk
interface Ethernet1/1
no shutdown
switchport trunk encapsulation dot1q
switchport mode trunk
interface Ethernet1/2
no shutdown
switchport trunk encapsulation dot1q
switchport mode trunk
interface Ethernet1/3
no shutdown
interface Vlan10
no shutdown
ip address 172.20.8.3 255.255.255.0
standby 10 ip 172.20.8.1
standby 10 preempt
ipv6 address 2001:25:20:10::3/64
interface Vlan20
no shutdown
ip address 172.20.0.3 255.255.248.0
standby 20 ip 172.20.0.1
standby 20 preempt
ipv6 address 2001:25:20:20::3/64
```

```
interface Vlan30
no shutdown
ip address 172.20.10.67 255.255.255.224
standby 30 ip 172.20.10.65
standby 30 preempt
ipv6 address 2001:25:20:30::3/64
interface Vlan40
no shutdown
ip address 172.20.10.99 255.255.255.224
standby 40 ip 172.20.10.97
standby 40 preempt
ipv6 address 2001:25:20:40::3/64
interface Vlan50
no shutdown
ip address 172.20.10.131 255.255.255.240
standby 50 ip 172.20.10.129
standby 50 preempt
ipv6 address 2001:25:20:50::3/64
router ospf 1
router-id 2.2.2.2
area 10 stub
passive-interface Vlan10
passive-interface Vlan20
passive-interface Vlan30
passive-interface Vlan40
passive-interface Vlan50
network 172.20.0.0 0.0.7.255 area 0
network 172.20.8.0 0.0.0.255 area 0
network 172.20.10.64 0.0.0.31 area 0
network 172.20.10.96 0.0.0.31 area 0
network 172.20.10.128 0.0.0.15 area 0
network 172.20.11.4 0.0.0.3 area 0
ip forward-protocol nd
no ip http server
no ip http secure-server
control-plane
line con 0
logging synchronous
line aux 0
line vty 0 4
login
end
```

SWAC1

Last configuration change at 21:19:04 UTC Tue Jun 16 2026
version 15.2
service timestamps debug datetime msec
service timestamps log datetime msec
no service password-encryption
service compress-config
hostname SWAC1
boot-start-marker
boot-end-marker
no aaa new-model
ip cef
no ipv6 cef
spanning-tree mode rapid-pvst
spanning-tree extend system-id
vlan internal allocation policy ascending
interface Ethernet0/0
no shutdown
switchport trunk encapsulation dot1q
switchport mode trunk
interface Ethernet0/1
no shutdown
switchport trunk encapsulation dot1q
switchport mode trunk
interface Ethernet0/2
no shutdown
interface Ethernet0/3
no shutdown
interface Ethernet1/0
no shutdown
switchport access vlan 10
switchport mode access
spanning-tree portfast edge
interface Ethernet1/1
no shutdown
interface Ethernet1/2
no shutdown
interface Ethernet1/3
no shutdown
interface Ethernet2/0
no shutdown
interface Ethernet2/1
no shutdown
interface Ethernet2/2

```
no shutdown
interface Ethernet2/3
  no shutdown
ip forward-protocol nd
no ip http server
no ip http secure-server
control-plane
line con 0
  logging synchronous
line aux 0
line vty 0 4
  login
end
```

SWAC2

```
Last configuration change at 21:18:58 UTC Tue Jun 16 2026
version 15.2
service timestamps debug datetime msec
service timestamps log datetime msec
no service password-encryption
service compress-config
hostname SWAC2
boot-start-marker
boot-end-marker
no aaa new-model
ip cef
no ipv6 cef
spanning-tree mode rapid-pvst
spanning-tree extend system-id
vlan internal allocation policy ascending
interface Ethernet0/0
  no shutdown
  switchport trunk encapsulation dot1q
  switchport mode trunk
interface Ethernet0/1
  no shutdown
  switchport trunk encapsulation dot1q
  switchport mode trunk
interface Ethernet0/2
  no shutdown
interface Ethernet0/3
  no shutdown
interface Ethernet1/0
  no shutdown
```

```
interface Ethernet1/1
  no shutdown
interface Ethernet1/2
  no shutdown
interface Ethernet1/3
  no shutdown
interface Ethernet2/0
  no shutdown
  switchport access vlan 20
  switchport mode access
  spanning-tree portfast edge
interface Ethernet2/1
  no shutdown
interface Ethernet2/2
  no shutdown
interface Ethernet2/3
  no shutdown
ip forward-protocol nd
no ip http server
no ip http secure-server
control-plane
line con 0
  logging synchronous
line aux 0
line vty 0 4
  login
end
```

SWAC3

```
Last configuration change at 21:18:55 UTC Tue Jun 16 2026
version 15.2
service timestamps debug datetime msec
service timestamps log datetime msec
no service password-encryption
service compress-config
hostname SWAC3
boot-start-marker
boot-end-marker
no aaa new-model
ip cef
no ipv6 cef
spanning-tree mode rapid-pvst
spanning-tree extend system-id
vlan internal allocation policy ascending
```

```
interface Ethernet0/0
  no shutdown
  switchport trunk encapsulation dot1q
  switchport mode trunk
interface Ethernet0/1
  no shutdown
  switchport trunk encapsulation dot1q
  switchport mode trunk
interface Ethernet0/2
  no shutdown
interface Ethernet0/3
  no shutdown
interface Ethernet1/0
  no shutdown
interface Ethernet1/1
  no shutdown
interface Ethernet1/2
  no shutdown
interface Ethernet1/3
  no shutdown
interface Ethernet2/0
  no shutdown
interface Ethernet2/1
  no shutdown
interface Ethernet2/2
  no shutdown
interface Ethernet2/3
  no shutdown
interface Ethernet3/0
  no shutdown
  switchport access vlan 30
  switchport mode access
  spanning-tree portfast edge
interface Ethernet3/1
  no shutdown
interface Ethernet3/2
  no shutdown
interface Ethernet3/3
  no shutdown
ip forward-protocol nd
no ip http server
no ip http secure-server
control-plane
line con 0
```

```
logging synchronous
line aux 0
line vty 0 4
  login
end
```