

Simulation Experiment Results

Victor Tsang (z5209633)

2022-11-04

Load in the results

```
library(knitr)
library(tidyverse)
library(latex2exp)

load("../data/synthetic-data.RData")
attach(synthetic.data.config)

estimates = readRDS("../data/sim_exp-estimate_extinction_results.RDS")
```

```
# Point estimates
performance.point_estimates = estimates %>%
  filter(!is.na(point)) %>%
  group_by(error_factor, method) %>%
  summarise(MSE_000 = mean((point - theta.true)^2)/1000,
            bias = mean(point)-theta.true,
            variance_000 = var(point)/1000,
            avg_runtime = mean(point_runtime))
```

```
## 'summarise()' has grouped output by 'error_factor'. You can override using the
## '.groups' argument.
```

```
kable(performance.point_estimates)
```

error_factor	method	MSE_000	bias	variance_000	avg_runtime
0.0	BA-MLE	234.5607	-0.9379571	234.7946	0.0000219
0.0	GRIWM	248.9280	145.5280000	227.9776	2.3971124
0.0	MINMI	247.4576	139.4092643	228.2509	0.0000109
0.0	MLE	438.6601	475.2971837	212.9656	0.0000173
0.0	SI-UGM	248.9648	150.6138962	226.5068	4.7065676
0.0	STRAUSS	234.8453	-0.7152842	235.0799	0.0000196
0.5	BA-MLE	244.0353	-22.0990141	243.7908	0.0000253
0.5	GRIWM	246.6816	107.0420000	235.4590	2.4313070
0.5	MINMI	250.6573	116.6643007	237.2840	0.0004708
0.5	MLE	428.0602	455.1437961	221.1254	0.0000192
0.5	SI-UGM	250.7756	117.2579537	237.2634	2.3305912
0.5	STRAUSS	245.5802	-22.8493286	245.3034	0.0000251

error_factor	method	MSE_000	bias	variance_000	avg_runtime
1.0	BA-MLE	365.6242	-45.7554617	363.8946	0.0000216
1.0	GRIWM	345.5350	46.5880000	343.7083	2.4390745
1.0	MINMI	373.1166	104.2616256	362.6088	0.0005133
1.0	MLE	516.8878	432.6138460	330.0631	0.0000176
1.0	SI-UGM	371.3002	115.2129004	358.3845	1.9374115
1.0	STRAUSS	366.4727	-50.5383309	364.2829	0.0000206
2.0	BA-MLE	542.9867	-233.5215118	488.9434	0.0000210
2.0	GRIWM	496.9831	-265.7930000	426.7639	2.4381696
2.0	MINMI	508.2312	21.2383726	508.2884	0.0005367
2.0	MLE	507.4514	253.7890364	443.4860	0.0000176
2.0	SI-UGM	501.5358	65.3780494	497.7593	1.6800792
2.0	STRAUSS	553.8156	-247.9251968	492.8416	0.0000199
4.0	BA-MLE	1712.8705	-817.7749246	1045.1599	0.0000204
4.0	GRIWM	2112.6249	-1159.8510000	768.1387	2.4349672
4.0	MINMI	1157.0951	-174.3894207	1127.8112	0.0005682
4.0	MLE	1038.6355	-302.6427854	947.9908	0.0000176
4.0	SI-UGM	1130.9207	-28.3481103	1131.2483	1.3896884
4.0	STRAUSS	1789.1141	-862.4420005	1046.3543	0.0000199

```
# Confidence Intervals
performance.conf_int_estimates = estimates %>%
  filter(!is.na(conf_int_runtime)) %>%
  mutate(width = upper - lower,
         contains_theta = ifelse(theta.true > lower & theta.true < upper, 1, 0)) %>%
  group_by(error_factor, method) %>%
  summarise(Coverage = mean(contains_theta),
            `Average Width` = mean(width),
            `Average Runtime` = mean(conf_int_runtime)) %>%
  ungroup() %>%
  arrange(desc(Coverage), `Average Width`, `Average Runtime`)# %>%
```

'summarise()' has grouped output by 'error_factor'. You can override using the
'.groups' argument.

```
# mutate(Coverage = scales::percent(Coverage, accuracy=0.1))
kable(performance.conf_int_estimates)
```

error_factor	method	Coverage	Average Width	Average Runtime
0.0	SI-UGM	0.973	1961.144	4.7065676
0.5	SI-UGM	0.962	2091.093	2.3305912
0.5	MINMI	0.959	2077.084	0.0012776
2.0	SI-UGM	0.949	2964.298	1.6800792
4.0	SI-UGM	0.949	4405.261	1.3896884
2.0	MINMI	0.947	2936.889	0.0013949
4.0	MINMI	0.947	4337.389	0.0014173
0.0	MINMI	0.945	1917.160	0.0000319
1.0	SI-UGM	0.937	2351.533	1.9374115
1.0	MINMI	0.933	2326.753	0.0012473
2.0	GRIWM	0.811	1947.517	2.4381696

error_factor	method	Coverage	Average Width	Average Runtime
4.0	GRIWM	0.707	3643.956	2.4349672
1.0	GRIWM	0.699	1046.012	2.4390745
0.5	GRIWM	0.507	547.268	2.4313070
0.0	GRIWM	0.000	0.000	2.3971124
0.0	GB-RM	NA	NA	0.0207461
4.0	GB-RM	NA	NA	0.0223523
1.0	GB-RM	NA	NA	0.0226802
2.0	GB-RM	NA	NA	0.0228241
0.5	GB-RM	NA	NA	0.0235220

Point Estimates

```
library(kableExtra)
```

```
## Warning: package 'kableExtra' was built under R version 4.2.2
```

```
##
```

```
## Attaching package: 'kableExtra'
```

```
## The following object is masked from 'package:dplyr':
```

```
##
```

```
## group_rows
```

```
for (err in error_factors) {
  experiment.results.kbl = performance.point_estimates %>%
    filter(error_factor == err) %>%
    mutate(across(!c(method, avg_runtime), round)) %>%
    mutate(avg_runtime=round(avg_runtime, digits=5)) %>%
    arrange(MSE_000) %>%
    ungroup() %>%
    select(-error_factor) %>%
    kable(booktabs=T, col.names = c("", "(000's years)", "(years)", "(000's years)", "(seconds)"), form
    add_header_above(c("Method" = 1, "MSE" = 1, "Bias"=1, "Variance"=1, "Average Runtime"=1))
  writeLines(experiment.results.kbl, paste0("../figures/table-sim-exp-point-error", err, ".tex"))
  print(experiment.results.kbl)
}
```

Method	MSE	Bias	Variance	Average Runtime
	(000's years)	(years)	(000's years)	(seconds)
BA-MLE	235	-1	235	0.00002
STRAUSS	235	-1	235	0.00002
MINMI	247	139	228	0.00001
GRIWM	249	146	228	2.39711
SI-UGM	249	151	227	4.70657
MLE	439	475	213	0.00002

Method	MSE	Bias	Variance	Average Runtime
	(000's years)	(years)	(000's years)	(seconds)
BA-MLE	244	-22	244	0.00003
STRAUSS	246	-23	245	0.00003
GRIWM	247	107	235	2.43131
MINMI	251	117	237	0.00047
SI-UGM	251	117	237	2.33059
MLE	428	455	221	0.00002


Method	MSE	Bias	Variance	Average Runtime
	(000's years)	(years)	(000's years)	(seconds)
GRIWM	346	47	344	2.43907
BA-MLE	366	-46	364	0.00002
STRAUSS	366	-51	364	0.00002
SI-UGM	371	115	358	1.93741
MINMI	373	104	363	0.00051
MLE	517	433	330	0.00002

Method	MSE	Bias	Variance	Average Runtime
	(000's years)	(years)	(000's years)	(seconds)
GRIWM	497	-266	427	2.43817
SI-UGM	502	65	498	1.68008
MLE	507	254	443	0.00002
MINMI	508	21	508	0.00054
BA-MLE	543	-234	489	0.00002
STRAUSS	554	-248	493	0.00002

Method	MSE	Bias	Variance	Average Runtime
	(000's years)	(years)	(000's years)	(seconds)
MLE	1039	-303	948	0.00002
SI-UGM	1131	-28	1131	1.38969
MINMI	1157	-174	1128	0.00057
BA-MLE	1713	-818	1045	0.00002
STRAUSS	1789	-862	1046	0.00002
GRIWM	2113	-1160	768	2.43497

```
performance.point_estimates %>%
  filter(!(method %in% c("GRIWM", "GRIWM-corrected"))) %>%
  ggplot(aes(x=error_factor, y=MSE_000, colour=method)) +
  geom_point() +
  geom_line() +
  theme_minimal() +
  # guides(colour="none") +
  # annotate("text", x=4.18, y=c(1950, 1750, 1300, 1200, 1100), label=c("BA-MLE", "Strauss", "MINMI", "MLE", "GRIWM"),
  labs(x="Error Factor", y=NULL, title="MSE ('000 years) of each Method")
```

MSE ('000 years) of each Method



```
#+ scale_y_continuous(trans='log10')
```

Confidence Intervals

```
options(scipen=9)
for (metric in c("Coverage", "Average Width", "Average Runtime")) {
  experiment.results.kbl = performance.conf_int_estimates %>%
    select(c(method, error_factor, one_of(metric))) %>%
    pivot_wider(id_cols = method,
                 names_from=error_factor,
                 values_from=one_of(metric),
                 names_prefix=paste(metric, "| error = sigma*")) %>%
    arrange(!syms(paste(metric, "| error = sigma*0"))) %>%
    kable(booktabs=T, col.names = c("Method", paste0(c(0,0.5,1,2,4), r"{$\sigma$}")), format="latex",
        # kable_styling(full_width = F) %>%
    add_header_above(c(" " = 1, metric = 4))

  print(experiment.results.kbl)
  writeLines(experiment.results.kbl, paste0("../figures/table-sim-exp-conf-int-", str_replace(tolower(m
})
```

Method	metric				
	$0*\sigma$	$0.5*\sigma$	$1*\sigma$	$2*\sigma$	$4*\sigma$
SI-UGM	0.973	0.962	0.949	0.949	0.937
MINMI	0.945	0.959	0.947	0.947	0.933
GRIWM	0.000	0.507	0.811	0.707	0.699
GB-RM	NA	NA	NA	NA	NA


Method	metric				
	$0*\sigma$	$0.5*\sigma$	$1*\sigma$	$2*\sigma$	$4*\sigma$
SI-UGM	1961.144	2091.093	2964.298	4405.261	2351.533
MINMI	1917.160	2077.084	2936.889	4337.389	2326.753
GRIWM	0.000	547.268	1947.517	3643.956	1046.012
GB-RM	NA	NA	NA	NA	NA

Method	metric				
	$0*\sigma$	$0.5*\sigma$	$1*\sigma$	$2*\sigma$	$4*\sigma$
SI-UGM	4.7065676	2.3305912	1.6800792	1.3896884	1.9374115
MINMI	0.0000319	0.0012776	0.0013949	0.0014173	0.0012473
GRIWM	2.3971124	2.4313070	2.4381696	2.4349672	2.4390745
GB-RM	0.0207461	0.0235220	0.0228241	0.0223523	0.0226802

```

estimates %>%
  filter(!is.na(lower)) %>%
  filter(error_factor==1) %>%
  select(method, lower, upper) %>%
  pivot_longer(cols=c(lower, upper)) %>%
  filter(!is.na(value)) %>%
  ggplot(aes(x=value, fill=name)) +
  geom_density(alpha=0.25) +
  geom_vline(aes(xintercept=theta.true)) +
  facet_wrap(method ~ .) +
  theme_minimal() +
  labs()

```



```
metric="Coverage"
performance.conf_int_estimates %>%
  select(c(method, error_factor, one_of(metric))) %>%
  pivot_wider(id_cols = method,
              names_from=error_factor,
              values_from=one_of(metric),
              names_prefix=paste(metric, "| error = sigma*")) %>%
  arrange(!syms(paste(metric, "| error = sigma*0")))
```

```
## # A tibble: 4 x 6
##   method 'Coverage | error = sigma*0' Coverage | error~1 Cover~2 Cover~3 Cover~4
##   <chr>                                <dbl>          <dbl>    <dbl>    <dbl>    <dbl>
## 1 SI-UGM                               0.973          0.962    0.949    0.949    0.937
## 2 MINMI                                0.945          0.959    0.947    0.947    0.933
## 3 GRIWM                                 0            0.507    0.811    0.707    0.699
## 4 GB-RM                                NA             NA       NA       NA       NA
## # ... with abbreviated variable names 1: 'Coverage | error = sigma*0.5',
## #   2: 'Coverage | error = sigma*2', 3: 'Coverage | error = sigma*4',
## #   4: 'Coverage | error = sigma*1'
```