

Constituency Parsing

SLP3 Ch 12, 13; INLP Ch 9, 10


Syntax

- ▶ Syntax studies rules and processes that govern the structure of sentences
- ▶ Syntax is only about structure, not about meaning
 - ▶ A sentence can be syntactically well-formed but semantically ill-formed
 - ▶ Colorless green ideas sleep furiously.
 - ▶ Two semantically identical sentences can have different syntactic structures
 - ▶ A dog is chasing a cat.
 - ▶ A cat is being chased by a dog.




Constituent parse tree

- ▶ Also called a phrase structure parse
- ▶ Each non-leaf node represents a phrase
 - ▶ S: sentence
 - ▶ NP: noun phrase
 - ▶ VP: verb phrase
 - ▶ ...



Dependency parse tree

- ▶ Each arc represents a binary dependency relation between two words
 - ▶ Relations may be typed (labeled)
 - ▶ Ex. Subject relation between a verb and a noun






Parse tree scoring

- ▶ Goal: assign a probability or score to each parse tree of a sentence
- ▶ Why?
 - ▶ Disambiguation!
 - ▶ A natural language sentence may have many possible parses



Ambiguity

- ▶ Astronomers saw stars with ears.



Parse tree scoring

- ▶ Goal: assign a probability or score to each parse tree of a sentence
- ▶ Common approach:
 - ▶ Decompose a parse tree into many parts
 - ▶ Score each part
 - ▶ Take the sum or product




Parsing

- ▶ Goal: given a sentence, find its highest scored parse tree
- ▶ Common approaches:
 - ▶ Dynamic programming
 - ▶ Greedy search / beam search




Learning


Training Corpus



Learning



Grammar / Parser



- ▶ Supervised Methods
 - ▶ Rely on a training corpus of sentences annotated with parses (treebank)
- ▶ Unsupervised Methods (Grammar Induction)
 - ▶ Do not require annotated data





Context-Free Grammars



Constituency

▶ Constituents

- ▶ Groups of words within sentences can be shown to act as single units.
- ▶ Ex: (The fox)(jumps(over(the dog)))

▶ These units form coherent classes

- ▶ Units in the same class behave in similar ways
 - ▶ ...with respect to their *internal* structure
 - ▶ ...and with respect to other (*external*) units in the language
- ▶ E.g., noun phrases



Constituency

- ▶ For example, it makes sense to say that the following are all *noun phrases* in English...

Harry the Horse
the Broadway coppers
they

a high-class spot such as Mindy's
the reason he comes into the Hot Box
three parties from Brooklyn

- ▶ Why?
 - ▶ Similar internal structures
 - ▶ e.g., determiner + modifier + noun + modifier
 - ▶ They can all precede verbs (external evidence)



Grammars and Constituency

- ▶ Grammar
 - ▶ the set of constituents and the rules that govern how they combine
- ▶ Lots of different theories of grammar
- ▶ Context-free grammars (CFGs)
 - ▶ Also known as: Phrase structure grammars
 - ▶ One of the simplest and most basic grammar formalisms



Context-Free Grammars

- ▶ A context-free grammar has four components
 - ▶ A set Σ of terminals (words)
 - ▶ A set N of nonterminals (phrases)
 - ▶ A start symbol $S \in N$
 - ▶ A set R of production rules
 - ▶ Specifies how a nonterminal can produce a string of terminals and/or nonterminals



Example Grammar

Grammar rule	Example
$S \rightarrow NP VP$	I + want a morning flight
$NP \rightarrow$ Pronoun Proper-Noun Det Nominal	I Los Angeles a + flight
$Nominal \rightarrow$ Nominal Noun Noun	morning + flight flights
$VP \rightarrow$ Verb Verb NP Verb NP PP Verb PP	do want + a flight leave + Boston + in the morning leave + on Thursday
$PP \rightarrow$ Preposition NP	from + Los Angeles



Example Grammar

Noun → flights | breeze | trip | morning
Verb → is | prefer | like | need | want | fly
Adjective → cheapest | non-stop | first | latest
| other | direct
Pronoun → me | I | you | it
Proper-Noun → Alaska | Baltimore | Los Angeles
| Chicago | United | American
Determiner → the | a | an | this | these | that
Preposition → from | to | on | near
Conjunction → and | or | but



Sentence Generation


- ▶ A grammar can be used to generate a string
 - ▶ starting from a string containing only the start symbol S
 - ▶ recursively applying the rules to rewrite the string
 - ▶ until the string contains only terminals
- ▶ The generative process specifies the **grammatical structure (parse tree)** of the string



Example

$S \rightarrow NP VP$
 $S \rightarrow Aux NP VP$
 $S \rightarrow VP$
 $NP \rightarrow Pronoun$
 $NP \rightarrow Proper-Noun$
 $NP \rightarrow Det Nominal$
 $NP \rightarrow Nominal$
 $Nominal \rightarrow Noun$
 $Nominal \rightarrow Nominal Noun$
 $Nominal \rightarrow Nominal PP$
 $VP \rightarrow Verb$
 $VP \rightarrow Verb NP$
 $VP \rightarrow Verb NP PP$
 $VP \rightarrow Verb PP$
 $VP \rightarrow Verb NP NP$
 $VP \rightarrow VP PP$
 $PP \rightarrow Preposition NP$

.....




Sentence Parsing

- ▶ Parsing is the process of taking a string and a grammar and returning one or more parse tree(s) for that string
 - ▶ If no parse tree can be found, then the string does not belong to the language
 - ▶ Parsing algorithms: CYK, Earley, etc.
 - ▶ To be introduced later




Ambiguity

- ▶ A sentence is ambiguous if it has more than one possible parse tree
 - ▶ ...and hence more than one interpretation
- ▶ Examples
 - ▶ Time flies like an arrow.




Ambiguity

- ▶ A sentence is ambiguous if it has more than one possible parse tree
 - ▶ ...and hence more than one interpretation
- ▶ Examples
 - ▶ Time flies like an arrow.




Ambiguity

- ▶ A sentence is ambiguous if it has more than one possible parse tree
 - ▶ ...and hence more than one interpretation
- ▶ Examples
 - ▶ Time flies like an arrow.




Ambiguity

- ▶ A sentence is ambiguous if it has more than one possible parse tree
 - ▶ ...and hence more than one interpretation
- ▶ Examples
 - ▶ Time flies like an arrow.




Ambiguity

- ▶ A sentence is ambiguous if it has more than one possible parse tree
 - ▶ ...and hence more than one interpretation
- ▶ Examples
 - ▶ Astronomers saw stars with ears.



Ambiguity

- ▶ A sentence is ambiguous if it has more than one possible parse tree
 - ▶ ...and hence more than one interpretation
- ▶ Examples
 - ▶ Astronomers saw stars with ears.



Probabilistic Grammars

- ▶ Also called **stochastic grammars**
- ▶ Each rule is associated with a probability

$$\alpha \rightarrow \beta : P(\alpha \rightarrow \beta | \alpha)$$


- ▶ Probability of a parse tree = product of the probabilities of all the rules used in generating the parse tree
- ▶ Weighted grammars
 - ▶ Replace probabilities with positive weights
 - ▶ Same expressiveness



Example

$S \rightarrow NP VP$	[.80]
$S \rightarrow Aux NP VP$	[.15]
$S \rightarrow VP$	[.05]
$NP \rightarrow Pronoun$	[.35]
$NP \rightarrow Proper-Noun$	[.30]
$NP \rightarrow Det Nominal$	[.20]
$NP \rightarrow Nominal$	[.15]
$Nominal \rightarrow Noun$	[.75]
$Nominal \rightarrow Nominal Noun$	[.20]
$Nominal \rightarrow Nominal PP$	[.05]
$VP \rightarrow Verb$	[.35]
$VP \rightarrow Verb NP$	[.20]
$VP \rightarrow Verb NP PP$	[.10]
$VP \rightarrow Verb PP$	[.15]
$VP \rightarrow Verb NP NP$	[.05]
$VP \rightarrow VP PP$	[.15]
$PP \rightarrow Preposition NP$	[1.0]

.....



$$P(T) = .05 \times .20 \times .20 \times .20 \times .75 \times .30 \times .60 \\ \times .10 \times .40 = 2.2 \times 10^{-6}$$




Example

$S \rightarrow NP VP$	1.0	$NP \rightarrow NP PP$	0.4
$PP \rightarrow P NP$	1.0	$NP \rightarrow \textit{astronomers}$	0.1
$VP \rightarrow V NP$	0.7	$NP \rightarrow \textit{ears}$	0.18
$VP \rightarrow VP PP$	0.3	$NP \rightarrow \textit{saw}$	0.04
$P \rightarrow \textit{with}$	1.0	$NP \rightarrow \textit{stars}$	0.18
$V \rightarrow \textit{saw}$	1.0	$NP \rightarrow \textit{telescopes}$	0.1




Example



$$\begin{aligned} P(t_1) &= 1.0 \times 0.1 \times 0.7 \times 1.0 \times 0.4 \\ &\quad \times 0.18 \times 1.0 \times 1.0 \times 0.18 \\ &= 0.0009072 \end{aligned}$$



Example



$$\begin{aligned} P(t_2) &= 1.0 \times 0.1 \times 0.3 \times 0.7 \times 1.0 \\ &\quad \times 0.18 \times 1.0 \times 1.0 \times 0.18 \\ &= 0.0006804 \end{aligned}$$






Parsing



Parsing


- ▶ Parsing with CFGs is the task of assigning proper parse trees to input strings

Book the dinner flight



Parser evaluation


- ▶ Represent a parse tree as a collection of tuples:
 $\langle (l_1, i_1, j_1), (l_2, i_2, j_2), \dots, (l_n, i_n, j_n) \rangle$
 - ▶ l_k is the nonterminal labeling the k-th phrase
 - ▶ i_k is the index of the first word in the k-th phrase
 - ▶ j_k is the index of the last word in the k-th phrase




- ▶ Convert gold-standard and predicted trees into this representation, then estimate precision, recall, and F1

Tree Comparison Example

Gold:



Predicted:



$$\left\{ \begin{array}{l} (NP, 3, 7), \\ (Nominal, 4, 7) \end{array} \right\} \left\{ \begin{array}{l} (NP, 1, 1), (S, 1, 7) \\ (VP, 2, 7), (PP, 5, 7) \\ (NP, 6, 7), (Nominal, 4, 4) \end{array} \right\} \left\{ (VP, 2, 4) \right\}$$

only in gold tree

in both tree

only in
predicted tree

$$P = 6/7$$

$$R = 6/8$$

$$F = 4/5$$




Parsing

- ▶ A brute-force approach
 - ▶ Enumerate all parse trees consistent with the input string
- ▶ Problem
 - ▶ Number of binary trees with n leaves is the Catalan number C_{n-1}
 - ▶ (Exponential growth)



Parsing

- ▶ Dynamic programming
 - ▶ Divide the problem into many sub-problems
 - ▶ Sub-problem: parsing the substring between positions i and j
 - ▶ Solutions to smaller sub-problems are reused in solving larger sub-problems



Parsing algorithms

- ▶ Bottom-up DP: CYK
 - ▶ Also known as CKY
 - ▶ Applies to CFG in **Chomsky Normal Form** (CNF)
- ▶ Top-down DP: Earley parser
 - ▶ Applies to any CFG



Chomsky Normal Form

- ▶ Only two types of production rules

$$A \rightarrow B C$$

$$A \rightarrow w$$

- ▶ What if your grammar isn't in CNF?
- ▶ Any arbitrary CFG can be rewritten into CNF
 - ▶ The resulting grammar accepts (and rejects) the same set of strings as the original grammar
 - ▶ But the resulting parse trees are different (i.e., binarized)



Conversion to CNF

- ▶ Eliminate chains of unary productions.
 - ▶ So... $A \rightarrow B, B \rightarrow C$ turns into $A \rightarrow C$
- ▶ Introduce new intermediate non-terminals into the grammar that distribute rules with length > 2 over several rules.
 - ▶ So... $S \rightarrow A B C$ turns into $S \rightarrow X C$ and $X \rightarrow A B$
 - ▶ X is a symbol that doesn't occur anywhere else in the grammar




CNF conversion

\mathcal{L}_1 Grammar	\mathcal{L}_1 in CNF
$S \rightarrow NP VP$	$S \rightarrow NP VP$
$S \rightarrow Aux NP VP$	$S \rightarrow X1 VP$
	$X1 \rightarrow Aux NP$
$S \rightarrow VP$	$S \rightarrow book \mid include \mid prefer$
	$S \rightarrow Verb NP$
	$S \rightarrow X2 PP$
	$S \rightarrow Verb PP$
	$S \rightarrow VP PP$
$NP \rightarrow Pronoun$	$NP \rightarrow I \mid she \mid me$
$NP \rightarrow Proper-Noun$	$NP \rightarrow TWA \mid Houston$
$NP \rightarrow Det Nominal$	$NP \rightarrow Det Nominal$
$Nominal \rightarrow Noun$	$Nominal \rightarrow book \mid flight \mid meal \mid money$
$Nominal \rightarrow Nominal Noun$	$Nominal \rightarrow Nominal Noun$
$Nominal \rightarrow Nominal PP$	$Nominal \rightarrow Nominal PP$
$VP \rightarrow Verb$	$VP \rightarrow book \mid include \mid prefer$
$VP \rightarrow Verb NP$	$VP \rightarrow Verb NP$
$VP \rightarrow Verb NP PP$	$VP \rightarrow X2 PP$
	$X2 \rightarrow Verb NP$
$VP \rightarrow Verb PP$	$VP \rightarrow Verb PP$
$VP \rightarrow VP PP$	$VP \rightarrow VP PP$
$PP \rightarrow Preposition NP$	$PP \rightarrow Preposition NP$



CYK

- ▶ Build a table so that a non-terminal A spanning from i to j in the input is placed in cell $[i-1, j]$ in the table.



	1	2	3	4	5
0					
1				A	
2					
3					
4					

- ▶ So a non-terminal spanning an entire string will sit in cell $[0, n]$
 - ▶ Hopefully an S




Example

A completed table for input
“Book the flight through
Houston”

<i>Book</i>	<i>the</i>	<i>flight</i>	<i>through</i>	<i>Houston</i>
S, VP, Verb Nominal, Noun [0,1]	[0,2]	S,VP,X2 [0,3]	[0,4]	S,VP,X2 [0,5]
	Det [1,2]	NP [1,3]	[1,4]	NP [1,5]
		Nominal, Noun [2,3]	[2,4]	Nominal [2,5]
			Prep [3,4]	PP [3,5]
				NP, Proper- Noun [4,5]

We fill the table from
bottom up




CYK

- ▶ Base case:

- ▶ A is in cell $[i-1, i]$ iff. there exists a rule $A \rightarrow w_i$

- ▶ Recursion:

- ▶ A is in cell $[i, j]$ iff. for some rule $A \rightarrow B C$ there is a B in cell $[i, k]$ and a C in cell $[k, j]$ for some k .



CYK Algorithm

function CKY-PARSE(*words*, *grammar*) **returns** *table*

for $j \leftarrow$ **from** 1 **to** LENGTH(*words*) **do**

$table[j-1, j] \leftarrow \{A \mid A \rightarrow words[j] \in grammar\}$

for $i \leftarrow$ **from** $j-2$ **downto** 0 **do**

for $k \leftarrow i+1$ **to** $j-1$ **do**

$table[i, j] \leftarrow table[i, j] \cup$

$\{A \mid A \rightarrow BC \in grammar,$

$B \in table[i, k],$

$C \in table[k, j]\}$

► Time complexity: $O(n^3|G|)$

► n is Sentence length and $|G|$ is number of grammar rules



CYK

- *The flight includes a meal.*

Grammar

- $S \rightarrow NP VP$
- $NP \rightarrow Det N$
- $VP \rightarrow V NP$
- $V \rightarrow \text{includes}$
- $Det \rightarrow \text{the}$
- $Det \rightarrow \text{a}$
- $N \rightarrow \text{meal}$
- $N \rightarrow \text{flight}$

	1	2	3	4	5
0					
1					
2					
3					
4					



CYK

- *The flight includes a meal.*

Grammar

- $S \rightarrow NP VP$
- $NP \rightarrow Det N$
- $VP \rightarrow V NP$
- $V \rightarrow \text{includes}$
- $Det \rightarrow \text{the}$
- $Det \rightarrow \text{a}$
- $N \rightarrow \text{meal}$
- $N \rightarrow \text{flight}$

	1	2	3	4	5
0	Det				
1					
2					
3					
4					



CYK

- *The **flight** includes a meal.*

Grammar

- $S \rightarrow NP VP$
- $NP \rightarrow Det N$
- $VP \rightarrow V NP$
- $V \rightarrow \text{includes}$
- $Det \rightarrow \text{the}$
- $Det \rightarrow \text{a}$
- $N \rightarrow \text{meal}$
- $N \rightarrow \text{flight}$

	1	2	3	4	5
0	Det				
1		N			
2					
3					
4					



CYK

- *The flight includes a meal.*

Grammar

- $S \rightarrow NP VP$
- $NP \rightarrow Det N$
- $VP \rightarrow V NP$
- $V \rightarrow \text{includes}$
- $Det \rightarrow \text{the}$
- $Det \rightarrow \text{a}$
- $N \rightarrow \text{meal}$
- $N \rightarrow \text{flight}$

	1	2	3	4	5
0	Det	NP			
1		N			
2					
3					
4					



CYK

- *The flight includes a meal.*

Grammar

- $S \rightarrow NP VP$
- $NP \rightarrow Det N$
- $VP \rightarrow V NP$
- $V \rightarrow \text{includes}$
- $Det \rightarrow \text{the}$
- $Det \rightarrow \text{a}$
- $N \rightarrow \text{meal}$
- $N \rightarrow \text{flight}$

	1	2	3	4	5
0	Det	NP			
1		N			
2			V		
3					
4					



CYK

- *The flight includes a meal.*

Grammar

- $S \rightarrow NP VP$
- $NP \rightarrow Det N$
- $VP \rightarrow V NP$
- $V \rightarrow \text{includes}$
- $Det \rightarrow \text{the}$
- $Det \rightarrow \text{a}$
- $N \rightarrow \text{meal}$
- $N \rightarrow \text{flight}$

	1	2	3	4	5
0	Det	NP			
1		N			
2			V		
3				Det	
4					



CYK

- *The flight includes a meal.*

Grammar

- $S \rightarrow NP VP$
- $NP \rightarrow Det N$
- $VP \rightarrow V NP$
- $V \rightarrow \text{includes}$
- $Det \rightarrow \text{the}$
- $Det \rightarrow \text{a}$
- $N \rightarrow \text{meal}$
- $N \rightarrow \text{flight}$

	1	2	3	4	5
0	Det	NP			
1		N			
2			V		
3				Det	
4					N



CYK

- *The flight includes a meal.*

Grammar

- $S \rightarrow NP VP$
- $NP \rightarrow Det N$
- $VP \rightarrow V NP$
- $V \rightarrow \text{includes}$
- $Det \rightarrow \text{the}$
- $Det \rightarrow \text{a}$
- $N \rightarrow \text{meal}$
- $N \rightarrow \text{flight}$

	1	2	3	4	5
0	Det	NP			
1		N			
2			V		
3				Det	NP
4					N



CYK

- *The flight includes a meal.*

Grammar

- $S \rightarrow NP VP$
- $NP \rightarrow Det N$
- $VP \rightarrow V NP$
- $V \rightarrow \text{includes}$
- $Det \rightarrow \text{the}$
- $Det \rightarrow \text{a}$
- $N \rightarrow \text{meal}$
- $N \rightarrow \text{flight}$

	1	2	3	4	5
0	Det	NP			
1		N			
2			V		VP
3				Det	NP
4					N



CYK

- *The flight includes a meal.*

Grammar

- $S \rightarrow NP VP$
- $NP \rightarrow Det N$
- $VP \rightarrow V NP$
- $V \rightarrow \text{includes}$
- $Det \rightarrow \text{the}$
- $Det \rightarrow \text{a}$
- $N \rightarrow \text{meal}$
- $N \rightarrow \text{flight}$

	1	2	3	4	5
0	Det	NP			S
1		N			
2			V		VP
3				Det	NP
4					N



CYK Parsing

- ▶ Is that really a parser?
 - ▶ We want a parse tree, not a yes/no answer
- ▶ Simple changes
 - ▶ Add back-pointers so that each state knows where it came from.
 - ▶ After filling the table, recursively retrieve the constituents from the top (i.e., the start symbol) down



CYK

- *The flight includes a meal.*

Grammar

- $S \rightarrow NP VP$
- $NP \rightarrow Det N$
- $VP \rightarrow V NP$
- $V \rightarrow \text{includes}$
- $Det \rightarrow \text{the}$
- $Det \rightarrow \text{a}$
- $N \rightarrow \text{meal}$
- $N \rightarrow \text{flight}$

	1	2	3	4	5
0	Det	NP			S
1		N			
2			V		VP
3				Det	NP
4					N

Ambiguity

- NP \rightarrow Det N
- NP \rightarrow N N

	1	2	3	4	5
0	Det N	??			
1		N			
2					
3					
4					



Ambiguity

- NP \rightarrow Det N
- NP \rightarrow N N

	1	2	3	4	5
0	Det N	NP ↑			
1		N			
2					
3					
4					



Ambiguity

- NP \rightarrow Det N
- NP \rightarrow N N

	1	2	3	4	5
0	Det N	NP N			
1					
2					
3					
4					



Ambiguity

- NP → Det NP
- NP → NP PP


	1	2	3	4	5
0	Det	NP	??		
1		N	NP		
2			PP		
3					
4					



Ambiguity

- NP → Det NP
- NP → NP PP


	1	2	3	4	5
0	Det	NP	NP		
1		N	NP		
2			PP		
3					
4					



Ambiguity

- NP → Det NP
- NP → NP PP


	1	2	3	4	5
0	Det	NP	NP		
1		N	NP		
2			PP		
3					
4					



Probabilistic Parsing

- ▶ We have a probabilistic grammar, e.g., PCFG
- ▶ We want to find the parse tree of an input string with the highest probability
- ▶ In cell $[i-1, j]$ of the table, associate each nonterminal A with the probability of the best parse tree rooted at A covering substring from i to j
- ▶ Recursive computation

$$P_{A,i,j} = \max_{B,C,k} P(A \rightarrow BC) \\ \times P_{B,i,k} \times P_{C,k,j}$$



CYK

- *The flight includes a meal.*

Grammar

- $S \rightarrow NP VP$ [.80]
- $NP \rightarrow Det N$ [.30]
- $VP \rightarrow V NP$ [.20]
- $V \rightarrow includes$ [.05]
- $Det \rightarrow the$ [.4]
- $Det \rightarrow a$ [.4]
- $N \rightarrow meal$ [.01]
- $N \rightarrow flight$ [.02]

	1	2	3	4	5
0					
1					
2					
3					
4					



CYK

- *The flight includes a meal.*

Grammar

- $S \rightarrow NP VP$ [.80]
- $NP \rightarrow Det N$ [.30]
- $VP \rightarrow V NP$ [.20]
- $V \rightarrow includes$ [.05]
- $Det \rightarrow the$ [.4]
- $Det \rightarrow a$ [.4]
- $N \rightarrow meal$ [.01]
- $N \rightarrow flight$ [.02]

	1	2	3	4	5
0	Det 0.4				
1					
2					
3					
4					



CYK

- *The **flight** includes a meal.*

Grammar

- $S \rightarrow NP VP$ [.80]
- $NP \rightarrow Det N$ [.30]
- $VP \rightarrow V NP$ [.20]
- $V \rightarrow \text{includes}$ [.05]
- $Det \rightarrow \text{the}$ [.4]
- $Det \rightarrow \text{a}$ [.4]
- $N \rightarrow \text{meal}$ [.01]
- $N \rightarrow \text{flight}$ [.02]

	1	2	3	4	5
0	Det 0.4				
1		N 0.02			
2					
3					
4					



CYK

- *The flight includes a meal.*

Grammar

- $S \rightarrow NP VP$ [.80]
- $NP \rightarrow Det N$ [.30]
- $VP \rightarrow V NP$ [.20]
- $V \rightarrow includes$ [.05]
- $Det \rightarrow the$ [.4]
- $Det \rightarrow a$ [.4]
- $N \rightarrow meal$ [.01]
- $N \rightarrow flight$ [.02]

	1	2	3	4	5
0	Det 0.4	NP .0024			
1		N 0.02			
2					
3					
4					



CYK

- *The flight includes a meal.*

Grammar

- $S \rightarrow NP VP$ [.80]
- $NP \rightarrow Det N$ [.30]
- $VP \rightarrow V NP$ [.20]
- $V \rightarrow includes$ [.05]
- $Det \rightarrow the$ [.4]
- $Det \rightarrow a$ [.4]
- $N \rightarrow meal$ [.01]
- $N \rightarrow flight$ [.02]

	1	2	3	4	5
0	Det 0.4	NP .0024			
1		N 0.02			
2			V .05		
3					
4					



CYK

- *The flight includes a meal.*

Grammar

- $S \rightarrow NP VP$ [.80]
- $NP \rightarrow Det N$ [.30]
- $VP \rightarrow V NP$ [.20]
- $V \rightarrow includes$ [.05]
- $Det \rightarrow the$ [.4]
- $Det \rightarrow a$ [.4]
- $N \rightarrow meal$ [.01]
- $N \rightarrow flight$ [.02]

	1	2	3	4	5
0	Det 0.4	NP .0024			
1		N 0.02			
2			V .05		
3				Det 0.4	
4					



CYK

- *The flight includes a meal.*

Grammar

- $S \rightarrow NP VP$ [.80]
- $NP \rightarrow Det N$ [.30]
- $VP \rightarrow V NP$ [.20]
- $V \rightarrow includes$ [.05]
- $Det \rightarrow the$ [.4]
- $Det \rightarrow a$ [.4]
- $N \rightarrow meal$ [.01]
- $N \rightarrow flight$ [.02]

	1	2	3	4	5
0	Det 0.4	NP .0024			
1		N 0.02			
2			V .05		
3				Det 0.4	
4					N 0.01



CYK

- *The flight includes a meal.*

Grammar

- $S \rightarrow NP VP$ [.80]
- $NP \rightarrow Det N$ [.30]
- $VP \rightarrow V NP$ [.20]
- $V \rightarrow includes$ [.05]
- $Det \rightarrow the$ [.4]
- $Det \rightarrow a$ [.4]
- $N \rightarrow meal$ [.01]
- $N \rightarrow flight$ [.02]

	1	2	3	4	5
0	Det 0.4	NP .0024			
1		N 0.02			
2			V .05		
3				Det 0.4	NP 0.001
4					N 0.01



CYK

- *The flight includes a meal.*

Grammar

- $S \rightarrow NP VP$ [.80]
- $NP \rightarrow Det N$ [.30]
- $VP \rightarrow V NP$ [.20]
- $V \rightarrow includes$ [.05]
- $Det \rightarrow the$ [.4]
- $Det \rightarrow a$ [.4]
- $N \rightarrow meal$ [.01]
- $N \rightarrow flight$ [.02]

	1	2	3	4	5
0	Det 0.4	NP .0024			
1		N 0.02			
2			V .05		VP .00001
3				Det 0.4	NP 0.001
4					N 0.01



CYK

- *The flight includes a meal.*

Grammar

- $S \rightarrow NP VP$ [.80]
- $NP \rightarrow Det N$ [.30]
- $VP \rightarrow V NP$ [.20]
- $V \rightarrow \text{includes}$ [.05]
- $Det \rightarrow \text{the}$ [.4]
- $Det \rightarrow \text{a}$ [.4]
- $N \rightarrow \text{meal}$ [.01]
- $N \rightarrow \text{flight}$ [.02]

	1	2	3	4	5
0	Det 0.4	NP .0024			S .00000001 92
1		N 0.02			
2			V .05		VP .00001
3				Det 0.4	NP 0.001
4					N 0.01



Ambiguity


- NP \rightarrow Det N [0.7]
- NP \rightarrow N N [0.3]

	1	2	3	4	5
0	Det 0.4 N 0.8				
1		N 0.02			
2					
3					
4					



Ambiguity

- NP \rightarrow Det N [0.7]
- NP \rightarrow N N [0.3]

	1	2	3	4	5
0	Det 0.4 N 0.8	NP .0056 			
1		N 0.02			
2					
3					
4					



Ambiguity


- NP → Det N [0.7]
- NP → N N [0.3]

	1	2	3	4	5
0	Det 0.4 N 0.8	NP .0048			
1		N 0.02			
2					
3					
4					



Ambiguity

- NP \rightarrow Det N [0.7]
- NP \rightarrow N N [0.3]

	1	2	3	4	5
0	Det 0.4 N 0.8	NP .0056 			
1		N 0.02			
2					
3					
4					






Learning




Learning a grammar from a corpus


Training Corpus



Induction



Grammar / Parser



- ▶ Supervised Methods
 - ▶ Rely on a training corpus of sentences annotated with parses (treebank)
- ▶ Unsupervised Methods (Grammar Induction)
 - ▶ Do not require annotated data



Supervised Methods

▶ Treebank

- ▶ A corpus in which each sentence has been (manually) paired with a parse tree
- ▶ Manual annotation is labor intensive and generally requires linguistic knowledge and detailed guidelines.
- ▶ Most well known is the Wall Street Journal section of the Penn TreeBank.
 - ▶ 1 M words from the 1987-1989 Wall Street Journal



Generative Methods

- ▶ Learning a PCFG from treebanks
 - ▶ Maximum likelihood estimation (treebank grammar)
 - ▶ We maximize $P(\text{sentence}, \text{parse})$
 - ▶ Closed-form solution: count and normalize


	Counts in treebank	MLE of rule probabilities
VP→Verb	20	0.2
VP→Verb NP	40	0.4
VP→Verb NP NP	25	0.25
VP→Verb PP	15	0.15



Generative Methods


- ▶ Learning a PCFG from treebanks
 - ▶ Maximum likelihood estimation (treebank grammar)
 - ▶ MLE has bad performance (F1 score <80)
 - ▶ Main reason: standard treebank nonterminals are not sufficiently informative

$S \rightarrow NP VP$	1
$VP \rightarrow V NP$	0.2
$NP \rightarrow DT NP$	0.5
$NP \rightarrow NP NP$	0.3
... ..	
$P \rightarrow He$	0.2
$P \rightarrow me$	0.2
$V \rightarrow found$	0.1
... ..	




$$P(T_1) = P(T_2)$$

Generative Methods beyond MLE



Lexicalization

[Collins. 1997; Charniak. 2000]



Tree Annotation

[Johnson. 1998; Klein et al. 2003]

► Problems



- Each rule has less training data. Smoothing is very important!
- Need to do additional annotations or design rules



Generative Methods beyond MLE

- ▶ **Latent Variable Grammars** [Matsuzaki et al. 2005; Petrov et al. 2007]
 - ▶ Each nonterminal is split into a finite number of subtypes
 - ▶ Each subtype rule is associated with a probability
 - ▶ Learning by EM
 - ▶ the nonterminal subtypes in the training parse trees are the hidden variables

<i>Subtype rule</i>	<i>Prob.</i>
$S[0] \rightarrow NP[0] VP[0]$	0.1
$S[1] \rightarrow NP[0] VP[0]$	0.15
$S[0] \rightarrow NP[1] VP[0]$	0.05
$S[1] \rightarrow NP[1] VP[0]$	0.08
... ..	



A subtype parse tree

Discriminative Methods

- ▶ We assume a **weighted** context-free grammar and maximize conditional likelihood $P(\text{gold parse} \mid \text{sentence})$

$$P(t|x) = \frac{\prod_{r \in (t,x)} \exp(W(r))}{Z(x)}$$

- ▶ We formulate the weight of a rule based on the input sentence
 - ▶ This can be viewed as having a different set of subtypes for each sentence
 - ▶ More expressive than earlier generative methods
- ▶ This is a CRF!




Discriminative Methods

- ▶ We formulate the weight of a rule based on the input sentence
 - ▶ ...from features of the (anchored) rule in the sentence


$$W(r: A \rightarrow BC, \langle p, q, d \rangle) = \sum_i \alpha_i f_i(r, \langle p, q, d \rangle)$$

- ▶ Possible features:
 - ▶ Rule identity $A \rightarrow BC$
 - ▶ Words at the span boundary
 $w_{p-1}, w_p, w_q, w_{q+1}$
 - ▶ Words at the split point w_d, w_{d+1}



Discriminative Methods

- ▶ We formulate the weight of a rule based on the input sentence
 - ▶ ...from features of the (anchored) rule in the sentence
 - ▶ ...using a neural network with word embeddings at the span boundary and split point as input



Discriminative Methods

- ▶ Maximizing conditional likelihood with gradient descent

$$P(t|x) = \frac{\prod_{r \in (t,x)} \exp(W(r))}{Z(x)}$$

- ▶ Partition function $Z(x)$ is computed with the inside algorithm (to be introduced next)
- ▶ Alternative objective: margin-based loss



Unsupervised Methods

- ▶ Learning from sentences with no parse tree annotation
 - ▶ ...sometimes with POS annotation
- ▶ Two tasks
 - ▶ Structure search
 - ▶ Try to find an optimal set of grammar rules
 - ▶ Parameter learning
 - ▶ Given a set of grammar rules, try to learn their probabilities



Structure search

- ▶ Two classes of approaches
 - ▶ Heuristic approaches
 - ▶ Create nonterminals and production rules using **heuristic criteria and rules**
 - ▶ Ex: Frequency of a substring, substitutability heuristic, distributional clustering, ...
 - ▶ Optimization-based approaches
 - ▶ Optimizing an **explicit objective function** (e.g., posterior) of the grammar structure by **local search**
 - ▶ Start with a trivial grammar
 - ▶ Search with a set of structure-change operations
- ▶ Empirical results
 - ▶ Poor on real data, often below simple baselines 😞



Parameter learning

- ▶ Maximum marginal likelihood estimation
 - ▶ We maximize $P(\text{sentence})$ with the parse tree marginalized
- ▶ Learning algorithm?
 - ▶ Expectation-maximization!
 - ▶ E-step: Compute the distribution of the parse tree for each training sentence
 - ▶ Infeasible to enumerate. But can compute expected counts of rule usage using **the inside-outside algorithm**.
 - ▶ M-step: Update the parameters to maximize expected log likelihood based on the distribution over the parse tree
 - ▶ Closed-form solution: normalize the expected counts



Inside-outside algorithm

- ▶ Assume the grammar is in the Chomsky normal form (CNF)
 - ▶ Only two types of rules
 - ▶ $N_1 \rightarrow N_2 N_3$
 - ▶ $N_1 \rightarrow w$




Inside-outside algorithm

► Notations

Sentence: sequence of words $w_1 \cdot \cdot \cdot w_m$

w_{ab} : the subsequence $w_a \cdot \cdot \cdot w_b$

N_{ab}^i : nonterminal N^i dominates $w_a \cdot \cdot \cdot w_b$



Span index:

- Here we use [inclusive, inclusive]
- When introducing CYK, we use [exclusive, inclusive], i.e., $(a - 1, b)$ for the same span




Inside-outside algorithm

- ▶ Given an input string, compute two types of probabilities

$$\text{Outside} = \alpha_j(p, q) = P(w_{1(p-1)}, N_{pq}^j, w_{(q+1)m} | G)$$

$$\text{Inside} = \beta_j(p, q) = P(w_{pq} | N_{pq}^j, G)$$



Computing inside probabilities

- ▶ Base case


$$\begin{aligned}\beta_j(k, k) &= P(w_k | N_{kk}^j, G) \\ &= P(N^j \rightarrow w_k | G)\end{aligned}$$



Computing inside probabilities

► Bottom-up recursion

$$\begin{aligned}\beta_j(p, q) &= P(w_{pq} | N_{pq}^j, G) \\ &= \sum_{r, s} \sum_{d=p}^{q-1} P(N^j \rightarrow N^r N^s) \beta_r(p, d) \beta_s(d+1, q)\end{aligned}$$



Computing inside probabilities

- ▶ Almost the same as CYK parsing, but uses **sum** instead of **max**
- ▶ Looks familiar?
 - ▶ HMM
 - ▶ Viterbi algorithm uses **max**
 - ▶ Forward algorithm uses **sum**
 - ▶ HMM is a special case of PCFG
 - ▶ Viterbi algorithm is a special case of CYK algorithm
 - ▶ Forward algorithm is a special case of inside algorithm



Computing outside probabilities

$$\text{Outside} = \alpha_j(p, q) = P(w_{1(p-1)}, N_{pq}^j, w_{(q+1)m} | G)$$

► Base case

(Nonterminal #1 is S)

↙
 $\alpha_1(1, m) = 1$


$$\alpha_j(1, m) = 0, \text{ for } j \neq 1$$




Computing outside probabilities

► Top-down recursion

$$\begin{aligned}\alpha_j(p, q) &= P(w_{1(p-1)}, N_{pq}^j, w_{(q+1)m} | G) \\ &= \left[\sum_{f,g} \sum_{e=q+1}^m \alpha_f(p, e) P(N^f \rightarrow N^j N^g) \beta_g(q+1, e) \right] \\ &\quad + \left[\sum_{f,g} \sum_{e=1}^{p-1} \alpha_f(e, q) P(N^f \rightarrow N^g N^j) \beta_g(e, p-1) \right]\end{aligned}$$



Inside-outside algorithm



- ▶ Time complexity: $O(n^3 |G|)$
 - ▶ n is Sentence length and $|G|$ is number of grammar rules



Inside-outside algorithm

- ▶ Expectation-maximization (EM)

- ▶ Initialize the probabilities (e.g., randomly)

- ▶ Repeat until convergence

- ▶ E-step: compute the expected counts

$$C(N^j \rightarrow N^r N^s \text{ used} | X, \Theta^t)$$

$$= \sum_{w_{1:m} \in X} E_{p(t|w_{1:m})} [C(N^j \rightarrow N^r N^s \text{ used in } t)]$$


- ▶ M-step: update the probabilities by normalizing expected counts

$$\theta_{jrs}^{t+1} = P(N^j \rightarrow N^r N^s) = \frac{C(N^j \rightarrow N^r N^s \text{ used} | X, \Theta^t)}{C(N^j \text{ used} | X, \Theta^t)}$$




Expected counts

$$C(N^j \rightarrow N^r N^s \text{ used} | X, \Theta^t) = \sum_{w_{1,m} \in X} \sum_{p=1}^{m-1} \sum_{q=p+1}^m \sum_{d=p}^{q-1} P(\dots | w_{1,m}, \Theta^t)$$



Expected counts

$$P(\dots | w_{1,m}, \Theta^t) = \frac{\alpha_j(p,q) P(N^j \rightarrow N^r N^s) \beta_r(p,d) \beta_s(d+1,q)}{P(w_{1,m})}$$



Inside-outside algorithm

- ▶ Expectation-maximization (EM)
 - ▶ Initialize the probabilities (e.g., randomly)
 - ▶ Repeat until convergence
 - ▶ E-step
 - ▶ Compute the inside probabilities
 - ▶ Compute the outside probabilities
 - ▶ Compute the expected counts
 - ▶ M-step
 - ▶ Update the probabilities




Inside-outside are just backprop!

- ▶ Expected counts can be computed by backprop
 - ▶ $C(N^j \rightarrow N^r N^s \text{ used} | X, \Theta^t) = \frac{\partial \log P(w_{1:m})}{\partial \Theta_{j,r,s}^t}$
 - ▶ The inside and then backprop procedure is almost the same as Inside-Outside
- ▶ See <https://aclanthology.org/W16-5901.pdf>




Computation graph of the inside algorithm



$$\beta_j(i, i) = P(N^j \rightarrow w_i)$$




Computation graph of the inside algorithm






Computation graph of the inside algorithm



Computation graph of the inside algorithm


$$P(w_{1:4}) = \beta_S(1,4)$$



Computation graph of the inside algorithm

$$P(w_{1:4}) = \beta_S(1,4)$$

$$\beta_j(p, q) = \sum_{r,s,d} P(N^j \rightarrow N^r N^s) \beta_r(p, d) \beta_s(d+1, q)$$



$$\beta_j(i, i) = P(N^j \rightarrow w_i)$$





Beyond CFG



Generative Grammars



Chomsky Hierarchy



M Rohrmeier, W Zuidema, G Wiggins, C Scharff. Principles of structure building in music, language and animal song.

Regular Grammars

- ▶ Production rules are of the form $A \rightarrow aB$ or $A \rightarrow a$



HMM = Probabilistic RG \subset CFG



Viterbi : Forward-Backward
 \approx
CYK : Inside-Outside

Mildly Context-Sensitive Grammars


- ▶ More expressive than CFG
 - ▶ Production is no longer independent of context
- ▶ Polynomial-time parsing
- ▶ Several formalisms
 - ▶ Tree-adjoining grammar (TAG)
 - ▶ Combinatory categorial grammar (CCG)
 - ▶ Linear context-free rewriting systems (LCFRS)
 - ▶ Multiple context-free grammars (MCFG)
 - ▶ ...




TAG Rule 1: Substitution



Derivation tree:



TAG Rule 2: Adjoin



Example: TAG Lexicon

$\alpha 2$:

NP
|
John

$\alpha 3$

:
NP
|
tapas

$\alpha 1$:


S
/ \
NP VP
/ \
VBZ NP
|
eats

$\beta 1$:





VP
/ \
RB VP*
|
always




Example: TAG derivation



Example: TAG derivation




Example: TAG derivation



Transition-based parsing

- ▶ Read words from left to right and take a sequence of actions to construct a tree
- ▶ Actions are picked greedily or using beam search
- ▶ More on this later...



stack	buffer	action	node
[]	[The little ...]	SHIFT	③
[The]	[little boy ...]	SHIFT	④
[The little]	[boy likes ...]	SHIFT	⑤
[... little boy]	[likes red ...]	REDUCE-R-NP	②
...

(a) bottom-up system

stack	buffer	action	node
[]	[The little ...]	NT-S	①
[(S]	[The little ...]	NT-NP	②
[(S (NP]	[The little ...]	SHIFT	③
[... (NP The]	[little boy ...]	SHIFT	④
[... The little]	[boy likes ...]	SHIFT	⑤
[... little boy]	[likes red ...]	REDUCE	/
...


(b) top-down system

stack	buffer	action	node
[]	[The little ...]	SHIFT	③
[The]	[little boy ...]	PJ-NP	②
[The NP]	[little boy ...]	SHIFT	④
[... NP little]	[boy likes...]	SHIFT	⑤
[... little boy]	[likes red ...]	REDUCE	/
...

(c) in-order system

Span-based parsing

- ▶ Discriminative parsing
 - ▶ Maximize conditional likelihood $P(\text{gold parse} \mid \text{sentence})$
- ▶ Tree score = product of span scores
 - ▶ Span score computed from features or using a neural network
- ▶ We can still use CYK!




$$\begin{aligned} s(t) = & s(1,1) \times s(2,2) \\ & \times s(3,3) \times s(4,4) \times s(3,4) \\ & \times s(2,4) \times s(1,4) \end{aligned}$$



Parsing as sequence labeling

- ▶ Cast constituency parsing as a sequence labeling task
 - ▶ Advantage: faster parsing speed



of common ancestor
shared with the next
word

lowest common
ancestor (LCA)
to the next word

unary chain connecting
the LCA and the current
word



Summary



Constituency Parsing

- ▶ Context-Free Grammars

- ▶ Terminals, nonterminals, start symbol, production rules
- ▶ Probabilistic Grammars: each rule has a probability

- ▶ Parsing

- ▶ CYK algorithm on CNF

- ▶ Learning

- ▶ Supervised: generative & discriminative methods
- ▶ Unsupervised: inside-outside algorithm

- ▶ Beyond CFG

- ▶ RG, MCSG
- ▶ Transition/span-based parsing, parsing as sequence labeling

