MRK HOTELS · ENGINEERING REFERENCE

Frontend → Backend Request Flow & Debug Guide

A single reference for tracing every Vue screen through Axios, Laravel middleware, controllers, services, database transactions, audit logs and real-time events — with the concrete checks to run when something goes wrong.

630	19	87	10
API V1 ROUTES CATALOGUED	END-TO-END FLOWS EXPLAINED	FRONTEND API GROUPS	DEBUG CHECKPOINTS

Prepared: 12 November 2026 · **Frontend:** 6651477 · **Backend:** d0de4d4

Scope: staff application, cashier/POS, inventory/procurement, reservations/folios, housekeeping/laundry, messaging, owner/superadmin and guest/public API surfaces.

1. How to use this guide

Start from the screen that failed, not from the database. The goal is to find the first layer where the request or response stops matching expectations.

If a button or page fails

- Open DevTools → Network, preserve the log, reproduce once.
- Find the red request. Copy method, full URL, headers, body, status and response.
- Match it to a flow in section 5 and an endpoint in section 8.
- Check token, tenant, role and active outlet before reading backend code.
- If the response is 500, go to the Laravel log and the controller named in the catalogue.

If data is wrong but the request succeeds

- Confirm the request filters: date, outlet/department, status, pagination.
- Compare one known row with its source table or ledger.
- Check whether the screen is stale: reload before blaming the API.
- For stock/folio totals, trace the movement or ledger entry, not the summary.
- For live boards, test HTTP refresh first; then test Echo/Reverb.

Vocabulary: “frontend” means the Vue app in `mrk-hotels-frontend`. “Backend” means the Laravel API in `mrk-hotels-api`. “Tenant” means one hotel. “Outlet” means a selling point or store with its own stock shelf. “Business date” is the hotel-local operating day, not necessarily the server date.

Contents

2 The request pipeline at a glance
3 Step-by-step lifecycle
4 Authentication, tenant and permissions
5 Feature flow walkthroughs (5.1–5.19)
6 Error response map
7 Debugging playbook
8 Complete API v1 route catalogue
A Frontend API module map
B Middleware glossary
C Environment, commands and verification

2. The request pipeline at a glance

Every authenticated staff request follows this path. A failure at any box produces a different kind of symptom.

01
Vue screen
Page/component state, form validation, selected outlet/date.

→

02
API module
`src/api/index.js` method builds URL, params and body.

→

03
Axios
`src/api/axios.js` adds base URL, token, tenant, language.

→

04
HTTP
Network request to `/api/v1/...` with JSON or FormData.

→

05
Laravel route
`routes/api.php` matches method + URI to a controller action.

06
Middleware
auth, tenant, features, trust, throttle, level, operate, report/POS gates.

→

07
Controller
Validation, authorization, domain checks, transaction boundaries.

→

08
Service / model
Business rules, stock posting, folio posting, number generation.

→

09
Database
Tenant-scoped reads/writes inside a transaction where required.

→

10
Audit + event
Audit row, notification, queued job, broadcast event.

11
JSON response
Resource/paginator payload with message, data, errors or meta.

→

12
Axios interceptor
Flattens pagination; clears token and redirects on 401.

→

13
UI update
Toast, table refresh, modal close, navigation, optimistic state.

→

14
Realtime
Echo receives a broadcast and refreshes other open screens.

> **Key rule:** a successful HTTP status only means the controller returned a response. It does not prove the business result is correct. For money, stock and folios, always verify the ledger/ movement row and the audit trail.

3. Step-by-step lifecycle

The concrete sequence behind one request, with the place to look when each step fails.

3.1 Navigation and route guard

The Vue router checks whether the destination requires authentication, a module, or a role. If the route is protected, the guard reads `auth_token` from `sessionStorage`, loads the profile if needed, and redirects guests to `/login`. A valid token is not enough: the user also needs the route's role/module permission. **Look here** when the screen never renders or redirects before any API call appears in Network.

3.2 User action and page state

The component validates the form, resolves the active outlet/date, and calls a method from an API module. Most “the API is broken” reports start with a missing required value here: no outlet, no business date, no table, no shelf, no customer, no shift. **Look here** when the request body is missing a field that the backend then rejects with 422.

3.3 API module and URL construction

`src/api/index.js` groups calls by domain (for example `orderApi`, `inventoryApi`, `reservationApi`). The module supplies the path under `/v1`, query params and body. The shared Axios instance already has the `/api` base, so a correct URL is `VITE_API_URL + /v1/...`. A duplicated `/api/api` or a missing `/v1` is a frontend URL bug, not a backend bug.

3.4 Axios request interceptor

Before the request leaves the browser, the interceptor adds `Authorization: Bearer <auth_token>`, optionally `X-Tenant-ID` for owner hotel switching, and `Accept-Language` from `localStorage.locale`. For `FormData`, it removes `Content-Type` so the browser can set the multipart boundary. **Look here** when the request works in an API client but fails in the app because a header is missing or wrong.

3.5 Network and response

Check the request URL, method, status, request headers, response headers and body. Laravel validation errors normally return 422 with an `errors` object; auth errors return 401; authorization/tenant errors return 403; missing records/routes return 404; conflicts return 409; throttling returns 429. A 500 means the request reached the backend but an exception escaped.

3.6 Laravel route matching

`routes/api.php` matches the method and URI. Route order matters: fixed paths such as `/orders/summary` and `/reservations/options` are registered before wildcard `{id}` routes. If a fixed path is treated as an id, or the route is missing from the catalogue, verify the route definition and run `php artisan route:list --path=api/v1`.

3.7 Middleware gates

The authenticated group runs `auth:sanctum`, `tenant`, `features`, `trust` and `throttle:api`. Individual routes add `level:N`, `operate`, `reports`, `pos-inventory`, `pos-reports` and ability checks such as `outlets.manage` or `housekeeping.work`. **Look here** for a 403 even though the same user can open other screens.

3.8 Controller validation and authorization

The controller validates the payload with Laravel validation, then performs domain checks that validation cannot express: is the order frozen, is the PO still open, does the room have an active reservation, is the outlet's shelf resolvable, is the credit account active, has the business day ended? These checks usually abort with 422 or 403 and a readable message.

3.9 Transaction and domain write

Money, stock, folio and procurement operations run inside `DB::transaction`. A failure must roll back the whole operation, not leave a header without lines or stock without a document. Use the audit row and the related movement/ledger row to prove what committed. If one exists without the other, treat it as a transaction or service bug.

3.10 Response shaping and UI update

Controllers return resources or explicit JSON. The Axios response interceptor flattens Laravel pagination metadata onto the payload, so pages read `data`, `current_page`, `last_page` and so on. The component then updates state, shows a toast, closes a modal or refreshes a list. **Look here** when the response is correct but the screen does not change.

3.11 Realtime follow-up

After commit, some actions dispatch broadcast events. Echo authorizes private channels through `POST /broadcasting/auth`, then listens. Realtime is a convenience layer: the HTTP response should already contain the authoritative result. If HTTP is right and the board is stale, debug Echo/Reverb; do not change the order/inventory controller.

4. Authentication, tenant and permissions

4.1 What the browser stores

Value	Storage	Purpose and debug note
`auth_token`	sessionStorage	Sanctum bearer token. Cleared on logout or 401. A new tab usually needs a new login.
`owner_viewing_hotel`	sessionStorage	Tenant id used by the Axios interceptor as `X-Tenant-ID` for owner switching. Wrong hotel = wrong header.
`active_outlet`	sessionStorage	Unlocked cashier/store outlet. Feature calls pass its id as a request field, not a global header.
`device_key`	localStorage	Stable trusted-device identity. Clearing site data makes the browser a new device.
`locale`	localStorage	Sent as `Accept-Language` so menu/API text follows the UI language.

4.2 Headers on every authenticated request

Header	Source	What it controls
`Authorization: Bearer …`	`auth_token`	Sanctum identity. Missing/expired → 401.
`X-Tenant-ID`	`owner_viewing_hotel`	Owner/superadmin hotel switching. Staff cannot use it to escape their tenant.
`Accept-Language`	`locale`	Localized menu/response content. Not an authorization header.
`Content-Type`	Axios or browser	JSON by default; removed for `FormData` uploads so the boundary is correct.
`Accept: application/json`	Axios default	Makes Laravel return JSON errors instead of an HTML redirect/page.

4.3 Tenant resolution and isolation

- **Staff:** locked to their own `tenant_id`. Sending another tenant header does not grant access.
- **Owner:** may switch between owned hotels using `X-Tenant-ID`, but is treated as read-only. Writes require `operate` and an allowed override.
- **Superadmin:** may switch tenant context and has broad ability, but the selected `X-Tenant-ID` still determines which hotel's data is read.
- **Inactive/suspended tenant:** 403. **Missing/unresolvable tenant:** 404. **No tenant context:** 422 in flows that explicitly require it.

4.4 Role levels and gates

Gate	Typical level	Meaning
Staff read	20	Outlets, menu, orders read, cashier reads.
Operational write	30–50	Cashier/POS, store/inventory, procurement documents.

Gate	Typical level	Meaning
Front desk / management	60–70	Reservations, folio, outlet management, some approvals.
Senior management	80	Voids, overrides, deletions, high-risk approvals.
Administrator	90+	Imports, tenant-level administration, sensitive settings.
`operate`	—	Blocks owner read-only sessions unless an override is allowed.
`features`	—	Feature flags/modules enabled for the tenant.
`trust`	—	Trusted-device/session policy.
`reports`	—	Report-specific access.
`pos-inventory` / `pos-reports`	—	POS access to inventory/report surfaces.

401 vs 403: 401 means “we do not know who you are” (missing/expired token). 403 means “we know who you are, but this tenant/role/feature/device may not do this.” Do not “fix” a 403 by clearing the token.

5.1 Login, token issuance and session restore

Use this when a user cannot sign in, is bounced back to the login screen, or the app opens without permissions.

#	Layer / file	What happens	Debug signal
1	**LoginPage.vue → authApi.login()**	The form posts email, password, optional property code, trust flag and device key to `POST /api/v1/auth/login`.	Network: request body; status 200/401/409/422/429.
2	**routes/api.php:182**	The route is public but throttled by `throttle:auth` and `throttle:auth:ip`.	429 means rate limited; wait or clear the throttle.
3	**AuthController@login**	Validates credentials. An email used by more than one hotel login returns **409** with `ambiguous: true`.	409 is not a wrong password; ask the user to choose the hotel/property.
4	**AuthController@login**	Checks the tenant, user status, role and trusted-device state. Unknown devices may receive a verification challenge instead of a token.	200 with `requires_device_verification` is expected; no token yet.
5	**AuthController@issueSession()**	Creates a Sanctum personal access token. Superadmin gets ability `['*']`; everyone else gets `[user_role]`.	The token is returned once; copy it from the login response for API testing.
6	**stores/auth.js**	Stores `auth_token` in `sessionStorage`, user/profile data, and the device key in `localStorage`.	Application → Session Storage / Local Storage.
7	**router/index.js:795**	The guard sees the token, fetches `GET /api/v1/auth/me` (up to 3 attempts), then checks role/module access.	If `/auth/me` fails, the token or tenant context is invalid.
8	**axios response interceptor**	Any 401 while a token exists clears `auth_token` and redirects to `/login`.	A surprise redirect usually means the token expired or the tenant was deactivated.

Most common cause: a stale `auth_token` or wrong `X-Tenant-ID`. Confirm `/auth/me` first, then inspect the failing call.

5.2 Trusted device, device challenge and PIN login

Use this when a known user is asked to verify a device, the code never arrives, or PIN login fails.

#	Layer / file	What happens	Debug signal
1	**LoginPage.vue**	The browser sends a stable `device_key` from `localStorage` plus `trust_device`.	Missing device key makes every login look like a new device.
2	**POST /auth/login**	Backend checks whether the device is already trusted for that user and tenant.	Response contains the challenge/verification requirement.
3	**POST /auth/login/verify-device**	The emailed/app code is verified. Success issues the normal session token.	422 = bad/expired code; 429 = resend throttle.
4	**POST /auth/login/verify-device/resend**	Sends a fresh code and invalidates the old challenge according to cache policy.	Use only when the first code expired; repeated taps hit throttle.
5	**POST /auth/login-pin**	PIN login is accepted only for a trusted device and a user with a PIN configured.	401 means PIN/device mismatch; 422 means PIN not configured.
6	**DeviceTrustController**	Admins at level 60+ can list and revoke trusted devices at `/auth/trusted-devices`.	If a lost phone must be removed, revoke its row and sign in again.

> **Debug:** compare the `device_key` in Local Storage with the row in the trusted-devices table. Clearing site data intentionally creates a new device.

5.3 Outlet selection, access code and active outlet

Use this when the cashier/bar or store panel will not open, the outlet list is empty, or an access code is rejected.

#	Layer / file	What happens	Debug signal
1	**useOutletContext.js**	Loads `GET /api/v1/outlets` at level 20. The response includes `stockDepartment` and `has_access_code`, never the hash.	Empty list: check tenant, role level and whether outlets exist.
2	**CashierLayout.vue / StoreManagerLayout.vue**	Filters outlets by type: bar/cashier selling points vs store/inventory outlets, then groups them for the two-step picker.	A missing tab usually means the outlet has the wrong type or no stock department.
3	**POST /outlets/{id}/verify-access**	The entered code is compared server-side. This route is level 20 and throttled at 20 requests/minute.	422 = wrong code; 429 = too many attempts; 403 = role/tenant gate.
4	**POST /outlets/{id}/claim-access**	If the outlet has no code yet, a manager-level user can claim it and set the first code.	409/422 means another user already claimed it or the code is already set.
5	**POST /outlets/{id}/reset-access**	Management at level 70+ with `outlets.manage` resets the code and shows the one-time generated code.	If reset is hidden, the user lacks the permission or is not an outlet manager.
6	**sessionStorage**	The unlocked outlet is stored as `active_outlet`. Feature calls pass its id as `outlet_id` or `department_id`; it is not a global header.	Check the request body/query, not only headers, when the backend says an outlet is missing.
7	**GET /outlets/{id}**	The detail response confirms type, stock department, creator and access-code status.	Use this to verify the exact outlet behind the UI label.

> **Remember:** access-code verification unlocks the UI gate; it does not replace role/tenant middleware. Both must pass.

5.4 Create a food & beverage order

Use this when placing an order fails, stock is rejected, or the order appears in the wrong outlet.

#	Layer / file	What happens	Debug signal
1	**OrderTakerDashboard.vue / cashier order screen**	Builds the cart, table/room selection, guest name, outlet id and line items, then calls `orderApi.create()`.	Copy the exact payload from the Network tab.
2	**src/api/index.js → orderApi**	Sends `POST /api/v1/orders` with bearer token and JSON body.	Confirm the URL starts with `/v1/orders`, not a duplicated `/api`.
3	**OrderController@store**	Validates outlet, table/room, items, quantities, modifiers and payment-related fields.	422 response keys identify the exact invalid field.
4	**OrderController@store**	Checks that the F&B business date is open and cleared, then resolves the stock shelf with `UserDepartment::shelfIdForOrder()`.	Business-date or shelf errors mean the outlet/department link is incomplete.
5	**FnbInventoryService**	Checks ingredient availability against the resolved shelf before creating the order.	422 'not enough stock' includes the item; compare shelf stock and recipe quantities.
6	**DB::transaction**	Creates the order and items, calculates totals and commits. Any exception rolls the whole order back.	No partial order should remain after a 500/422.
7	**OrderUpdated event**	Broadcasts to the tenant/kitchen channels after commit so boards refresh.	If the API succeeds but the kitchen does not update, debug Echo, not the order controller.

> **Fast check:** repeat the same request with the same outlet, shelf and item ids in an API client. If it fails there too, the problem is backend/domain data, not Vue.

5.5 Kitchen item status, serve and recall

Use this when the kitchen board does not move an item, or a waiter cannot mark food ready/served.

#	Layer / file	What happens	Debug signal
1	**KitchenBoardPage.vue**	Loads orders with `GET /api/v1/orders` and filters by outlet/business date/status.	An empty board can be a date, outlet or status filter problem.
2	**orderApi.markItemStatus()**	Sends `PATCH /api/v1/orders/{id}/items/{itemId}/status` with the target status.	Confirm both ids: order id and order-item id are different.
3	**OrderController@markItemStatus**	Validates the transition and updates the item state; order-level status may follow.	422 means the transition is not allowed from the current state.
4	**OrderUpdated event**	Broadcasts the changed order so cashier, waiter and kitchen boards converge.	Use browser WebSocket frames to confirm the event arrived.
5	**Echo channels**	Private tenant/user channels are authorized by `POST /broadcasting/auth` using the same Sanctum token.	401/403 on broadcasting auth means the token or channel authorization failed.

> **Split-brain symptom:** the database is correct but one screen is stale. Reload that screen; if it then shows the right state, investigate the realtime channel.

5.6 Settle an order: cash, room bill or credit account

Use this when payment is rejected, an order stays unpaid, or a room/credit posting is wrong.

#	Layer / file	What happens	Debug signal
1	**CashierOrderSummaryPage.vue / waiter settlement panel**	Calls one of `/orders/{id}/pay`, `/orders/{id}/bill-to-room` or `/orders/{id}/settle-credit-account`.	The three settlement paths have different validation and different debug signals.
2	**OrderController@pay**	Locks the order row, rejects frozen/merged/already-paid orders, checks who may collect, then marks paid and records a payment.	422 is a state problem; 403 is an ownership/role problem.
3	**OrderController@billToRoom**	Finds an active reservation for the room; if the room is merely occupied, it opens a walk-in folio, then increments room charges atomically.	422 means no active booking/room or the guest has not arrived.
4	**OrderController@settleCreditAccount**	Requires an active `creditor` or `no_charge` account belonging to the tenant.	422 means the account is inactive, wrong type or from another tenant.
5	**PaymentService / folio update**	Writes the payment or room/credit posting inside the same transaction as the order state change.	If the order is paid but no payment/folio row exists, inspect the transaction and logs.
6	**freeTableIfCleared()**	Releases the table when no running orders remain.	Table still occupied usually means another running order exists.
7	**AuditService**	Writes an audit row with settlement mode, provider, user and timestamp.	Use audit history to prove who settled and when.

Cash shift check: if cash collection is blocked by register state, open the POS shift first at `/pos/shift/open`.

5.7 Void, split, merge, transfer and freeze

Use this when an order cannot be corrected or the wrong ticket was changed.

#	Layer / file	What happens	Debug signal
1	**Order actions**	Void uses `POST /orders/{id}/void`; split/merge/transfer use their dedicated endpoints.	Do not edit the database directly; these actions have stock/folio side effects.
2	**OrderController**	Locks the affected order(s), validates status and permissions, then reverses or moves items.	422 = invalid state; 403 = wrong role/ownership.
3	**Inventory reversal**	Voiding may return consumed ingredients to stock; the movement is written with the order reference.	Check stock movements for the order id if quantities look wrong.
4	**CashierController@freeze/unfreeze**	Frozen orders cannot be settled until unfrozen. Freeze is level 30 + operate.	422 'Order is frozen' is intentional, not a broken payment.
5	**Audit + broadcast**	The change is audited and an `OrderUpdated` event is dispatched.	A missing audit row means the action did not reach the controller.

Rule: correct a settled ticket through a refund/void workflow, not by deleting the order. Deleting breaks payment and audit history.

5.8 F&B business date and day close

Use this when the day-close button is disabled, close fails, or reports show the wrong day.

#	Layer / file	What happens	Debug signal
1	**GET /api/v1/business-date**	The frontend loads the current open business date for the tenant.	Timezone mismatch is the first thing to check.
2	**CashierDayClosePage.vue**	Loads close history with `GET /api/v1/fnb/day-closes` and posts `POST /api/v1/fnb/day-close`.	The posted date must be `Y-m-d` in hotel-local time.
3	**FbDayCloseController@store**	Rejects the current date, already-closed dates, running orders and unsettled orders.	422 messages state the exact blocker; 409 means already closed.
4	**FbDayClose snapshot**	Builds and stores totals/snapshot for the closed date.	Compare snapshot totals with reports before investigating discrepancies.
5	**Timezone update**	The day-close screen may update the hotel timezone at `PUT /api/v1/fnb/timezone`.	Changing timezone changes which UTC range belongs to a business date.

Debug order: confirm timezone → confirm business date → count running orders → count unsettled orders → inspect close snapshot.

5.9 POS shift and cash register

Use this when the cash drawer is closed, shift history is missing, or expected cash does not match.

#	Layer / file	What happens	Debug signal
1	**StoreCashRegisterPage.vue / POS screens**	Calls `GET /pos/shift/current` to decide whether a shift is open.	A closed shift blocks cash operations by design.
2	**POST /pos/shift/open**	Records opening float and opens the drawer for the current user/tenant.	422 means a shift is already open or the float is invalid.
3	**POST /pos/shift/close**	Closes against counted cash and stores the variance.	Compare counted, expected and variance in the response.
4	**GET /pos/shifts**	Lists historical shifts, newest first.	Empty history: wrong tenant, date range or no closed shifts.
5	**CashRegisterController**	Daily summary combines opening float, floats added, expenses, sales and expected cash.	A date filter must be sent in the request; the server does not guess the UI date.

> **Expected-cash mismatch:** reconcile payments, cash movements, void/refund rows and shift boundaries before changing code.

5.10 Inventory catalogue, stock and low-stock views

Use this when items are missing, stock looks wrong, or the store panel shows the wrong shelf.

#	Layer / file	What happens	Debug signal
1	**inventoryApi / inventoryOpsApi**	Loads `GET /api/v1/inventory`, item detail, movements and low-stock views.	Check query params: `outlet_id`, `department_id`, category, search, page.
2	**InventoryController**	Applies tenant scope and optional shelf/department filter, then returns paginated items.	Wrong shelf usually means the request omitted or sent the wrong department id.
3	**UserDepartment::shelfIdForOrder()**	Backend resolves the stock shelf for the selected outlet rather than trusting a client-supplied shelf.	If the outlet has no stock department, stock checks cannot resolve.
4	**InventoryService**	Returns quantities and movement history; stock is the sum of movements, not an editable field.	Use movements to explain a quantity, not direct DB edits.
5	**InventoryUpdated event**	Stock changes broadcast so other open panels refresh.	Refresh manually to distinguish stale UI from wrong data.

> **Important:** the outlet/department link is data. Fix the link in outlet/department management before debugging the inventory query.

5.11 Stock adjustment (wastage, consumption, adjustment)

Use this when a stock adjustment cannot be saved or stock does not change.

#	Layer / file	What happens	Debug signal
1	**StoreStockAdjustPage.vue**	Builds a sheet with type, business date, reason, line items, quantities and SI units, then calls `POST /api/v1/inventory-stock-adjustments`.	Copy the payload; unit and factor mistakes are common.
2	**StockAdjustmentController@store**	Validates `type` as `wastage|consumption|adjustment`, business date and unique items.	422 names the invalid type/date/item.
3	**Shelf resolution**	Resolves the shelf through `UserDepartment::shelfIdForOrder()`.	A missing shelf produces a domain error even when the item exists.
4	**DB::transaction**	Creates the adjustment header/lines and posts stock movements through `InventoryService`.	If the header exists but stock did not move, inspect the transaction/logs.
5	**Audit + broadcast**	Writes the audit trail and dispatches `InventoryUpdated`.	Audit row proves the write; broadcast is a separate concern.

SI-unit check: the UI may show cartons while the backend stores base units. Verify the conversion factor on the item.

5.12 Physical stock take

Use this when a count cannot be saved, posted or voided, or counted quantities do not match stock.

#	Layer / file	What happens	Debug signal
1	**StoreStockCountsPage.vue**	Loads the count sheet and default item scope, then saves counted quantities with `POST /api/v1/inventory-stock-takes`.	The default scope is the selected shelf; confirm the shelf before counting.
2	**PhysicalStockTakeController@store**	Validates the count date, items and quantities; creates a draft/count record.	422 means an item/quantity/date is invalid.
3	**StockTransactionService::postTake()**	Posts the variance between counted and system quantity as stock movements.	Compare counted, system and variance before posting.
4	**StockTransactionService::voidTake()**	Voids the take and reverses its movements.	A voided take must not still contribute to stock.
5	**Audit + event**	Records who counted/posted/voided and broadcasts inventory changes.	Use audit history for accountability.

> **Do not edit stock directly.** Re-post or void the count so movement history remains explainable.

5.13 Stock transfer

Use this when a transfer cannot be sent, received stock is wrong, or the destination outlet is missing.

#	Layer / file	What happens	Debug signal
1	**StoreTransfersPage.vue**	Builds source/destination outlets, lines, SI units and costs, then calls `POST /api/v1/inventory-transfers`.	Only outlets with a stock department should appear.
2	**StockTransferController@store**	Validates source/destination, items, quantities and the `send` flag.	422 identifies the invalid line or outlet.
3	**postTransfer()**	Deducts from the source shelf and adds to the destination shelf in one transaction.	If one side moved and the other did not, inspect transaction logs; it should roll back.
4	**Status lifecycle**	Draft can be edited; sent/completed is stock-affecting; void reverses the movement.	Check status before trying to edit.
5	**Audit + broadcast**	Writes the transfer audit and emits `InventoryUpdated`.	Both outlets should refresh after the event.

Check first: both outlets must have stock departments, and the destination must not be the source.

5.14 Requisition → purchase order → goods received note

Use this when procurement documents cannot progress or received goods do not increase stock.

#	Layer / file	What happens	Debug signal
1	**RequisitionListPage.vue**	Creates/submits a requisition via `/purchase-requisitions`.	Approval state controls whether a PO can be raised.
2	**PurchaseOrderListPage.vue**	Creates a PO via `POST /purchase-orders`, then manager/finance approvals use their dedicated endpoints.	422 = invalid supplier/item/price; 403 = wrong approval level.
3	**GoodsReceivedNoteListPage.vue**	Posts `POST /goods-received-notes` with PO id, received/rejected quantities, unit costs and attachments.	422 over-delivery means received quantity exceeds the remaining PO quantity.
4	**GoodsReceivedNoteController@store**	Runs in a transaction: validates the PO is open, resolves the inventory item, records the GRN, increments received quantity and posts stock in.	Check the GRN, PO received quantity and stock movement together.
5	**Unit conversion**	Received quantities in an alternate unit are converted to the item base unit before stock-in.	A missing conversion factor is rejected rather than posting a wrong quantity.
6	**Recall/void**	Recalling a GRN requires a reason; after the receiving business day only management may recall it.	403/422 explains whether the day or role blocks the edit.
7	**Audit + notification**	Writes audit and notifies procurement/receivers.	A missing stock increase with a successful GRN is a transaction/log investigation.

> **Do not create a second GRN to fix a mistake.** Recall or void the original so PO received quantities and stock stay aligned.

5.15 Reports and exports

Use this when a report is empty, totals disagree with operations, or an export/download fails.

#	Layer / file	What happens	Debug signal
1	**Report pages**	Call `reportApi` endpoints under `/api/v1/reports` with date range, outlet/department and filters.	Copy the query string; most report bugs are wrong filters.
2	**EnsureReportAccess**	Checks the user's report permission and tenant scope before the controller runs.	403 means the report is not enabled for that role/hotel.
3	**Report controller/service**	Aggregates operational tables using the hotel timezone and business date rules.	Compare one source row (order/payment/stock movement) with the report total.
4	**Export endpoints**	PDF/CSV generation may stream a file rather than JSON.	Network response type should be blob; a JSON error shown as a download means backend validation failed.
5	**Caching/queues**	Some reports or notifications are queued; a missing result may still be processing.	Check queue worker and failed-jobs table.

Reconciliation: pick one known transaction, trace it to its source table, then compare with the report filter and timezone.

5.16 Reservations, check-in, folio and checkout

Use this when a booking cannot be created, check-in fails, or a folio/payment is wrong.

#	Layer / file	What happens	Debug signal
1	**Reservation pages**	Load `GET /reservations`, options and folio; create/update via `POST/PUT /reservations`.	Viewing is level 60; writes also require `operate`.
2	**ReservationController@store/update**	Validates guest, room type, dates, occupancy and rate, then checks availability.	422 = dates/room/occupancy conflict.
3	**POST /reservations/{id}/check-in**	Validates arrival, room readiness and overrides, then marks the room occupied and the reservation checked in.	422 means the room is not ready or the booking state is wrong.
4	**Folio endpoints**	Charges, discounts, adjustments, inclusions, transfers and attachments post to the folio ledger.	Use the folio ledger, not the reservation total, to explain a guest bill.
5	**POST /reservations/{id}/check-out**	Checks unsettled folio balance, posts room charges and releases the room.	A blocked checkout usually has an unpaid folio entry or unresolved credit posting.
6	**Invoice/payment**	Invoices generate from the folio; payments are recorded against reservation/folio.	Trace the payment id and folio entry id together.

> **Golden rule:** the folio ledger is the source of truth for the guest bill. Reservation totals are a summary and can lag after adjustments.

5.17 Housekeeping, laundry and guest requests

Use this when tasks do not appear, statuses do not move, or laundry charges do not reach the bill.

#	Layer / file	What happens	Debug signal
1	**Housekeeping pages**	Load `GET /housekeeping-tasks`, dashboard and board at level 40.	Empty board: check date, room, assignee and status filters.
2	**Task actions**	Create/assign/start/confirm/verify/complete use dedicated endpoints; some require `can:housekeeping.work`.	403 = role/ability; 422 = invalid task transition.
3	**Laundry orders**	Create/update at `/laundry-orders`; cloth types and compositions are separate registries.	Missing price = cloth type/composition not configured.
4	**Guest requests**	Guest portal requests use public/guest-token routes and then appear in staff queues.	Check the guest portal token and tenant before debugging staff views.
5	**Charges**	Laundry settlement may post to a room folio or a payment record.	Follow the same folio/payment trace as F&B room billing.

Check the registry first: a laundry item cannot be priced or billed until its cloth type and composition exist.

5.18 Messaging, notifications and realtime

Use this when messages do not arrive, notifications are missing, or live boards do not update.

#	Layer / file	What happens	Debug signal
1	**conversationApi / notificationApi**	Loads conversations, messages and notifications over normal authenticated HTTP.	If HTTP works but live updates do not, the issue is Echo/Reverb.
2	**src/plugins/echo.js**	Creates the Echo/Reverb client and subscribes to private/presence channels.	Browser console shows WebSocket connection and subscription errors.
3	**POST /broadcasting/auth**	Authorizes private channels with the Sanctum token and channel rules in `routes/channels.php`.	401/403 here means the token or channel membership is wrong.
4	**Broadcast events**	`OrderUpdated` and `InventoryUpdated` are `ShouldBroadcastNow`.	Check the event payload and whether the listener is subscribed to that channel.
5	**Notifications**	Database notifications are written by services; email/SMS may be queued.	Check the notifications table, queue worker and failed jobs.

Separate the layers: HTTP data → event dispatch → queue/Reverb → channel auth → client listener. Fix the first broken layer.

5.19 Owner portal and superadmin hotel switching

Use this when an owner sees the wrong hotel, cannot edit, or a superadmin action is forbidden.

#	Layer / file	What happens	Debug signal
1	**Owner pages**	The owner selects a hotel; the frontend stores it as `owner_viewing_hotel`.	Check Session Storage before every owner request.
2	**axios interceptor**	Adds `X-Tenant-ID` from `owner_viewing_hotel` to every request.	If the header is missing, the backend uses the owner's own tenant and returns the wrong scope.
3	**SetTenantContext**	Allows owner/superadmin switching, but marks owners read-only; staff cannot switch tenants.	403 on write is expected for an owner unless an override is allowed.
4	**CanOperate**	Blocks owner writes unless the request carries an allowed `override`.	A read works but a write fails: inspect `operate`/override, not the endpoint.
5	**Superadmin**	Superadmin tokens have `*` ability and can switch tenants.	Still verify the selected `X-Tenant-ID`; a valid token can point at the wrong hotel.

> **Owner rule:** owner access is for visibility. Do not treat a read-only 403 as a broken token.

6. Error response map

Read the status first, then the message and validation keys. The same status can have different fixes.

Status	Typical meaning	Where to look	First fix to try
200/201	Request accepted; business result may still be wrong.	Response payload, audit row, movement/ledger row.	Verify the specific record, not just the toast.
401	Missing, expired or invalid Sanctum token.	Session Storage, `/auth/me`, token expiry.	Log in again; confirm the Authorization header exists.
403	Authenticated but forbidden by role, tenant, feature, trust, owner read-only or ability.	Middleware, user role level, feature flags, tenant status, `operate`.	Do not clear the token. Check the exact gate named in the message.
404	Route not found, tenant not found, or record not in this tenant.	`route:list`, URL path, tenant scope, deleted record.	Confirm method/URI and that the record belongs to the active tenant.
409	Conflict: ambiguous login email, already-closed day, duplicate resource.	Auth ambiguous flag, day-close history, unique keys.	Resolve the existing resource; do not retry blindly.
419	CSRF/session page expired (more common with cookie/session auth than bearer API).	Session/cookie config, proxy, Sanctum SPA setup.	Refresh session; confirm the API uses the intended auth mode.
422	Validation failed or a domain rule aborted the action.	`errors` object, controller abort message, business date/stock/folio state.	Fix the named field or state; the request reached the domain.
429	Rate limit hit.	`throttle:auth`, `throttle:api`, access-code 20/min, public webhooks.	Wait; do not loop retries. Check for duplicate submit handlers.
500	Unhandled exception, missing config, DB/queue/ storage failure.	`storage/logs/laravel.log`, failed jobs, storage permissions, DB connection.	Use the stack trace; identify the controller/service line, then reproduce.
503	Service unavailable: maintenance, queue/ broadcast dependency, upstream integration.	Deploy status, Reverb/queue workers, external provider.	Check service health before changing application code.

Common response shapes

Shape	Example / meaning
Success message	`{ "message": "Order marked as paid.", "order": { ... }, "payment": { ... } }`
Validation error	`{ "message": "The given data was invalid.", "errors": { "items.0.quantity": ["..."] } }`
Paginated list	`{ "data": [...], "meta": { "current_page": 1, "last_page": 3, "total": 42 } }` — Axios flattens meta onto the payload.
Ambiguous login	`{ "message": "...", "ambiguous": true }` with HTTP 409; ask for the hotel/property.

Shape	Example / meaning
Day close conflict	`{ "message": "This F&B business day is already closed.", "day_close": { ... } }` with HTTP 409.

7. Debugging playbook

A repeatable sequence that avoids guessing. Stop at the first checkpoint that does not match.

#	Checkpoint	What to capture / verify	What it proves
1	Reproduce once	DevTools Network with “Preserve log”; one user action, one request. Note the exact screen, outlet, date and user.	The failing request is identified, not a later side effect.
2	Read the request	Method, full URL, status, request headers, query, JSON body or FormData fields.	Frontend sent what the backend expects.
3	Read the response	Status, `message`, `errors`, data/meta. Do not stop at “it failed”.	The backend named the failing rule or field.
4	Check session context	`auth_token`, `owner_viewing_hotel`, `active_outlet`, `device_key`, `locale`.	The right user, hotel and outlet are in play.
5	Confirm the route	Compare the URL with section 8 and `php artisan route:list --path=api/v1`.	The request is hitting an existing action, not a typo/404.
6	Replay outside Vue	Use curl/Postman with the same token, tenant and body. Never paste production secrets into shared logs.	Separates frontend state bugs from backend/domain bugs.
7	Read the backend log	`storage/logs/laravel.log`, failed jobs, web server log. Search the request timestamp and controller.	The stack trace or domain abort behind a 500/422.
8	Inspect the committed records	Audit row, order/payment, stock movement, GRN/PO, folio entry. Check tenant id and timestamps.	The transaction actually wrote the expected business result.
9	Test realtime separately	Refresh the screen over HTTP. If correct after refresh, inspect Echo/Reverb/channel auth, not the controller.	The data is right; only the live update is stale.
10	Record the cause	Add a regression test at the closest layer: component, API contract, controller feature test or service test.	The same failure does not return silently.

Replay template

Use the real base URL from `VITE_API_URL`. If it is `http://localhost:8000/api`, the endpoint below becomes `http://localhost:8000/api/v1/orders`.

```
curl -i -X POST "$API_BASE/v1/orders" \
  -H "Authorization: Bearer $TOKEN" \
  -H "Accept: application/json" \
  -H "Content-Type: application/json" \
  -H "Accept-Language: en" \
  -H "X-Tenant-ID: $TENANT_ID" \
  -d '{"outlet_id":"...","items":[{"item_id":"...","quantity":1}]}'
```

> **Do not guess the tenant:** use the tenant id from the authenticated user/profile, not an arbitrary hotel id. For staff, the backend ignores attempts to switch; for owners/superadmins, the wrong `X-Tenant-ID` silently reads the wrong hotel.

Where to look by symptom

Symptom	First place to look
Redirected to login immediately	Token expiry, `/auth/me` failure, tenant inactive, Axios 401 handler.
Screen opens but is empty	Request query filters, outlet/date, pagination, response `data`, tenant scope.
Button does nothing	Form validation, disabled state, missing active outlet/date, JavaScript console error.
403 on only one action	Route `level`, `operate`, feature flag, ability, owner read-only.
422 on a valid-looking form	Read `errors`; check unit conversion, business date, stock shelf, state transition.
Saved but list unchanged	Response handling, list refresh, pagination/filter, stale realtime, cached store.
Order paid but no payment row	Transaction rollback, payment service, DB connection, audit/logs.
GRN saved but stock unchanged	GRN transaction, resolved inventory item, unit conversion, `InventoryService::adjustStock`.
Kitchen board stale	HTTP refresh first; then Echo connection, `/broadcasting/auth`, channel name, event listener.
Report total differs	Timezone/business date, outlet/department filter, source ledger/movement, queued report.

8. Complete API v1 route catalogue

All **630** routes whose URI starts with `api/v1`, grouped by the first path segment. The catalogue is generated from `php artisan route:list --json`, so it reflects the backend commit used for this guide. Public routes appear alongside authenticated routes; always read the middleware column.

> **How to read the middleware column:** `auth:sanctum` = token required; `tenant` = tenant context; `features` = feature enabled; `trust` = trusted session/device; `throttle:*` = rate limit; `level:N` = minimum role level; `operate` = owner write gate; `reports` / `pos-inventory` / `pos-reports` = module-specific gates. A route with no auth middleware is public or webhook-protected by another mechanism.

Accounting 6 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/accounting/balance-sheet	Finance\AccountingController@balanceSheet	api · auth:sanctum · tenant · features · trust · throttle:api · level:70
GET|HEAD	/api/v1/accounting/day-close	Finance\AccountingController@dayCloseReport	api · auth:sanctum · tenant · features · trust · throttle:api · level:70
POST	/api/v1/accounting/day-close	Finance\AccountingController@storeDayClose	api · auth:sanctum · tenant · features · trust · throttle:api · level:70
GET|HEAD	/api/v1/accounting/day-closes	Finance\AccountingController@dayCloses	api · auth:sanctum · tenant · features · trust · throttle:api · level:70
GET|HEAD	/api/v1/accounting/general-ledger	Finance\AccountingController@generalLedger	api · auth:sanctum · tenant · features · trust · throttle:api · level:70
GET|HEAD	/api/v1/accounting/trial-balance	Finance\AccountingController@trialBalance	api · auth:sanctum · tenant · features · trust · throttle:api · level:70

Activity Log Report 1 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/activity-log-report	Reception\ActivityLogReportController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:60

Attendance 27 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/attendance/absences	Staff\StaffAttendanceController@absenceRequests	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
POST	/api/v1/attendance/absences	Staff\StaffAttendanceController@reportAbsence	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:attendance
GET|HEAD	/api/v1/attendance/absences/mine	Staff\StaffAttendanceController@myAbsenceRequests	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
POST	/api/v1/attendance/absences/{requestId}/decide	Staff\StaffAttendanceController@decideAbsenceRequest	api · auth:sanctum · tenant · features · trust · throttle:api · level:80 · throttle:attendance
GET|HEAD	/api/v1/attendance/attachments/{attachmentId}	Staff\StaffAttendanceController@viewAttachment	api · auth:sanctum · tenant · features · trust · throttle:api · level:20

Method	URI	Controller action	Middleware
POST	/api/v1/attendance/clock-in	Staff\StaffAttendanceController@clockIn	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:attendance
POST	/api/v1/attendance/clock-out	Staff\StaffAttendanceController@clockOut	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:attendance
GET|HEAD	/api/v1/attendance/devices	Staff\StaffAttendanceController@devices	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
GET|HEAD	/api/v1/attendance/devices/mine	Staff\StaffAttendanceController@myDevices	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
POST	/api/v1/attendance/devices/register	Staff\StaffAttendanceController@registerDevice	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:attendance
POST	/api/v1/attendance/devices/{deviceRowId}/revoke	Staff\StaffAttendanceController@revokeDevice	api · auth:sanctum · tenant · features · trust · throttle:api · level:80 · throttle:attendance
GET|HEAD	/api/v1/attendance/on-shift	Staff\StaffAttendanceController@onShift	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
GET|HEAD	/api/v1/attendance/penalties	Staff\StaffAttendanceController@penalties	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
POST	/api/v1/attendance/penalties	Staff\StaffAttendanceController@imposePenalty	api · auth:sanctum · tenant · features · trust · throttle:api · level:80 · throttle:attendance
GET|HEAD	/api/v1/attendance/penalties/mine	Staff\StaffAttendanceController@myPenalties	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
POST	/api/v1/attendance/penalties/{penaltyId}/decide	Staff\StaffAttendanceController@decidePenalty	api · auth:sanctum · tenant · features · trust · throttle:api · level:80 · throttle:attendance
GET|HEAD	/api/v1/attendance/photos/{attendanceId}	Staff\StaffAttendanceController@viewPhoto	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
GET|HEAD	/api/v1/attendance/policy	Staff\StaffAttendanceController@policy	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
PUT	/api/v1/attendance/policy	Staff\StaffAttendanceController@updatePolicy	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
POST	/api/v1/attendance/qr-token	Staff\StaffAttendanceController@issueQrToken	api · auth:sanctum · tenant · features · trust · throttle:api · level:80 · throttle:attendance
GET|HEAD	/api/v1/attendance/register	Staff\StaffAttendanceController@register	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
GET|HEAD	/api/v1/attendance/requirements	Staff\StaffAttendanceController@requirements	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
GET|HEAD	/api/v1/attendance/settings	Staff\StaffAttendanceController@settings	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
PUT	/api/v1/attendance/settings	Staff\StaffAttendanceController@updateSettings	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
GET|HEAD	/api/v1/attendance/status	Staff\StaffAttendanceController@status	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
GET|HEAD	/api/v1/attendance/suspicious	Staff\StaffAttendanceController@suspicious	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
GET|HEAD	/api/v1/attendance/users/{userId}/history	Staff\StaffAttendanceController@history	api · auth:sanctum · tenant · features · trust · throttle:api · level:80

Authentication & session 13 routes

Method	URI	Controller action	Middleware
POST	/api/v1/auth/change-password	Auth\AuthController@changePassword	api · auth:sanctum · tenant · features · trust · throttle:api
POST	/api/v1/auth/forgot-password	Auth\AuthController@forgotPassword	api · throttle:auth
POST	/api/v1/auth/login	Auth\AuthController@login	api · throttle:auth · throttle:auth:ip
POST	/api/v1/auth/login-pin	Auth\AuthController@loginPin	api · throttle:auth · throttle:auth:ip
POST	/api/v1/auth/login/verify-device	Auth\AuthController@verifyDeviceTrust	api · throttle:auth · throttle:auth:ip
POST	/api/v1/auth/login/verify-device/resend	Auth\DeviceTrustResendController@resend	api · throttle:auth · throttle:auth:ip
POST	/api/v1/auth/logout	Auth\AuthController@logout	api · auth:sanctum · tenant · features · trust · throttle:api
GET|HEAD	/api/v1/auth/me	Auth\AuthController@me	api · auth:sanctum · tenant · features · trust · throttle:api
POST	/api/v1/auth/register	Auth\AuthController@register	api · throttle:auth · throttle:auth:ip
POST	/api/v1/auth/reset-password	Auth\AuthController@resetPassword	api · throttle:auth
GET|HEAD	/api/v1/auth/trusted-devices	Auth\DeviceTrustController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
DELETE	/api/v1/auth/trusted-devices/{id}	Auth\DeviceTrustController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
POST	/api/v1/auth/update-profile	Auth\AuthController@updateProfile	api · auth:sanctum · tenant · features · trust · throttle:api

Booking Requisitions 4 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/booking-requisitions	Booking\BookingRequisitionController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
DELETE	/api/v1/booking-requisitions/{id}	Booking\BookingRequisitionController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
GET|HEAD	/api/v1/booking-requisitions/{id}	Booking\BookingRequisitionController@show	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
POST	/api/v1/booking-requisitions/{id}/respond	Booking\BookingRequisitionController@respond	api · auth:sanctum · tenant · features · trust · throttle:api · level:60

Business date 1 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/business-date	Reception\NightAuditController@businessDate	api · auth:sanctum · tenant · features · trust · throttle:api · level:40

Calls 6 routes

Method	URI	Controller action	Middleware
POST	/api/v1/calls	Messaging\CallController@initiate	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/calls/{callId}/accept	Messaging\CallController@accept	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/calls/{callId}/cancel	Messaging\CallController@cancel	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/calls/{callId}/decline	Messaging\CallController@decline	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/calls/{callId}/end	Messaging\CallController@end	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/calls/{callId}/signal	Messaging\CallController@signal	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging

Cashier board & accounts 12 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/cashier/accounts	FoodBeverage\CashierController@accounts	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
GET|HEAD	/api/v1/cashier/creditors	FoodBeverage\CreditorController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
POST	/api/v1/cashier/creditors	FoodBeverage\CreditorController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:70
DELETE	/api/v1/cashier/creditors/{id}	FoodBeverage\CreditorController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:70
PUT	/api/v1/cashier/creditors/{id}	FoodBeverage\CreditorController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:70
GET|HEAD	/api/v1/cashier/frozen-orders	FoodBeverage\CashierController@frozenOrders	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
GET|HEAD	/api/v1/cashier/inventory-items	FoodBeverage\CashierController@inventoryItems	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
GET|HEAD	/api/v1/cashier/tables/today-orders-batch	FoodBeverage\CashierController@todayOrdersBatch	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
GET|HEAD	/api/v1/cashier/tables/{tableId}/today-orders	FoodBeverage\CashierController@tableTodayOrders	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
PUT	/api/v1/cashier/tables/{tableId}/waiter	FoodBeverage\CashierController@assignWaiter	api · auth:sanctum · tenant · features · trust · throttle:api · level:30
GET|HEAD	/api/v1/cashier/waiters	FoodBeverage\CashierController@waiters	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
GET|HEAD	/api/v1/cashier/waiters/{userId}/orders	FoodBeverage\CashierController@waiterOrders	api · auth:sanctum · tenant · features · trust · throttle:api · level:20

Categories 4 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/categories	Inventory\CategoryCatalogController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
POST	/api/v1/categories	Inventory\CategoryCatalogController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
DELETE	/api/v1/categories/{category}	Inventory\CategoryCatalogController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
PUT	/api/v1/categories/{category}	Inventory\CategoryCatalogController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:80

Checkin Overrides 5 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/checkin-overrides	Hotel\CheckinOverrideController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
POST	/api/v1/checkin-overrides	Hotel\CheckinOverrideController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
GET|HEAD	/api/v1/checkin-overrides/active	Hotel\CheckinOverrideController@active	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
GET|HEAD	/api/v1/checkin-overrides/stats	Hotel\CheckinOverrideController@stats	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
POST	/api/v1/checkin-overrides/{id}/revoke	Hotel\CheckinOverrideController@revoke	api · auth:sanctum · tenant · features · trust · throttle:api · level:80

Company database 6 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/companies	Hotel\CompanyController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
POST	/api/v1/companies	Hotel\CompanyController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
DELETE	/api/v1/companies/{company}	Hotel\CompanyController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
PUT	/api/v1/companies/{company}	Hotel\CompanyController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
GET|HEAD	/api/v1/companies/{company}/postings	Hotel\CompanyController@postings	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
POST	/api/v1/companies/{company}/settle	Hotel\CompanyController@settle	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate

Currency Rates 4 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/currency-rates	Finance\CurrencyRateController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:60

Method	URI	Controller action	Middleware
POST	/api/v1/currency-rates	Finance\CurrencyRateController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
DELETE	/api/v1/currency-rates/{rate}	Finance\CurrencyRateController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
PUT	/api/v1/currency-rates/{rate}	Finance\CurrencyRateController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate

Departments 4 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/departments	Inventory\DepartmentController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
POST	/api/v1/departments	Inventory\DepartmentController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
DELETE	/api/v1/departments/{department}	Inventory\DepartmentController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:80 · operate
PUT	/api/v1/departments/{department}	Inventory\DepartmentController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:80 · operate

Distribution channels 8 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/distribution/logs	Reception\DistributionController@logs	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
GET|HEAD	/api/v1/distribution/sources	Reception\DistributionController@sources	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
POST	/api/v1/distribution/sources	Reception\DistributionController@storeSource	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · level:80
PUT	/api/v1/distribution/sources/reorder	Reception\DistributionController@reorderSources	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · level:80
DELETE	/api/v1/distribution/sources/{source}	Reception\DistributionController@destroySource	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · level:80
PUT	/api/v1/distribution/sources/{source}	Reception\DistributionController@updateSource	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · level:80
GET|HEAD	/api/v1/distribution/stop-sell-schedules	Reception\DistributionController@schedules	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
POST	/api/v1/distribution/stop-sell-schedules	Reception\DistributionController@updateSchedules	api · auth:sanctum · tenant · features · trust · throttle:api · level:60

F&B business date & day close 8 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/fnb/credit-accounts	FoodBeverage\CreditAccountController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:20

Method	URI	Controller action	Middleware
POST	/api/v1/fnb/credit-accounts	FoodBeverage\CreditAccountController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:70
DELETE	/api/v1/fnb/credit-accounts/{id}	FoodBeverage\CreditAccountController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:70
PUT	/api/v1/fnb/credit-accounts/{id}	FoodBeverage\CreditAccountController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:70
GET|HEAD	/api/v1/fnb/day-close	FoodBeverage\FbDayCloseController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:30
POST	/api/v1/fnb/day-close	FoodBeverage\FbDayCloseController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:30
GET|HEAD	/api/v1/fnb/day-closes	FoodBeverage\FbDayCloseController@history	api · auth:sanctum · tenant · features · trust · throttle:api · level:30
PUT	/api/v1/fnb/timezone	FoodBeverage\FbDayCloseController@updateTimezone	api · auth:sanctum · tenant · features · trust · throttle:api · level:30

Folio ledger 5 routes

Method	URI	Controller action	Middleware
PUT	/api/v1/folio/entries/{id}	Hotel\FolioController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
DELETE	/api/v1/folio/entries/{id}/attachment	Hotel\FolioController@deleteAttachment	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
GET|HEAD	/api/v1/folio/entries/{id}/attachment	Hotel\FolioController@downloadAttachment	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
POST	/api/v1/folio/entries/{id}/void	Hotel\FolioController@void	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
GET|HEAD	/api/v1/folio/search	Hotel\FolioController@search	api · auth:sanctum · tenant · features · trust · throttle:api · level:60

Fun Games 5 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/fun-games	Fun\FunGameOrderController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:40
POST	/api/v1/fun-games	Fun\FunGameOrderController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:40 · operate
DELETE	/api/v1/fun-games/{id}	Fun\FunGameOrderController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:40 · operate
GET|HEAD	/api/v1/fun-games/{id}	Fun\FunGameOrderController@show	api · auth:sanctum · tenant · features · trust · throttle:api · level:40
PUT	/api/v1/fun-games/{id}	Fun\FunGameOrderController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:40 · operate

Goods received notes 7 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/goods-received-notes	Procurement\GoodsReceivedNoteController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:50
POST	/api/v1/goods-received-notes	Procurement\GoodsReceivedNoteController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:50 · operate
GET|HEAD	/api/v1/goods-received-notes/{id}	Procurement\GoodsReceivedNoteController@show	api · auth:sanctum · tenant · features · trust · throttle:api · level:50
PUT	/api/v1/goods-received-notes/{id}	Procurement\GoodsReceivedNoteController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:50
POST	/api/v1/goods-received-notes/{id}/email	Procurement\GoodsReceivedNoteController@email	api · auth:sanctum · tenant · features · trust · throttle:api · level:50
GET|HEAD	/api/v1/goods-received-notes/{id}/pdf	Procurement\GoodsReceivedNoteController@printPdf	api · auth:sanctum · tenant · features · trust · throttle:api · level:50
POST	/api/v1/goods-received-notes/{id}/void	Procurement\GoodsReceivedNoteController@void	api · auth:sanctum · tenant · features · trust · throttle:api · level:50

Guest 5 routes

Method	URI	Controller action	Middleware
POST	/api/v1/guest/portal/auth	Guest\GuestPortalController@authenticate	api · BlockListBots · throttle:auth
GET|HEAD	/api/v1/guest/portal/booking	Guest\GuestPortalController@booking	api · BlockListBots · throttle:public
GET|HEAD	/api/v1/guest/portal/folio	Guest\GuestPortalController@folio	api · BlockListBots · throttle:public
GET|HEAD	/api/v1/guest/portal/requests	Guest\GuestPortalController@serviceRequests	api · BlockListBots · throttle:public
POST	/api/v1/guest/portal/requests	Guest\GuestPortalController@createServiceRequest	api · BlockListBots · throttle:public

Guests 9 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/guests	Hotel\GuestController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
POST	/api/v1/guests	Hotel\GuestController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
GET|HEAD	/api/v1/guests/guest-list	Reception\GuestReportController@guestList	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
GET|HEAD	/api/v1/guests/lookup	Hotel\GuestController@lookup	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
DELETE	/api/v1/guests/{id}	Hotel\GuestController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
GET|HEAD	/api/v1/guests/{id}	Hotel\GuestController@show	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
PUT	/api/v1/guests/{id}	Hotel\GuestController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/guests/{id}/deletion-preview	Hotel\GuestController@deletionPreview	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
POST	/api/v1/guests/{id}/restore	Hotel\GuestController@restore	api · auth:sanctum · tenant · features · trust · throttle:api · level:80

Hotel Settings 3 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/hotel-settings	Staff\HotelSettingsController@show	api · auth:sanctum · tenant · features · trust · throttle:api
PUT	/api/v1/hotel-settings	Staff\HotelSettingsController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
DELETE	/api/v1/hotel-settings/logo	Staff\HotelSettingsController@removeLogo	api · auth:sanctum · tenant · features · trust · throttle:api · level:80

Housekeeping dashboard 2 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/housekeeping/board	Housekeeping\HousekeepingController@board	api · auth:sanctum · tenant · features · trust · throttle:api · level:40
GET|HEAD	/api/v1/housekeeping/dashboard	Housekeeping\HousekeepingController@dashboard	api · auth:sanctum · tenant · features · trust · throttle:api · level:40

Housekeeping tasks 10 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/housekeeping-tasks	Housekeeping\HousekeepingController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:40
POST	/api/v1/housekeeping-tasks	Housekeeping\HousekeepingController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:40 · operate
DELETE	/api/v1/housekeeping-tasks/{id}	Housekeeping\HousekeepingController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:40 · operate · Can:housekeeping.work
GET|HEAD	/api/v1/housekeeping-tasks/{id}	Housekeeping\HousekeepingController@show	api · auth:sanctum · tenant · features · trust · throttle:api · level:40
PUT	/api/v1/housekeeping-tasks/{id}	Housekeeping\HousekeepingController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:40 · operate · Can:housekeeping.work
POST	/api/v1/housekeeping-tasks/{id}/assign	Housekeeping\HousekeepingController@assign	api · auth:sanctum · tenant · features · trust · throttle:api · level:40 · operate
POST	/api/v1/housekeeping-tasks/{id}/complete	Housekeeping\HousekeepingController@complete	api · auth:sanctum · tenant · features · trust · throttle:api · level:40 · operate
POST	/api/v1/housekeeping-tasks/{id}/confirm	Housekeeping\HousekeepingController@confirm	api · auth:sanctum · tenant · features · trust · throttle:api · level:40 · operate
POST	/api/v1/housekeeping-tasks/{id}/start	Housekeeping\HousekeepingController@start	api · auth:sanctum · tenant · features · trust · throttle:api · level:40 · operate · Can:housekeeping.work

Method	URI	Controller action	Middleware
POST	/api/v1/housekeeping-tasks/{id}/verify	Housekeeping\HousekeepingController@verify	api · auth:sanctum · tenant · features · trust · throttle:api · level:40 · operate

Data import 3 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/importers	Admin\ImportController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:90
POST	/api/v1/importers/{importerKey}/run	Admin\ImportController@run	api · auth:sanctum · tenant · features · trust · throttle:api · level:90
POST	/api/v1/importers/{importerKey}/validate	Admin\ImportController@validate	api · auth:sanctum · tenant · features · trust · throttle:api · level:90

Integrations & webhooks 41 routes

Method	URI	Controller action	Middleware
DELETE	/api/v1/integrations/booking-com/disconnect	Integration\BookingComController@disconnect	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
GET|HEAD	/api/v1/integrations/booking-com/logs	Integration\BookingComController@logs	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
POST	/api/v1/integrations/booking-com/pull/reservations	Integration\BookingComController@pullReservations	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
GET|HEAD	/api/v1/integrations/booking-com/settings	Integration\BookingComController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
PUT	/api/v1/integrations/booking-com/settings	Integration\BookingComController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
POST	/api/v1/integrations/booking-com/sync/availability	Integration\BookingComController@syncAvailability	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
POST	/api/v1/integrations/booking-com/sync/rates	Integration\BookingComController@syncRates	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
POST	/api/v1/integrations/booking-com/test	Integration\BookingComController@testConnection	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
GET|HEAD	/api/v1/integrations/dashboard	Superadmin\IntegrationDashboardController@index	api · auth:sanctum · tenant · features · trust · throttle:api · RequireSuperadmin
GET|HEAD	/api/v1/integrations/quickbooks/accounts	Integration\QuickBooksController@getAccounts	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
GET|HEAD	/api/v1/integrations/quickbooks/auth-url	Integration\QuickBooksController@getAuthUrl	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
POST	/api/v1/integrations/quickbooks/callback	Integration\QuickBooksController@handleCallback	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
DELETE	/api/v1/integrations/quickbooks/disconnect	Integration\QuickBooksController@disconnect	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
GET|HEAD	/api/v1/integrations/quickbooks/logs	Integration\QuickBooksController@logs	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
GET|HEAD	/api/v1/integrations/quickbooks/settings	Integration\QuickBooksController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:80

Method	URI	Controller action	Middleware
PUT	/api/v1/integrations/quickbooks/settings	Integration\QuickBooksController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
POST	/api/v1/integrations/quickbooks/sync/invoices	Integration\QuickBooksController@syncInvoices	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
POST	/api/v1/integrations/quickbooks/sync/payments	Integration\QuickBooksController@syncPayments	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
POST	/api/v1/integrations/quickbooks/test	Integration\QuickBooksController@testConnection	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
GET|HEAD	/api/v1/integrations/staah/mappings	Integration\StaahController@mappings	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
POST	/api/v1/integrations/staah/mappings	Integration\StaahController@storeMapping	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
DELETE	/api/v1/integrations/staah/mappings/{mapping}	Integration\StaahController@destroyMapping	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
PUT	/api/v1/integrations/staah/mappings/{mapping}	Integration\StaahController@updateMapping	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
POST	/api/v1/integrations/staah/pull	Integration\StaahController@pull	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
POST	/api/v1/integrations/staah/push-data	Integration\StaahWebhookController@pushData	api · throttle:webhook
GET|HEAD	/api/v1/integrations/staah/receipts	Integration\StaahController@receipts	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
POST	/api/v1/integrations/staah/reservations	Integration\StaahWebhookController@reservations	api · throttle:webhook
GET|HEAD	/api/v1/integrations/staah/settings	Integration\StaahController@settings	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
PUT	/api/v1/integrations/staah/settings	Integration\StaahController@updateSettings	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
POST	/api/v1/integrations/staah/sync	Integration\StaahController@sync	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
GET|HEAD	/api/v1/integrations/xero/accounts	Integration\XeroController@getAccounts	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
GET|HEAD	/api/v1/integrations/xero/auth-url	Integration\XeroController@getAuthUrl	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
POST	/api/v1/integrations/xero/callback	Integration\XeroController@handleCallback	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
DELETE	/api/v1/integrations/xero/disconnect	Integration\XeroController@disconnect	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
GET|HEAD	/api/v1/integrations/xero/logs	Integration\XeroController@logs	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
GET|HEAD	/api/v1/integrations/xero/reports/{report}	Integration\XeroController@getReport	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
GET|HEAD	/api/v1/integrations/xero/settings	Integration\XeroController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
PUT	/api/v1/integrations/xero/settings	Integration\XeroController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:80

Method	URI	Controller action	Middleware
POST	/api/v1/integrations/xero/sync/invoices	Integration\XeroController@syncInvoices	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
POST	/api/v1/integrations/xero/sync/payments	Integration\XeroController@syncPayments	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
POST	/api/v1/integrations/xero/test	Integration\XeroController@testConnection	api · auth:sanctum · tenant · features · trust · throttle:api · level:80

Inventory catalogue & movements 7 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/inventory	Inventory\InventoryController@index	api · auth:sanctum · tenant · features · trust · throttle:api · CheckPosInventoryAccess:50
POST	/api/v1/inventory	Inventory\InventoryController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:50 · operate
DELETE	/api/v1/inventory/{id}	Inventory\InventoryController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:50 · operate
GET|HEAD	/api/v1/inventory/{id}	Inventory\InventoryController@show	api · auth:sanctum · tenant · features · trust · throttle:api · CheckPosInventoryAccess:50
PUT	/api/v1/inventory/{id}	Inventory\InventoryController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:50 · operate
POST	/api/v1/inventory/{id}/adjust	Inventory\InventoryController@adjust	api · auth:sanctum · tenant · features · trust · throttle:api · level:50 · operate
GET|HEAD	/api/v1/inventory/{id}/movements	Inventory\InventoryController@movements	api · auth:sanctum · tenant · features · trust · throttle:api · CheckPosInventoryAccess:50

Goods returns 3 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/inventory-goods-returns	Inventory\GoodsReturnController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:50
POST	/api/v1/inventory-goods-returns	Inventory\GoodsReturnController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
POST	/api/v1/inventory-goods-returns/{return}/void	Inventory\GoodsReturnController@void	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate · level:70

Store indents 13 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/inventory-indents	Inventory\IndentController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
POST	/api/v1/inventory-indents	Inventory\IndentController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
GET|HEAD	/api/v1/inventory-indents/{indent}	Inventory\IndentController@show	api · auth:sanctum · tenant · features · trust · throttle:api · level:20

Method	URI	Controller action	Middleware
PUT	/api/v1/inventory-indents/{indent}	Inventory\IndentController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
POST	/api/v1/inventory-indents/{indent}/accept	Inventory\IndentController@accept	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
POST	/api/v1/inventory-indents/{indent}/approve	Inventory\IndentController@approve	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
POST	/api/v1/inventory-indents/{indent}/email	Inventory\IndentController@email	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
GET|HEAD	/api/v1/inventory-indents/{indent}/pdf	Inventory\IndentController@printPdf	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
POST	/api/v1/inventory-indents/{indent}/recall	Inventory\IndentController@recall	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
POST	/api/v1/inventory-indents/{indent}/reject	Inventory\IndentController@reject	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
POST	/api/v1/inventory-indents/{indent}/send	Inventory\IndentController@send	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
POST	/api/v1/inventory-indents/{indent}/supply	Inventory\IndentController@supply	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
POST	/api/v1/inventory-indents/{indent}/void	Inventory\IndentController@void	api · auth:sanctum · tenant · features · trust · throttle:api · level:20

Market lists 4 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/inventory-market-lists	Inventory\MarketListController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:50
POST	/api/v1/inventory-market-lists	Inventory\MarketListController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
POST	/api/v1/inventory-market-lists/{list}/submit	Inventory\MarketListController@submit	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
POST	/api/v1/inventory-market-lists/{list}/void	Inventory\MarketListController@void	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate · level:70

Production runs 3 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/inventory-production-runs	Inventory\ManufacturingController@runs	api · auth:sanctum · tenant · features · trust · throttle:api · level:50
POST	/api/v1/inventory-production-runs	Inventory\ManufacturingController@storeRun	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
POST	/api/v1/inventory-production-runs/{run}/void	Inventory\ManufacturingController@voidRun	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate · level:70

Recipes 3 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/inventory-recipes	Inventory\ManufacturingController@recipes	api · auth:sanctum · tenant · features · trust · throttle:api · level:50
POST	/api/v1/inventory-recipes	Inventory\ManufacturingController@storeRecipe	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
PUT	/api/v1/inventory-recipes/{recipe}	Inventory\ManufacturingController@updateRecipe	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate

Inventory Requisition Items 1 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/inventory-requisition-items	Inventory\InventoryController@requisitionItems	api · auth:sanctum · tenant · features · trust · throttle:api · level:20

Stock adjustments 5 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/inventory-stock-adjustments	Inventory\StockAdjustmentController@index	api · auth:sanctum · tenant · features · trust · throttle:api · CheckPosInventoryAccess:50
POST	/api/v1/inventory-stock-adjustments	Inventory\StockAdjustmentController@store	api · auth:sanctum · tenant · features · trust · throttle:api · CheckPosInventoryAccess:60 · operate
GET|HEAD	/api/v1/inventory-stock-adjustments/{adjustment}	Inventory\StockAdjustmentController@show	api · auth:sanctum · tenant · features · trust · throttle:api · CheckPosInventoryAccess:50
POST	/api/v1/inventory-stock-adjustments/{adjustment}/email	Inventory\StockAdjustmentController@email	api · auth:sanctum · tenant · features · trust · throttle:api · CheckPosInventoryAccess:50
POST	/api/v1/inventory-stock-adjustments/{adjustment}/void	Inventory\StockAdjustmentController@void	api · auth:sanctum · tenant · features · trust · throttle:api · CheckPosInventoryAccess:60 · operate · CheckPosInventoryAccess:70

Physical stock takes 5 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/inventory-stock-takes	Inventory\PhysicalStockTakeController@index	api · auth:sanctum · tenant · features · trust · throttle:api · CheckPosInventoryAccess:50
POST	/api/v1/inventory-stock-takes	Inventory\PhysicalStockTakeController@store	api · auth:sanctum · tenant · features · trust · throttle:api · CheckPosInventoryAccess:60 · operate
PUT	/api/v1/inventory-stock-takes/{take}/counts	Inventory\PhysicalStockTakeController@updateCounts	api · auth:sanctum · tenant · features · trust · throttle:api · CheckPosInventoryAccess:60 · operate
POST	/api/v1/inventory-stock-takes/{take}/post	Inventory\PhysicalStockTakeController@post	api · auth:sanctum · tenant · features · trust · throttle:api · CheckPosInventoryAccess:60 · operate
POST	/api/v1/inventory-stock-takes/{take}/void	Inventory\PhysicalStockTakeController@void	api · auth:sanctum · tenant · features · trust · throttle:api · CheckPosInventoryAccess:60 · operate · CheckPosInventoryAccess:70

Stock transfers 4 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/inventory-transfers	Inventory\StockTransferController@index	api · auth:sanctum · tenant · features · trust · throttle:api · CheckPosInventoryAccess:50
POST	/api/v1/inventory-transfers	Inventory\StockTransferController@store	api · auth:sanctum · tenant · features · trust · throttle:api · CheckPosInventoryAccess:60 · operate
POST	/api/v1/inventory-transfers/{transfer}/send	Inventory\StockTransferController@send	api · auth:sanctum · tenant · features · trust · throttle:api · CheckPosInventoryAccess:60 · operate
POST	/api/v1/inventory-transfers/{transfer}/void	Inventory\StockTransferController@void	api · auth:sanctum · tenant · features · trust · throttle:api · CheckPosInventoryAccess:60 · operate · CheckPosInventoryAccess:70

Invoices 3 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/invoices	Finance\InvoiceController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
GET|HEAD	/api/v1/invoices/{id}	Finance\InvoiceController@show	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
GET|HEAD	/api/v1/invoices/{id}/download	Finance\InvoiceController@download	api · auth:sanctum · tenant · features · trust · throttle:api · level:60

Issue Reports 5 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/issue-reports	Issue\IssueReportController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
POST	/api/v1/issue-reports	Issue\IssueReportController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
GET|HEAD	/api/v1/issue-reports/{id}	Issue\IssueReportController@show	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
POST	/api/v1/issue-reports/{id}/comments	Issue\IssueReportController@comment	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
POST	/api/v1/issue-reports/{id}/respond	Issue\IssueReportController@respond	api · auth:sanctum · tenant · features · trust · throttle:api · level:80

Laundry compositions 5 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/laundry-cloth-compositions	Laundry\ClothCompositionController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:40
POST	/api/v1/laundry-cloth-compositions	Laundry\ClothCompositionController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:40 · operate
DELETE	/api/v1/laundry-cloth-compositions/{id}	Laundry\ClothCompositionController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:40 · operate

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/laundry-cloth-compositions/{id}	Laundry\ClothCompositionController@show	api · auth:sanctum · tenant · features · trust · throttle:api · level:40
PUT	/api/v1/laundry-cloth-compositions/{id}	Laundry\ClothCompositionController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:40 · operate

Laundry cloth types 5 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/laundry-cloth-types	Laundry\ClothTypeController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:40
POST	/api/v1/laundry-cloth-types	Laundry\ClothTypeController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:40 · operate
DELETE	/api/v1/laundry-cloth-types/{id}	Laundry\ClothTypeController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:40 · operate
GET|HEAD	/api/v1/laundry-cloth-types/{id}	Laundry\ClothTypeController@show	api · auth:sanctum · tenant · features · trust · throttle:api · level:40
PUT	/api/v1/laundry-cloth-types/{id}	Laundry\ClothTypeController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:40 · operate

Laundry orders 5 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/laundry-orders	Laundry\LaundryOrderController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:40
POST	/api/v1/laundry-orders	Laundry\LaundryOrderController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:40 · operate
DELETE	/api/v1/laundry-orders/{id}	Laundry\LaundryOrderController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:40 · operate
GET|HEAD	/api/v1/laundry-orders/{id}	Laundry\LaundryOrderController@show	api · auth:sanctum · tenant · features · trust · throttle:api · level:40
PUT	/api/v1/laundry-orders/{id}	Laundry\LaundryOrderController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:40 · operate

Menu accompaniments 5 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/menu-accompaniments	FoodBeverage\MenuAccompanimentController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
POST	/api/v1/menu-accompaniments	FoodBeverage\MenuAccompanimentController@store	api · auth:sanctum · tenant · features · trust · throttle:api · CanManageAccompaniments
PUT	/api/v1/menu-accompaniments/reorder	FoodBeverage\MenuAccompanimentController@reorder	api · auth:sanctum · tenant · features · trust · throttle:api · CanManageAccompaniments
DELETE	/api/v1/menu-accompaniments/{accompaniment}	FoodBeverage\MenuAccompanimentController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · CanManageAccompaniments

Method	URI	Controller action	Middleware
PUT	/api/v1/menu-accompaniments/{accompaniment}	FoodBeverage\MenuAccompanimentController@update	api · auth:sanctum · tenant · features · trust · throttle:api · CanManageAccompaniments

Menu Audit 2 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/menu-audit	FoodBeverage\MenuAuditController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:30 · CanManageMenu
GET|HEAD	/api/v1/menu-audit/{entityType}/{entityId}	FoodBeverage\MenuAuditController@entity	api · auth:sanctum · tenant · features · trust · throttle:api · level:30 · CanManageMenu

Menu categories 5 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/menu-categories	FoodBeverage\MenuCategoryController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
POST	/api/v1/menu-categories	FoodBeverage\MenuCategoryController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:30 · CanManageMenu
PUT	/api/v1/menu-categories/reorder	FoodBeverage\MenuCategoryController@reorder	api · auth:sanctum · tenant · features · trust · throttle:api · level:30 · CanManageMenu
DELETE	/api/v1/menu-categories/{category}	FoodBeverage\MenuCategoryController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:30 · CanManageMenu
PUT	/api/v1/menu-categories/{category}	FoodBeverage\MenuCategoryController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:30 · CanManageMenu

Menu items 9 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/menu-items	FoodBeverage\MenuItemController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
POST	/api/v1/menu-items	FoodBeverage\MenuItemController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:30 · CanManageMenu
DELETE	/api/v1/menu-items/{id}	FoodBeverage\MenuItemController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:30 · CanManageMenu
GET|HEAD	/api/v1/menu-items/{id}	FoodBeverage\MenuItemController@show	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
PUT	/api/v1/menu-items/{id}	FoodBeverage\MenuItemController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:30 · CanManageMenu
GET|HEAD	/api/v1/menu-items/{menuItem}/ingredients	FoodBeverage\MenuItemIngredientController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
POST	/api/v1/menu-items/{menuItem}/ingredients	FoodBeverage\MenuItemIngredientController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:30 · CanManageMenu
DELETE	/api/v1/menu-items/{menuItem}/ingredients/{ingredient}	FoodBeverage\MenuItemIngredientController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:30 · CanManageMenu

Method	URI	Controller action	Middleware
PUT	/api/v1/menu-items/{menuItem}/ingredients/{ingredient}	FoodBeverage\MenuItemIngredientController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:30 · CanManageMenu

Menu sub-categories 4 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/menu-sub-categories	FoodBeverage\MenuSubCategoryController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
POST	/api/v1/menu-sub-categories	FoodBeverage\MenuSubCategoryController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:30 · CanManageMenu
DELETE	/api/v1/menu-sub-categories/{subCategory}	FoodBeverage\MenuSubCategoryController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:30 · CanManageMenu
PUT	/api/v1/menu-sub-categories/{subCategory}	FoodBeverage\MenuSubCategoryController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:30 · CanManageMenu

Messaging & conversations 75 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/messages/announcements	Messaging\AnnouncementController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/announcements	Messaging\AnnouncementController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/announcements/{id}/acknowledge	Messaging\AnnouncementController@acknowledge	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
GET|HEAD	/api/v1/messages/conversations	Messaging\ConversationController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/conversations	Messaging\ConversationController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
GET|HEAD	/api/v1/messages/conversations/{id}	Messaging\ConversationController@show	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
GET|HEAD	/api/v1/messages/conversations/{id}/messages	Messaging\ConversationController@messages	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/conversations/{id}/messages	Messaging\ConversationController@send	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/conversations/{id}/messages/{messageId}/delete	Messaging\MessageActionController@deleteConversationMessage	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/conversations/{id}/messages/{messageId}/view-once	Messaging\MessageActionController@openViewOnce	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/conversations/{id}/read	Messaging\ConversationController@markRead	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
GET|HEAD	/api/v1/messages/escalations	Messaging\EscalationController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/escalations	Messaging\EscalationController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/escalations/{id}/resolve	Messaging\EscalationController@resolve	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/messages/export	Messaging\ExportController	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/forward	Messaging\ForwardController	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
GET|HEAD	/api/v1/messages/groups	Messaging\GroupConversationController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/groups	Messaging\GroupConversationController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
GET|HEAD	/api/v1/messages/groups/{id}	Messaging\GroupConversationController@show	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/groups/{id}/members	Messaging\GroupConversationController@addMembers	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
DELETE	/api/v1/messages/groups/{id}/members/{userId}	Messaging\GroupConversationController@removeMember	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
GET|HEAD	/api/v1/messages/groups/{id}/messages	Messaging\GroupConversationController@messages	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/groups/{id}/messages	Messaging\GroupConversationController@send	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/groups/{id}/messages/{messageId}/convert-task	Messaging\TaskGroupController@convert	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/groups/{id}/messages/{messageId}/delete	Messaging\MessageActionController@deleteGroupMessage	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/groups/{id}/messages/{messageId}/view-once	Messaging\MessageActionController@openGroupViewOnce	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/groups/{id}/read	Messaging\GroupConversationController@markRead	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
GET|HEAD	/api/v1/messages/guest-messages	Messaging\GuestMessageController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/guest-messages	Messaging\GuestMessageController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
GET|HEAD	/api/v1/messages/guest-notification-settings	Messaging\GuestNotificationSettingsController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
PUT	/api/v1/messages/guest-notification-settings	Messaging\GuestNotificationSettingsController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
GET|HEAD	/api/v1/messages/handovers	Messaging\ShiftHandoverController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/handovers	Messaging\ShiftHandoverController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/handovers/{id}/acknowledge	Messaging\ShiftHandoverController@acknowledge	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
PUT	/api/v1/messages/location	Messaging\StaffLocationController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
GET|HEAD	/api/v1/messages/meetings	Messaging\MeetingController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/meetings	Messaging\MeetingController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/messages/meetings/users	Messaging\MeetingController@searchUsers	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/meetings/{id}/respond	Messaging\MeetingController@respond	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
GET|HEAD	/api/v1/messages/nearby	Messaging\StaffLocationController@nearby	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/pin	Messaging\PinStarController@pin	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
GET|HEAD	/api/v1/messages/pinned	Messaging\PinStarController@pinned	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/polls/vote	Messaging\PollController@vote	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
GET|HEAD	/api/v1/messages/preferences	Messaging\NotificationPreferenceController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/preferences	Messaging\NotificationPreferenceController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
DELETE	/api/v1/messages/preferences/{id}	Messaging\NotificationPreferenceController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
PUT	/api/v1/messages/preferences/{id}	Messaging\NotificationPreferenceController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/reactions	Messaging\MessageActionController@toggleReaction	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
GET|HEAD	/api/v1/messages/retention-policies	Messaging\RetentionPolicyController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/retention-policies	Messaging\RetentionPolicyController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging · level:80
DELETE	/api/v1/messages/retention-policies/{id}	Messaging\RetentionPolicyController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging · level:80
GET|HEAD	/api/v1/messages/rooms	Messaging\RoomLinkController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/rooms	Messaging\RoomLinkController@link	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
GET|HEAD	/api/v1/messages/rooms/search	Messaging\RoomLinkController@searchRooms	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
DELETE	/api/v1/messages/rooms/{id}	Messaging\RoomLinkController@unlink	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
GET|HEAD	/api/v1/messages/scheduled	Messaging\ScheduledMessageController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/scheduled	Messaging\ScheduledMessageController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
DELETE	/api/v1/messages/scheduled/{id}	Messaging\ScheduledMessageController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
GET|HEAD	/api/v1/messages/search	Messaging\SearchController	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
GET|HEAD	/api/v1/messages/sos	Messaging\SosController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging

Method	URI	Controller action	Middleware
POST	/api/v1/messages/sos	Messaging\SosController@initiate	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/sos/{id}/acknowledge	Messaging\SosController@acknowledge	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/sos/{id}/resolve	Messaging\SosController@resolve	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/star	Messaging\PinStarController@star	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
GET|HEAD	/api/v1/messages/starred	Messaging\PinStarController@starred	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/task-groups	Messaging\TaskGroupController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
GET|HEAD	/api/v1/messages/templates	Messaging\MessageTemplateController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/templates	Messaging\MessageTemplateController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
DELETE	/api/v1/messages/templates/{id}	Messaging\MessageTemplateController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
PUT	/api/v1/messages/templates/{id}	Messaging\MessageTemplateController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/translate	Messaging\TranslateController	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/unpin	Messaging\PinStarController@unpin	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
GET|HEAD	/api/v1/messages/unread-count	Messaging\ConversationController@unreadCount	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/messages/unstar	Messaging\PinStarController@unstar	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
GET|HEAD	/api/v1/messages/users	Messaging\ConversationController@users	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging

Night audit 7 routes

Method	URI	Controller action	Middleware
POST	/api/v1/night-audit/close	Reception\NightAuditController@close	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
GET|HEAD	/api/v1/night-audit/history	Reception\NightAuditController@history	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
GET|HEAD	/api/v1/night-audit/logs	Reception\NightAuditLogController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
GET|HEAD	/api/v1/night-audit/report	Reception\NightAuditController@report	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
GET|HEAD	/api/v1/night-audit/transactions	Reception\NightAuditTransactionController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
POST	/api/v1/night-audit/transactions	Reception\NightAuditTransactionController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:60

Method	URI	Controller action	Middleware
DELETE	/api/v1/night-audit/transactions/{id}	Reception\NightAuditTransactionController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:60

Notifications 5 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/notifications	NotificationController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
GET|HEAD	/api/v1/notifications/alerts	NotificationController@alerts	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
POST	/api/v1/notifications/read-all	NotificationController@markAllRead	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
GET|HEAD	/api/v1/notifications/unread-count	NotificationController@unreadCount	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
POST	/api/v1/notifications/{id}/read	NotificationController@markRead	api · auth:sanctum · tenant · features · trust · throttle:api · level:20

F&B orders & settlement 20 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/orders	FoodBeverage\OrderController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
POST	/api/v1/orders	FoodBeverage\OrderController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · operate
GET|HEAD	/api/v1/orders/form-options	FoodBeverage\OrderController@formOptions	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
GET|HEAD	/api/v1/orders/summary	FoodBeverage\OrderController@summary	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
GET|HEAD	/api/v1/orders/{id}	FoodBeverage\OrderController@show	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
PUT	/api/v1/orders/{id}	FoodBeverage\OrderController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · operate
POST	/api/v1/orders/{id}/bill-to-room	FoodBeverage\OrderController@billToRoom	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · operate
POST	/api/v1/orders/{id}/items	FoodBeverage\OrderController@addItems	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · operate
POST	/api/v1/orders/{id}/items/transfer	FoodBeverage\OrderController@transferOrderItems	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · operate
DELETE	/api/v1/orders/{id}/items/{itemId}	FoodBeverage\OrderController@removeOrderItem	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · operate
PUT	/api/v1/orders/{id}/items/{itemId}	FoodBeverage\OrderController@updateOrderItem	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · operate
PATCH	/api/v1/orders/{id}/items/{itemId}/status	FoodBeverage\OrderController@markItemStatus	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · operate
POST	/api/v1/orders/{id}/merge	FoodBeverage\OrderController@mergeOrder	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · operate

Method	URI	Controller action	Middleware
POST	/api/v1/orders/{id}/pay	FoodBeverage\OrderController@pay	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · operate
POST	/api/v1/orders/{id}/settle-credit-account	FoodBeverage\OrderController@settleCreditAccount	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · operate
POST	/api/v1/orders/{id}/split	FoodBeverage\OrderController@splitOrder	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · operate
POST	/api/v1/orders/{id}/transfer	FoodBeverage\OrderController@transferOrder	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · operate
POST	/api/v1/orders/{id}/void	FoodBeverage\OrderController@voidOrder	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · operate
POST	/api/v1/orders/{order}/freeze	FoodBeverage\CashierController@freeze	api · auth:sanctum · tenant · features · trust · throttle:api · level:30 · operate
POST	/api/v1/orders/{order}/unfreeze	FoodBeverage\CashierController@unfreeze	api · auth:sanctum · tenant · features · trust · throttle:api · level:30 · operate

Outlets & access codes 8 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/outlets	FoodBeverage\OutletController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
POST	/api/v1/outlets	FoodBeverage\OutletController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:70 · CanManageOutlets
POST	/api/v1/outlets/selling-points	FoodBeverage\OutletController@storeSellingPoint	api · auth:sanctum · tenant · features · trust · throttle:api · level:30
DELETE	/api/v1/outlets/{id}	FoodBeverage\OutletController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:70 · CanManageOutlets
PUT	/api/v1/outlets/{id}	FoodBeverage\OutletController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:70 · CanManageOutlets
POST	/api/v1/outlets/{id}/claim-access	FoodBeverage\OutletController@claimAccess	api · auth:sanctum · tenant · features · trust · throttle:api · level:30
POST	/api/v1/outlets/{id}/reset-access	FoodBeverage\OutletController@resetAccess	api · auth:sanctum · tenant · features · trust · throttle:api · level:70 · CanManageOutlets
POST	/api/v1/outlets/{id}/verify-access	FoodBeverage\OutletController@verifyAccess	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:20,1

Owner portal 3 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/owner/dashboard	Owner\OwnerController@dashboard	api · auth:sanctum · tenant · features · trust · throttle:api · RequireOwner
GET|HEAD	/api/v1/owner/hotels	Owner\OwnerController@hotels	api · auth:sanctum · tenant · features · trust · throttle:api · RequireOwner
GET|HEAD	/api/v1/owner/hotels/{id}	Owner\OwnerController@hotel	api · auth:sanctum · tenant · features · trust · throttle:api · RequireOwner

Owner accounts 2 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/owners	Tenants\TenantController@owners	api · auth:sanctum · tenant · features · trust · throttle:api · RequireSuperadmin
POST	/api/v1/owners	Tenants\TenantController@storeOwner	api · auth:sanctum · tenant · features · trust · throttle:api · RequireSuperadmin

Payments 12 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/payments	Finance\PaymentController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
POST	/api/v1/payments	Finance\PaymentController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
POST	/api/v1/payments/clickpesa/callback	Finance\PaymentController@clickPesaCallback	api · throttle:webhook
POST	/api/v1/payments/clickpesa/initiate	Finance\PaymentController@clickPesaInitiate	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
GET|HEAD	/api/v1/payments/options	Finance\PaymentController@options	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
POST	/api/v1/payments/selcom/callback	Finance\PaymentController@selcomCallback	api · throttle:webhook
DELETE	/api/v1/payments/{id}	Finance\PaymentController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate · Can:payment.mutation
GET|HEAD	/api/v1/payments/{id}	Finance\PaymentController@show	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
PUT	/api/v1/payments/{id}	Finance\PaymentController@edit	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate · Can:payment.mutation
POST	/api/v1/payments/{id}/confirm	Finance\PaymentController@confirm	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate · Can:payment.mutation
POST	/api/v1/payments/{id}/refund	Finance\PaymentController@refund	api · auth:sanctum · tenant · features · trust · throttle:api · level:80 · Can:payment.mutation
POST	/api/v1/payments/{id}/reject	Finance\PaymentController@reject	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate · Can:payment.mutation

Subscription plans 5 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/plans	Superadmin\PlanController@index	api · auth:sanctum · tenant · features · trust · throttle:api · RequireSuperadmin
POST	/api/v1/plans	Superadmin\PlanController@store	api · auth:sanctum · tenant · features · trust · throttle:api · RequireSuperadmin
DELETE	/api/v1/plans/{slug}	Superadmin\PlanController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · RequireSuperadmin
GET|HEAD	/api/v1/plans/{slug}	Superadmin\PlanController@show	api · auth:sanctum · tenant · features · trust · throttle:api · RequireSuperadmin

Method	URI	Controller action	Middleware
PUT	/api/v1/plans/{slug}	Superadmin\PlanController@update	api · auth:sanctum · tenant · features · trust · throttle:api · RequireSuperadmin

Guest portal 17 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/portal/analytics/overview	Portal\PortalAnalyticsController@overview	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
GET|HEAD	/api/v1/portal/heavy-jobs	Portal\TenantComputeController@indexJobs	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
POST	/api/v1/portal/heavy-jobs	Portal\TenantComputeController@storeJob	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
GET|HEAD	/api/v1/portal/heavy-jobs/{id}	Portal\TenantComputeController@showJob	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
GET|HEAD	/api/v1/portal/notification-settings	Portal\PortalNotificationSettingsController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
PUT	/api/v1/portal/notification-settings	Portal\PortalNotificationSettingsController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
GET|HEAD	/api/v1/portal/payments	Portal\PortalPaymentController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
POST	/api/v1/portal/payments/initiate	Portal\PortalPaymentController@initiate	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
GET|HEAD	/api/v1/portal/payments/options	Portal\PortalPaymentController@options	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
GET|HEAD	/api/v1/portal/schema	Portal\TenantComputeController@indexSchema	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
POST	/api/v1/portal/schema	Portal\TenantComputeController@storeSchema	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
DELETE	/api/v1/portal/schema/{slug}	Portal\TenantComputeController@destroySchema	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
GET|HEAD	/api/v1/portal/schema/{slug}/rows	Portal\TenantComputeController@rows	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
POST	/api/v1/portal/schema/{slug}/rows	Portal\TenantComputeController@storeRow	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
DELETE	/api/v1/portal/schema/{slug}/rows/{rowId}	Portal\TenantComputeController@destroyRow	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
GET|HEAD	/api/v1/portal/subscription	Portal\PortalSubscriptionController@show	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
PUT	/api/v1/portal/subscription	Portal\PortalSubscriptionController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:80

POS shifts & devices 7 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/pos/devices	FoodBeverage\PosDeviceController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:20

Method	URI	Controller action	Middleware
POST	/api/v1/pos/devices/{device}/block	FoodBeverage\PosDeviceController@block	api · auth:sanctum · tenant · features · trust · throttle:api · level:30 · operate
POST	/api/v1/pos/devices/{device}/unblock	FoodBeverage\PosDeviceController@unblock	api · auth:sanctum · tenant · features · trust · throttle:api · level:30 · operate
POST	/api/v1/pos/shift/close	FoodBeverage\PosShiftController@close	api · auth:sanctum · tenant · features · trust · throttle:api · level:30 · operate
GET|HEAD	/api/v1/pos/shift/current	FoodBeverage\PosShiftController@current	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
POST	/api/v1/pos/shift/open	FoodBeverage\PosShiftController@open	api · auth:sanctum · tenant · features · trust · throttle:api · level:30 · operate
GET|HEAD	/api/v1/pos/shifts	FoodBeverage\PosShiftController@shifts	api · auth:sanctum · tenant · features · trust · throttle:api · level:20

Public website & booking 10 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/public/availability	Portal\PublicController@availability	api · BlockListBots
POST	/api/v1/public/booking-requisitions	Portal\PublicController@storeBookingRequisition	api · BlockListBots · throttle:public
GET|HEAD	/api/v1/public/booking-requisitions/status	Portal\PublicController@bookingStatus	api · BlockListBots · throttle:public
GET|HEAD	/api/v1/public/hotels	Portal\PublicController@hotels	api · BlockListBots
GET|HEAD	/api/v1/public/hotels/{id}	Portal\PublicController@hotelShow	api · BlockListBots
GET|HEAD	/api/v1/public/invoices/download	Portal\PublicController@invoiceDownload	api · BlockListBots · throttle:public
GET|HEAD	/api/v1/public/options	Portal\PublicController@options	api · BlockListBots
POST	/api/v1/public/payments/initiate	Portal\PublicController@initiatePayment	api · BlockListBots · throttle:public
GET|HEAD	/api/v1/public/plans	Closure	api · BlockListBots
POST	/api/v1/public/reservations	Portal\PublicController@storeReservation	api · BlockListBots · throttle:public

Purchase orders 11 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/purchase-orders	Procurement\PurchaseOrderController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:50
POST	/api/v1/purchase-orders	Procurement\PurchaseOrderController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:50 · operate
GET|HEAD	/api/v1/purchase-orders/{id}	Procurement\PurchaseOrderController@show	api · auth:sanctum · tenant · features · trust · throttle:api · level:50
PUT	/api/v1/purchase-orders/{id}	Procurement\PurchaseOrderController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:50 · operate
POST	/api/v1/purchase-orders/{id}/approve	Procurement\PurchaseOrderController@approve	api · auth:sanctum · tenant · features · trust · throttle:api · level:70
POST	/api/v1/purchase-orders/{id}/cancel	Procurement\PurchaseOrderController@cancel	api · auth:sanctum · tenant · features · trust · throttle:api · level:50 · operate

Method	URI	Controller action	Middleware
POST	/api/v1/purchase-orders/{id}/email	Procurement\PurchaseOrderController@email	api · auth:sanctum · tenant · features · trust · throttle:api · level:50
POST	/api/v1/purchase-orders/{id}/manager-approve	Procurement\PurchaseOrderController@managerApprove	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
GET|HEAD	/api/v1/purchase-orders/{id}/pdf	Procurement\PurchaseOrderController@printPdf	api · auth:sanctum · tenant · features · trust · throttle:api · level:50
POST	/api/v1/purchase-orders/{id}/reject	Procurement\PurchaseOrderController@reject	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
POST	/api/v1/purchase-orders/{id}/void	Procurement\PurchaseOrderController@void	api · auth:sanctum · tenant · features · trust · throttle:api · level:80

Purchase requisitions 6 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/purchase-requisitions	Procurement\PurchaseRequisitionController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:50
POST	/api/v1/purchase-requisitions	Procurement\PurchaseRequisitionController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:50 · operate
GET|HEAD	/api/v1/purchase-requisitions/{id}	Procurement\PurchaseRequisitionController@show	api · auth:sanctum · tenant · features · trust · throttle:api · level:50
POST	/api/v1/purchase-requisitions/{id}/approve	Procurement\PurchaseRequisitionController@approve	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
POST	/api/v1/purchase-requisitions/{id}/cancel	Procurement\PurchaseRequisitionController@cancel	api · auth:sanctum · tenant · features · trust · throttle:api · level:50 · operate
POST	/api/v1/purchase-requisitions/{id}/reject	Procurement\PurchaseRequisitionController@reject	api · auth:sanctum · tenant · features · trust · throttle:api · level:80

QZ printer signing 2 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/qz/certificate	Printer\QzSigningController@certificate	api · throttle:qz
GET|POST|HEAD	/api/v1/qz/sign	Printer\QzSigningController@sign	api · throttle:qz

Reports 33 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/reports/arrivals	Reports\ReportController@arrivals	api · auth:sanctum · tenant · features · trust · throttle:api · CheckReportAccess:60
GET|HEAD	/api/v1/reports/audit-logs	Reports\ReportController@auditLogs	api · auth:sanctum · tenant · features · trust · throttle:api · CheckReportAccess:70
GET|HEAD	/api/v1/reports/bookings	Reports\ReportController@bookings	api · auth:sanctum · tenant · features · trust · throttle:api · CheckReportAccess:60
GET|HEAD	/api/v1/reports/dashboard	Reports\ReportController@dashboard	api · auth:sanctum · tenant · features · trust · throttle:api · CheckReportAccess:20

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/reports/fnb	Reports\ReportController@fnb	api · auth:sanctum · tenant · features · trust · throttle:api · CheckReportAccess:60
GET|HEAD	/api/v1/reports/inventory/closing-stock	Inventory\InventoryReportController@closingStock	api · auth:sanctum · tenant · features · trust · throttle:api · CheckReportAccess:70
GET|HEAD	/api/v1/reports/inventory/goods-return-register	Inventory\InventoryReportController@goodsReturnRegister	api · auth:sanctum · tenant · features · trust · throttle:api · CheckReportAccess:70
GET|HEAD	/api/v1/reports/inventory/grn-detail	Inventory\InventoryReportController@grnDetail	api · auth:sanctum · tenant · features · trust · throttle:api · CheckReportAccess:70
GET|HEAD	/api/v1/reports/inventory/grn-register	Inventory\InventoryReportController@grnRegister	api · auth:sanctum · tenant · features · trust · throttle:api · CheckReportAccess:70
GET|HEAD	/api/v1/reports/inventory/indent-register	Inventory\InventoryReportController@indentRegister	api · auth:sanctum · tenant · features · trust · throttle:api · CheckReportAccess:70
GET|HEAD	/api/v1/reports/inventory/ledger-summary	Inventory\InventoryReportController@ledgerSummary	api · auth:sanctum · tenant · features · trust · throttle:api · CheckReportAccess:70
GET|HEAD	/api/v1/reports/inventory/low-stock	Inventory\InventoryReportController@lowStock	api · auth:sanctum · tenant · features · trust · throttle:api · CheckReportAccess:70
GET|HEAD	/api/v1/reports/inventory/manufacturing-detail	Inventory\InventoryReportController@manufacturingDetail	api · auth:sanctum · tenant · features · trust · throttle:api · CheckReportAccess:70
GET|HEAD	/api/v1/reports/inventory/market-list-register	Inventory\InventoryReportController@marketListRegister	api · auth:sanctum · tenant · features · trust · throttle:api · CheckReportAccess:70
GET|HEAD	/api/v1/reports/inventory/mms-bill-passing	Inventory\InventoryReportController@mmsBillPassing	api · auth:sanctum · tenant · features · trust · throttle:api · CheckReportAccess:70
GET|HEAD	/api/v1/reports/inventory/mms-consumption	Inventory\InventoryReportController@mmsConsumption	api · auth:sanctum · tenant · features · trust · throttle:api · CheckReportAccess:70
GET|HEAD	/api/v1/reports/inventory/movement-detail	Inventory\InventoryReportController@movementDetail	api · auth:sanctum · tenant · features · trust · throttle:api · CheckReportAccess:70
GET|HEAD	/api/v1/reports/inventory/purchase-order-detail	Inventory\InventoryReportController@purchaseOrderDetail	api · auth:sanctum · tenant · features · trust · throttle:api · CheckReportAccess:70
GET|HEAD	/api/v1/reports/inventory/purchase-order-register	Inventory\InventoryReportController@purchaseOrderRegister	api · auth:sanctum · tenant · features · trust · throttle:api · CheckReportAccess:70
GET|HEAD	/api/v1/reports/inventory/stock-adjustment-report	Inventory\InventoryReportController@stockAdjustmentReport	api · auth:sanctum · tenant · features · trust · throttle:api · CheckReportAccess:70
GET|HEAD	/api/v1/reports/inventory/stock-take-detail	Inventory\InventoryReportController@stockTakeDetail	api · auth:sanctum · tenant · features · trust · throttle:api · CheckReportAccess:70
GET|HEAD	/api/v1/reports/inventory/tax-detail	Inventory\InventoryReportController@taxDetail	api · auth:sanctum · tenant · features · trust · throttle:api · CheckReportAccess:70
GET|HEAD	/api/v1/reports/inventory/transaction-summary	Inventory\InventoryReportController@transactionSummary	api · auth:sanctum · tenant · features · trust · throttle:api · CheckReportAccess:70
GET|HEAD	/api/v1/reports/inventory/transfer-register	Inventory\InventoryReportController@transferRegister	api · auth:sanctum · tenant · features · trust · throttle:api · CheckReportAccess:70
GET|HEAD	/api/v1/reports/occupancy	Reports\ReportController@occupancy	api · auth:sanctum · tenant · features · trust · throttle:api · CheckReportAccess:60
GET|HEAD	/api/v1/reports/overview	Reports\ReportController@overview	api · auth:sanctum · tenant · features · trust · throttle:api · CheckReportAccess:70
GET|HEAD	/api/v1/reports/revenue	Reports\ReportController@revenue	api · auth:sanctum · tenant · features · trust · throttle:api · CheckReportAccess:70

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/reports/room-status	Reports\ReportController@roomStatus	api · auth:sanctum · tenant · features · trust · throttle:api · CheckReportAccess:60
GET|HEAD	/api/v1/reports/staff-dashboard	Reports\ReportController@staffDashboard	api · auth:sanctum · tenant · features · trust · throttle:api · CheckReportAccess:20
GET|HEAD	/api/v1/reports/stock-ledger	Reports\ReportController@stockLedger	api · auth:sanctum · tenant · features · trust · throttle:api · CheckPosReportAccess
GET|HEAD	/api/v1/reports/superadmin/dashboard	Reports\ReportController@superadminDashboard	api · auth:sanctum · tenant · features · trust · throttle:api · RequireSuperadmin
GET|HEAD	/api/v1/reports/tenants/{id}/analytics	Reports\ReportController@tenantAnalytics	api · auth:sanctum · tenant · features · trust · throttle:api · RequireSuperadmin
GET|HEAD	/api/v1/reports/wired/{report}	Reports\WiredReportController@show	api · auth:sanctum · tenant · features · trust · throttle:api · CheckPosReportAccess

Reservations, check-in & folio 26 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/reservations	Hotel\ReservationController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
POST	/api/v1/reservations	Hotel\ReservationController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
POST	/api/v1/reservations/cancel-group	Hotel\ReservationController@cancelGroup	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
GET|HEAD	/api/v1/reservations/options	Hotel\ReservationController@options	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
DELETE	/api/v1/reservations/{id}	Hotel\ReservationController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
GET|HEAD	/api/v1/reservations/{id}	Hotel\ReservationController@show	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
PUT	/api/v1/reservations/{id}	Hotel\ReservationController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
POST	/api/v1/reservations/{id}/cancel	Hotel\ReservationController@cancel	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
POST	/api/v1/reservations/{id}/check-in	Hotel\ReservationController@checkIn	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
POST	/api/v1/reservations/{id}/check-out	Hotel\ReservationController@checkOut	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
GET|HEAD	/api/v1/reservations/{id}/deletion-preview	Hotel\ReservationController@deletionPreview	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
GET|HEAD	/api/v1/reservations/{id}/folio	Hotel\ReservationController@folio	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
POST	/api/v1/reservations/{id}/folio/adjustment	Hotel\FolioController@adjustment	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
POST	/api/v1/reservations/{id}/folio/attachments	Hotel\FolioController@uploadAttachments	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
POST	/api/v1/reservations/{id}/folio/charge	Hotel\FolioController@charge	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate

Method	URI	Controller action	Middleware
POST	/api/v1/reservations/{id}/folio/creditors	Hotel\FolioController@postToCreditors	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
POST	/api/v1/reservations/{id}/folio/discount	Hotel\FolioController@discount	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
POST	/api/v1/reservations/{id}/folio/inclusion	Hotel\FolioController@inclusion	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
POST	/api/v1/reservations/{id}/folio/open-new-folio	Hotel\FolioController@openNewFolio	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
POST	/api/v1/reservations/{id}/folio/transfer	Hotel\FolioController@transfer	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
PUT	/api/v1/reservations/{id}/group	Hotel\ReservationController@groupAmend	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
POST	/api/v1/reservations/{id}/invoice	Finance\InvoiceController@generate	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
POST	/api/v1/reservations/{id}/invoice/send	Finance\InvoiceController@send	api · auth:sanctum · tenant · features · trust · throttle:api · level:60
POST	/api/v1/reservations/{id}/no-show	Hotel\ReservationController@noShow	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
POST	/api/v1/reservations/{id}/post-room-charge	Hotel\ReservationController@postRoomCharge	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
POST	/api/v1/reservations/{id}/restore	Hotel\ReservationController@restore	api · auth:sanctum · tenant · features · trust · throttle:api · level:80

Rooms 11 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/rooms	Hotel\RoomController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:40
POST	/api/v1/rooms	Hotel\RoomController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
GET|HEAD	/api/v1/rooms/inventory	Hotel\RoomController@inventory	api · auth:sanctum · tenant · features · trust · throttle:api · level:40
PUT	/api/v1/rooms/rates	Hotel\RoomController@updateRates	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
GET|HEAD	/api/v1/rooms/stop-sell	Hotel\RoomController@stopSell	api · auth:sanctum · tenant · features · trust · throttle:api · level:40
POST	/api/v1/rooms/stop-sell	Hotel\RoomController@storeStopSell	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
DELETE	/api/v1/rooms/stop-sell/{id}	Hotel\RoomController@destroyStopSell	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
DELETE	/api/v1/rooms/{id}	Hotel\RoomController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
GET|HEAD	/api/v1/rooms/{id}	Hotel\RoomController@show	api · auth:sanctum · tenant · features · trust · throttle:api · level:40
PUT	/api/v1/rooms/{id}	Hotel\RoomController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:80

Method	URI	Controller action	Middleware
POST	/api/v1/rooms/{id}/status	Hotel\RoomController@updateStatus	api · auth:sanctum · tenant · features · trust · throttle:api · level:80

Statuses 6 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/statuses	Messaging\StatusController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/statuses	Messaging\StatusController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
DELETE	/api/v1/statuses/{id}	Messaging\StatusController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
GET|HEAD	/api/v1/statuses/{id}	Messaging\StatusController@show	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/statuses/{id}/react	Messaging\StatusController@react	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging
POST	/api/v1/statuses/{id}/view	Messaging\StatusController@view	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · throttle:messaging

Store & cash register 30 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/store/activity-log	Store\ActivityLogController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:50
GET|HEAD	/api/v1/store/cash-register	Store\CashRegisterController@current	api · auth:sanctum · tenant · features · trust · throttle:api · level:50
POST	/api/v1/store/cash-register/close	Store\CashRegisterController@close	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
POST	/api/v1/store/cash-register/floats	Store\CashRegisterController@addFloat	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
POST	/api/v1/store/cash-register/open	Store\CashRegisterController@open	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
GET|HEAD	/api/v1/store/cash-register/shifts	Store\CashRegisterController@shifts	api · auth:sanctum · tenant · features · trust · throttle:api · level:50
GET|HEAD	/api/v1/store/categories	Store\CategoryController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:50
POST	/api/v1/store/categories	Store\CategoryController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:50 · operate
DELETE	/api/v1/store/categories/{category}	Store\CategoryController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:50 · operate
PUT	/api/v1/store/categories/{category}	Store\CategoryController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:50 · operate
GET|HEAD	/api/v1/store/customers	Store\CustomerController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:50
POST	/api/v1/store/customers	Store\CustomerController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:50 · operate

Method	URI	Controller action	Middleware
DELETE	/api/v1/store/customers/{customer}	Store\CustomerController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:50 · operate
PUT	/api/v1/store/customers/{customer}	Store\CustomerController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:50 · operate
GET|HEAD	/api/v1/store/discounts	Store\DiscountController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:50
POST	/api/v1/store/discounts	Store\DiscountController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
DELETE	/api/v1/store/discounts/{discount}	Store\DiscountController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
PUT	/api/v1/store/discounts/{discount}	Store\DiscountController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
GET|HEAD	/api/v1/store/expenses	Store\ExpenseController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:50
POST	/api/v1/store/expenses	Store\ExpenseController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
DELETE	/api/v1/store/expenses/{expense}	Store\ExpenseController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:70 · operate
GET|HEAD	/api/v1/store/low-stock	Store\LowStockController@index	api · auth:sanctum · tenant · features · trust · throttle:api · CheckPosInventoryAccess:50
GET|HEAD	/api/v1/store/reports	Store\ReportController@summary	api · auth:sanctum · tenant · features · trust · throttle:api · level:50
GET|HEAD	/api/v1/store/sales	Store\SaleController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:50
POST	/api/v1/store/sales	Store\SaleController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:40 · operate
GET|HEAD	/api/v1/store/sales/{sale}	Store\SaleController@show	api · auth:sanctum · tenant · features · trust · throttle:api · level:50
POST	/api/v1/store/sales/{sale}/void	Store\SaleController@void	api · auth:sanctum · tenant · features · trust · throttle:api · level:70 · operate
GET|HEAD	/api/v1/store/settings	Store\SettingController@show	api · auth:sanctum · tenant · features · trust · throttle:api · level:50
PUT	/api/v1/store/settings	Store\SettingController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:60 · operate
GET|HEAD	/api/v1/store/stock-movements	Store\MovementController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:50

Suppliers 5 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/suppliers	Inventory\SupplierController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:50
POST	/api/v1/suppliers	Inventory\SupplierController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:50 · operate
DELETE	/api/v1/suppliers/{id}	Inventory\SupplierController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:50 · operate

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/suppliers/{id}	Inventory\SupplierController@show	api · auth:sanctum · tenant · features · trust · throttle:api · level:50
PUT	/api/v1/suppliers/{id}	Inventory\SupplierController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:50 · operate

Table locations 4 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/table-locations	FoodBeverage\TableLocationController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
POST	/api/v1/table-locations	FoodBeverage\TableLocationController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:40 · CanManageTables:locations
DELETE	/api/v1/table-locations/{id}	FoodBeverage\TableLocationController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:40 · CanManageTables:locations
PUT	/api/v1/table-locations/{id}	FoodBeverage\TableLocationController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:40 · CanManageTables:locations

Tables 4 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/tables	FoodBeverage\RestaurantTableController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:20
POST	/api/v1/tables	FoodBeverage\RestaurantTableController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · CanManageTables
DELETE	/api/v1/tables/{id}	FoodBeverage\RestaurantTableController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · CanManageTables
PUT	/api/v1/tables/{id}	FoodBeverage\RestaurantTableController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:20 · CanManageTables

Tenants & hotels 11 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/tenants	Tenants\TenantController@index	api · auth:sanctum · tenant · features · trust · throttle:api · RequireSuperadmin
POST	/api/v1/tenants	Tenants\TenantController@store	api · auth:sanctum · tenant · features · trust · throttle:api · RequireSuperadmin
GET|HEAD	/api/v1/tenants/{id}	Tenants\TenantController@show	api · auth:sanctum · tenant · features · trust · throttle:api · RequireSuperadmin
PUT	/api/v1/tenants/{id}	Tenants\TenantController@update	api · auth:sanctum · tenant · features · trust · throttle:api · RequireSuperadmin
POST	/api/v1/tenants/{id}/approve	Tenants\TenantController@approve	api · auth:sanctum · tenant · features · trust · throttle:api · RequireSuperadmin
GET|HEAD	/api/v1/tenants/{id}/backup	Tenants\TenantController@backup	api · auth:sanctum · tenant · features · trust · throttle:api · RequireSuperadmin

Method	URI	Controller action	Middleware
POST	/api/v1/tenants/{id}/branding	Tenants\TenantController@updateBranding	api · auth:sanctum · tenant · features · trust · throttle:api · RequireSuperadmin
POST	/api/v1/tenants/{id}/reactivate	Tenants\TenantController@reactivate	api · auth:sanctum · tenant · features · trust · throttle:api · RequireSuperadmin
POST	/api/v1/tenants/{id}/reject	Tenants\TenantController@reject	api · auth:sanctum · tenant · features · trust · throttle:api · RequireSuperadmin
POST	/api/v1/tenants/{id}/subscription	Tenants\TenantController@updateSubscription	api · auth:sanctum · tenant · features · trust · throttle:api · RequireSuperadmin
POST	/api/v1/tenants/{id}/suspend	Tenants\TenantController@suspend	api · auth:sanctum · tenant · features · trust · throttle:api · RequireSuperadmin

Units Of Measure 4 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/units-of-measure	Inventory\UnitOfMeasureController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:50
POST	/api/v1/units-of-measure	Inventory\UnitOfMeasureController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:70 · operate
DELETE	/api/v1/units-of-measure/{id}	Inventory\UnitOfMeasureController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:70 · operate
PUT	/api/v1/units-of-measure/{id}	Inventory\UnitOfMeasureController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:70 · operate

Users & staff 11 routes

Method	URI	Controller action	Middleware
GET|HEAD	/api/v1/users	Users\UserController@index	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
POST	/api/v1/users	Users\UserController@store	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
DELETE	/api/v1/users/{id}	Users\UserController@destroy	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
GET|HEAD	/api/v1/users/{id}	Users\UserController@show	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
PUT	/api/v1/users/{id}	Users\UserController@update	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
POST	/api/v1/users/{id}/activate	Users\UserController@activate	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
POST	/api/v1/users/{id}/attachments	Users\UserController@attach	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
DELETE	/api/v1/users/{id}/attachments/{attachmentId}	Users\UserController@deleteAttachment	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
POST	/api/v1/users/{id}/invite	Users\UserController@invite	api · auth:sanctum · tenant · features · trust · throttle:api · level:80
POST	/api/v1/users/{id}/reset-password	Users\UserController@resetPassword	api · auth:sanctum · tenant · features · trust · throttle:api · level:80

Method	URI	Controller action	Middleware
POST	/api/v1/users/{id}/set-pin	Users\UserController@setPin	api · auth:sanctum · tenant · features · trust · throttle:api · level:80

Appendix A. Frontend API module map

The shared API registry exports these groups from `src/api/index.js`. Use the group name to find the frontend caller, then use section 8 to find the backend route.

publicApi · authApi · reportApi · accountingApi · nightAuditApi · businessDateApi · fbDayCloseApi · activityLogReportApi · guestReportApi · userApi · issueReportApi · roomApi · guestApi · hotelSettingsApi · deviceTrustApi · reservationApi · paymentApi · currencyRateApi · distributionSourceApi · companyApi · invoiceApi · housekeepingApi · inventoryApi · inventoryOpsApi · storeApi · departmentApi · unitsApi · supplierApi · menuItemApi · menuSubCategoryApi · menuCategoryApi · menuAuditApi · menuAccompanimentApi · tableApi · tableLocationApi · orderApi · outletApi · cashierApi · posApi · creditAccountApi · menuItemIngredientApi · laundryApi · clothTypeApi · clothCompositionApi · attendanceApi · funGameApi · purchaseRequisitionApi · purchaseOrderApi · goodsReceivedNoteApi · bookingRequisitionApi · tenantApi · superadminReportApi · ownerApi · conversationApi · groupApi · messageActionApi · statusApi · featuresApi · templateApi · scheduledApi · announcementApi · escalationApi · handoverApi · preferenceApi · retentionApi · roomLinkApi · taskGroupApi · staffLocationApi · guestMessageApi · guestNotificationSettingsApi · meetingApi · sosApi · callApi · notificationApi · planApi · portalSubscriptionApi · portalPaymentApi · integrationDashboardApi · bookingComApi · distributionApi · importApi · quickbooksApi · xeroApi · checkinOverrideApi · portalNotificationSettingsApi · portalAnalyticsApi · guestPortalApi

> **Search tip:** from the frontend repository, search for the API group (for example `orderApi`) to find every screen that uses it. From the backend repository, search the URI or controller action from section 8.

Appendix B. Middleware glossary

Middleware	What it enforces / debug meaning
`auth:sanctum`	Requires a valid bearer token. Failure → 401.
`tenant`	Resolves and locks tenant context; handles owner/superadmin switching; rejects inactive tenants. Failure → 403/404.
`features`	Checks the tenant's enabled modules/features. A valid user can still get 403 when the hotel lacks the module.
`trust`	Enforces trusted-device/session policy for sensitive access.
`throttle:api`	General API rate limit. Duplicate submit handlers often show up as 429 here.
`throttle:auth`	Login/device/PIN rate limit. Repeated retries lock the user out temporarily.
`level:N`	Minimum numeric role level. Compare with the user's role in the profile/permissions response.
`operate`	Owner write gate. Owners are read-only unless an allowed override is present; superadmin passes.
`reports`	Report-specific access. A report can be visible in the menu but forbidden by this gate.
`pos-inventory`	Allows POS surfaces to access inventory data without granting full store management.
`pos-reports`	Allows POS-specific reporting.
`can:outlets.manage`	Outlet management ability, used with level 70+ for resets/CRUD.
`can:housekeeping.work`	Housekeeping work ability for task start/update/delete.
`bot`	Guest portal bot protection; usually paired with public throttling.
`throttle:public` / `throttle:webhook`	Public booking and integration webhook protection. A 429 from a provider usually means retry/backoff, not invalid data.

Appendix C. Environment, commands and verification

Frontend

- `VITE_API_URL` must include `/api`, e.g. `https://api.example.com/api`.
- `VITE_REVERB_*` config drives Echo/Reverb. A wrong host/key breaks only realtime.
- `npm run dev` for local development; `npx vite build` for production build.
- Netlify publishes `dist` with SPA fallback; API calls still go to `VITE_API_URL`.

Backend

- `php artisan route:list --path=api/v1` confirms the route exists.
- `tail -f storage/logs/laravel.log` for the exception behind a 500/domain abort.
- `php artisan queue:work` for queued notifications/reports; check `failed_jobs`.
- `php artisan config:clear` after environment changes; confirm the active `.env`.

Useful commands

```
# Backend route inventory
php artisan route:list --path=api/v1

# Backend tests for one flow
php artisan test --filter=OrderTest

# Frontend tests for one spec
npx vitest run src/__tests__/cashier-gate.spec.js

# Frontend production build
npx vite build

# Frontend lint on changed files
npx eslint src/path/to/File.vue
npx oxlint src/path/to/File.vue
```

Verification checklist before calling a fix done

#	Check	Evidence
1	The failing request now returns the expected status and payload.	Network screenshot/response copied into the issue.
2	The UI reflects the result without a manual hard refresh.	Reload the screen; the same state appears.
3	The business record is correct.	Order/payment, stock movement, GRN/PO, folio or audit row.
4	Permissions still hold for the intended role and tenant.	Test as the affected user, not only as superadmin.
5	Realtime updates still arrive (if the flow uses them).	Second browser/session receives the change; no console errors.

#	Check	Evidence
6	A regression test covers the failure.	Focused Vitest or PHPUnit test passes.

Scope note: this guide documents the application as of frontend `6651477` and backend `d0de4d4`. The route catalogue is generated from the backend route list at build time; if a route is added later, rebuild this PDF so the catalogue stays accurate.