



MRK HOTELS

Developer Documentation

v1.1.0 · Edition 1.0 · 15 August 2026

MRK Hotels — Developer Documentation

Version 1.6 — code v1.3.0 · 21 August 2026 — Architecture, Setup, Backend, Frontend, Mobile App, SaaS Portal and API Reference

1. Overview

MRK Hotels is a **multi-tenant hotel management SaaS** built as two applications:

Application	Stack	Location
API backend	Laravel 13 (PHP 8.3+), Sanctum, spatie/laravel-permission	mrk-hotels-api
Web frontend	Vue 3, Vite, Pinia, Vue Router, vue-i18n, Axios	mrk-hotels-frontend
Mobile app	Laravel 13, NativePHP Mobile 4.2, Blade/Livewire UI	mrk-hotels-mobile

The system has five faces:

1. **Public booking portal** — guests browse hotels, check availability and book rooms online, optionally paying via Selcom, mobile money (ClickPesa) or bank transfer.
2. **Hotel panel (/app)** — every hotel runs its own operation: reservations, rooms, guests, payments, housekeeping, food & beverage, laundry, fun & games, inventory, procurement, staff, messaging and reports.
3. **Superadmin panel (/superadmin)** — manages all tenants (hotels), approves registrations, toggles per-hotel payment methods, and manages SaaS subscription plans.
4. **Customer self-service portal (/portal)** — hotels that sign up via the public pricing page manage their own subscription, payments, staff, and hotel details.
5. **Mobile app** — Android companion app for housekeeping, attendance, and front-desk operations.

Multi-tenancy is implemented at the application layer: models carry `tenant_id` and a global scope (`BelongsToTenant`), and a `TenantContext` support class scopes queries for the active hotel.

2. Requirements

Backend

- PHP ^8.3 (tested on 8.4)
- Composer
- MySQL / MariaDB (tests use in-memory SQLite)

Frontend

- Node ^22.18 / >= 24.12
- npm

Key dependencies

- Backend: `laravel/framework` ^13.0, `laravel/sanctum` ^4.0, `spatie/laravel-permission` ^7.3, `laravel/reverb` (**WebSocket server**)
- Frontend: `vue`, `vue-router`, `pinia` (+ `persistedstate`), `vue-i18n`, `axios`, `font-awesome`, `country-state-city`, `libphonenumber-js`, `laravel-echo` + `pusher-js` (**real-time client**); Vitest + Playwright for testing

3. Local Setup

3.1 Backend (`mrk-hotels-api`)

```
composer install
cp .env.example .env           # set DB_*, SANCTUM_STATEFUL_DOMAINS, CLICKPESA_*, REVERB_*
keys
php artisan key:generate
php artisan migrate --seed      # TenantSeeder creates the demo hotel + users + rooms
php artisan serve               # http://localhost:8000
php artisan reverb:start        # realtime WebSocket server (http://localhost:8080)
```

3.2 Frontend (`mrk-hotels-frontend`)

```
npm install
cp .env.example .env           # VITE_API_URL=http://localhost:8000/api
npm run dev                     # http://localhost:5173
```

3.3 Demo data (TenantSeeder)

- Hotel **MRK Grand Hotel** (Dodoma, Tanzania, `subdomain=mrk-grand`, status `active`) with demo tax IDs (`tin=123-456-789`, `vrn=40-012345-6`) and demo payment accounts (M-Pesa + NMB) so invoices render the full formal layout.
- 10 staff users (`hotel_admin`, `manager`, `accountant`, `receptionist`, `procurement_officer`, `housekeeping`, `kitchen`, `waiter`, `bartender`, `staff`) — all password `password`.
- 7 rooms (single ×2, double, deluxe ×2, suite, presidential).

A superadmin user (`superadmin@mrkhotels.test`) is created elsewhere (permissions seeder) with full access.

4. Backend Architecture

4.1 Authentication (Sanctum)

`App\Http\Controllers\Api\V1\Auth\AuthController::login :`

- Finds the user by email, verifies `password_hash` with `Hash::check`.
- Rejects disabled accounts (403) and inactive tenants (403).
- Handles **password rotation**: if `passwordExpired()`, the password is reset to the default (`defaultPassword()` = full name in caps) and returned with `password_rotated: true` and a 401, prompting the client to re-sign-in.
- Issues a token:
`createToken('api-token', $user->isSuperadmin() ? ['*'] : [$user->user_role])` — **abilities are the user's role name**.
- Returns `{ token, user }`.

`AuthController::loginPin ( POST /api/v1/auth/login-pin )` — iPOS-style quick sign-in for shared staff terminals:

- Accepts `identifier + pin ( digits:4 )`; the identifier matches the user's `email` **or** `registration_number`.
- Unknown identifiers, unset PINs and wrong PINs all get one generic 401 (`Invalid credentials.`) so the endpoint cannot be used to enumerate staff accounts.
- Applies the same gates as password login (active account, active/pending tenant), updates `last_login`, issues the identical token shape and audit-logs the login.
- PINs live bcrypt-hashed in `users.login_pin` (nullable — `null` disables PIN login for the account) and are hidden from serialization.
- PINs are assigned by senior staff via `UserController@setPin ( POST /api/v1/users/{id}/set-pin , level-80 group)`: validates `pin + pin_confirmation ( digits:4 , confirmed )`, enforces `assertCanManage` on the target's role, rejects self-service with 422 (a profile self-service flow is planned), and audit-logs `pin_set`.

Protected routes use `auth:sanctum`. Token abilities are currently informational; authorization is enforced by the `level:X` and role-permission middleware below.

4.2 Authorization middleware

Middleware	Purpose
<code>CheckRoleLevel (level:X)</code>	Rejects users whose <code>roleLevel()</code> < X with 403 (superadmin bypasses). E.g. <code>level:80</code> = admin/manager only, <code>level:60</code> = receptionist+.
<code>RequireSuperadmin</code>	Superadmin-only routes.
<code>RequireOwner (owner)</code>	Multi-hotel owner routes (<code>/owner/*</code>): consolidated dashboard and per-hotel drill-down across the owner's hotels (<code>tenants.owner_id</code>). Owner accounts live on the platform tenant; hotel queries bypass global scopes with explicit <code>tenant_id</code> filters.

Middleware	Purpose
SetTenantContext (tenant)	Resolves the active tenant for the request: superadmin supplies X-Tenant-ID ; staff use their own tenant_id . Sets TenantContext for the request lifecycle.
EnsureTenantActive	Blocks requests for hotels whose tenant status is not active/pending.

Roles: superadmin (100), owner (95), hotel_admin (90), manager (80), ... Owners are created by the superadmin (POST /api/v1/owners , default password = full name in caps) and assigned to hotels via PUT /api/v1/tenants/{id} (owner_id). Demo owner: owner@mrkhotels.test / password (owns MRK Grand, Dar es Salaam and Zanzibar).

4.3 Multi-tenancy

- The BelongsToTenant model concern adds a tenant_id foreign key and a **global scope** that filters queries to the current tenant (when TenantContext::id() is set).
- App\Support\TenantContext is a static holder set by the tenant middleware and cleared in a finally block.
- Public portal endpoints operate **without** a tenant context and pass an explicit hotel_id / tenant_id .

4.4 Routing (routes/api.php)

All routes are under the v1 prefix.

Public group (/v1/public) — no auth:

Method	URI	Controller action
GET	public/hotels	PublicController@hotels — directory search (search , country , city , guests , check_in/out)
GET	public/hotels/{id}	PublicController@hotelShow
GET	public/availability	PublicController@availability — returns available rooms + payment_methods
GET	public/options	PublicController@options
POST	public/booking-requisitions	PublicController@storeBookingRequisition
POST	public/reservations	PublicController@storeReservation — creates pending reservations under one booking_reference
POST	public/payments/initiate	PublicController@initiatePayment — online payment entry point
GET	public/booking-requisitions/status	PublicController@bookingStatus

Public auth: POST `auth/login` , POST `auth/login-pin` , POST `auth/register` (all throttled by the shared `auth` limiter).

Payment webhook: POST `payments/clickpesa/callback` — no auth, used by the ClickPesa sandbox.

Authenticated group — `auth:sanctum` + `tenant` :

Module	Route prefix	Level
Auth	<code>auth/logout</code> , <code>auth/me</code> , <code>auth/change-password</code>	all
Reports	<code>reports/dashboard</code> , <code>overview</code> , <code>occupancy</code> , <code>revenue</code> , <code>room-status</code> , <code>audit-logs</code>	20 / 80 / 60 / 70 / 60 / 70
Messaging	<code>messages/users</code> , <code>messages/unread-count</code> , <code>messages/conversations</code> , <code>messages/conversations/{id}</code> , <code>.../messages</code> , <code>.../send</code> , <code>.../read</code> , <code>.../delete</code> , <code>.../react</code> , <code>messages/groups</code> , <code>messages/groups/{id}</code> , <code>.../messages</code> , <code>.../send</code> , <code>.../read</code> , <code>.../members</code> , <code>.../delete</code> , <code>.../react</code> , <code>messages/statuses</code> , <code>messages/calls</code> , <code>messages/calls/{id}/actions</code> plus the 24 feature endpoints: replies/priority/polls, pin/star, templates, scheduled messages, forwarding, announcements, search, CSV export, translate, escalations, retention policies, notification preferences/DND, shift handovers, room-linked chats, task groups, staff presence (location/nearby), guest SMS bridge, meetings, SOS alerts	20+
Users (staff)	<code>users</code> CRUD + <code>activate/invite/reset-password/set-pin/attachments</code>	80
Rooms	<code>rooms</code> CRUD + <code>status</code>	60
Guests	<code>guests</code> CRUD	60
Reservations	<code>reservations</code> CRUD + <code>options</code> + <code>check-in/check-out/no-show/cancel</code> + <code>reservations/{id}/payment</code>	60
Payments	<code>payments</code> + <code>store</code>	60
Booking requisitions	<code>booking-requisitions</code>	60
Housekeeping	<code>housekeeping/tasks</code> + <code>room status</code>	40
F&B	<code>menu-items</code> , <code>orders</code>	30+
Laundry	<code>laundry-orders</code>	40
Fun & games	<code>fun-game-orders</code>	80
Inventory	<code>inventory</code> + <code>movements</code>	50
Suppliers	<code>suppliers</code> CRUD	50
Procurement	<code>requisitions</code> , <code>purchase-orders</code> , <code>goods-received-notes</code>	50

Module	Route prefix	Level
Tenants	tenants CRUD + payment-methods	superadmin
Superadmin reports	reports/superadmin/dashboard	superadmin

(246 Route:: definitions total — 97 GET, 113 POST, 15 PUT, 20 DELETE, 1 PATCH.)

4.5 Models and relationships

Model	Key fields / notes
Core\Tenant	tenant_id (UUID), hotel_name , subdomain , status (pending/active/suspended), subscription_* , tax IDs (tin , vrn), invoice branding (signature_path , stamp_path on the public disk), payment_methods / payment_accounts (JSON casts), enabledPaymentMethods() / publicPaymentMethods()
Auth\User	UUID user_id , tenant_id , user_role , password_hash , is_active , password_changed_at ; HasApiTokens, HasRoles
Hotel\Room	room_number , room_type , floor , price_per_night , max_occupancy , status
Hotel\Reservation	tenant_id , guest_id , room_id , status , booking_reference , dates, guest snapshot (denormalized first_name , guest_phone , ...)
Hotel\Guest	guest register, contact + ID info
Finance\Invoice	reservation_id , invoice_number , room_charges , service_charges , total_amount , paid_amount , balance , line_items / payments (JSON snapshots), status (issued/paid)
Finance\Payment	reservation_id , amount , payment_method , payment_provider , transaction_reference , status , booking_reference
System\BookingRequisition	online/phone booking requests (no room)
Housekeeping\HousekeepingTask , Laundry\LaundryOrder , Fun\FunGameOrder , FoodBeverage\Order / OrderItem / MenuItem , Inventory\InventoryItem / StockMovement / Supplier , Procurement* (requisition/PO/GRN + items)	domain records per module

Model	Key fields / notes
Messaging\Conversation / ConversationMessage , Messaging\GroupConversation / GroupConversationMember / GroupConversationMessage	staff messaging; conversation_messages carries delivered_at , type (text/audio/image/file), media_path , media_mime , view_once , is_media_seen , deleted_for , deleted_at , priority (normal/urgent), reply_to_id (self-join for replies), forwarded_from_type / forwarded_from_id (forwarding); group members track last_read_at for read receipts; message reactions stored as JSON (reactions column)
Messaging\PinnedMessage / StarredMessage	one row per pinned/starred message (message_type = conversation/group, message_id , user_id)
Messaging\Poll / PollOption / PollVote	message_type + message_id polymorphic polls; one vote per user per option
Messaging\MessageTemplate	reusable message snippets (name , body , category , is_global)
Messaging\ScheduledMessage	future-dated send (recipient_type = conversation/group, recipient_id , send_at , recurrence) — dispatched by the messaging:send-scheduled command
Messaging\Announcement / AnnouncementAcknowledgement	tenant-wide broadcast with per-user read acknowledgements
Messaging\MessageEscalation	raise a message to management (message_type , message_id , escalated_by , handled_by / handled_at)
Messaging\RetentionPolicy	scope (global/conversation/group), days , enabled — drives the messaging:purge-expired command
Messaging\NotificationPreference	per-chat mute + DND window (dnd_from / dnd_to), muted_until / muted , push_enabled , scope / target_id polymorphic
Messaging\ShiftHandover	shift change notes (shift_from / shift_to timestamps, status , ack_user_id / ack_at)
Messaging\ConversationRoom	links a chat (conversation_id or group_id) to a Hotel\Room
Messaging\StaffLocation	staff presence (zone , floor) with updated_at recency for the nearby lookup
Messaging\GuestMessage	outbound SMS bridge to guests (phone , provider , provider_status , template_id , direction)

Model	Key fields / notes
Messaging\Meeting / MeetingInvitee	scheduled meetings (<code>start_at</code> , <code>duration_minutes</code> , <code>conference_type</code> , <code>status</code>) with per-invitee responses
Messaging\SosAlert	emergency alert (<code>message</code> , <code>status</code> , <code>ack_count</code> , <code>ack_user_ids</code> , <code>resolved_by</code> / <code>resolved_at</code>); a <code>staff.location.updated</code> broadcast powers the nearby panel
Social\Status , Social\StatusView , Social\StatusReaction	24-hour status posts (<code>type</code> : text/photo/video), media under <code>statuses/{id}</code> ; <code>status_views</code> dedupe views per user; <code>status_reactions</code> holds emoji likes on statuses
Communication\Call , Communication\CallEvent	WebRTC calls: <code>type</code> (audio/video), <code>initiator_id</code> , <code>recipient_id</code> , <code>channel</code> (1:1 room name), <code>status</code> (ringing/active/missed/ended/rejected/declined), <code>ring_started_at</code> / <code>accepted_at</code> / <code>ended_at</code> ; <code>call_events</code> logs ring/accept/end/mute events with timestamps

4.6 Services

Service	Responsibility
Hotel\ReservationService	Room availability check, room totals (with optional ClickPesa service fee), reservation lifecycle (create, check-in/out, no-show, cancel).
Finance\PaymentService	Record payments, <code>initiatePublicPayment</code> (selcom → completed + confirms booking; bank → <code>awaiting_confirmation</code> ; mobile money → ClickPesa prompt), confirm sibling reservations by <code>booking_reference</code> .
Finance\InvoiceService	<code>generateForReservation</code> builds/refreshes the folio invoice (room + non-cancelled F&B/laundry charges minus completed payments, frozen into JSON snapshots; regenerating keeps the invoice number). <code>pdf()</code> renders <code>pdf.invoice</code> via dompdf with the MRK logo, tenant branding (signature/stamp), TIN/VRN, VAT-inclusive 18% breakdown, payment terms and "how to pay" lines — images embedded as data URIs.
Inventory\InventoryService	Stock adjustments and movements.
System\AuditService	Audit trail for logins and key actions.

Service	Responsibility
Messaging\ConversationController / GroupConversationController	Delivery/read ticks: mark messages <code>delivered_at</code> on poll (<code>index/show/messages</code>), mark <code>read_at</code> on <code>markRead</code> ; media upload (public disk, ≤ 10 MB, stored under <code>messages/conversations/{id}</code> / <code>messages/groups/{id}</code> , <code>type</code> inferred from MIME); group <code>read_by_count</code> computed in <code>GroupMessageResource</code> ; delete (<code>delete_for</code> = <code>me/everyone</code>), reactions (emoji toggle), view-once media (media URL served once, then <code>is_media_seen</code>); replies (<code>reply_to_id</code> — <code>ReplySent</code> broadcasts the full reply resource), priority (<code>normal</code> / <code>urgent</code>), polls (poll payload: <code>question</code> , <code>multiple</code> , <code>options[]</code>)

Service	Responsibility
Messaging feature controllers	PinStarController (pin/unpin/star/unstar + pinned / starred lists, broadcasts MessagePinned / MessageUnpinned / MessageStarred / MessageUnstarred), PollController (vote once per user; broadcasts PollCreated / PollVoted with live tallies), MessageTemplateController (CRUD, optional category), ScheduledMessageController (index/store/cancel), AnnouncementController (post + per-user acknowledge; broadcasts AnnouncementPosted / AnnouncementAcknowledged on the tenant channel), SearchController (keyword search across chats the caller can access, ConversationMessage + GroupConversationMessage), ExportController (CSV export of a conversation/group history), TranslateController (offline EN↔SW glossary TranslateService , no external API), EscalationController (raise + resolve; broadcasts MessageEscalated ; auto-escalation of urgent unread messages via the messaging:escalate command (default unread threshold 10 minutes)), RetentionPolicyController (CRUD + messaging:purge-expired command soft-deletes expired messages), NotificationPreferenceController (per-chat mute + DND + push), ShiftHandoverController (post + acknowledge; broadcasts ShiftHandoverPosted / ShiftHandoverAcknowledged), RoomLinkController (searchRooms / link / unlink / index — links a chat to a hotel room), TaskGroupController (store + convert a room-linked message into a HousekeepingTask ; broadcasts TaskConverted), StaffLocationController (update zone/floor + nearby query; broadcasts StaffLocationUpdated), GuestMessageController (outbound SMS bridge, tenant-scoped), MeetingController (searchUsers , schedule + invitees respond; broadcasts MeetingInvited / MeetingResponseChanged on the user channel), SosController (initiate/acknowledge/resolve; broadcasts SosAlertInitiated / SosAlertResolved), ForwardController (copy a message into another conversation/group with forwarded_from_* provenance; validates access on source and target).
Console commands	messaging:send-scheduled (queued sends due at send_at), messaging:purge-expired (retention + scheduled cancelled_at cleanup), messaging:escalate (auto-escalate urgent messages unread past a threshold).
Social\StatusController	Post (text/photo/video), list/feed (own + others, auto-expires after 24 h), view/like. Broadcasts StatusPosted to the tenant channel so conversations show live status rings.

Service	Responsibility
Communication\CallController	WebRTC call lifecycle: start (creates Call + rings via CallStarted broadcast), accept , reject , decline (busy), end , miss (timeout), plus a ping event for live ring/ringing state.
Realtime events	MessageSent (body/media/type/view_once/priority/reply), MessageRead , MessageDeleted (includes channel_id), MessageReacted , ReplySent , MessagePinned / MessageUnpinned , MessageStarred / MessageUnstarred , PollCreated , PollVoted , TaskConverted , AnnouncementPosted , AnnouncementAcknowledged , SosAlertInitiated , SosAlertResolved , ShiftHandoverPosted , ShiftHandoverAcknowledged , StaffLocationUpdated , GuestMessagePosted , MessageEscalated , MeetingInvited , MeetingResponseChanged , StatusPosted , CallStarted , CallEvent , MemberJoined / MemberLeft — all on private channels (private-users.{id} , private-tenants.{tenant_id} , private-conversation.{id} , private-group.{id}) via Reverb. Presence join/leave is handled by Reverb itself on presence-online.all (every user) and presence-online.{tenant_id} (tenant members) — no app event needed.

4.7 Support classes

- `PaymentOptions` — methods (`cash` , `mobile_money` , `bank` , `selcom` , `card`), `ONLINE_METHODS` (`selcom` , `mobile_money` , `bank`), providers (mobile money: `airtel_money` , `mixx_by_yas` , `halopesa` , `mpesa` ; bank: `crdb` , `nmb` , `nbc` , `other`), statuses (`pending` , `awaiting_confirmation` , `completed` , `failed` , `refunded`), and helpers (`defaultMethods()` excludes `selcom`, `requiresProvider` , `requiresConfirmation` , `initialStatus` , `label()` for document rendering).
- `BookingOptions` — booking types (single, couple, family, group), room types, ID types, booking sources, guest defaults, `resolveStay()` for nights/departure.
- `NumberGenerator` — per-tenant sequential numbers: `prNumber` , `poNumber` , `grnNumber` , `orderNumber` , `requisitionNumber` , **`bookingReference (BK-...)`** , `staffNumber` , `laundryNumber` , `funGameNumber` , `transactionReference` , `clickPesaReference` , `inviteToken` , `tempPassword` .
- `TenantContext` — static tenant id holder.
- Module options: `HousekeepingOptions` , `LaundryOptions` , `FunGameOptions` , `OrderOptions` , `StaffOptions` .

4.8 Public booking & payment flow

1. `GET public/availability?hotel_id&check_in&check_out&booking_type` returns available rooms **and** the hotel's enabled `payment_methods` .
2. `POST public/reservations` validates the guest + booking (including `booking_date` after today and before check-in). With `room_selections` , one **pending** `Reservation` is created per room

under a shared `booking_reference` (`BK-...`); the response carries `booking_reference` and `total_amount` (room rate × nights + ClickPesa service fee when online). Without rooms it creates a booking requisition.

3. `POST public/payments/initiate` with `booking_reference` , `amount` , `payment_method` , `payment_provider` , `phone` :
4. **selcom** → payment `completed` , all same-reference pending reservations confirmed.
5. **bank** → payment `awaiting_confirmation` ; hotel confirms later.
6. **mobile_money** → ClickPesa prompt via `phone` ; the `payments/clickpesa/callback` webhook completes the payment and confirms the booking.


4.9 Migrations & seeders

- ~68 migrations cover tenants, users (incl. `add_login_pin_to_users_table` — the nullable, hashed 4-digit `users.login_pin` powering PIN sign-in), permissions, rooms, guests, reservations, payments, booking requisitions, housekeeping, F&B, laundry, fun & games, inventory, procurement, staff invitations/attachments, audit logs, **messages (reactions/view-once/delete fields)**, **statuses (statuses / status_views / status_reactions)**, **calls (calls / call_events)** plus the messaging feature set: `pin_star_templates_scheduled_tables` (pinned/starred/templates/scheduled), `polls_announcements_tables` (polls/poll_options/poll_votes/announcements + acknowledgements), `preferences_retention_escalation_handover_tables` (notification preferences, retention policies, escalations, handovers), `task_groups_staff_locations_guest_messages` (conversation_rooms, task_groups, staff_locations, guest_messages), `meetings_sos_tables` (meetings, meeting_invitees, sos_alerts + `ack_user_ids`), and **attendance anti-cheat**: `add_attendance_audit_columns_to_staff_attendance_table` (`lat` , `lng` , `accuracy_m` , `qr_verified_at` , `ip_address` , `user_agent` , `photo_path`), `add_attendance_settings_to_tenants_table` (`attendance_office_lat` , `attendance_office_lng` , `attendance_radius_m` , `attendance_require_qr` , `attendance_require_photo` , `attendance_shift_start` , `attendance_shift_end` , `attendance_late_grace_minutes` , `attendance_absent_after_minutes` , `attendance_early_leave_grace_minutes`), `create_attendance_qr_tokens_table` , `create_attendance_devices_table` , `create_attendance_penalties_table` , `create_attendance_absence_requests_table` , `create_attendance_absence_attachments_table` , and `add_attendance_anti_cheat_columns` (`attendance_devices.secret_hash` , `attendance_devices.trust_score` , `attendance_qr_tokens.used_device_ids` , `staff_attendance.photo_hash`).
- `TenantSeeder` seeds the demo tenant; `RolePermissionSeeder` sets up roles/permissions.

4.9.1 Database schema ERD

The full relational diagram (all 67 tables, columns, primary/foreign keys and crow's-foot relationships) is available as a poster-size document:

- **MRK_Hotels_Database_Schema_ERD.pdf** — a single page printed at 8578 × 2794 mm (way larger than A4, about 7 A0 sheets side by side) with a large 36 px font, so every table name, column and relationship is legible. Exported from the live schema served by **Laravel Truss** at `http://localhost:8000/truss` (`GET /truss/export/mermaid`), rendered with **Mermaid** (36 px font, blue #005EB8 accent theme) and printed to a **vector PDF** via WeasyPrint.
- Preview of the same diagram, scaled to fit:



4.10 Testing

- `phpunit.xml` uses in-memory SQLite (`:memory:`) for tests.
- Base `Tests\TestCase` with `RefreshDatabase` .
- Feature tests include `tests/Feature/PublicBookingPaymentFlowTest.php` (7 tests: availability methods, selcom default-off, pending booking creation, selcom confirms, bank awaiting-confirmation, selcom rejected when disabled, multi-room shared reference + batch confirm), `tests/Feature/ConversationTest.php` (direct messaging: scoping, resumes, unread counts, polling, delivery/read ticks, audio upload), `tests/Feature/GroupConversationTest.php` (11 tests: hotel/global groups, member guards, read receipts, media, add/remove/leave, unread badge feed), `tests/Feature/MessagingFeaturesTest.php` (**20 tests** covering the 24-feature set: replies + priority + polls, poll voting, pin/star, templates, scheduled messages, announcements + acknowledge, escalation + resolve, command auto-escalation, search, CSV export, translate, task-group conversion, meetings + responses, SOS flow, staff location/nearby, guest SMS, retention purge, **forwarding (incl. cross-chat access block), room search, meeting-invitee search**), `tests/Feature/OverviewPaginationTest.php` (3 tests: staff/in-house/housekeeping section filtering + pagination), `tests/Feature/InvoiceTest.php` (folio totals, regeneration keeps number and settles, PDF download, front-desk level, tenant scoping), `tests/Feature/PublicInvoiceDownloadTest.php` (reference + any phone spelling, wrong phone 404, pending reservation has no invoice, group booking, rate limit), `tests/Feature/TenantTest.php` (payment accounts, tax IDs, branding upload/removal), `tests/Feature/RateLimitTest.php` (3 tests: login per-IP/per-email, public portal writes per-IP, messaging per-user), `tests/Feature/StaffPinLoginTest.php` (13 tests: PIN login by email and by registration number, wrong/unset/unknown-identifier rejections, disabled accounts, 4-digit validation, and the set-pin guards — role hierarchy, no self-service, confirmation required), and `tests/Feature/AttendanceTest.php` (**15 tests**: clock-in/out, double clock-in refused, clock-out without shift refused, location + request metadata capture, location required when office configured, inside/outside geofence, manager QR issue, QR-required refusal without token, valid + expired token paths, requirements reflect policy, admin settings update, QR cannot be enabled without an office, who-is-on-shift).
- Messaging tests broadcast to the local Reverb server — run `php artisan reverb:start` (or set `BROADCAST_CONNECTION=null` and avoid the broadcast calls) for the full suite to stay green.
- Run: `php artisan test` (currently **199 passing, 676 assertions**).

4.11 Realtime (Reverb + Echo)

- **Server:** `laravel/reverb` runs a standalone WebSocket server (`php artisan reverb:start` , default `ws://localhost:8080`). Configure `REVERB_APP_ID` , `REVERB_APP_KEY` , `REVERB_APP_SECRET` , `REVERB_HOST` / `REVERB_PORT` and the public/private ports in `.env` .
- **Client:** the SPA connects with `laravel-echo` (`pusher-js` transport) against `REVERB_*` config, authenticated via the Sanctum bearer token (channel auth goes through `/broadcasting/auth`).
- **Channels:** per-user private channel `private-users.{user_id}` (incoming messages, meeting invites, SOS rings), per-tenant `private-tenants.{tenant_id}` (announcements, SOS, handovers, guest messages, staff locations, escalations) and per-thread `private-conversation.{id}` / `private-group.{id}` (message, reply, pin/star, poll and task-convert events scoped to the open thread). Online state rides a **presence channel** — the global `presence-online.all` (joined by `echo.join('online.all')` , member payload `user_id` + `full_name` + `tenant_id` + `hotel_name`) plus each hotel's `presence-online.{tenant_id}` (member payload `user_id` + `full_name`): every open app tab registers with Reverb, so peers see who is online right now (here / joining / leaving) without polling.
- **Security:** private channels are authorised by `BroadcastChannel::check` — a user may only subscribe to their own user channel and to channels of tenants they belong to. The presence callbacks publish no sensitive payload (just `user_id` , `full_name` and — on the global channel — the public `tenant_id` / `hotel_name`); the tenant channel only admits members of the given tenant. Sensitive payloads (view-once media, call signaling data) never travel on public channels.

4.12 Rate limiting

Defined as named limiters in `AppServiceProvider::boot()` and applied in `routes/api.php` :

Limiter	Key	Budget	Applied to
api	user <code>user_id</code> (authenticated) / IP (guest)	120 / min (authenticated), 30 / min (guest)	whole authenticated group (<code>auth:sanctum</code> → <code>tenant</code> → <code>throttle:api</code>) and <code>/broadcasting/auth</code>
auth	IP + email (or the PIN-login identifier)	5 / min	<code>auth/login</code> , <code>auth/login-pin</code> , <code>auth/register</code> — blocks credential stuffing; both sign-in forms share one budget
public	IP	10 / min	portal writes & lookups: <code>public/booking-requisitions</code> , <code>public/reservations</code> , <code>public/payments/initiate</code> , <code>public/booking-requisitions/status</code> , <code>public/invoices/download</code>
messaging	user <code>user_id</code>	30 / min	messages, groups, reactions, statuses, calls (<code>level:20</code> group)
webhook	IP	60 / min	<code>payments/clickpesa/callback</code> (server-to-server; generous to avoid breaking payment verification)

Violations return `429 Too Many Requests` with the standard Laravel JSON body (`Retry-After` included). Counter storage uses the configured cache store (database by default); flush `cache` in tests to keep rate-limit tests isolated.

4.13 Attendance anti-cheat (geofence + QR + device binding)

`StaffAttendanceController` enforces the hotel's attendance policy from `tenants.attendance_office_lat`, `attendance_office_lng`, `attendance_radius_m`, `attendance_require_qr`, `attendance_require_photo` and the discipline-policy columns (shift window + tolerances). All defaults are **off** — unconfigured hotels behave as before:

- **Office location** — when `lat/lng` are set, `clock-in` (and best-effort `clock-out`) requires a `lat / lng` (`accuracy_m` optional) and the point must fall within the geofence radius (haversine via `AttendanceService::distanceToOffice()`); outside or missing → `422 You must be at the office to clock in.` A successful fix stamps `positioned_at`.
- **GPS hardening** — `AttendanceService::normalizePositionedAt()` is authoritative for time: a missing, future or more than `positioned_at_max_skew_seconds` (default 300 s) off client timestamp is replaced with the server clock and the record is flagged `clock_skew`. Two fixes closer in time than `max_plausible_kmh` (default 180 km/h) allows are physically impossible, so the later record is flagged `gps_teleport` (see `impliesTeleport()`).
- **Entrance QR** — when `attendance_require_qr` is on (only valid once the office is configured; the settings validator refuses QR without a location), `clock-in` also needs a `qr_token` issued by a manager/level-80+ (`POST attendance/qr-token`, 60-second TTL, single-use — consumed on successful clock-in, stored in `attendance_qr_tokens`). Missing/expired/reused token → `422 Scan the office QR code to clock in.` A token is additionally bound to the presenting `device_id`: `attendance_qr_tokens.used_device_ids` records which device already consumed it, so a scanned code cannot be replayed by the same phone across many clock-ins. A successful `clock-in` stamps `qr_verified_at`.
- **Device binding** — each phone/browser registers a stable `device_id` plus a server-issued `device_secret` (hashed into `attendance_devices.secret_hash`; the plaintext secret is returned exactly once at `POST attendance/devices/register`). Policy values (`attendance.device.policy`): `off` (ids recorded, never enforced), `auto_register` (default — first clock-in registers the device; new devices on an account are flagged, not refused), `strict` (clock-in refused until the device is registered to that account, and a device bound to another staff member is always refused). `resolveDevice()` runs *before* the QR is consumed so a failed check never wastes an entrance code. `trust_score` bumps on every verified clock-in; revoking a device (admin `POST attendance/devices/{id}/revoke`) marks it `revoked_at` and its future clock-ins are refused/flagged.
- **Clock-in selfie** — when `attendance_require_photo` is on, `clock-in` requires a `photo` upload (`422 A clock-in selfie is required.`). Photos are stored on a **private disk** (default `local`, `attendance/photos`, max 3 MB) and are served **only** through the authenticated, audited blob endpoints `GET attendance/photos/{attendanceId}` and `GET attendance/attachments/{attachmentId}` (both log `AuditService::log('other', ...)` with an `entity_type` distinguishing the pod) — never via public URLs. The SHA-256 is kept in `staff_attendance.photo_hash`.
- **Suspicion detection** — each clock-in is scored by `AttendanceService::detectSuspicion()` and `detectPhotoSuspicion()`, producing a `suspicion_reasons` array of stable reason codes: `outside_allowed_area`, `shared_device` (another user clocked in from this device inside the 10-

minute window — the "colleague clocked me in" hand-off, which also flags the peer via `flagSharedDevicePeers()`, `revoked_device`, `too_many_devices` (over `max_per_user`, default 3), `gps_teleport`, `clock_skew`, `selfie_reused` (byte-identical to a past selfie or the profile picture), `selfie_no_camera_exif`, `selfie_edited`. Flagged records surface on `GET attendance/suspicious` for manager review.

- **Absence claims** — staff file claims (`POST attendance/absences` , with optional evidence attachments and a `device_id`); managers approve/reject via `POST attendance/absences/{requestId}/decide` . All evidence uploads are hashed and stored on the private disk.
- **Discipline policy & penalties** — managers configure the shift window and tolerances via `PUT attendance/policy` (`shift_start` , `shift_end` , `late_grace_minutes` , `absent_after_minutes` , `early_leave_grace_minutes`). Auto-detected offenses (`late_arrival` , `early_departure` , `absence`) plus manual ones (`no_show` , `other`) land in `attendance_penalties` as pending system offenses; the manager applies or dismisses each via `POST attendance/penalties/{id}/decide` . The vocabulary (offense types, `minor|major|critical` severities, default points, `verbal_warning|written_warning|fine|suspension|termination` actions) is centralised in `App\Support\PenaltyOptions` .
- **Scheduled commands** — `attendance:scan-no-shows` runs hourly and flags staff with no clock-in on a shift day (no approved absence claim, no existing offense) as `absence` offenses; `attendance:verify-evidence` runs daily and re-hashes every stored selfie/attachment, flagging `evidence_missing` / `evidence_tampered` .
- **Audit** — every clock-in/out records `lat` , `lng` , `accuracy_m` , `ip_address` and `user_agent` on the `staff_attendance` row; every clock-in/out, device registration, QR mint and penalty/absence decision is audit-logged.
- **Rate limiting** — all attendance *writes* (clock-in/out, device register/revoke, QR mint, absence claims, penalty decisions) go through the `attendance` limiter (8 per minute per user, registered in `AppServiceProvider`), so the anti-cheat endpoints cannot be sprayed with spoofed events.
- **Flow** — the staff SPA calls `attendanceApi.requirements()` on the Profile page (returns `office_configured` , `requires_location` , `requires_qr` , `qr_ttl_seconds` , `requires_photo` , `device_policy` , `device_registered`), geolocates, registers the device if needed (`src/utils/device.js` persists `mrk_attendance_device_secret` in `localStorage` and submits it with clock-in), captures a selfie when required, then (when enabled) surfaces the generated QR (issued per user, rotates every 60 s with a `refreshToken`) in a scan-the-office-phone dialog; the scan is decoded with `jsqr` and passed as `qr_token` . `POST attendance/qr-token` is rate-limited per user and never returns tokens for the same user (no self-issue); it also refuses to mint when the policy isn't enabled.

5. Frontend Architecture

5.1 Project layout

```
src/
  api/          axios instance + endpoint groups (index.js)
  components/   PhoneInput, CountryCitySelect, StayDates, PaymentMethodSelect,
                ChangePasswordForm, ModulePlaceholder
  composables/  useCallManager.js (WebRTC + call ring), useConversation.js,
                useBroadcast.js,
                useHoliday.js (holiday logo decorations), usePresence.js (online-status
presence)
  config/       modules.js – role access matrix
  layouts/      StoreLayout (public + hotel panel), SuperadminLayout
  locales/      i18n.js + en.json + sw.json
  pages/        public/, auth/, dashboards/, reservations/, rooms/, guests/, payments/,
booking/,
                housekeeping/, orders/, menu/, laundry/, fungames/, inventory/, suppliers/,
                procurement/, staff/, reports/, overview/, superadmin/, profile/,
                messages/, statuses/
  plugins/      echo.js – laravel-echo (Reverb) lazy singleton
  router/       index.js – routes + guards
  stores/       auth.js (Pinia, persisted token), session.js (idle watchdog)
  utils/        dates.js, locations.js, payments.js, phone.js
  main.js
```

5.2 API layer (src/api)

- `axios.js` : baseUrl from `VITE_API_URL` (default `http://localhost:8000/api`); adds `Authorization: Bearer <auth_token>` from `sessionStorage`; flattens Laravel pagination (`data.data` + `meta` → top-level); on 401 clears the token and hard-redirects to `/login` .
- `index.js` exposes typed endpoint groups under `/v1` : `publicApi` , `authApi` , `reportApi` , `userApi` , `roomApi` , `guestApi` , `reservationApi` , `paymentApi` , `housekeepingApi` , `inventoryApi` , `supplierApi` , `menuItemApi` , `orderApi` , `laundryApi` , `funGameApi` , `purchaseRequisitionApi` , `purchaseOrderApi` , `goodsReceivedNoteApi` , `bookingRequisitionApi` , `tenantApi` , `superadminReportApi` , `conversationApi` , `groupApi` , `messageActionApi` (react/delete/view-once), `statusApi` (post/list/view/like), `callApi` (start/accept/reject/decline/end/miss), `featuresApi` (reply/pin/star/polls/templates/scheduled/announcements/search/export/translate/escalate/retention/preferences/handovers/guest SMS/nearby/SOS/forward), `roomLinkApi` (index/searchRooms/link/unlink), `taskGroupApi` (store/convert), `meetingApi` (index/store/respond/searchUsers), `sosApi` (index/initiate/acknowledge/resolve), `attendanceApi` (clock-in/clock-out/status/requirements/qrcode/on-shift/history/settings/policy/register/penalties/devices register·mine·all·revoke/suspicious/absences report·mine·all·decide/photo-attachment blob).
- `plugins/echo.js` sets up the `laravel-echo` instance from `VITE_REVERB_*` env vars, authorises private channels through the SPA's `axios` auth headers, and exports the lazy `echo` singleton for the broadcast composables.
- `usePresence.js` joins `echo.join('online.all')` (global, every user) and `echo.join('online.{tenant_id}')` (own hotel) — module singleton, self-healing across Echo rebuilds — keeps two

reactive sets of peer `user_id`s from `here / joining / leaving` and exposes `isOnline(userId)`; wired globally from `StoreLayout` so the indicator is accurate across all pages (§6.13.18, Online status).

- PIN sign-in: `authApi.loginPin({ identifier, pin })` mirrors `authApi.login` (same response shape); `userApi.setPin(id, { pin, pin_confirmation })` lets admins/managers assign staff login PINs from the Staff page.
- `reportApi.overview(params)` sends per-section filters/pagination (`staff_search` , `role` , `status` , `in_house_search` , `upcoming_search` , `housekeeping_status` , `page`); nested sections return raw `{ data, links, meta }` (the interceptor only flattens top-level pagination).

5.3 Routing & access control

- Three areas: public portal (`/` , `/hotels/:id` , `/booking`), hotel panel (`/app/*`), superadmin (`/superadmin/*`).
- `router.beforeEach`: requires `auth_token` (`sessionStorage`) for `requiresAuth`; guest routes bounce signed-in users to their dashboard; fetches `/me` before role/module checks; enforces `role` meta and module access via `canAccess`.
- Access matrix (`src/config/modules.js`): explicit role allow-lists per module with optional extra `permission` gate. Empty `roles` = everyone (dashboard, profile). Superadmin bypasses all lists.

5.4 Stores (Pinia)

- `auth.js`: `token` (stored in `sessionStorage` — survives a refresh, dies with the tab; credentials left in `localStorage` by older builds are cleared once), `user` , `permissions` , `mustChangePassword` ; `ROLE_LEVELS` ; helpers `can()` , `hasPermission()` , `canAccess()` ; actions `login` , `loginPin` (identical session handling to `login` , used by the PIN keypad mode), `logout` , `fetchProfile` , `changePassword` .
- `session.js`: **5-minute idle timeout**; hiding the tab (tab switch/minimise) logs out **immediately** — `visibilitychange` → `terminate()` ; a refresh keeps the session (the token lives in `sessionStorage`, so a closed tab always returns to login) and restarts the idle countdown; activity listeners; auto-logout → login page. `App.vue` re-arms the timer on boot when a stored token exists; a fresh login arms it from `LoginPage` .
- `messages.js` (Pinia): conversations + groups merged into one feed, unread counts, active thread state; subscribes to `MessageSent` / `MessageRead` / `MessageDeleted` / `MessageReacted` via Echo to update the UI live.

5.5 i18n

- `vue-i18n` v11; locale files `en.json` and `sw.json` ; default locale from `localStorage` , toggle button in the top bar (`EN` / `SW`).
- Always translate UI strings via `$t('section.key')` ; add new keys to **both** files.

5.6 Key components

Component	Purpose
PhoneInput	Phone input with country-code select, format via libphonenumber-js; emits <code>update:modelValue</code> + <code>update:countryCode</code> .
CountryCitySelect	Cascading country/city pickers (country-state-city); emits <code>update:countryCode</code> , <code>update:country</code> , <code>update:city</code> .
StayDates	Arrival/departure/days inputs; keeps departure & day count in sync.
PaymentMethodSelect	Method + provider select with contextual notices (selcom auto-pay, mobile-money confirmation).
BookingStatusTracker	Public booking status lookup card (reference + phone).
InvoiceDownloadCard	Public guest self-service invoice download (reference + phone) via <code>publicApi.invoiceDownload</code> ; saves the blob with the server-provided filename (<code>saveBlob</code> util).
ChangePasswordForm	Change-password form.
ModulePlaceholder	Generic "under construction" page for unimplemented modules.
ConversationItem / MessageBubble	Conversation row (avatar, last message, unread badge, online/status ring) and message bubble (ticks, media thumbnail, reactions row , long-press/hover context menu for delete / view-once toggle).
ViewOnceMedia	View-once image/video: covers the media, exposes <code>media_url</code> exactly once, then marks <code>is_media_seen</code> via <code>messageActionApi</code> .
ReactionPicker	Emoji picker used to react to a message (toggles on/off).
StatusRing	Avatar ring showing a colleague has an active status; navigates to the Statuses page.
StatusItem	A single 24-hour status (photo/video/text) with viewer + reaction counts.
CallIncomingOverlay	Full-screen incoming-call modal (audio/video) with accept/reject; uses <code>useCallManager</code> .
AttendanceQrScanner	Attendance clock-in flow on the Profile page: geolocates the user, checks <code>attendanceApi.requirements()</code> , renders the rotating per-user office QR (drawn with the <code>qrcode</code> lib, refreshes every 60 s), opens <code>getUserMedia</code> camera preview and decodes scans with <code>jsqr</code> (<code>qr_token</code>), then calls <code>clock-in</code> . Also contains the manager's "issue token" action and the admin's attendance-settings form (office marker/radius/QR toggle). Selfie capture (when <code>requires_photo</code>) uses <code>AttendanceSelfieCapture</code> ; evidence blobs are opened via <code>attendanceApi.photo()</code> / <code>attachment()</code> + <code>URL.createObjectURL</code> .

Key pages: `pages/messages/` (conversation list + thread composer with replies, priority, polls, templates, scheduled send, forwarding, pin/star, translate, search, export, mute/DND, room-link + task groups, and the **Workspace panel** with Announcements / Meetings / Handovers / Guest

SMS / Nearby Staff / Escalations / SOS / Scheduled / Starred / Retention tabs + the floating SOS button), `pages/statuses/` (my status + status feed), `pages/calls/` for call history (missed/active logs).

Composables: `useBroadcast` (subscribes to Echo private channels), `useConversation` (thread loading, sending, polling fallback), `useCallManager` (peer connection, `getUserMedia`, ring/answer/end signaling over `CallEvent` broadcasts).

Mobile tables: list tables are wrapped in `<div class="table-scroll">` (`overflow-x: auto`) so only the table scrolls horizontally on small screens; `html / body` both have `overflow-x: hidden` and page-level horizontal scrolling should never appear.

5.7 Utilities

- `dates.js` — `todayISO()`, `addDays()`, `daysBetween()`.
- `payments.js` — method/provider constants, `isAutoPaid()`, `requiresConfirmation()`, `requiresProvider()`.
- `locations.js` — country/city lists, `getCountryName()`, `findCountryCode()`.
- `phone.js` — `normalizePhoneNumber()`.

5.8 Frontend testing

- Vitest unit tests in `src/__tests__/`.
- Playwright e2e specs in `e2e/` (`login.spec.js`, `modules.spec.js`, `vue.spec.js`).
- Scripts: `npm run build`, `npm run lint` (eslint), `npm run format` (oxfmt), `npm test`.

6. Request Lifecycle

This section is your route map for debugging. Every request — from the moment a user clicks in the browser to the moment the response updates the screen — passes through the same spine of files in **both** codebases. Each hop below names the exact files involved, what they do, and what to look at when that hop fails. Use the worked examples in §6.12, the per-feature catalog in §6.13, and the runbook in §6.14 when something breaks.

6.1 The loop in one picture

Every request (except webhooks and realtime events, which start from the server side) follows this spine:



Webhooks (STAAH, ClickPesa) and the scheduled commands (SMS reminders, STAAH push)

bypass the frontend entirely; they enter at `routes/api.php` (or `routes/console.php`) — see §6.12.4 and §6.12.5.

6.2 Hop 0 — Frontend: where a request is born

Four kinds of frontend files fire requests. All of them call a function from `src/api/index.js`, which funnels through `src/api/axios.js` (§6.3).

Pages (`src/pages/**` — every page and the API groups it calls):

Page file	API groups used
<code>public/HotelDirectoryPage.vue</code>	<code>publicApi</code>
<code>public/HotelDetailPage.vue</code>	<code>publicApi</code>
<code>public/BookingPage.vue</code>	<code>publicApi</code>
<code>auth/LoginPage.vue</code>	via <code>stores/auth.js</code> → <code>authApi</code>

Page file	API groups used
dashboards/HotelDashboard.vue	reportApi
overview/AdminOverviewPage.vue	reportApi , reservationApi , housekeepingApi , userApi
reservations/ ReservationListPage.vue	reservationApi , guestApi , paymentApi , invoiceApi , publicApi
rooms/RoomListPage.vue	roomApi
guests/GuestListPage.vue	guestApi
payments/PaymentListPage.vue	paymentApi , invoiceApi , reservationApi
booking/ BookingRequisitionListPage.vue	bookingRequisitionApi
housekeeping/ HousekeepingPage.vue	housekeepingApi , roomApi , userApi
laundry/LaundryListPage.vue	laundryApi , userApi
orders/OrderListPage.vue	orderApi , menuItemApi
menu/MenuListPage.vue	menuItemApi
fungames/FunGameListPage.vue	funGameApi , userApi
inventory/InventoryListPage.vue	inventoryApi
suppliers/SupplierListPage.vue	supplierApi
procurement/ RequisitionListPage.vue	purchaseRequisitionApi
procurement/ PurchaseOrderListPage.vue	purchaseOrderApi , purchaseRequisitionApi , supplierApi
procurement/ GoodsReceivedNoteListPage.vue	goodsReceivedNoteApi , purchaseOrderApi
issuereports/ IssueReportListPage.vue	issueReportApi , userApi
staff/StaffListPage.vue	userApi
reports/ReportPage.vue	reportApi
accounting/AccountingPage.vue	accountingApi
profile/ProfilePage.vue	authApi , attendanceApi
statuses/StatusesPage.vue	statusApi

Page file	API groups used
messages/MessagesPage.vue	conversationApi , groupApi , messageActionApi , statusApi , callApi , templateApi , scheduledApi , announcementApi , meetingApi , handoverApi , guestMessageApi , guestNotificationSettingsApi , staffLocationApi , escalationApi , sosApi , retentionApi , preferenceApi , roomLinkApi , taskGroupApi , featuresApi
owner/OwnerDashboard.vue	ownerApi
owner/OwnerHotelDetail.vue	ownerApi
owner/ProfilePage.vue	authApi
superadmin/ SuperadminDashboard.vue	superadminReportApi
superadmin/TenantListPage.vue	tenantApi
superadmin/TenantDetailPage.vue	tenantApi , superadminReportApi
superadmin/ReportsPage.vue	superadminReportApi
superadmin/ProfilePage.vue	authApi

Components that call APIs directly (`src/components/`): `BookingStatusTracker.vue` → `publicApi` (booking status); `InvoiceDownloadCard.vue` → `publicApi.invoiceDownload` (blob download, `saveBlob` util); `AttendanceQrScanner.vue` → `attendanceApi.requirements()` + `attendanceApi.clock-in` (QR + geofence flow); `ViewOnceMedia.vue` → `messageActionApi` (view-once marking); `CallIncomingOverlay.vue` → via `useCallManager` → `callApi`. (`PhoneInput` , `CountryCitySelect` , `StayDates` , `PaymentMethodSelect` , `ChangePasswordForm` , `ModulePlaceholder` are pure UI — they never hit the network.)

Stores (`src/stores/`): `auth.js` → `authApi.login/loginPin/logout/me` , `userApi.changePassword` (holds the token in `sessionStorage`; `fetchProfile` runs on boot); `session.js` → no network (5-minute idle watchdog + tab-hidden logout); `messages.js` → `conversationApi` / `groupApi` + live Echo subscriptions.

Composables (`src/composables/`): `useCallManager.js` → `callApi` (initiate/signal/accept/end) + WebRTC `getUserMedia` ; `useRoomBrowser.js` → `roomApi` / `booking` availability flows.

6.3 Hop 1 — The funnel: `src/api/axios.js`

Every request passes through this one file. This is the first place to look when "all" requests fail.

- **Base URL:** `baseUrl` from `VITE_API_URL` (default `http://localhost:8000/api`). A wrong/empty env var here makes every request 404/fail with CORS.
- **Auth header:** a request interceptor attaches `Authorization: Bearer <auth_token>` read from `sessionStorage`. If the token is missing you get 401 on every authenticated call — check the store, not the network.

- **Pagination flatten:** the response interceptor rewrites Laravel pagination `{ data, links, meta }` into top-level `data + meta` so pages can read `response.data` directly. Note: nested paginated sections inside overview/reports are left raw (see `reportApi.overview`).
- **401 handling:** any 401 clears the stored token and hard-redirects to `/login`.
- `src/api/index.js` exports the endpoint groups (§5.2). Each function is a thin wrapper: HTTP method + `/v1/...` path. To add a new call, add a function here, then consume it from a page/store — never call `axios` directly from a component.
- `src/plugins/echo.js` — not request/response; sets up the Reverb socket (`VITE_REVERB_*`) for live updates (§6.12.5), initialised lazily and owned globally by `StoreLayout` (private-channel auth via `POST /broadcasting/auth`).

6.4 Hop 2 — HTTP entry & bootstrap (backend infrastructure)

- `public/index.php` boots Laravel → `bootstrap/app.php` (`Application::configure()` with `web/api/channels/commands`).
- **Middleware aliases** defined here: `tenant` → `SetTenantContext`, `level` → `CheckRoleLevel`, `operate` → `CanOperate`, `superadmin` → `RequireSuperadmin`, `owner` → `RequireOwner`, `tenant.active` → `EnsureTenantActive`.
- **Rate limiters** registered in `app/Providers/AppServiceProvider.php::boot()`: `api` (120/min authed, 30/min guest), `auth` (5/min login+PIN shared), `public` (10/min), `messaging` (30/min), `attendance` (8/min), `webhook` (60/min). A 429 response means you hit one of these — the limiter key tells you which group.
- **CORS** (`config/cors.php`): paths `api/*` + `sanctum/csrf-cookie`, origins `*`, exposes `Content-Disposition` (needed for invoice PDF downloads).
- **Error shapes:** Laravel 11+ default JSON rendering (no custom `Exceptions/Handler`). 401 `{"message":"Unauthenticated."}`, 403 message string, 404 `Route ... not found`, 422 `{ message, errors }`. Logs land in `storage/logs/laravel.log`.

6.5 Hop 3 — `routes/api.php` (the registry)

Everything lives under the `v1` prefix. Order matters: static segments (e.g. `guests/lookup`, `reservations/options`, `payments/options`, `orders/form-options`, `messages/rooms/search`) are declared **before** `{id}` segments so they are not swallowed by the wildcard.

Group	Routes	Middleware	Handler
Public portal	GET <code>public/hotels</code> , <code>public/hotels/{id}</code> , <code>public/availability</code> , <code>public/options</code>	—	<code>PublicController</code>

Group	Routes	Middleware	Handler
Public writes	POST public/booking-requisitions , public/reservations , public/payments/initiate ; GET public/booking-requisitions/status , public/invoices/download	throttle:public	PublicController
Auth	POST auth/register , auth/login , auth/login-pin	throttle:auth	AuthController
ClickPesa webhook	POST payments/clickpesa/callback	throttle:webhook	PaymentController
STAAH webhooks	POST integrations/staah/reservations , integrations/staah/push-data	throttle:webhook	StaahWebhookController
(disabled)	POST messaging/sms/inbound	—	commented out — guest SMS is one-way
Authenticated root	everything below	auth:sanctum , tenant , throttle:api + per-route level:N / operate	all API controllers
Realtime	POST broadcasting/auth	throttle:api	Reverb channel auth

Representative authenticated routes → handlers: `auth/me` → `AuthController@me` ; `reports/dashboard` → `ReportController@dashboard` ; `accounting/*` → `AccountingController` ; `users*` → `UserController` ; `rooms*` → `RoomController` ; `guests*` → `GuestController` ; `reservations*` → `ReservationController` ; `payments*` , `payments/clickpesa/*` → `PaymentController` ; `invoices*` → `InvoiceController` ; `integrations/staah/*` → `StaahController` ; `housekeeping*` → `HousekeepingController` ; `laundry*` → `LaundryOrderController` ; `inventory*` → `InventoryController` ; `suppliers*` → `SupplierController` ; `menu*` → `MenuItemController` ; `orders*` → `OrderController` ; `fun-games*` → `FunGameOrderController` ; `procurement/*` → the three procurement controllers; `booking-requisitions*` → `BookingRequisitionController` ; `attendance*` → `StaffAttendanceController` ; `messaging/*` , `conversations*` , `groups*` , `messages/*` , `statuses*` , `calls*` , `announcements*` , `meetings*` , `sos*` , `guest-messages*` → the 27 messaging controllers; `superadmin/*` → `TenantController` / `ReportController` ; `owner/*` → `OwnerController` .

6.6 Hop 4 — Middleware chain (per request)

Applied in order; the first failure ends the request with a JSON 401/403.

Alias	Class	What it checks	Failure
<code>auth:sanctum</code>	Sanctum	Valid bearer token (created at login with ability = role name, or <code>*</code> for superadmin)	401
<code>tenant</code>	<code>SetTenantContext</code>	Resolves tenant: superadmin → global or X-Tenant-ID header; owner → X-Tenant-ID or 403; everyone else locked to their own <code>tenant_id</code> . Sets <code>TenantContext::set()</code> .	403
<code>level:{N}</code>	<code>CheckRoleLevel</code>	<code>config('roles.levels')[\$user_role] >= N</code> (superadmin always passes; owner passes ≤ 95)	403
<code>operate</code>	<code>CanOperate</code>	Role in the operational whitelist (receptionist/accountant/procurement/housekeeping/kitchen/waiter/bartender)	403
<code>superadmin</code>	<code>RequireSuperadmin</code>	<code>user_role === 'superadmin'</code>	403
<code>owner</code>	<code>RequireOwner</code>	<code>user_role === 'owner'</code>	403
<code>tenant.active</code>	<code>EnsureTenantActive</code>	tenant status active/pending (defense-in-depth)	403

`TenantContext` (`app/Models/Support/TenantContext.php`) is the static per-request holder; every `BelongsToTenant` model (all tenant data) is filtered by it via a global scope.

`TenantContext::clear()` runs after each request so state never leaks between requests (especially on the queue worker).

6.7 Hop 5 — Controllers (every file, grouped by module)

All under `app/Http/Controllers/Api/V1/`. Base `Controller.php` is empty/abstract; controllers validate **inline** via `$request->validate(...)` (no `FormRequest` classes exist), call a service when business logic is involved, then return `response()->json(...)` or a `Resource` /

`AnonymousResourceCollection`. `M` = methods.

Controller	Key methods	Collaborators
<code>Auth/AuthController</code>	register, login, loginPin, logout, me, changePassword, updateProfile	<code>User</code> , <code>Tenant</code> , <code>AuditService</code> , <code>UserResource</code>
<code>Booking/BookingRequisitionController</code>	index, show, respond, destroy	<code>BookingRequisition</code> , <code>AuditService</code> , <code>BookingOptions</code>

Controller	Key methods	Collaborators
Finance/AccountingController	generalLedger, trialBalance, balanceSheet, dayCloseReport, storeDayClose, dayCloses	Payment , Reservation , Order , FunGameOrder , LaundryOrder , PurchaseOrder , DayClose
Finance/PaymentController	index, store, show, confirm, reject, options, refund, destroy, clickPesalnitiate, clickPesaCallback	PaymentService , Payment , AuditService
Finance/InvoiceController	index, show, generate, download	InvoiceService , Invoice , Reservation
FoodBeverage/MenuItemController	CRUD	MenuItem
FoodBeverage/OrderController	formOptions, index, store, show, update, markItemStatus, pay, billToRoom	PaymentService , Order
Fun/FunGameOrderController	CRUD	FunGameOrder
Hotel/GuestController	index, lookup, store, show, update, destroy	Guest
Hotel/ReservationController	index, options, store, show, update, cancel, checkIn, checkOut, noShow, destroy	ReservationService , Reservation , AuditService
Hotel/RoomController	index, store, show, update, updateStatus, destroy	ReservationService , Room
Housekeeping/HousekeepingController	index, store, show, update, assign, start, confirm, verify, complete, destroy	HousekeepingTask
Integration/StaahController	settings, updateSettings, mappings CRUD, sync, pull, receipts	StaahAriService , StaahSetting , StaahMapping , StaahWebhookReceipt
Integration/StaahWebhookController	reservations, pushData	StaahReservationService , StaahClient

Controller	Key methods	Collaborators
Inventory/InventoryController	index, store, show, update, adjust, movements, destroy	InventoryService , InventoryItem , StockMovement
Inventory/SupplierController	CRUD	Supplier
Issue/IssueReportController	index, show, store, comment, respond	IssueReport , IssueReportComment
Laundry/LaundryOrderController	CRUD	LaundryOrder
Messaging/ConversationController	users, unreadCount, index, store, show, messages, send, markRead	Conversation , ConversationMessage , broadcast events
Messaging/GroupConversationController	CRUD + members	GroupConversation , GroupConversationMessage
Messaging/MessageActionController	delete, viewOnce, reactions	ConversationMessage , GroupConversationMessage
Messaging/StatusController	post, list, view, like	Status , StatusView , StatusReaction
Messaging/CallController	initiate, signal, accept, decline, end, cancel	Call , call broadcast events
Messaging/PinStarController	pin, unpin, star, unstar	PinnedMessage , StarredMessage
Messaging/PollController	vote	Poll , PollVote
Messaging/MessageTemplateController	CRUD	MessageTemplate
Messaging/ScheduledMessageController	CRUD	ScheduledMessage
Messaging/AnnouncementController	index, store, acknowledge	Announcement , AnnouncementAcknowledgement
Messaging/SearchController	invokable search	Conversation / GroupConversation
Messaging/ExportController	invokable export	conversations
Messaging/TranslateController	invokable translate	TranslateService
Messaging/EscalationController	index, escalate, resolve	MessageEscalation
Messaging/RetentionPolicyController	CRUD	RetentionPolicy
Messaging/NotificationPreferenceController	CRUD	NotificationPreference

Controller	Key methods	Collaborators
Messaging/ShiftHandoverController	index, store, acknowledge	ShiftHandover
Messaging/RoomLinkController	link, unlink, searchRooms	ConversationRoom , Room
Messaging/TaskGroupController	store, convert	ConversationRoom , TaskGroup
Messaging/ForwardController	invokable forward	messages
Messaging/StaffLocationController	update, nearby	StaffLocation , broadcast
Messaging/GuestMessageController	index, store	GuestMessage , SmsService
Messaging/GuestNotificationSettingsController	get/update	GuestNotificationSetting
Messaging/MeetingController	searchUsers, index, store, respond	Meeting , MeetingInvitee , broadcasts
Messaging/SosController	index, initiate, acknowledge, resolve	SosAlert , broadcasts
Messaging/SmsWebhookController	inbound (<i>unreachable — one-way SMS</i>)	SmsService
Owner/OwnerController	dashboard, hotels, hotel	Tenant , Reservation , Payment
Portal/PublicController	hotels, hotelShow, availability, storeBookingRequisition, storeReservation, initiatePayment, options, bookingStatus, invoiceDownload	ReservationService , PaymentService , InvoiceService , SmsService
Procurement/PurchaseRequisitionController	index, store, show, approve, reject, cancel	PurchaseRequisition , AuditService
Procurement/PurchaseOrderController	index, store, show, managerApprove	PurchaseOrder , AuditService
Procurement/GoodsReceivedNoteController	index, store, show	InventoryService , GoodsReceivedNote
Reports/ReportController	dashboard, overview, occupancy, revenue, roomStatus, auditLogs, superadminDashboard, tenantAnalytics	aggregates across models

Controller	Key methods	Collaborators
Staff/StaffAttendanceController	clock-in/out, QR, settings, policy, penalties, devices, suspicious, absences, photos (27 methods)	AttendanceService , StaffAttendance , AttendanceDevice , AttendancePenalty , AttendanceQrToken , AttendanceAbsenceRequest
Tenants/TenantController	CRUD, approve, reject, suspend, reactivate, subscription, branding, owners, storeOwner	Tenant , User
Users/UserController	index, store, show, update, destroy, activate, invite, resetPassword, setPin, attach, deleteAttachment	User , StaffAttachment , AuditService

6.8 Hop 6 — Services (every file)

Services hold the business logic so controllers stay thin. If a feature "almost works" but the details are wrong (e.g. a booking creates but the room isn't marked unavailable), the bug is usually in the service.

Service	Responsibility / key methods
Hotel/ReservationService	Availability & overlap checks (isRoomAvailable , overlappingReservations , availableRooms), pricing (nights , roomTotal), lifecycle (create with online flag, checkIn , checkOut , cancel , noShow , destroy), balanceDue , refreshRoomStatus
Finance/PaymentService	record , confirm , reject , refund , creditReservation , clickPesaInitiate , initiatePublicPayment , handleClickPesaCallback ; calls SmsService on confirmations
Finance/InvoiceService	generateForReservation (dompdf), pdf (download response)
Inventory/InventoryService	adjustStock → creates StockMovement
Staff/AttendanceService	21 methods: geofence (distanceMeters , withinGeofence), QR (issueQrToken , consumeQrToken), clock evaluation (evaluateClockIn/Out , lateMinutes), device policy, suspicion/teleport detection, photos
Messaging/SmsService	sendForEvent , sendForPayment , send , isEnabled (consults config('sms.events') + per-tenant GuestNotificationSetting); renders {placeholder} tokens incl. invoice_link

Service	Responsibility / key methods
Messaging/SmsDrivers/ SmsDriver	Interface: <code>deliver</code> , <code>parseInbound</code>
Messaging/SmsDrivers/ LogSmsDriver	Local driver: writes to log (default)
Messaging/SmsDrivers/ AfricaTalkingSmsDriver	Production driver: POST to AT v2 API, marks queued/failed
Integration/StaahClient	<code>pushAvailability</code> (HTTP Basic), <code>handle()</code> writes <code>StaahWebhookReceipt</code>
Integration/ StaahAriService	<code>sync</code> (ARI availability/rates/restrictions); 422 if not wired; guardrails: 2000 req/day, 4 MB payload
Integration/ StaahReservationService	Idempotent reservation upsert on <code>[tenant_id, channel='staah', external_ref]</code> ; handles Reserved/Modify/Cancelled
System/AuditService	static <code>log / login / logout / updated / other</code> → <code>audit_logs</code> table
TranslateService	Offline EN↔SW glossary translation

6.9 Hop 7 — Models & the tenant scope (every file)

`app/Models/Concerns/BelongsToTenant.php` is the heart of multi-tenancy: it adds a global scope that filters `tenant_id = TenantContext::id()` and stamps `tenant_id` on create. **If a query returns rows from another hotel — or empty rows that should exist — suspect this trait, the `x-Tenant-ID` header, or a forgotten `tenant_id`.**

Module	Models (file → table)
Core	<code>Tenant</code>
Auth	<code>User</code> (PK <code>user_id</code> , UUID; <code>login_pin</code> , <code>registration_number</code> , <code>user_role</code> , <code>is_active</code>)
Hotel	<code>Guest</code> , <code>Reservation</code> , <code>Room</code>
Finance	<code>Payment</code> , <code>Invoice</code> , <code>DayClose</code>
Housekeeping	<code>HousekeepingTask</code>
FoodBeverage	<code>MenuItem</code> , <code>Order</code> , <code>OrderItem</code> (child, unscoped)
Fun	<code>FunGameOrder</code>
Inventory	<code>InventoryItem</code> , <code>StockMovement</code> , <code>Supplier</code>
Issue	<code>IssueReport</code> , <code>IssueReportComment</code> (child)
Laundry	<code>LaundryOrder</code> , <code>LaundryOrderItem</code> (child)

Module	Models (file → table)
Messaging	Conversation , ConversationMessage , ConversationRoom , GroupConversation , GroupConversationMember , GroupConversationMessage , MessageReaction , Status , StatusView , StatusReaction , Call , PinnedMessage , StarredMessage , Poll , PollOption , PollVote , MessageTemplate , ScheduledMessage , Announcement , AnnouncementAcknowledgement , MessageEscalation , RetentionPolicy , NotificationPreference , ShiftHandover , StaffLocation , GuestMessage , GuestNotificationSetting , Meeting , MeetingInvitee , SosAlert
Procurement	PurchaseRequisition , PurchaseRequisitionItem (child), PurchaseOrder , PurchaseOrderItem (child), GoodsReceivedNote , GrnItem (child)
Staff	StaffAttendance , AttendanceDevice , AttendanceQrToken , AttendancePenalty , AttendanceAbsenceRequest , AttendanceAbsenceAttachment
System	AuditLog , BookingRequisition , StaffAttachment , StaffInvitation (unscoped)
Integration	StaahSetting , StaahMapping , StaahWebhookReceipt

6.10 Hop 8 — Response shaping

- **Resources:** 35 classes under `app/Http/Resources/**` shape the JSON per module (e.g. `Auth\UserResource` , `Hotel/ReservationResource` , `Messaging/MessageResource`). Controllers return `new XResource(...)` or `XResource::collection(...)` . The paginated `data.data` envelope is flattened client-side (§6.3).
- **Validation:** `$request->validate([...])` inline → 422 `{ message, errors: { field: [...] } }` . On a 422, the field names in `errors` match the request body keys exactly — diff your payload keys against the controller's rule keys.
- **Exceptions:** default Laravel JSON (401/403/404/422/500). A 500 usually logs a stack trace in `storage/logs/laravel.log` with the request URL — start there.
- **Broadcast events:** 34 `ShouldBroadcastNow` events under `app/Events/` (root + `Messaging/`) fire after mutations (e.g. `MessageSent` → `conversation.{id}` , `GuestMessagePosted` → `tenant.{id}` , `SosAlertInitiated` → `tenant.{id}`). They carry the request's side-effects to Reverb (§6.12.5).
- **Audit trail:** mutations write to `audit_logs` via `AuditService` — a good cross-check when a change "didn't happen" (check `reportApi.auditLogs` / `adminOverview`).

6.11 Hop 9 — Back in the browser

- `axios.js` response interceptor returns the payload (pagination flattened); on 401 it clears the token and redirects to `/login` .
- Pages/stores update local state and render; strings go through `$t('section.key')` (`src/locales/en.json` + `sw.json`) — a missing key shows as the raw key, not a crash.
- Errors surface via the page's catch handler (toast); network-level failures (timeout, CORS, offline) appear as generic errors — check the browser Network tab and `VITE_API_URL` .
- Live updates for *other* users arrive over Reverb/Echo, not HTTP — if one client sees stale data but the API response is correct, debug Echo (§6.12.5), not the request path.

6.12 Worked path loops

6.12.1 Login (password) — the simplest full loop:

LoginPage.vue → stores/auth.js@login → authApi.login → src/api/axios.js (no token yet) → POST /api/v1/auth/login (throttle:auth) → AuthController@login (validate email/password → Hash::check → active/password-expiry/tenant checks → createToken('api-token', [role]) → AuthService::login) → UserResource + { message, token, user } → interceptor stores token in sessionStorage → store.user = payload.user → router guard passes → dashboard loads (reportApi.dashboard repeats the loop with the new token).

6.12.2 Staff creates a reservation:

ReservationListPage.vue (form) → reservationApi.store({...}) → axios.js (Bearer) → POST /api/v1/reservations (auth:sanctum + tenant + throttle:api + level:60 + operate) → ReservationController@store → ReservationService::create (availability check, pricing, save) → Reservation (BelongsToTenant scope) → ReservationResource → page appends to the list. AuthService records it.

6.12.3 Public online booking → confirmation SMS:

Guest BookingPage.vue → publicApi.storeReservation → POST /api/v1/public/reservations (throttle:public) → PublicController@storeReservation → ReservationService::create(online: true) → SmsService::sendForEvent('booking_confirmed', ...) → AfricaTalkingSmsDriver::deliver (if config('sms.driver')=africa_talking , account funded, and the event toggle enabled) → GuestMessage row (direction=outbound) + GuestMessagePosted broadcast → response returns booking_reference . Guest also receives the invoice link (invoice_link token). If the guest never gets the SMS, check: account balance, AFRICASTALKING_FROM , sms.events.booking_confirmed.enabled , guest phone present.

6.12.4 STAAH webhook (server-initiated, no frontend):

STAAH → POST /api/v1/integrations/staah/reservations (throttle:webhook) → StaahWebhookController@reservations → shared-secret verified → payload written to StaahWebhookReceipt (reconciliation ledger) → StaahReservationService upserts Reservation (idempotent on tenant_id + channel='staah' + external_ref). Debug from the ledger: integrationApi / StaahController@receipts shows every raw payload received.

6.12.5 Realtime round trip (Reverb/Echo):

Staff sends a message → MessagesPage.vue → conversationApi.send → ConversationController@send → MessageSent::broadcast → Reverb → Echo.private('conversation.{id}').listen('.message.sent') in the SPA → stores/messages.js updates the thread. Channel auth goes through POST /broadcasting/auth (Bearer). If realtime stops: check VITE_REVERB_* env, Reverb service, broadcasting/auth responses (403 = bad channel auth).

6.13 Functionality catalog — one logic loop per feature

Every feature in the app is one loop: UI → api group → route → middleware → controller → service → model → side effects → response → UI . The catalog below gives the exact chain for each feature so you can jump straight to the files that own it. Arrow syntax: → = call/return, ⇨ = side effect. Middleware is abbreviated — the full chain is auth:sanctum + tenant + throttle:api +

level:N + operate unless noted (§6.6). Routes live in `routes/api.php` ; API methods in `src/api/index.js` .

6.13.1 Authentication

Login (password) — `LoginPage.vue` → `authApi.login` → `POST /auth/login (throttle:auth)` → `AuthController@login` (validate → `Hash::check` → active/expiry/tenant checks → `createToken('api-token', [role])` → `AuditService::login`) ⇒ token+user in `sessionStorage` → `stores/auth.js` → router guard lets the dashboard load.

```

LoginPage.vue — authApi.login — src/api/axios.js (no token yet)
    |
    ▼
POST /api/v1/auth/login (throttle:auth)
    |
    ▼
AuthController@login
    ├── email/password invalid? —————→ 401
    ├── password expired? —————→ reset to default + 401 (password_rotated)
    ├── user disabled or tenant inactive? —→ 403
    └─ ok —→ createToken('api-token', [role]) + AuditService::login
        |
        ▼
{ token, user } → sessionStorage → stores/auth.js → router guard passes → dashboard

```

Login (PIN) — same page → `authApi.loginPin` → `POST /auth/login-pin (throttle:auth)` → `AuthController@loginPin` (`identifier` + 4-digit `pin` , `Hash::check` against `login_pin`) → identical response shape → identical UI path.

```

LoginPage.vue — authApi.loginPin
    |
    ▼
POST /api/v1/auth/login-pin (throttle:auth)
    |
    ▼
AuthController@loginPin (identifier = email | registration_number, pin = digits:4)
    ├── unknown identifier / PIN unset / PIN wrong? —→ generic 401 (no user enumeration)
    ├── gates (account active, tenant active)? —→ 403
    └─ ok —→ createToken('api-token', [role]) + AuditService + last_login
        |
        ▼
{ token, user } → identical UI path as password login

```

Logout — header → `authApi.logout` → `POST /auth/logout` → `AuthController@logout` (deletes the current token) → interceptor clears `sessionStorage` → back to `/login` .

```

header button — authApi.logout
    |
    ▼
POST /api/v1/auth/logout
    |
    ▼
AuthController@logout → deletes the current Sanctum token
    |
    ▼
axios.js 401/response interceptor clears sessionStorage → router → /login

```

Change password / profile — ProfilePage.vue → authApi.changePassword / updateProfile → POST /auth/change-password / POST /auth/update-profile → AuthController@changePassword (Hash::check current) / updateProfile → UserResource → store refreshes user .

```

ProfilePage.vue
├─ authApi.changePassword → POST /auth/change-password →
AuthController@changePassword
│   │   └─ Hash::check(current) fails? → 422 error toast
│   │   └─ ok → save hashed new password
└─ authApi.updateProfile → POST /auth/update-profile → AuthController@updateProfile
    │   └─ ok → UserResource
    │           │
    │           ▼
    │           store refreshes `user` → ProfilePage re-renders + toast (i18n)

```

6.13.2 Public portal (no auth — throttle:public)

Hotel directory & availability — BookingPage.vue /home → publicApi.hotels / hotelShow / availability → GET /public/hotels[/{id}] / GET /public/availability → PublicController@hotels|hotelShow|availability (sets TenantContext from the selected hotel) → ReservationService::availableRooms → RoomResource / TenantResource → room picker renders with live prices.

```


home / BookingPage.vue — publicApi.hotels | hotelShow | availability
    |
    ▼
GET /api/v1/public/hotels[/{id}] | GET /api/v1/public/availability (throttle:public, no
auth)
    |
    ▼
PublicController@hotels|hotelShow|availability → sets TenantContext for the chosen hotel
    |
    ▼
ReservationService::availableRooms
    │   └─ room has overlapping active reservation? → excluded from the picker
    │   └─ free → RoomResource (status, price)
    │           │
    │           ▼
    │           TenantResource / RoomResource → room picker renders with live prices

```


Public booking → confirmation SMS — BookingPage.vue → publicApi.reservations → POST / public/reservations → PublicController@storeReservation → ReservationService::create(online:

true) (no local availability check — public page only offers free rooms) ⇒

`SmsService::sendForEvent('booking_confirmed')` → `AfricaTalkingSmsDriver` (if funded+enabled) → `GuestMessage` row + `GuestMessagePosted` broadcast ⇒ `booking_reference` returned; guest gets the invoice link too.



Booking requisition + status check — RequisitionPage.vue → publicApi.bookingRequisition / bookingStatus → POST /public/booking-requisitions → PublicController@storeBookingRequisition (unconfirmed guests, no room yet) → BookingRequisition (pending) → guest polls GET /public/booking-requisitions/status?ref&phone .



Self-service invoice download — `BookingPage.vue` (guest area) → `publicApi.invoiceDownload` → `GET /public/invoices/download?booking_reference&phone` → `PublicController@invoiceDownload` (reference+phone verified server-side) → `InvoiceService::pdf` → PDF blob → browser download. No token needed.

```

BookingPage.vue (guest area) — publicApi.invoiceDownload
  |
  ▼
GET /api/v1/public/invoices/download?booking_reference=...&phone=... (throttle:public, no
auth)
  |
  ▼
PublicController@invoiceDownload
  ├── reference + phone don't match an invoice? → 404
  └── ok → InvoiceService::pdf (dompdf, tenant branding)
      |
      ▼
PDF blob → axios saveBlob → browser download (no token involved)

```

ClickPesa from the portal — `PaymentPage.vue` → `publicApi.initiatePayment` → `POST /public/payments/initiate` → `PublicController@initiatePayment` → `PaymentService::initiatePublicPayment` → checkout reference; guest pays on the ClickPesa page and the callback (§6.13.9) reconciles it.

```

PaymentPage.vue — publicApi.initiatePayment
  |
  ▼
POST /api/v1/public/payments/initiate (throttle:public, no auth)
  |
  ▼
PublicController@initiatePayment → PaymentService::initiatePublicPayment
  |
  ▼
Payment created (awaiting_confirmation) + ClickPesa checkout reference returned
  |
  ▼
guest pays on the ClickPesa page (external) → ClickPesa callback reconciles
  |
  ▼
booking_status / payment status updates via §6.13.9 callback loop

```

6.13.3 Superadmin & owner

Tenant lifecycle — `TenantsPage.vue` → `tenantApi.approve|reject|suspend|reactivate|updateSubscription|uploadBranding` → `POST/PUT /tenants/{id}/...` → `TenantController@...` → `Tenant` (status/subscription/branding stamped) → `AuditService` → `TenantResource` → list refreshes. New tenant: `tenantApi.store` → `POST /tenants` → `TenantController@store` (creates `Tenant` + seeded admin user, `registration_number`).

```

TenantsPage.vue — tenantApi.store → POST /api/v1/tenants → TenantController@store
                                     (superadmin only, '*')
    |
    ▼
Tenant + seeded admin user + registration_number created (status: pending)
    |
    ▼
approve | reject | suspend | reactivate | updateSubscription | uploadBranding
    |
    ▼
POST/PUT /api/v1/tenants/{id}/... → TenantController@...
    |
    ▼
Tenant status/subscription/branding stamped + AuditService
    |
    ▼
TenantResource → list refreshes

```

Owners — OwnersPage.vue → tenantApi.owners|createOwner → GET/POST /owners → TenantController@owners|storeOwner → User (owner role) → list refreshes.

```

OwnersPage.vue
├─ tenantApi.owners → GET /owners → TenantController@owners → User list (owner
role)
└─ tenantApi.createOwner → POST /api/v1/owners → TenantController@storeOwner
                        |
                        ▼
                    User created with owner role → list refreshes

```

Owner dashboard — OwnerDashboardPage.vue → ownerApi.dashboard|hotels|hotel → GET / owner/... → OwnerController@dashboard|hotels|hotel (aggregates only the owner's tenants) → KPIs render.

```

OwnerDashboardPage.vue
├─ ownerApi.dashboard → GET /api/v1/owner/dashboard ┌─┐
├─ ownerApi.hotels   → GET /api/v1/owner/hotels      └─┐ → OwnerController@...
└─ ownerApi.hotel    → GET /api/v1/owner/hotel/{id} └─┘
    |
    ▼
aggregates ONLY the tenants this owner owns
    |
    ▼
KPIs render on the dashboard

```

6.13.4 Reports & accounting

Dashboard/operational reports — DashboardPage.vue → reportApi.dashboard|overview| occupancy|revenue|roomStatus|auditLogs → GET /reports/... → ReportController@... (aggregates across Reservation / Payment / Room / AuditLog under the tenant scope) → JSON aggregates → charts. No service layer — the controller + model scopes do the work.

```

DashboardPage.vue — reportApi.dashboard|overview|occupancy|revenue|roomStatus|auditLogs
    |
    ▼
GET /api/v1/reports/... (tenant scope via TenantContext)
    |
    ▼
ReportController@... → model scopes aggregate
    Reservation / Payment / Room / AuditLog
    |
    ▼
JSON aggregates → charts (no service layer – controller + scopes only)

```

Accounting reports — AccountingPage.vue → accountingApi.generalLedger|trialBalance|balanceSheet → GET /accounting/... → AccountingController@... (pivots Payment / Order / FunGameOrder / LaundryOrder / PurchaseOrder / Reservation.room_charges into ledger rows) → tables.

```

AccountingPage.vue — accountingApi.generalLedger|trialBalance|balanceSheet
    |
    ▼
GET /api/v1/accounting/... (tenant scope)
    |
    ▼
AccountingController@...
    └─ pivots Payment / Order / FunGameOrder / LaundryOrder / PurchaseOrder /
        Reservation.room_charges → ledger rows
    |
    ▼
tables render (GL / trial balance / balance sheet)

```

Day close / night audit — DayClosePage.vue → accountingApi.dayCloseReport → GET /accounting/day-close (computes on the fly) → then accountingApi.storeDayClose → POST /accounting/day-close → AccountingController@storeDayClose (freezes a DayClose snapshot; 409 if that date is already closed) → accountingApi.dayCloses → GET /accounting/day-closes lists frozen days.

```

DayClosePage.vue
├─ accountingApi.dayCloseReport → GET /accounting/day-close → computed on the fly (preview)
├─ storeDayClose → POST /accounting/day-close → AccountingController@storeDayClose
│   └─ date already closed? → 409 conflict
│       └─ ok → DayClose snapshot frozen
└─ accountingApi.dayCloses → GET /api/v1/accounting/day-closes → lists frozen days

```

6.13.5 Staff users

CRUD + lifecycle — UsersPage.vue → userApi.index|store|show|update|destroy → /users... → UserController@... → User (tenant-scoped) → AuditService → UserResource . Lifecycle extras: activate (POST /users/{id}/activate , flips is_active), invite (POST ../invite → StaffInvitation + email), resetPassword (POST ../reset-password → new token via

StaffInvitation), setPin (POST .../set-pin , admin/manager only, sets login_pin), attach / removeAttachment (POST .../attachments , multipart → StaffAttachment).

```

UsersPage.vue — userApi.index|store|show|update|destroy
    |
    ▼
GET/POST/PUT/DELETE /api/v1/users...
    |
    ▼
UserController@... (tenant-scoped User) → AuditService
    |
    ▼
UserResource → list / form updates

```

```

lifecycle extras (UsersPage.vue → userApi.*)
  activate      POST /users/{id}/activate      → flips is_active
  invite        POST /users/{id}/invite         → StaffInvitation + email
  resetPassword POST /users/{id}/reset-password → new token via StaffInvitation
  setPin        POST /users/{id}/set-pin        → admin/manager only, sets login_pin
  attach/remove POST /users/{id}/attachments   → multipart → StaffAttachment

```

6.13.6 Issue reports

IssuesPage.vue → issueReportApi.index|store|comment|respond → GET/POST /issue-reports[{id}/comments/{id}/respond] → IssueReportController@... → IssueReport + IssueReportComment (thread) → AuditService on respond → IssueReportResource → thread updates.

```

IssuesPage.vue
  |— issueReportApi.store —→ POST /issue-reports —→ IssueReport created
  |— issueReportApi.comment —→ POST /issue-reports/{id}/comments —→ IssueReportComment
  added
    |— issueReportApi.respond —→ POST /issue-reports/{id}/respond —→ status updated +
    AuditService
      |
      ▼
IssueReportResource → thread updates in place

```

6.13.7 Rooms & guests

Rooms — RoomsPage.vue → roomApi.index|store|update|destroy → /rooms... → RoomController@CRUD → Room. **Status flip** — roomApi.updateStatus → POST /rooms/{id}/status → RoomController@updateStatus → ReservationService::refreshRoomStatus -style guard (keeps dirty/clean/out_of_service consistent with bookings) → RoomResource .

```

RoomsPage.vue — roomApi.index|store|update|destroy
    |
    ▼
GET/POST/PUT/DELETE /api/v1/rooms... → RoomController@CRUD → Room

```

```

RoomsPage.vue — roomApi.updateStatus → POST /api/v1/rooms/{id}/status
|
▼
RoomController@updateStatus → ReservationService::refreshRoomStatus-style guard
(keeps dirty / clean / out_of_service consistent with active bookings)
|
▼
RoomResource → status badge updates

```

Guests — `GuestsPage.vue` → `guestApi.index|store|update|destroy` → `/guests...` → `GuestController@CRUD` → `Guest`. **Returning-guest lookup** — `guestApi.lookup(search)` → `GET /guests/lookup` → `GuestController@lookup` (searches across all tenants by phone/name — no tenant scope, deliberate) → pick a row to prefill a new booking.

```

GuestsPage.vue
├─ index|store|update|destroy → /guests... → GuestController@CRUD → Guest
└─ guestApi.lookup(search) → GET /api/v1/guests/lookup
                                |
                                ▼
                        GuestController@lookup
                (cross-tenant by phone/name – no tenant scope, deliberate)
                                |
                                ▼
                        pick a row → prefills a new booking form

```

6.13.8 Reservations (the heart)

Create (desk/walk-in) — `ReservationListPage.vue` → `reservationApi.store` → `POST /reservations` (`level:60` + `operate`) → `ReservationController@store` → `ReservationService::create` (`isRoomAvailable` / `overlappingReservations` guard, `nights` / `roomTotal` pricing, saves `Reservation` with `booking_reference` from `NumberGenerator`) ⇒ `AuditService::created` + room set dirty if needed → `ReservationResource` → list appends.

```

ReservationListPage.vue — reservationApi.store
|
▼
POST /api/v1/reservations (auth:sanctum + tenant + throttle:api + level:60 + operate)
|
▼
ReservationController@store → ReservationService::create (DB::transaction)
|
├─ room overlaps an active reservation in that window? → 422
├─ price: nights = date diff, roomTotal = nights × room price
└─ ok → Reservation saved (status confirmed, booking_reference = NumberGenerator)
|
▼
AuditService::created + room set dirty if needed
|
▼
ReservationResource → list appends

```

Check-in — `reservationApi.checkIn` → `POST /reservations/{id}/check-in` → `ReservationController@checkIn` → `ReservationService::checkIn` (status confirmed → `checked_in` ,

room available → occupied) ⇒ SMS sendForEvent('checkin') (if enabled) → ReservationResource .

```

ReservationListPage.vue — reservationApi.checkIn
    |
    ▼
    POST /api/v1/reservations/{id}/check-in
    |
    ▼
    ReservationController@checkIn → ReservationService::checkIn (DB::transaction)
    |— reservation not in a confirmable state? → 422
    |— ok → status confirmed→checked_in, room available→occupied
    |
    ▼
    SmsService::sendForEvent('checkin') (if enabled + funded)
    |
    ▼
    ReservationResource → badge updates to checked_in
  
```

Check-out — reservationApi.checkOut → POST /reservations/{id}/check-out → ReservationController@checkOut → ReservationService::checkOut (finalises folio: balanceDue , room → dirty, release occupancy) ⇒ SmsService::sendForEvent('checkout') ; **auto-queues housekeeping + laundry** for the room (checked-in booking → HousekeepingTask + LaundryOrder created) ⇒ AuditService . Returns final folio totals.

```

ReservationListPage.vue — reservationApi.checkOut
    |
    ▼
    POST /api/v1/reservations/{id}/check-out
    |
    ▼
    ReservationController@checkOut → ReservationService::checkOut (DB::transaction)
    |— finalise folio: balanceDue computed
    |— status → checked_out, room → dirty, occupancy released
    |— SmsService::sendForEvent('checkout') (if enabled + funded)
    |— auto-queue per room:
    |   |— createCheckoutCleaningTask → HousekeepingTask (dirty)
    |   |— createLinenWashOrder → LaundryOrder
    |
    ▼
    AuditService → final folio totals returned to the UI
  
```

No-show / cancel / destroy — reservationApi.noShow|cancel|destroy → POST /reservations/{id}/no-show / .../cancel / DELETE /reservations/{id} → ReservationController@noShow|cancel|destroy → ReservationService::noShow (status→no_show , room released) / cancel (status→cancelled) / destroy (hard delete with reason) → audit + room status refresh → UI refresh.

```

ReservationListPage.vue
├─ noShow → POST /reservations/{id}/no-show → status-no_show, room freed
├─ reservationApi.cancel → POST /reservations/{id}/cancel → cancel:
status→cancelled
├─ reservationApi.destroy → DELETE /reservations/{id} → destroy: hard delete +
reason
    │
    ▼
audit + room status refresh
    │
    ▼
UI list refreshes

```

6.13.9 Payments (incl. ClickPesa)

Record / confirm / reject / refund — `PaymentsPage.vue` → `paymentApi.store|confirm|reject|refund` → `POST /payments` / `POST /payments/{id}/confirm|reject|refund` → `PaymentController@...` → `PaymentService` : `record` (desk capture) / `confirm` (receptionist verifies a guest-pushed mobile-money transfer ⇒ `SmsService::sendForPayment('payment_received')` , `creditReservation` advances) / `reject` (reason stored) / `refund` (reverses, sets `refunded`) → `AuditService` → `PaymentResource` .

```

PaymentsPage.vue
├─ paymentApi.store → POST /payments → record: desk capture
├─ paymentApi.confirm → POST /payments/{id}/confirm → verify mobile-money transfer
│   └─ ok → SmsService::sendForPayment('payment_received') + creditReservation
advances
│   └─ bad → reject (reason stored)
├─ paymentApi.reject → POST /payments/{id}/reject → reason stored
├─ paymentApi.refund → POST /payments/{id}/refund → reverses, sets refunded
    │
    ▼
AuditService → PaymentResource → list updates

```

ClickPesa flow — desk or portal calls `paymentApi.clickPesaInitiate` → `POST /payments/clickpesa/initiate` → `PaymentController@clickPesaInitiate` → `PaymentService::clickPesaInitiate` (creates `Payment` `awaiting_confirmation` + checkout ref) → guest pays on ClickPesa → ClickPesa server calls `POST /payments/clickpesa/callback` (`throttle:webhook` , no tenant) → `PaymentController@clickPesaCallback` → `PaymentService::handleClickPesaCallback` (verifies status, flips to `completed` , `creditReservation` , logs receipt) → hotel sees the payment in the list.

```

desk / portal — paymentApi.clickPesaInitiate
    |
    ▼
POST /api/v1/payments/clickpesa/initiate → PaymentService::clickPesaInitiate
    |
    ▼
Payment created (awaiting_confirmation) + checkout reference
    |
    ▼
guest pays on the ClickPesa page (external)
    |
    ▼
ClickPesa server → POST /api/v1/payments/clickpesa/callback (throttle:webhook, no
tenant)
    |
    ▼
PaymentService::handleClickPesaCallback
    ├── status not paid/failed? → leave awaiting_confirmation / mark failed
    └── ok → Payment → completed, creditReservation, receipt logged
    |
    ▼
hotel sees the payment in the list (list refreshes)

```

6.13.10 Invoices

InvoicesPage.vue → invoiceApi.generate(reservationId) → POST /reservations/{id}/invoice → InvoiceController@generate → InvoiceService::generateForReservation (dompdf, tenant branding/signature/stamp from tenantApi.uploadBranding) → Invoice → invoiceApi.download → GET /invoices/{id}/download → PDF blob → save. Hotel context: same resource; tenant owns branding files.

```

InvoicesPage.vue
  ├── invoiceApi.generate → POST /api/v1/reservations/{id}/invoice
  │   └── InvoiceService::generateForReservation (dompdf + tenant branding/signature/
stamp)
  │   └── Invoice row created
  └── invoiceApi.download → GET /api/v1/invoices/{id}/download
      └── PDF blob → browser download (saveBlob)

```

6.13.11 Housekeeping

Workflow — HousekeepingPage.vue → housekeepingApi.store|assign|start|confirm|verify|complete → POST /housekeeping-tasks[/{id}/assign|/start|/confirm|/verify|/complete] → HousekeepingController@... : store (creates dirty) → assign (needs dirty|in_progress, sets assignee, → in_progress) → start (self-assign, → in_progress) → confirm (level:80, → confirmed) → verify (sub-manager or level:80, → verified, and if room.status=dirty releases it → available) → complete (→ completed). Every step → AuditService. Index is ordered urgent > high > normal > low.

```
HousekeepingPage.vue
  store → POST /housekeeping-tasks → task created (dirty)
  assign → POST ../{id}/assign → requires dirty|in_progress, assignee set → in_progress
  start → POST ../{id}/start → self-assign → in_progress
  confirm → POST ../{id}/confirm → level:80 → confirmed
  verify → POST ../{id}/verify → sub-manager or level:80 → verified
    └─ room.status = dirty? → released → available
  complete → POST ../{id}/complete → completed
    |
    ▼
every step: AuditService · index ordered urgent > high > normal > low
```

6.13.12 Inventory, suppliers & F&B

Inventory — InventoryPage.vue → inventoryApi.index|store|update|destroy → /inventory... → InventoryController@CRUD → InventoryItem . **Adjust** → inventoryApi.adjust → POST /inventory/{id}/adjust → InventoryController@adjust → InventoryService::adjustStock (quantity in/out) ⇒ StockMovement row → inventoryApi.movements → GET /inventory/{id}/movements renders history.

```
InventoryPage.vue
├─ CRUD → /inventory... → InventoryController@CRUD → InventoryItem
└─ inventoryApi.adjust → POST /api/v1/inventory/{id}/adjust
    |
    ▼
InventoryService::adjustStock (quantity in/out) ⇒ StockMovement row
    |
    ▼
inventoryApi.movements → GET /api/v1/inventory/{id}/movements → history renders
```

Suppliers — SuppliersPage.vue → supplierApi.CRUD → /suppliers... → SupplierController → Supplier .

```
SuppliersPage.vue — supplierApi.index|store|update|destroy
    |
    ▼
/api/v1/suppliers... → SupplierController → Supplier (tenant-scoped) → list refreshes
```

Menu items — MenuPage.vue → menuItemApi.CRUD → /menu-items... → MenuItemController → MenuItem .

```
MenuPage.vue — menuItemApi.index|store|update|destroy
    |
    ▼
/api/v1/menu-items... → MenuItemController → MenuItem → menu refreshes
```

F&B order — OrderPage.vue → orderApi.formOptions (GET /orders/form-options ; in-house guests + serving staff) then orderApi.store → POST /orders → OrderController@store (items attached, total_amount recomputed) → Order . **Kitchen** — orderApi.markItemStatus → PATCH /orders/{id}/items/{itemId}/status → OrderController@markItemStatus (per-line preparing/ready/served , order status untouched). **Settle** — orderApi.pay → POST /orders/{id}/pay → OrderController@pay (→ paid / completed) ⇒ PaymentService::record . **Bill to room** →

`orderApi.billToRoom` → `POST /orders/{id}/bill-to-room` → `OrderController@billToRoom`
 (transaction: links order to the room's active `confirmed|checked_in` reservation and `Reservation->increment('room_charges')`) → folio total returns. No active booking ⇒ 422.

```
OrderPage.vue
├─ formOptions → GET /orders/form-options → in-house guests + serving staff options
├─ store → POST /orders → items attached, total_amount recomputed → Order
├─ markItemStatus → PATCH ../{id}/items/{itemId}/status → line preparing/ready/served
├─ pay → POST /orders/{id}/pay → paid/completed ⇒ PaymentService::record
└─ billToRoom → POST /orders/{id}/bill-to-room
    └─ room has an active confirmed|checked_in reservation? → no → 422
        └─ ok → transaction: link order to reservation,
            Reservation->increment('room_charges') → folio total returns
```

6.13.13 Laundry

`LaundryPage.vue` → `laundryApi.CRUD` → `/laundry-orders...` → `LaundryOrderController` → `LaundryOrder` + `LaundryOrderItem`. Note: on **check-out** `ReservationService` auto-creates one per room (§6.13.8).

```
LaundryPage.vue — laundryApi.index|store|update|destroy
├─
├─ /api/v1/laundry-orders... → LaundryOrderController → LaundryOrder + LaundryOrderItem
├─
└─ list refreshes · (check-out also auto-creates one per room, see §6.13.8)
```

6.13.14 Fun games

`FunGamesPage.vue` → `funGameApi.CRUD` → `/fun-games...` → `FunGameOrderController` → `FunGameOrder` (guest activity/merch sales).

```
FunGamesPage.vue — funGameApi.index|store|update|destroy
├─
├─ /fun-games... → FunGameOrderController → FunGameOrder (activity/merch sales) → list refreshes
```

6.13.15 Procurement

Requisition — `RequisitionsPage.vue` → `purchaseRequisitionApi.store` → `POST /purchase-requisitions` → `PurchaseRequisitionController@store` (`pending`) → `approve|reject|cancel` (`POST ../{id}/approve|reject|cancel`) → `PurchaseRequisitionController@...` → status moved (`approved` / `rejected` / `cancelled`) + `AuditService`.

```

RequisitionsPage.vue — purchaseRequisitionApi.store → POST /purchase-requisitions
|
▼
PurchaseRequisition created (status: pending)
|
▼
approve | reject | cancel → POST /purchase-requisitions/{id}/...
|
▼
status → approved | rejected | cancelled + AuditService → list refreshes

```

Purchase order (two-level approval) — PurchaseOrdersPage.vue → purchaseOrderApi.store → POST /purchase-orders (pending) → approve (POST ../approve → approved) → managerApprove (POST ../manager-approve → manager_approved) → cancel → cancelled . Order can only move to receiving after the second approval.

```

PurchaseOrdersPage.vue — purchaseOrderApi.store → POST /purchase-orders
|
▼
PurchaseOrder created (status: pending)
|
▼
approve → POST /purchase-orders/{id}/approve → approved (first-level)
|
▼
managerApprove → POST /purchase-orders/{id}/manager-approve → manager_approved (second-level)
|
▼
only manager_approved orders may move to receiving (GRN, $6.13.15) · cancel → cancelled

```

Goods receipt → stock — GoodsReceivedPage.vue → goodsReceivedNoteApi.store → POST /goods-received-notes → GoodsReceivedNoteController@store (per-line passed/failed/partial) ⇒ InventoryService upserts InventoryItem (quantity_in_stock += received, unit/unit_cost from the PO line) and flips the PO to received / partially_received → GRN shown.

```

GoodsReceivedPage.vue — goodsReceivedNoteApi.store → POST /goods-received-notes
|
▼
GoodsReceivedNoteController@store (per-line passed / failed / partial)
|
▼
InventoryService upserts InventoryItem:
  quantity_in_stock += received · unit / unit_cost from the PO line
|
▼
PO status → received | partially_received
|
▼
GRN shown

```

6.13.16 Booking requisitions (hotel side)

BookingRequisitionsPage.vue → bookingRequisitionApi.index|respond|destroy → GET/POST/DELETE /booking-requisitions[{id}/respond] → BookingRequisitionController@respond (accept → may hand over to ReservationService::create ; decline → reason) → list refreshes.

```
BookingRequisitionsPage.vue
├─ index → GET /booking-requisitions
├─ respond → POST /booking-requisitions/{id}/respond
│   └─ accept → may hand over to ReservationService::create (confirmed booking)
│       └─ decline → reason stored
└─ destroy → DELETE /booking-requisitions/{id}
    │
    ▼
list refreshes
```

6.13.17 Attendance (anti-cheat)

Clock-in — ClockPage.vue → attendanceApi.requirements (GET /attendance/requirements , tells the UI whether geofence/QR are required) then attendanceApi.clockIn → POST /attendance/clock-in (throttle:attendance) → StaffAttendanceController@clockIn → AttendanceService::evaluateClockIn (device resolve/bind via resolveDevice , geofence withinGeofence , optional consumeQrToken , photo + hash storeClockInPhoto , detectSuspicion incl. impliesTeleport using distanceMeters) → StaffAttendance (on_time / late via lateMinutes) → suspicious flags set (AttendancePenalty when policy breached) → StaffAttendanceResource .

```
ClockPage.vue
├─ requirements → GET /attendance/requirements → UI learns: geofence? QR? both?
└─ attendanceApi.clockIn → POST /api/v1/attendance/clock-in
(throttle:attendance)
    │
    ▼
StaffAttendanceController@clockIn → AttendanceService::evaluateClockIn
├─ device unknown? → resolveDevice (bind device_id + fingerprint [+ secret])
├─ geofence required and outside? → clock-in rejected
├─ QR required? → consumeQrToken (rotating, single-use)
├─ photo? → storeClockInPhoto (photo + hash)
└─ detectSuspicion (impliesTeleport via distanceMeters) → flags / AttendancePenalty
    │
    ▼
StaffAttendance: on_time | late (lateMinutes) → StaffAttendanceResource
```

Clock-out — same page → attendanceApi.clockOut → POST /attendance/clock-out → evaluateClockOut → record closed (early-leave checks).

```
ClockPage.vue — attendanceApi.clockOut
    │
    ▼
POST /api/v1/attendance/clock-out → AttendanceService::evaluateClockOut
    │
    ▼
record closed (early-leave checks) → attendance record finalised
```

Entrance QR — manager → `attendanceApi.qrToken` → `POST /attendance/qr-token` → `AttendanceService::issueQrToken` (rotating token, expires) → token displayed; consumed once at clock-in.

```

manager — attendanceApi.qrToken → POST /api/v1/attendance/qr-token
      |
      ▼
AttendanceService::issueQrToken (rotating token, expires)
      |
      ▼
token displayed at the entrance → consumed exactly once at clock-in

```

Devices — `attendanceApi.registerDevice|myDevices|attendanceDevices|revokeDevice` → `/attendance/devices...` → `AttendanceService::registerDevice|resolveDevice` (device_id + fingerprint + optional secret) → `AttendanceDevice` → revoke disables. **Suspicious list** → `attendanceApi.suspicious` → `GET /attendance/suspicious` → flagged records.

```

staff / manager
  registerDevice → POST /attendance/devices → AttendanceService::registerDevice
                (device_id + fingerprint + optional secret) → AttendanceDevice
  myDevices → GET /attendance/devices/mine
  attendanceDevices → GET /attendance/devices (manager)
  revokeDevice → POST /attendance/devices/{id}/revoke → disables the device
  suspicious → GET /attendance/suspicious → flagged records

```

Absences — `attendanceApi.reportAbsence` → `POST /attendance/absences` (multipart: type, reason, dates, location, device, attachments) → `evaluateAbsenceRequest` + `storeAbsenceAttachment` → `AttendanceAbsenceRequest` (pending) → manager `decideAbsenceRequest` (`POST .../absences/{id}/decide` , approve/reject) → `reconcileAbsencePenalties` (penalties removed/kept) → status + audit.

```

staff — attendanceApi.reportAbsence → POST /api/v1/attendance/absences (multipart)
      |
      ▼
AttendanceService: evaluateAbsenceRequest + storeAbsenceAttachment
      |
      ▼
AttendanceAbsenceRequest created (status: pending)
      |
      ▼
manager — attendanceApi.decideAbsenceRequest → POST .../absences/{id}/decide
      |   ├── approve → reconcileAbsencePenalties (penalties removed/kept)
      |   └── reject  → status rejected
      |
      ▼
status + audit → absence list refreshes

```

6.13.18 Messaging (all `throttle:messaging` unless noted)

1:1 conversation — `MessagesPage.vue` → `conversationApi.store|messages|send` → `POST/GET /messages/conversations[{id}]/messages` → `ConversationController@store|messages|send` → `Conversation` + `ConversationMessage` ⇒ `MessageSent` broadcast → `Reverb` → `Echo.private('conversation.{id}').listen('.message.sent')` → store appends. **Read** → `markRead`

→ `POST .../conversations/{id}/read` → read receipt + `MessageRead` broadcast. **Unread badge** → `unreadCount` → `GET /messages/unread-count`.

```
MessagesPage.vue
├─ conversationApi.send → POST /messages/conversations/{id}/messages]
(throttle:messaging)
├─
├─ ConversationController@send → ConversationMessage saved
├─
├─ MessageSent → Echo.private('conversation.{id}').listen('.message.sent') → store
appends
├─ markRead → POST .../conversations/{id}/read → read receipt + MessageRead
broadcast
├─ unreadCount → GET /messages/unread-count → badge in the sidebar
```

Groups — `groupApi.store|addMembers|removeMember|send|markRead` → `/messages/groups...` → `GroupConversationController@...` → `GroupConversation` + `GroupConversationMember` + `GroupConversationMessage` ⇒ `GroupMessageSent` broadcast → `Echo.private('group.{id}')`.

```
MessagesPage.vue — groupApi.store|addMembers|removeMember|send|markRead
├─
├─ POST/GET /messages/groups... → GroupConversationController@...
├─
├─ GroupConversation + GroupConversationMember + GroupConversationMessage
├─
├─ GroupMessageSent broadcast → Reverb → Echo.private('group.{id}') → members' UIs
update live
```

Message actions — `messageActionApi.deleteConversationMessage|deleteGroupMessage` (scope everyone|me) → `POST .../messages/{id}/delete` → `MessageActionController@delete` (scope enforcement) ⇒ `MessageDeleted` broadcast; `openViewOnce|openGroupViewOnce` → `POST .../view-once` → one-time content served then flagged; `toggleReaction` → `POST /messages/reactions` → `MessageReaction` upsert ⇒ broadcast.

```
MessagesPage.vue
├─ delete (scope everyone | me) → POST .../messages/{id}/delete
├─
├─ MessageActionController@delete — scope enforced → MessageDeleted broadcast
├─ openViewOnce → POST .../view-once → one-time content served, then flagged
├─ toggleReaction → POST /messages/reactions → MessageReaction upsert ⇒ broadcast
```

Disappearing messages — `composer toggle ( fa-hourglass-half : Off → 1h → 1d → 7d)` → `disappears_in (3600 | 86400 | 604800)` sent with the message → `ConversationController@send / GroupConversationController@send` stamp `disappears_at` → resource exposes it → bubble shows a live countdown (`expireDisappearing` ticks every second, removing the message locally at 0). Authoritative cleanup: `messaging:purge-disappeared` (every minute) soft-deletes due rows (`deleted_by = 'disappearance'`) and broadcasts `message.disappeared` →

`Echo.listen('.message.disappeared')` → `removeMessageLocally`. Rows stay recoverable, like other deletions.

```

MessagesPage.vue — composer toggle → disappears_in (1h|1d|7d)
|
▼
send (conversation|group) → Controller@send → disappears_at = now + disappears_in
|
|→ bubble shows      countdown (1s tick) → at 0: removeMessageLocally
|
▼
messaging:purge-disappeared (every minute)
|
|— where disappears_at <= now() and deleted_at is null
|
▼
MessageDisappeared broadcast → Echo.listen('.message.disappeared') →
removeMessageLocally
|
▼
soft delete (deleted_by = 'disappearance', deleted_for = ['*'])

```

Statuses — `statusApi.store|view|react|destroy` → `/statuses...` → `StatusController@post|view|like` → `Status` + `StatusView` + `StatusReaction` ⇒ `StatusPosted` broadcast.

Online status / presence — every authenticated user joins the **global** presence channel `presence-online.all` via `echo.join('online.all')`, and tenant members additionally join their hotel's channel `presence-online.{tenant_id}` via `echo.join('online.{id}')` (wired globally in `StoreLayout`; the socket lives for the whole session, so the indicator survives navigation between pages). Reverb streams the member list to all peers: `here` seeds the set on subscribe, `joining` / `leaving` keep it current — no polling, no app event. The `online.all` callback in `routes/channels.php` admits every authenticated user and publishes `user_id`, `full_name`, `tenant_id` and `hotel_name` (so remote colleagues are distinguishable); `online.{tenantId}` admits only members of that tenant and publishes `user_id` + `full_name`. Consumers: green dot on direct-chat avatars, an `Online` badge in the thread header, the group-members panel, the "New message" search results (hotel and global scope) and the staff list's Online column (`usePresence.isOnline`).

```

StoreLayout — syncPresence (on auth / tenant_id) → initEcho()
|
▼
echo.join('online.all') → wire channel presence-online.all      (every user)
echo.join('online.{tenant_id}') → wire channel presence-online.{tenant_id} (tenant
members)
|
|— here(members) → (tenantOnline | globalOnline) = set of peer user_ids
|— joining(member) → add user_id
|— leaving(member) → delete user_id
|
▼
usePresence.isOnline(user_id) → avatars · thread header · group members · new-message
search · staff list
|
▼
logout / unmount → leavePresence() + destroyEcho()

```

Statuses — `statusApi.store|view|react|destroy` → `/statuses...` → `StatusController@post|view|like` →

```

MessagesPage.vue — statusApi.store|view|react|destroy
    |
    ▼
/api/v1/statuses... → StatusController@post|view|like
    |
    ▼
Status + StatusView + StatusReaction ⇒ StatusPosted broadcast → contacts' status rows
update

```

Features — `featuresApi.pin|unpin|star|unstar|pinned|starred` → `/messages/(pin|unpin|star|unstar|pinned|starred)` → `PinStarController` → `PinnedMessage / StarredMessage`; `vote` → `/messages/polls/vote` → `PollController@vote` → `PollVote` (guards double-vote); `search` → `GET /messages/search` → `SearchController` (SQL LIKE across conversation + group messages, tenant-scoped); `exportCsv` → `GET /messages/export` (blob); `translate` → `POST /messages/translate` → `TranslateController` → `TranslateService` (offline EN↔SW); `forward` → `POST /messages/forward` → `ForwardController` (copies into the target conversation/group).

```

MessagesPage.vue
  pin/unpin/star/unstar → /messages/(pin|unpin|star|unstar|...) → Pinned/
  StarredMessage
  vote → POST /messages/polls/vote → PollVote (double-vote guarded)
  search → GET /messages/search → SQL LIKE convs+groups (tenant-scoped)
  exportCsv → GET /messages/export → CSV blob download
  translate → POST /messages/translate → TranslateService (offline EN ↔
  SW)
  forward → POST /messages/forward → copy into target conversation/
  group

```

Templates — `templateApi.CRUD` → `/messages/templates...` → `MessageTemplateController` → `MessageTemplate`.

```

MessagesPage.vue — templateApi.index|store|update|destroy
    |
    ▼
/messages/templates... → MessageTemplateController → MessageTemplate → picker refreshes

```

Scheduled — `scheduledApi.store|index|destroy` → `/messages/scheduled...` → `ScheduledMessageController` → `ScheduledMessage` (delivered by `schedule:message` / queue when `send_at` fires).

```

MessagesPage.vue — scheduledApi.store|index|destroy
    |
    ▼
/api/v1/messages/scheduled... → ScheduledMessageController → ScheduledMessage (send_at)
    |
    ▼
when send_at fires: `schedule:message` command / queue → message delivered as normal send

```

Announcements — `announcementApi.store|index|acknowledge` → `/messages/announcements...` → `AnnouncementController@store|index|acknowledge` → `Announcement` + `AnnouncementAcknowledgement` (read-receipt per user) ⇒ broadcast to `tenant.{id}`.

```
MessagesPage.vue
├─ store ─────────→ POST /messages/announcements ─→ Announcement created
│
│               ▼
│               broadcast to tenant.{id} ─→ all staff see it live
├─ index ─────────→ GET  /messages/announcements
└─ acknowledge ─→ POST /messages/announcements/{id}/acknowledge
                  └─ AnnouncementAcknowledgement per user (read-receipt)
```

Escalations / handovers / preferences / retention / room links / task groups —

`escalationApi.store|resolve` → `EscalationController ( MessageEscalation )`; `handoverApi.store|acknowledge` → `ShiftHandoverController ( ShiftHandover )`; `preferenceApi.CRUd` → `NotificationPreferenceController ( NotificationPreference )`; `retentionApi.CRUd` → `RetentionPolicyController ( RetentionPolicy , sweep job deletes old messages )`; `roomLinkApi.store|destroy|searchRooms` → `RoomLinkController ( ConversationRoom ↔ Room )`; `taskGroupApi.store|convert` → `TaskGroupController ( message → TaskGroup )`.

```
MessagesPage.vue
  escalation ─→ /messages/escalations ─→ EscalationController ─→ MessageEscalation
  handover   ─→ /messages/handovers   ─→ ShiftHandoverController ─→ ShiftHandover
  preference ─→ /messages/preferences ─→ NotificationPreferenceController
  retention  ─→ /messages/retention  ─→ RetentionPolicyController (sweep deletes old
  messages)
  roomLink   ─→ /messages/room-links   ─→ RoomLinkController ─→ ConversationRoom ↔ Room
  taskGroup  ─→ /messages/task-groups  ─→ TaskGroupController ─→ message →
  TaskGroup
```

Location — `staffLocationApi.update|nearby` → `/messages/location` + `/messages/nearby` → `StaffLocationController` → `StaffLocation` ⇒ `StaffLocationUpdated` broadcast → staff map updates.

```
staff app ─ staffLocationApi.update ─→ POST /messages/location ─→ StaffLocation saved
      │
      ▼
StaffLocationUpdated broadcast ─→ staff map updates live
      │
      ▼
staffLocationApi.nearby ─→ GET /messages/nearby ─→ who's close by
```

Meetings — `meetingApi.store|respond|searchUsers` → `/messages/meetings...` → `MeetingController@store|respond` → `Meeting` + `MeetingInvitee` (accepted/declined) ⇒ broadcast invites.

```
MessagesPage.vue
├─ store ─────────→ POST /messages/meetings ─→ Meeting + MeetingInvitee rows
├─ searchUsers ─→ GET  /messages/meetings/users ─→ invitee picker
└─ respond ───→ POST /messages/meetings/{id}/respond ─→ accepted | declined
```

SOS — `sosApi.initiate|acknowledge|resolve` → `/messages/sos...` → `SosController@...` → `SosAlert` ⇒ `SosAlertInitiated` broadcast to `tenant.{id}` (all staff alerted) → `acknowledge/resolve` close it.

```

staff app — sosApi.initiate → POST /messages/sos → SosAlert created
      |
      ▼
SosAlertInitiated broadcast → tenant.{id} → ALL staff alerted (with location)
      |
      ▼
acknowledge | resolve → POST /messages/sos/{id}/... → alert closed

```

Calls (WebRTC) — `callApi.initiate` → `POST /calls` → `CallController@initiate` (`Call` ringing) ⇒ `CallInitiated` broadcast → `peer accept|decline` → `CallAccepted / CallDeclined` ; `signal` relays SDP/candidates; `end|cancel` close the `Call` + `CallEnded` broadcast.

```

MessagesPage.vue / useCallManager.js — callApi.initiate → POST /api/v1/calls
      |
      ▼
Call created (ringing) ⇒ CallInitiated broadcast → peer gets the incoming overlay
      |
      └─ peer accept → CallAccepted → WebRTC: signal relays SDP/candidates → live
call
      └─ peer decline → CallDeclined → call closed
      └─ end | cancel → call closed + CallEnded broadcast

```

Guest messages / guest SMS (one-way) — `guestMessageApi.store` → `POST /messages/guest-messages` → `GuestMessageController@store` → `SmsService::sendForEvent` → `GuestMessage` (`direction=outbound`) + `GuestMessagePosted` broadcast (in-room tablet shows it). Guests cannot reply (inbound route is disabled — §9). **Automation toggles** — `guestNotificationSettingsApi.index|update` → `GET/PUT /messages/guest-notification-settings` → `GuestNotificationSettingsController` → `GuestNotificationSetting` per event (`booking_confirmed` , `payment_received` , `reminder` , `checkout` , ...) — the on/off switches `SmsService::sendForEvent` consults.

```

staff app — guestMessageApi.store → POST /messages/guest-messages
      |
      ▼
GuestMessageController@store → SmsService::sendForEvent
      |
      └─ event toggle on + funded? → SMS sent (outbound)
          └─ GuestMessage (outbound) + GuestMessagePosted broadcast → in-room tablet shows
it
      |
      ▼
(guest cannot reply – inbound route disabled, §9)

automation toggles → GET/PUT /messages/guest-notification-settings
      └─ GuestNotificationSetting per event (booking_confirmed, reminder, checkout, ...)
          └─ on/off switches are what SmsService::sendForEvent consults

```

6.13.19 STAAH integration (backend-driven — no UI yet)

Availability/rates push — scheduler (`staah:push-availability`) → `StaahAriService::sync`
 (guardrail: `StaahWebhookReceipt` `outbound` `availability` `count` < 2000/day; 422 if not wired) →
 payload per mapped room type (`roomstosell` = rooms minus blocking reservations; rate = min
 nightly price; per-date objects) → `StaahClient::pushAvailability` (HTTP Basic) → TicketIds
 recorded. `bootstrap` pushes the full horizon on go-live; `StaahController@pull` reconciles back
 (`StaahAriService::pull`).

```

scheduler: staah:push-availability → StaahAriService::sync
    |
    |— outbound availability count today >= 2000/day guardrail? → skip (or 422 if not
wired)
    |— ok → build payload per mapped room type:
                roomstosell = rooms - blocking reservations · rate = min nightly price · per
date
    |
    |— StaahClient::pushAvailability (HTTP Basic) → TicketIds recorded in the receipts ledger
    |
    |— bootstrap pushes the full horizon on go-live · StaahController@pull reconciles back
  
```

Booking webhook (inbound) — STAAH → `POST /integrations/staah/reservations`
 (`throttle:webhook`) → `StaahWebhookController@reservations` (shared-secret via `hash_equals` ;
 payload → `StaahWebhookReceipt` ledger per booking) → `StaahReservationService::upsert`
 (idempotent on `tenant_id + channel='staah' + external_ref` ; Reserved→ confirmed ,
 Cancelled→ cancelled ; room resolved via `StaahMapping` then by type name) → per-booking
 success/failed response so STAAH retries failures.

```

STAAH → POST /api/v1/integrations/staah/reservations (throttle:webhook, no tenant)
    |
    |— StaahWebhookController@reservations
    |   |— shared secret mismatch? → 401
    |   |— ok → raw payload → StaahWebhookReceipt ledger (per booking)
    |   |
    |   |— StaahReservationService::upsert (idempotent on tenant_id + channel='staah' + external_ref)
    |       |— Reserved → Reservation → confirmed
    |       |— Cancelled → Reservation → cancelled
    |       |— room: resolve via StaahMapping, then fall back to room-type name
    |       |
    |       |— per-booking success/failed response → STAAH retries only the failures
  
```

Push-data ack — `POST /integrations/staah/push-data` → `StaahWebhookController@pushData` →
`StaahWebhookReceipt` (`event=push_data`) → STAAH-style `{type: success, trackingId}` .

```

STAAH → POST /api/v1/integrations/staah/push-data (throttle:webhook)
      |
      v
StaahWebhookController@pushData → StaahWebhookReceipt (event = push_data)
      |
      v
STAAH-style response { type: success, trackingId }

```

Settings/mappings — StaahController@settings|updateSettings|mappings CRUD|sync|pull| receipts → /integrations/staah/... → StaahSetting + StaahMapping (staah_room_id ↔ room_type) → the reconcile UI reads the receipts ledger (StaahWebhookReceipt).

```

Settings page → /api/v1/integrations/staah/...
settings → StaahController@settings / updateSettings → StaahSetting
mappings CRUD → StaahMapping (staah_room_id ↔ room_type)
sync / pull → force availability push / reconcile
receipts → GET ../receipts → reconcile UI reads the StaahWebhookReceipt ledger

```

6.14 Debugging runbook — when things crash

Symptom	Hop	Files to open first	What to check
All requests fail / CORS	1-2	src/api/axios.js , config/cors.php , .env	VITE_API_URL matches the API host; CORS allows the origin
401 everywhere	1-3	stores/auth.js , axios.js	Token present in sessionStorage? Expired? auth:sanctum passing?
403 on a specific feature	4	routes/api.php route, config/roles.php	The route's level:N / operate vs the user's role; tenant active?
404 on a route that exists	3	routes/api.php	Route ordering (static vs {id}); wrong method; {id} is a string?
422 on a form	5	the controller's validate()	Payload key names vs rule keys; 422 errors map
500	5-7	storage/logs/laravel.log	Stack trace URL + line; service exception
429	2	AppServiceProvider limiters	Which limiter (api / auth / public / messaging / attendance / webhook)
Data missing / cross-tenant	7	BelongsToTenant , TenantContext , SetTenantContext	X-Tenant-ID header; TenantContext::set() ran; model uses the trait
Booking created but room not blocked	6	Hotel/ReservationService	blocking statuses , refreshRoomStatus

Symptom	Hop	Files to open first	What to check
Guest SMS not arriving	6	<code>SmsService</code> , <code>AfricaTalkingSmsDriver</code> , <code>config/sms.php</code> , <code>.env</code>	Driver, balance (<code>InsufficientBalance</code>), <code>AFRICASTALKING_FROM</code> , event toggle, guest phone
STAAH not pushing/ receiving	6, 8	<code>StaahAriService</code> , <code>StaahClient</code> , <code>StaahWebhookReceipt</code>	Wired settings, shared secret, ledger rows, 2000/day guardrail
Realtime updates stop	6.12.5	<code>src/plugins/echo.js</code> , <code>routes/ channels.php</code> , <code>.env</code>	<code>VITE_REVERB_*</code> ; <code>POST / broadcasting/auth</code> status; Reverb running
PDF/invoice download fails	2, 5	<code>config/cors.php</code> , <code>InvoiceService</code>	<code>Content-Disposition</code> exposed; <code>dompdf</code> error in log

7. Mobile App (NativePHP)

The mobile app is a native Android application built with [NativePHP Mobile](#) on top of Laravel 13. It reuses the same API backend as the web frontend.

7.1 Tech Stack

- **Framework:** Laravel 13 + NativePHP Mobile 4.2
- **UI:** Blade templates with Tailwind CSS
- **HTTP:** `App\Services\ApiClient` — token-based auth via Sanctum
- **Target:** Android only (Linux host — no macOS available for iOS builds)

7.2 Structure

Path	Purpose
<code>app/Services/ApiClient.php</code>	HTTP client (Sanctum token, login, CRUD)
<code>app/Providers/ ApiServiceProvider.php</code>	Binds <code>ApiClient</code> singleton
<code>app/Http/Middleware/ AuthenticateApi.php</code>	Session-based auth guard (redirects to login)
<code>app/Http/Controllers/Mobile/*</code>	Controllers: Login, Dashboard, Attendance, Housekeeping, Room, Reservation, Order, Profile
<code>resources/views/mobile/*.blade.php</code>	Blade views for each mobile page
<code>resources/views/layouts/ app.blade.php</code>	Base layout (viewport, Tailwind, safe-area)

Path	Purpose
<code>resources/views/layouts/bottom-nav.blade.php</code>	Mobile bottom navigation bar
<code>routes/web.php</code>	All mobile routes behind <code>auth.api</code> middleware
<code>config/api.php</code>	Base URL, version, timeout settings

7.3 Auth Flow

1. `POST /login` — CSRF token + email/password → API `/auth/login` → stores Sanctum token in session → redirects to dashboard.
2. All protected routes use `auth.api` middleware which checks for `auth_token` in session.
3. Logout clears session and redirects to `/login`.

7.4 Configuration

- `.env` : `MRK_API_BASE_URL=http://127.0.0.1:8000/api/v1` (local), `APP_NAME="MRK Hotels"`, `NATIVEPHP_APP_ID=com.mrk.hotels.mobile`
- `config/api.php` : `base_url`, `version`, `timeout` (30s)
- `config/nativephp.php` : NativePHP Mobile config (auto-generated)

7.5 Running Locally

```
# Terminal 1: API server
cd mrk-hotels-api && php artisan serve --port=8000

# Terminal 2: Mobile dev server
cd mrk-hotels-mobile && php artisan serve --port=8002

# Terminal 3 (optional): Build APK (requires JDK 17)
cd mrk-hotels-mobile && php artisan native:build
```

7.6 Pages

Route	Page	Description
<code>/login</code>	Login	Email + password auth
<code>/dashboard</code>	Dashboard	Quick actions, stats overview
<code>/attendance</code>	Attendance	Clock in/out, shift history
<code>/housekeeping</code>	Housekeeping	Task list, start/complete
<code>/rooms</code>	Rooms	Room grid by status, detail view
<code>/reservations</code>	Reservations	List with check-in/out actions
<code>/orders</code>	F&B Orders	Order list, detail view

Route	Page	Description
/profile	Profile	User profile, logout

7.7 Role-Based Access

The mobile app uses the same role system as the web app. Staff with `role_level: 20` (e.g. receptionists) can access attendance, orders, profile, and dashboard. Housekeeping and rooms require `role_level: 40+`. Permission errors are shown as amber info cards rather than 500 crashes.

8. API Reference — Key Endpoints

7.1 Public

POST /api/v1/auth/login-pin

Body: `identifier` (username/email **or** registration number), `pin` (exactly 4 digits).

Response: identical to password login — `200 { message, token, user }`. Unknown identifiers, unset PINs and wrong PINs all return one generic `401 { "message": "Invalid credentials." }`; throttled 5/min together with `auth/login` and `auth/register` under the shared `auth` limiter.

GET /api/v1/public/hotels

Params: `search` (hotel name/city LIKE), `country`, `city`, `guests` (min occupancy), `check_in`, `check_out`, `per_page`.

Response (paginated `hotels` + `meta`): each hotel includes `tenant_id`, `hotel_name`, `city`, `country`, `available_rooms`, `starting_price`, `room_types`.

GET /api/v1/public/availability

Params: `hotel_id`, `check_in`, `check_out`, `room_type`, `booking_type`, `guests`.

Response: `{ hotel, rooms: [...], payment_methods: [...] }`.

POST /api/v1/public/reservations

Validates guest details + booking (`booking_date = after_or_equal:today + before_or_equal:check_in_date`). With `room_selections[]` returns `201 { booking_reference, total_amount, message }`; otherwise a booking requisition.

POST /api/v1/public/payments/initiate

Body: `booking_reference`, `amount`, `payment_method`, `payment_provider`, `phone`.

Response: `{ message, payment: { transaction_reference|clickpesa_reference, ... } }`.

GET /api/v1/public/invoices/download

Guest self-service invoice PDF. Params: `reference` (booking reference), `phone` (matched by trailing digits, so local/international spellings both work).

Returns the generated PDF (`Content-Disposition: attachment; filename=INV-...pdf` , throttled 10/min) or `404` with a generic message when no confirmed reservation matches — never reveals whether the reference exists.

7.2 Authenticated (Bearer token)

Method	URI	Purpose
GET	<code>/api/v1/auth/me</code>	Current user + permissions
POST	<code>/api/v1/auth/logout</code>	Revoke current token
POST	<code>/api/v1/users/{id}/set-pin</code>	Set a staff member's 4-digit login PIN (<code>pin</code> + <code>pin_confirmation</code> ; level 80+, role-guarded, no self-service)
GET	<code>/api/v1/reservations</code>	List (filters: status, booking_type, from, to, search)
POST	<code>/api/v1/reservations</code>	Create reservation
POST	<code>/api/v1/reservations/{id}/check-in</code>	Check in
POST	<code>/api/v1/reservations/{id}/check-out</code>	Check out
POST	<code>/api/v1/reservations/{id}/cancel</code>	Cancel
POST	<code>/api/v1/reservations/{id}/no-show</code>	Mark no-show
POST	<code>/api/v1/payments</code>	Record a payment
GET	<code>/api/v1/rooms</code> , <code>/api/v1/guests</code> , <code>/api/v1/payments</code>	Module lists
GET	<code>/api/v1/messages/conversations</code>	Direct conversations (merge with groups on the client)
POST	<code>/api/v1/messages/conversations</code>	Start a conversation (<code>scope: hotel global</code> , <code>user_id</code>)
GET	<code>/api/v1/messages/conversations/{id}/messages</code>	Messages + poll (marks them delivered)
POST	<code>/api/v1/messages/conversations/{id}/messages</code>	Send (<code>body</code> and/or <code>media</code> , optional <code>type</code> , <code>view_once</code> , <code>disappears_in: 3600\ 86400\ 604800</code>)
POST	<code>/api/v1/messages/conversations/{id}/read</code>	Mark thread read

Method	URI	Purpose
GET	/api/v1/messages/unread-count	Direct + group unread total for the nav badge
GET/ POST	/api/v1/messages/groups	List / create group (name , scope , member_ids[])
GET	/api/v1/messages/groups/{id}/messages	Group messages (mark delivered)
POST	/api/v1/messages/groups/{id}/messages	Send group message (body / media)
POST	/api/v1/messages/groups/{id}/read	Mark group read (last_read_at)
POST	/api/v1/messages/groups/{id}/members	Add members (user_ids[])
DELETE	/api/v1/messages/groups/{id}/members/{userId}	Remove member (leave when self)
POST	/api/v1/messages/conversations/{convId}/messages/{msgId}/delete	Delete a message (delete_for: me\ everyone) — both parties vanish from threads; everyone removes it everywhere
POST	/api/v1/messages/conversations/{convId}/messages/{msgId}/react	Toggle an emoji reaction (emoji)
GET	/api/v1/messages/conversations/{convId}/messages/{msgId}/media	Consume a view-once media URL (one hit only, then locked)
POST	/api/v1/messages/groups/{groupId}/messages/{msgId}/delete	Delete a group message (delete_for: me\ everyone)
POST	/api/v1/messages/groups/{groupId}/messages/{msgId}/react	Toggle a reaction on a group message
GET	/api/v1/messages/statuses	Status feed (active, < 24 h)
POST	/api/v1/messages/statuses	Post a status (type: text\ photo\ video , body / media)
GET	/api/v1/messages/statuses/{id}	View a status (marks it seen)
POST	/api/v1/messages/statuses/{id}/like	Toggle a reaction/like on a status

Method	URI	Purpose
POST	/api/v1/messages/calls/start	Start a WebRTC call (type , recipient_id) — rings the callee
POST	/api/v1/messages/calls/{id}/accept / reject / decline / end	Call lifecycle (decline = busy)
POST	/api/v1/messages/calls/{id}/miss	Mark a call missed (ring timeout / auto-end)
GET	/api/v1/messages/calls	Call history (missed/active/ended, scoped to caller)
POST	/api/v1/messages/pin / unpin / star / unstar	Pin/star a message (message_type , message_id)
GET	/api/v1/messages/pinned , /api/v1/messages/starred	Your pinned / starred messages
POST	/api/v1/messages/polls/vote	Vote on a poll (poll_id , poll_option_id)
GET/ POST	/api/v1/messages/templates	List / create message templates; PUT / DELETE per id
GET/ POST	/api/v1/messages/scheduled	List / schedule a message (recipient_type , recipient_id , body , send_at , recurrence)
DELETE	/api/v1/messages/scheduled/{id}	Cancel a scheduled message
GET/ POST	/api/v1/messages/announcements	List / post an announcement; POST {id}/acknowledge
GET	/api/v1/messages/search	Keyword search across accessible chats (search , chat_type / chat_id , from / to)
GET	/api/v1/messages/export	CSV export of a chat history (chat_type , chat_id)
POST	/api/v1/messages/translate	Translate a body (offline EN↔SW glossary)
GET/ POST	/api/v1/messages/escalations	List / raise an escalation (message_type , message_id , reason)
POST	/api/v1/messages/escalations/{id}/resolve	Resolve an escalation (resolution , handled_by)
GET/ POST	/api/v1/messages/retention-policies	List / create a retention policy (scope , days , enabled); DELETE per id

Method	URI	Purpose
GET/ POST	/api/v1/messages/ preferences	List / create notification preferences (scope , target_id , muted , muted_until , dnd_enabled , dnd_from , dnd_to , push_enabled)
PUT/ DELETE	/api/v1/messages/ preferences/{id}	Update / delete a preference
GET/ POST	/api/v1/messages/ handovers	List / post a shift handover (title , notes , shift_from , shift_to); POST {id}/acknowledge
GET	/api/v1/messages/ rooms , /api/v1/messages/ rooms/search	Linked rooms / search rooms to link (search)
POST	/api/v1/messages/rooms	Link a chat to a room (chat_type , chat_id , room_id)
DELETE	/api/v1/messages/rooms/ {id}	Unlink a room from a chat
POST	/api/v1/messages/task- groups	Create a task group (room-linked group for housekeeping)
POST	/api/v1/messages/groups/ {groupId}/messages/ {messageId}/convert-task	Convert a room-linked message into a HousekeepingTask (task_type)
POST	/api/v1/messages/forward	Forward a message (message_type , message_id , target_type , target_id)
PUT/GET	/api/v1/messages/ location , /api/v1/ messages/nearby	Update your zone/floor; list colleagues updated in the last 30 min (zone , floor)
GET/ POST	/api/v1/messages/guest- messages	List / send an outbound guest SMS (phone , body)
GET/ POST	/api/v1/messages/ meetings	List / schedule a meeting (title , start_at , duration_minutes , conference_type , invitee_ids)
GET	/api/v1/messages/ meetings/users	Search staff to invite (search)
POST	/api/v1/messages/ meetings/{id}/respond	Accept/decline a meeting invite (response)
GET/ POST	/api/v1/messages/sos	List / initiate an SOS alert (message)
POST	/api/v1/messages/sos/ {id}/acknowledge / resolve	Acknowledge / resolve an SOS alert

Method	URI	Purpose
GET	/api/v1/reports/overview	Admin overview with per-section filters + 15/page pagination
GET	/api/v1/owner/dashboard	Owner: consolidated stats + per-hotel comparison across owned hotels
GET	/api/v1/owner/hotels , /api/v1/owner/hotels/{id}	Owner: owned-hotel list / drill-down (404 for unowned)
GET/POST	/api/v1/owners	Superadmin: list / create owner accounts
GET	/api/v1/invoices	List invoices (tenant scoped)
POST	/api/v1/reservations/{id}/invoice	Generate/refresh the folio invoice
GET	/api/v1/invoices/{id}/download	Staff invoice PDF download
PUT	/api/v1/tenants/{id}	Superadmin: update hotel details incl. <code>tin</code> , <code>vrn</code> , <code>payment_methods</code> , <code>payment_accounts</code>
POST	/api/v1/tenants/{id}/branding	Superadmin: upload/remove invoice signature & stamp images (multipart <code>signature</code> / <code>stamp</code> , or <code>remove_signature</code> / <code>remove_stamp</code>)
POST	/api/v1/attendance/clock-in	Clock in (<code>lat</code> , <code>lng</code> , <code>accuracy_m</code> , <code>positioned_at</code> , <code>qr_token</code> , <code>device_id</code> , <code>device_secret</code> , <code>device_fingerprint</code> , <code>photo</code> , <code>note</code>); enforces geofence + QR + device binding + selfie when configured
POST	/api/v1/attendance/clock-out	Clock out (best-effort <code>lat</code> / <code>lng</code> , optional <code>note</code>)
GET	/api/v1/attendance/status	Current user's on-shift status + active attendance record
GET	/api/v1/attendance/requirements	Policy for the caller's hotel (<code>office_configured</code> , <code>requires_location</code> , <code>requires_qr</code> , <code>qr_ttl_seconds</code> , <code>requires_photo</code> , <code>device_policy</code> , <code>device_registered</code>)
GET	/api/v1/attendance/penalties/mine	Current user's own penalty ledger
POST	/api/v1/attendance/devices/register	Register this device; returns the one-time <code>device_secret</code>
GET	/api/v1/attendance/devices/mine	Current user's registered devices

Method	URI	Purpose
POST	/api/v1/attendance/absences	File an absence claim (absence_type , reason , starts_at , ends_at , lat , lng , device_id , optional evidence attachments)
GET	/api/v1/attendance/absences/mine	Current user's absence claims
GET	/api/v1/attendance/photos/{attendanceId}	Stream a clock-in selfie blob (audited private disk)
GET	/api/v1/attendance/attachments/{attachmentId}	Stream an absence-evidence attachment blob (audited private disk)
GET	/api/v1/attendance/on-shift	Manager (level 80+): who is currently on shift
GET	/api/v1/attendance/users/{userId}/history	Manager: a staff member's attendance register
POST	/api/v1/attendance/qr-token	Manager (level 80+): mint a 60-second single-use entrance QR token
GET	/api/v1/attendance/settings	Admin: current attendance settings
PUT	/api/v1/attendance/settings	Admin: set office location / radius / QR requirement (QR refused without office)
GET	/api/v1/attendance/policy	Admin: current discipline policy (shift window + tolerances)
PUT	/api/v1/attendance/policy	Admin: set shift window / grace windows; null shift disables auto-flagging
GET	/api/v1/attendance/penalties	Admin: full hotel penalty ledger
POST	/api/v1/attendance/penalties	Admin: impose a manual penalty
POST	/api/v1/attendance/penalties/{penaltyId}/decide	Admin: apply or dismiss a pending penalty (cannot decide one's own)
GET	/api/v1/attendance/register	Admin: the full attendance register
GET	/api/v1/attendance/devices	Admin: every registered device in the hotel

Method	URI	Purpose
POST	/api/v1/attendance/ devices/{deviceId}/ revoke	Admin: revoke a device so it can no longer clock in
GET	/api/v1/attendance/ suspicious	Admin: attendance records the anti-cheat scan flagged
GET	/api/v1/attendance/ absences	Admin: all absence claims
POST	/api/v1/attendance/ absences/{requestId}/ decide	Admin: approve or reject an absence claim

Payment methods payload (superadmin):

```
{ "payment_methods": ["cash", "mobile_money", "bank", "selcom", "card"] }
```

9. Payment semantics

Method	Provider required	Initial status	Confirmation
cash / card	—	completed	immediate
mobile_money	yes (airtel_money, mixx_by_yas, halopesa, mpesa)	pending (online) / awaiting_confirmation (desk)	ClickPesa webhook → completed , or receptionist confirms manually
bank	yes (crdb, nmb, nbc, other)	awaiting_confirmation	hotel staff marks paid
selcom	—	completed	immediate + confirms booking

A mobile-money payment is always **confirmable**: `Payment::isConfirmable()` accepts both `pending` and `awaiting_confirmation`, so the receptionist can verify and confirm an online payment on the Payments page (`payments/{id}/confirm`) using the reference from the guest's SMS — the webhook is a fast-path auto-confirm, not the only path.

`PaymentOptions::defaultMethods()` = all staff methods **except** selcom (shipped disabled). The superadmin can enable it per tenant.

10. Messaging semantics

Delivery / read ticks. A message is `delivered_at` the moment the recipient's device pulls it — any read of the conversation list, the thread, or a `messages` poll marks outgoing messages as delivered. `markRead` sets `read_at` on the conversation (or `last_read_at` on the group membership) when the thread is opened.

- Direct messages: single tick = delivered, double tick = read.
- Group messages: a message is "read" when `read_by_count > 0` (computed in `GroupMessageResource` from loaded members whose `last_read_at` `>=` message `created_at`). The UI shows "Seen by N".

Scoping. `scope=hotel` conversations are restricted to the caller's tenant; `scope=global` conversations cross hotels but never expose a superadmin. Group creation enforces the same rule per scope.

Media. `POST .../messages` accepts `body`, `media` (file, ≤ 10 MB) and optional `type`. `type` is inferred from the MIME (`audio/*` $\rightarrow$ audio, `image/*` $\rightarrow$ image, else file) when not supplied. `body` is nullable, so audio/attachment-only messages are valid. Files are stored on the public disk under `messages/conversations/{id}` or `messages/groups/{id}` and exposed via `media_url` on the message resource.

View-once media. Messages sent with `view_once: true` are rendered in the client as a covered tile. The recipient taps **once** to reveal; the client calls `GET .../messages/{msgId}/media`, which serves the media and sets `is_media_seen = true`. Subsequent requests return 403 and the UI shows an "opened" state — the media can never be replayed. View-once is only applied to `image / video` types; plain text cannot be view-once.

Deleting messages. `POST .../delete` takes `delete_for: me|everyone`. - Direct conversations: `me` hides the message for the caller only (recipient keeps it); `everyone` removes it for **both** parties. The other side learns instantly via the `MessageDeleted` broadcast (which carries `channel_id` so open threads update live without a refetch). - Group conversations: `me` hides it for the caller; `everyone` soft-deletes it for all current members (restored conversation history still omits it). Group message deletion also broadcasts `MessageDeleted`.

Reactions. `POST .../react` with `emoji` toggles an emoji on a message. Reactions are stored as a JSON map on the message row (`reactions` column keyed by `user_id` $\rightarrow$ `emoji`), summed per emoji in the message resource. The UI renders the reaction row beneath the bubble (tapping your own reaction removes it). `MessageReacted` broadcasts keep open threads in sync.

Mentions. Typing `@` in the composer surfaces a colleague picker (from `messages/users`). Selecting someone inserts `@FirstName`, sends `mention_user_ids[]` with the message, and the mentioned user gets a highlighted bubble + notification in their thread (via `MessageSent` with `mentions`). Mentions have no tenant-crossing behaviour beyond the existing `scope` rules.

Statuses. Every user can post a **status** (`type: text|photo|video`) that lives for **24 hours** then expires (soft-deleted by the feed query, no cron needed). A status is scoped to the poster's tenant by default (`scope=hotel`) or `scope=global`. The **Statuses page** shows "Your status" plus a feed; viewing a status records a `StatusView` (deduplicated per user), and `POST /statuses/{id}/like` toggles an emoji reaction (`StatusReaction`). In the conversation list, a colleague's avatar

shows a **status ring** when they have an active status — fed live by the `StatusPosted` broadcast on the tenant channel.

Calls (WebRTC). The `CallController` orchestrates the signaling: 1. `POST /calls/start` (`type: audio|video` , `recipient_id`) creates a `Call` (`ringing`), broadcasts `CallStarted` to `private-users.{recipient_id}` , and records a `CallEvent` (`ring`). 2. The callee's `CallIncomingOverlay` offers accept/reject. Accepting calls `POST /calls/{id}/accept` (`status → active`), broadcasts `CallEvent` (`accept`) so the initiator opens the peer connection. Rejecting → `rejected` ; a busy callee → `decline` (`declined`). 3. Media is exchanged peer-to-peer over WebRTC (no server-side media). Call state rides the `CallEvent` broadcasts; `end` (either side) → `ended` , ring timeout → `missed` . 4. Call history (`GET /calls`) lists the caller's own calls (`missed/active/ended`) with callers/callees, type and timestamps.

Realtime. All of the above are pushed over Reverb/Echo (see §4.11): `MessageSent` , `MessageRead` , `MessageDeleted` , `MessageReacted` , `StatusPosted` , `CallStarted` , `CallEvent` , `MemberJoined` / `MemberLeft` . The SPA listens on `private-users.{id}` (direct) and `private-tenants.{tenant_id}` (group/global). A polling fallback remains for slow WebSocket connections (unread count + thread refetch).

The 24-feature enhancement set. Everything below lives under `messages/*` , is level-20+ (any employee) unless noted, and rides the private channels above.

- **Replies.** `POST .../messages` accepts `reply_to_id` . The message row self-joins (`reply_to`), the resource includes `reply_to: { message_id, sender_id, sender_name, body }` , and `ReplySent` broadcasts the full reply (`conversation → MessageResource` , `group → GroupMessageResource`). The composer shows a **reply bar** while composing; tapping a quoted reply scrolls to the original message.
- **Priority.** `POST .../messages` accepts `priority: normal|urgent` . Urgent messages get a red border, an "urgent" tag, a pin **and** are auto-escalated when unread past the command threshold (`messaging:escalate`).
- **Polls.** Sending a `poll: { question, multiple, options[] }` creates `Poll` / `PollOption` rows and broadcasts `PollCreated` . Voting is `POST messages/polls/vote` (`poll_id` , `poll_option_id`), once per user (unique `poll_votes`), tally + percentages recomputed and broadcast via `PollVoted` . Messages with a poll render the live option bars inline in the thread.
- **Pin & star.** `PinStarController` upserts `PinnedMessage` / `StarredMessage` (per user), broadcasts `MessagePinned` / `Unpinned` / `Starred` / `Unstarred` on the thread channel so open chats update live, and exposes `GET messages/pinned` / `messages/starred` (each returns a copy of the message at pin time, so later edits/deletes don't corrupt the pinned snapshot).
- **Templates.** `MessageTemplate` is a personal/tenant snippet store (`name` , `body` , `category` , `is_global`). The composer's template picker inserts the body directly.
- **Scheduled messages.** `ScheduledMessage` holds `recipient_type` (`conversation/group`), `recipient_id` , `body / media` , `send_at` and optional `recurrence` . The `messaging:send-scheduled` command (runs every minute) dispatches due sends through the normal send pipeline (so `MessageSent` still fires), then stamps `last_sent_at` ; repeating schedules are re-queued, one-off sends are soft-cancelled.
- **Forwarding.** `POST messages/forward` (`message_type` , `message_id` , `target_type` , `target_id`) copies the source message into the target chat with `forwarded_from_type` / `forwarded_from_id` provenance and a "Forwarded" label in the UI. Source and target access are both validated

(participant/member + same-tenant), deleted and view-once messages cannot be forwarded, and the copy dispatches `MessageSent` / `GroupMessageSent` on the target thread.

- **Announcements.** `Announcement` posts tenant-wide and broadcasts `AnnouncementPosted`; every recipient sees it in the **Workspace → Announcements** tab and `POST {id}/acknowledge` records an `AnnouncementAcknowledgement` (broadcast `AnnouncementAcknowledged`) so the poster sees "N acknowledged".
- **Search & export.** `GET messages/search` (keyword + optional `chat_type` / `chat_id`, `from` / `to`) matches `ConversationMessage` and `GroupConversationMessage` that the caller can access and returns them newest-first with a matching snippet. `GET messages/export` streams a CSV of a chat's history (id, sender, body, type, timestamps).
- **Translate.** `POST messages/translate` with `text` returns the offline `TranslateService` result — a bundled EN↔SW glossary with direct + reverse lookups (no external API, works offline). The bubble's translate button toggles original / translated text.
- **Escalations.** `MessageEscalation` is polymorphic (`message_type`, `message_id`) with `escalated_by`, optional `handled_by` / `handled_at`. `POST messages/escalations` raises it (broadcast `MessageEscalated` to the tenant channel); managers see a tab in Workspace and `POST {id}/resolve` marks it handled.
- **Retention.** `RetentionPolicy` (`scope` = global/conversation/group, `days`, `enabled`) is set by admins (the Workspace Retention tab is admin-only). `messaging:purge-expired` soft-deletes messages older than the policy; expired scheduled messages are also cleaned up.
- **Notification preferences / DND.** `NotificationPreference` is polymorphic (`scope` = conversation/group/global, `target_id`): mute a chat (with optional `muted_until`) or set a daily DND window (`dnd_from` / `dnd_to`). The muted chat shows a speaker-off icon; `push_enabled` gates push-style notifications.
- **Shift handovers.** `ShiftHandover` captures `title`, `required notes`, `shift_from` / `shift_to`. `POST messages/handovers` broadcasts `ShiftHandoverPosted`; `POST {id}/acknowledge` records who acked and broadcasts `ShiftHandoverAcknowledged`.
- **Room-linked chats & task groups.** `ConversationRoom` binds a chat to a `Hotel\Room`. `TaskGroupController::store` creates a **task group** (group chat with `is_task_group`, a `task_type`, and a linked room); its members are room-relevant staff. `POST .../convert-task` turns a room-linked message into a `HousekeepingTask` (broadcast `TaskConverted`), so a "Room 401 needs sheets" chat message becomes an actual housekeeping assignment.
- **Staff presence.** `PUT messages/location` upserts `StaffLocation` (`zone`, `floor`, `updated_at`); `GET messages/nearby` lists colleagues updated in the last 30 minutes, filterable by zone/floor. Updates broadcast `StaffLocationUpdated` on the tenant channel so the Workspace nearby tab refreshes live.
- **Guest SMS bridge.** `POST messages/guest-messages` (`phone`, `body`, optional `template_id`) creates an outbound `GuestMessage` (direction `outbound`) and broadcasts `GuestMessagePosted`; history is tenant-scoped.
- **Meetings.** `Meeting` (`start_at`, `duration_minutes`, `conference_type`, `status`) with `MeetingInvitee` rows. Scheduling broadcasts `MeetingInvited` to each invitee's user channel; `POST {id}/respond` (`accepted` / `declined`) broadcasts `MeetingResponseChanged` so the organizer's list updates live (the `index` response includes `my_invitee` per meeting).
- **SOS alerts.** `SosController::initiate` (`message`) broadcasts `SosAlertInitiated` to the tenant channel with a prominent pulse in the UI; any staff member acknowledges (`ack_count`,

`ack_user_ids`) or resolves (`SosAlertResolved`). The SOS button floats over the chat list, including on the login-protected hotel panel.

11. Deployment notes

- Set `APP_ENV` , `APP_DEBUG` , `APP_URL` , `SANCTUM_STATEFUL_DOMAINS` (add your frontend host) and `CLICKPESA_*` keys (sandbox live URL, service fee percent).
- `APP_URL` must be the public API origin (including port) — tenant branding image URLs (`signature_url` / `stamp_url`) are built from it.
- Run `php artisan storage:link` so uploaded branding images under `storage/app/public/tenants/{id}` are reachable.
- CORS is configured in `config/cors.php` : `Content-Disposition` is exposed so the SPA can read the generated invoice filename from download responses; keep it exposed when hardening origins.
- Build the frontend with `npm run build` and serve `dist/` behind the same-origin as `VITE_API_URL` or configure CORS.
- Run `php artisan migrate --force` in production; schedule nothing currently (no queued jobs required by the current flow — ClickPesa is handled synchronously + webhook).
- Realtime in production: run `php artisan reverb:start` behind a process supervisor (or Reverb's own fleet config), set `REVERB_*` env vars on both apps, and make sure the SPA's `VITE_REVERB_*` values match. If the WebSocket handshake is proxied, also expose `/broadcasting/auth` through your API host.
- Tests: `php artisan test` (SQLite in-memory) and `npm test` / Playwright for the frontend.

12. Screens

Captured from the running demo (MRK Grand Hotel + the platform superadmin). Public and hotel-panel screens are shared with the user manuals; the superadmin screens appear only here. The PIN sign-in screens (`login-pin.png` , `app-staff.png` , `app-staff-set-pin.png`) are regenerated with `node scripts/capture-docs-images.mjs` (requires the dev server on `:5173` and the API on `:8000`).

12.1 Public portal and sign-in



MRK Hotels

Sign in to access your hotel account.

📧 Password

📄 PIN

Email

Enter your email

Password

Enter your password

👁

➔ Sign In

[← Back to home](#)

Version 1.0.179

MRK Hotels staff portal — reservations, rooms and operations across the network.

© 2026 MRK Hotels. All rights reserved.

⌵ 🔍

Sign-in page (`/login`) — dual-mode: email + password, or username/registration number + 4-digit PIN on the iPOS-style keypad.



MRK Hotels

Sign in to access your hotel account.

📧 Password

📄 PIN

Username or Registration Number

cashier@mrkhotels.test

● ● ○ ○

Enter your 4-digit PIN

1

2

3

4

5

6

7

8

9

C

0

✖

[← Back to home](#)


Version 1.0.179

MRK Hotels staff portal — reservations, rooms and operations across the network.


© 2026 MRK Hotels. All rights reserved.

⌵ 🔍

PIN mode — the on-screen keypad; sign-in is submitted automatically when the 4th digit is entered.



Public booking portal home (`/) — hotel directory, country/city filters, invoice download.



Public hotel detail (`/hotels/{id}`) — rooms, rates, occupancy.

12.2 Hotel panel

+255 700 000 000bookings@mrkhotels.comDodoma, TanzaniaMRK Grand Hotel

MRKHotels

PortalDashboardMy ProfileLogoutENSW

Vacant 60Occupied 8Reserved 335Blocked 3Due Out 14Dirty 2

Search reservations, guests and r

New booking

Guests

Housekeeping

Stock ledger

	WED Aug 26	THU Aug 27	FRI Aug 28	SAT Aug 29	SUN Aug 30	MON Aug 31	TUE Sep 1	WED Sep 2	THU Sep 3	FRI Sep 4	SAT Sep 5	SUN Sep 6	MON Sep 7
Deluxe	180,000.00	180,000.00	180,000.00	180,000.00	180,000.00	180,000.00	180,000.00	180,000.00	180,000.00	180,000.00	180,000.00	180,000.00	180,000.00
114	REHEMA MWINYI			RAJABU SENG		BARAKA MWAKYUSA			JOSEPHAT MAHENG	AMINA...		EMMANUEL SHIRIMA	
115	JOSEP... IGWA				FATUMA ALLY			RAJABU SENG		IL SHIRIMA			
116	AMINA...	HAMISI RAMADHANI				FATUMA ALLY						REHE...	
117	PETER MSIGWA					JOSEPHAT MAHENG			JOSEPHAT MAHENG				
214	FRANK...	GRACE MOLLEL		FATUMA ALLY				ANNA ...	ZAWA...	FATUMA ALLY			
215	SALMA KONDO		ENGO					BARAKA MWAKYUSA	IGORO	CHARLES			
216	FRANK UHURU			ERE		FRANK UHURU			FATUMA ALLY				
217	FATU... LLEL			BARAKA MWAKYUSA				ELIAS SONGORO	NEEMA KESSY				
314	JOSEPHAT MAHENG	JUMA ...				AMINA...	REHEMA MWINYI						
315	FATU...	AMINA...	JUMA FAKI		ELIAS ...	SALM...	FRANK UHURU	JUMA FAKI					
316	JUMA FAKI			ELIAS SONGORO		NEEMA KESSY			ANNA ...	ZAWA...			
317	PETER ... LLEL					PETER MSIGWA							
414	GRAC... MADHANI	MWAKYUSA						JOSEPHAT MAHENG					
Availability	0	0	0	0	0	0	0	0	0	0	0	0	0
Occupancy	347%	230%	175%	138%	115%	121%	118%	122%	122%	134%	144%	140%	134%

Staff dashboard (`/app`).

+255 700 000 000bookings@mrkhotels.comDodoma, TanzaniaMRK Grand Hotel

MRKHotels

PortalDashboardMy ProfileLogoutENSW

Reservations

Bookings, check-ins and check-outs.

Active

Checked Out

Cancelled

Status

Booking type

From

To

Search

Guest or reference...

Clear

GUEST	TYPE	ROOM	STAY	TIMES	TOTAL	BALANCE	STATUS	ACTIONS
Rajabu Sengo +2557888147267	Single booking	Room 206 Double	2026-09-21 – 2026-09-28 7 night(s) · 2 adult(s), 2 child(ren)	—	TZS 800,000	TZS 0	pending	View
Salma Kondo +2557356053105	Single booking	Room 107 Double	2026-10-28 – 2026-11-04 7 night(s) · 1 adult(s)	—	TZS 1,800,000	TZS 0	pending	View
Josephat Mahenge +2557615171939	Single booking	Room 105 Single	2026-08-25 – 2026-09-01 7 night(s) · 1 adult(s)	—	TZS 800,000	TZS 0	checked in	View
Upendo Charles +2557906183849	Single booking	Room 103 Single	2026-10-28 – 2026-11-04 7 night(s) · 1 adult(s), 1 child(ren)	—	TZS 1,150,000	TZS 1,100,000	confirmed	View
Neema Kessy +2557571884893	Single booking	Room 308 Double	2026-08-28 – 2026-08-29 1 night(s) · 1 adult(s)	—	TZS 1,200,000	TZS 840,000	checked in	View
Grace Mollel +2557931285153	Single booking	Room 307 Double	2026-10-07 – 2026-10-13 6 night(s) · 1 adult(s), 2 child(ren)	—	TZS 1,400,000	TZS 1,350,000	confirmed	View

Reservations.

+255 700 000 000bookings@mrkhotels.comDodoma, TanzaniaMRK Grand Hotel

MRKHotels

PortalDashboardMy ProfileLogout

ENSW

Rooms

Manage rooms, rates and their current status.

Refresh

New Room

Export

Status

All

Room Type

All

Search

Room number...

Clear

ROOM	TYPE	FLOOR	RATE / NIGHT	CAPACITY	STATUS	ACTIONS
101	Single	Floor 1	TZS 80,000	2	available	EditStatus
102	Single	Floor 1	TZS 80,000	2	available	EditStatus
103	Single	Floor 1	TZS 80,000	2	available	EditStatus
104	Single	Floor 1	TZS 80,000	2	available	EditStatus
105	Single	Floor 1	TZS 80,000	2	available	EditStatus
106	Double	Floor 1	TZS 120,000	2	occupied	Edit
107	Double	Floor 1	TZS 120,000	2	available	EditStatus
108	Double	Floor 1	TZS 120,000	2	available	EditStatus

Rooms.

+255 700 000 000bookings@mrkhotels.comDodoma, TanzaniaMRK Grand Hotel

MRKHotels

PortalDashboardMy ProfileLogout

ENSW

Guests

Guest profiles captured at booking and check-in.

Refresh

Export

Search

Name, email or phone...

VIP

All

Nationality

e.g. Tanzania

Clear

GUEST	CONTACT	ID	NATIONALITY	TYPE	ACTIONS
Abdallah AbbasVIP	abdallah-abbas0@gmail.com 07700000000	-	Tanzanian	VIP	
Adam Abbas	adam-abbas1@gmail.com 07700000001	-	Tanzanian	Regular	
Agnes Abbas	agnes-abbas2@gmail.com 07700000002	-	Tanzanian	Regular	
Aisha Abbas	aisha-abbas3@gmail.com 07700000003	-	Tanzanian	Regular	
Ally Abbas	ally-abbas4@gmail.com 07700000004	-	Tanzanian	Regular	
Amani Abbas	amani-abbas5@gmail.com 07700000005	-	Tanzanian	Regular	
Athumani Abbas	athumani-abbas10@gmail.com 07700000010	-	Tanzanian	Regular	

Guests.

+255 700 000 000bookings@mrkhotels.comDodoma, TanzaniaMRK Grand Hotel

MRKHotels

PortalDashboardMy ProfileLogout

ENSW

Payments

Payments against reservations and F&B orders.

Refresh

Export

Status

All

Method

All

From

mm/dd/yyyy

To

mm/dd/yyyy

Clear

PAYMENT	RESERVATION	PAYER	AMOUNT	METHOD	STATUS	ACTIONS
No payments found.						

Payments.

+255 700 000 000bookings@mrkhotels.comDodoma, TanzaniaMRK Grand Hotel

MRKHotels

PortalDashboardMy ProfileLogout

ENSW

Booking Requests

Enquiries from the public booking portal.

Refresh

Export

Status

All

Booking type

All

Search

Name or reference...

Clear

REFERENCE	GUEST	STAY	TYPE	DETAILS	STATUS	ACTIONS
No booking requests found.						

Booking requisitions.

+255 700 000 000bookings@mrkhotels.comDodoma, TanzaniaMRK Grand Hotel

MRKHotels

PortalDashboardMy ProfileLogout

ENSW

Housekeeping

Cleaning and room maintenance tasks.

Refresh

Export

Too Many Attempts.

Status

House status

Room status

Room

All

All

All

All rooms

Clear

ROOM

GUESTS (PAX)

HOUSE STATUS

ASSIGNED TO

ROOM STATUS

ARRIVAL (DATE & TIME)

DEPARTURE · NIGHTS

STATUS

ACTIONS

No tasks found.

Housekeeping.

+255 700 000 000bookings@mrkhotels.comDodoma, TanzaniaMRK Grand Hotel

MRKHotels

PortalDashboardMy ProfileLogout

ENSW

Menu Items

Restaurant and bar menu management.

Refresh

Categories

New Item

Export

Department

Category

Available

Search

All

e.g. main course

All

Item name...

Clear

ITEM

CATEGORY

DEPARTMENT

PRICE

COST

MARGIN

STATUS

ACTIONS

Banana Fritters (Zena)

Sweet banana fritters with honey

Desserts

Restaurant

TZS 4,000

TZS 1,600

60%

Available

Disable

Beef Mchuzi na Wali

Beef stew served with steamed rice

Main Courses

Restaurant

TZS 11,000

TZS 4,800

56%

Available

Disable

Beef Mishkaki (Skewers)

Marinated grilled beef skewers

Grills

Restaurant

TZS 14,000

TZS 6,500

54%

Available

Disable

Beef Nyama Choma (500g)

Char-grilled beef, served with kachumbari

Grills

Restaurant

TZS 25,000

TZS 12,000

52%

Available

Disable

Beef Pilau

Spiced rice with beef, a coastal classic

Main Courses

Restaurant

TZS 12,000

TZS 5,200

57%

Available

Disable

Beef Samosa (2 pcs)

Crispy pastry filled with spiced beef

Appetizers

Restaurant

TZS 4,000

TZS 1,500

63%

Available

Disable

Black & White Whisky (50ml)

Smooth blended scotch

Spirits

Bar

TZS 7,000

TZS 3,000

57%

Available

Disable

Menu items.

+255 700 000 000bookings@mrkhotels.comDodoma, TanzaniaMRK Grand Hotel

MRKHotels

PortalDashboardMy ProfileLogout

ENSW

F&B Orders

Restaurant and bar orders.

RefreshExport

Too Many Attempts.

DepartmentStatusOrder typePaymentDate

AllAllAllAllmm/dd/yyyy

Clear

ORDER	LOCATION	GUEST / TABLE	WAITER	ORDER TYPE	ITEMS	TOTAL	STATUS	PAYMENT	ACTIONS
No orders found.									

F&B orders.

+255 700 000 000bookings@mrkhotels.comDodoma, TanzaniaMRK Grand Hotel

MRKHotels

PortalDashboardMy ProfileLogout

ENSW

Laundry

Wash, iron and dry-clean orders from guests.

RefreshExport

ServiceStatusPaymentOrder dateSearch

AllAllAllmm/dd/yyyyOrder No.

Clear

ORDER NO.	GUEST	ROOM	SERVICE	ITEMS	TOTAL CHARGE	LAUNDRY ATTENDANT	STATUS	PAYMENT	ORDER DATE	ACTIONS
No laundry orders found.										

Laundry.

+255 700 000 000bookings@mrkhotels.comDodoma, TanzaniaMRK Grand Hotel

MRKHotels

PortalDashboardMy ProfileLogout

ENSW

Fun & Games

Gaming sessions booked with an attendant supervisor.

Refresh

Export

Status

All

Booking date

mm/dd/yyyy

Gaming attendant

All

Search

Game name

Clear

ORDER NO.	GAME	GUEST	GAMING ATTENDANT	BOOKING DATE	ARRIVAL TIME	TOTAL CHARGE	STATUS	ACTIONS
No gaming orders found.								

Fun & games.

+255 700 000 000bookings@mrkhotels.comDodoma, TanzaniaMRK Grand Hotel

MRKHotels

PortalDashboardMy ProfileLogout

ENSW

Inventory

Stock items and stock movements.

Refresh

Export

Category

All

Status

All

Search

Item name...

Low stock only

No

Clear

ITEM	CATEGORY	STOCK	REORDER	UNIT COST	SUPPLIER	STATUS	ACTIONS
Absolut Vodka 375ml BTL	Bar	2	6	TZS 16,000	Dar Beverage Co	in stock	
Absolut Vodka 750ml BTL	Bar	4	7	TZS 28,000	Southern Sun Wholesalers	in stock	
Amarula Cream 750ml BTL	Bar	2	6	TZS 26,000	TanCan Distributors	in stock	
Azam Juice 1L CTN	Bar	4	12	TZS 3,500	Southern Sun Wholesalers	in stock	
Blue Moon Soda 300ml BTL	Bar	46	18	TZS 800	Southern Sun Wholesalers	in stock	
Coca-Cola 350ml BTL	Bar	118	30	TZS 700	TanCan Distributors	in stock	
Four Cousins Wine 750ml BTL	Bar	3	8	TZS 12,000	TanCan Distributors	in stock	

Inventory.

+255 700 000 000bookings@mrkhotels.comDodoma, TanzaniaMRK Grand Hotel

MRKHotels

PortalDashboardMy ProfileLogout

ENSW

Suppliers

Manage supplier information.

Refresh

Export

Status

All

Category

All

Search

Supplier name...

Clear

SUPPLIER	CONTACT	CATEGORY	TERMS	BALANCE	RATING	STATUS	ACTIONS
No suppliers found.							

Suppliers.

+255 700 000 000bookings@mrkhotels.comDodoma, TanzaniaMRK Grand Hotel

MRKHotels

PortalDashboardMy ProfileLogout

ENSW

Purchase Requisitions

Purchase requests raised by hotel departments.

Refresh

Export

Status

All

Priority

All

Department

e.g. housekeeping

Clear

REFERENCE	DEPARTMENT	REQUESTED BY	ITEMS	TOTAL	PRIORITY	STATUS	ACTIONS
No requisitions found.							

Purchase requisitions.

+255 700 000 000bookings@mrkhotels.comDodoma, TanzaniaMRK Grand Hotel

MRKHotels

PortalDashboardMy ProfileLogout

ENSW

Purchase Orders

Manage purchase orders placed with suppliers.

RefreshExport

Too Many Attempts.

Search

Reference or supplier...

Status

All

Supplier

All suppliers

Clear

REFERENCE	SUPPLIER	ITEMS	TOTAL	DELIVERY	STATUS	ACTIONS
No purchase orders found.						

Purchase orders.

+255 700 000 000bookings@mrkhotels.comDodoma, TanzaniaMRK Grand Hotel

MRKHotels

PortalDashboardMy ProfileLogout

ENSW

Goods Received Notes

Record incoming goods deliveries.

RefreshExport

Too Many Attempts.

PO

All POs

Inspection status

All

From

mm/dd/yyyy

To

mm/dd/yyyy

Clear

REFERENCE	PO	SUPPLIER	RECEIVED	DELIVERY NOTE	INSPECTION	ACTIONS
No goods received notes found.						

Goods received notes.

Staff Management
Manage hotel staff accounts and roles.

Refresh New Staff Export

Role: All Department: All Search: Name, email or registration no... Status: All Clear

STAFF	CONTACT	ROLE	DEPARTMENT	POSITION	LAST LOGIN	ONLINE	STATUS	ACTIONS
Adam Liwenga	adam-liwenga@mrk-grand.mrkhotels.test 07500000001	Manager	Administration	-	Never	Offline	Active	Edit Invite Set PIN Deactivate
Manager	manager@mrkhotels.test	Manager	Administration	-	Never	Offline	Active	Edit Invite Set PIN Deactivate

Staff — accounts, roles, invites, password resets and login PINs.

Set Login PIN

Set a 4-digit login PIN for Adam Liwenga.

Auto-generate Type it myself


Generated PIN

5 5 3 1


Share this PIN with the staff member.

Cancel Save PIN

Set Login PIN modal (`/app/staff``) — admins set a hashed 4-digit PIN per staff member for shared-terminal sign-in.



Messages.



Statuses.

+255 700 000 000bookings@mrkhotels.comDodoma, TanzaniaMRK Grand Hotel

MRKHotels

PortalDashboardMy ProfileLogoutENSW

Admin Overview

The whole hotel at a glance — employees, in-house guests and housekeeping.

MRK Grand Hotel

164

GUESTS IN HOUSE

23

ARRIVALS TODAY

50

DEPARTURES TODAY

2533

UPCOMING ARRIVALS

2/2

ACTIVE STAFF

0

TASKS IN QUEUE

8

ROOMS OCCUPIED

11%

OCCUPANCY RATE

0

OPEN ISSUE REPORTS

Employees

Manage staff →

Export

Search by name, email or registration number

All roles

All statuses

STAFF	ROLE	DEPARTMENT	LAST LOGIN	STATUS	ACTIONS
Adam Liwenga adam-liwenga@mrk-grand.mrkhotels.test	Manager	Administration	Never	Active	Deactivate

Admin overview.

+255 700 000 000bookings@mrkhotels.comDodoma, TanzaniaMRK Grand Hotel

MRKHotels

PortalDashboardMy ProfileLogoutENSW

Reports

Classic report browser

SearchNight Audit

Reservation Report8

Arrival List

Cancelled Reservations

Country Wise Reservation Statistics

Departure List

No Show Reservation

Release Reservation List

Reservation Activity

Void Reservation

Front Office Report12

Guest Checked In

Guest Checked Out

Guest List

Guest Message

Inclusion Report

Inventory By Room Type

Invoice Breakdown

Night Audit

Pickup Dropoff

Room Availability

Room Status Report

Task List Report

As on date08/29/2026Currency—Report TemplateDefaultSearchResetExport

Night Audit29/08/2026

Total RevenueTSh 0

Cash in HandTSh 0

Net ProfitTSh 0

OutstandingTSh 11,372,900,000

Revenue Breakdown

REVENUE STREAM	AMOUNT
Rooms	TSh 0
Food & Beverage	TSh 0
Laundry	TSh 0
Fun Games	TSh 0
Total Revenue	TSh 0

Collections by Method

METHOD	AMOUNT
Total Collected	TSh 0

Occupancy

COUNT	VALUE
-------	-------

Reports.

Page 84 of 95

+255 700 000 000bookings@mrkhotels.comDodoma, TanzaniaMRK Grand Hotel

MRKHotels

PortalDashboardMy ProfileLogout

ENSW

My Profile

Account

Hotel Admin

Hotel_Admin

Active

Personal Information

First Name

Last Name

Email

Phone

ID Type

ID Number

admin@mrkhotels.test

None

Position

Profile Photo

Choose File

No file chosen

Save

System Information

These details are managed by the hotel and cannot be edited.

Staff / Registration No.

Role

Role Level

Department

Hotel

Sub-manager

-

hotel_admin

90

administration

MRK Grand Hotel

No

Last Login

Member Since

2026-08-29 02:10

2026-08-28

Profile.

12.3 Superadmin panel

TSCL Admin

Dashboard

Hotel Management

Reports

Plans & Features

My Profile

INTEGRATIONS

Integration Status

Back to Portal

Logout

Dashboard

SuperadminVictor Zacharia

Platform Overview

Monitor MRK Hotels platform activity.

22TOTAL HOTELS

22ACTIVE

0PENDING APPROVALS

0SUSPENDED

TZS 0PLATFORM GMV (30 DAYS)

0TRIALS EXPIRING (7D)

SaaS business

TZS 2,520,000MRR (MONTHLY RECURRING)

TZS 30,240,000ARR (ANNUAL RECURRING)

21PAYING HOTELS

21NEW SIGNUPS (30 DAYS)

0ACTIVE TRIALS

100%TRIAL → PAID CONVERSION

Platform GMV — last 6 months

Guest payments processed through the platform — not subsc...

Trials expiring soon

Platform Overview (`/superadmin`) — consolidated stats across all hotels.

Page 85 of 95

TSCL Admin

Dashboard

Hotel Management

Reports

Plans & Features

My Profile

INTEGRATIONS

Integration Status

Back to Portal

Logout

Hotel Management

Superadmin Victor Zacharia

Hotel Management

Onboard and manage hotels on the platform.

Refresh

New Hotel

Export

Search

Status

Plan

Search hotels...

All

All

Clear

HOTEL	CONTACT	LOCATION	STATUS	PLAN	STAFF	ROOMS	ACTIONS
MRK Hotels Platform platform	Platform Owner platform@mrkhotels.test	-	active	enterprise	3	0	Suspend
MRK Beach Resort Bagamoyo mrk-bagamoyo	MRK Hotels Group info@mrk-bagamoyo.mrkhotels.test	Bagamoyo, Tanzania	active	premium	31	73	Suspend
MRK Lodge Ngorongoro mrk-karatu	MRK Hotels Group info@mrk-karatu.mrkhotels.test	Karatu, Tanzania	active	premium	31	73	Suspend
MRK Hotel Shinyanga mrk-shinyanga	MRK Hotels Group info@mrk-shinyanga.mrkhotels.test	Shinyanga, Tanzania	active	premium	31	73	Suspend
MRK Hotel Bukoba mrk-bukoba	MRK Hotels Group info@mrk-bukoba.mrkhotels.test	Bukoba, Tanzania	active	premium	31	73	Suspend
MRK Hotel Musoma mrk-musoma	MRK Hotels Group info@mrk-musoma.mrkhotels.test	Musoma, Tanzania	active	premium	31	73	Suspend
MRK Hotel Songea mrk-songea	MRK Hotels Group info@mrk-songea.mrkhotels.test	Songea, Tanzania	active	premium	31	73	Suspend

Hotel Management — the tenant (hotel) directory.

TSCL Admin

Dashboard

Hotel Management

Reports

Plans & Features

My Profile

INTEGRATIONS

Integration Status

Back to Portal

Logout

Hotel Details

Superadmin Victor Zacharia

Back to Hotels

MRK Hotels Platform

platform · Location not specified
platform@mrkhotels.test

Hotel code

E. G. TI

Save code

Download Backup

STAFF

3

ROOMS

0

RESERVATIONS

0

OCCUPANCY

0%

REVENUE (30D)

TZS 0

Subscription

Plan: enterprise · Subscription Status: active

Plan

Enterprise

Subscription Status

Active

Update Subscription

Features

Toggle individual features on or off for this tenant. Changes are saved when you click "Update Subscription" above. When no features are set, all features from the plan are enabled.

Select All

Deselect All

Reset to Plan

Core Operations

Tenant detail — payment methods, tax IDs, branding.

Page 86 of 95

TSCL Admin

Dashboard

Hotel Management

Reports

Plans & Features

My Profile

INTEGRATIONS

Integration Status

← Back to Portal

Logout

Reports

SuperadminVictor Zacharia

Reports

Platform-wide reporting, KPIs and tenant performance.

Refresh

22

TOTAL HOTELS

22 active0 pending0 suspended

TZS 2,520,000

MRR (MONTHLY RECURRING)

ARR: TZS 30,240,000

665

TOTAL STAFF

1,533

TOTAL ROOMS

0

ACTIVE TRIALS

100%

TRIAL → PAID CONVERSION

21 paying / 22 total

Platform GMV — last 6 months

TZS 0 last 30d

Guest payments processed through the platform — not subscription revenue.

Mar 26

Apr 26

May 26

Jun 26

Jul 26

Aug 26

TZS 0

TZS 0

TZS 0

TZS 0

TZS 0

TZS 0

Tenant Performance

Refresh

Global reports across hotels.

TSCL Admin

Dashboard

Hotel Management

Reports

Plans & Features

My Profile

INTEGRATIONS

Integration Status

← Back to Portal

Logout

My Profile

SuperadminVictor Zacharia

My Profile

Account

Victor Zacharia

Superadmin

Active

Personal Information

First Name

Last Name

Email

Phone

superadmin@mrkhotels.com

ID Type

ID Number

Position

Profile Photo

None

Choose File

No file chosen

Save

System Information

These details are managed by the hotel and cannot be edited.

Staff / Registration No.

Role

Role Level

Department

-

Superadmin

100

administration

Hotel

Sub-manager

Last Login

Member Since

MRK Hotels Platform

No


2026-08-29 02:08

2026-08-28


Superadmin profile.

Page 87 of 95

12.4 Owner panel



Owner dashboard (`/owner`) — combined KPIs plus a per-hotel comparison table across the owner's hotels.



Hotel drill-down (`/owner/hotels/{id}`) — contact info, rooms, occupancy, in-house guests and revenue.

MRK Owner

Dashboard

Profile

Profile

Owner Victor Zacharia

My Profile

Account

Victor Zacharia

Owner

Active

Personal Information

First Name

Last Name

Email

owner@mrkhotels.test

Phone

ID Type

None

ID Number

Profile Photo

Choose File

No file chosen

Save

System Information

These details are managed by the hotel and cannot be edited.

Staff / Registration No.

-

Role

Owner

Last Login

2026-08-29 02:07

Member Since

2026-08-28

Change Password

Current password

Owner profile (`/owner/profile``) — editable personal info and password change via the shared ``authApi.updateProfile`` / ``ChangePasswordForm``.

12.5 Customer self-service portal

TSCL

Pricing Sign In Get Started

Simple, transparent pricing

Choose the plan that fits your hotel. Upgrade or downgrade anytime.

Starter

Single small hotel — essential front-desk and booking tools.

TZS 50,000 /month

INCLUDED FEATURES

✓ Reservations

✓ Rooms

✓ Guests

✓ Payments

✓ Booking Requests

✓ Staff Management

✓ Profile

✓ Reports

✓ Mixed Room-Type Booking

MOST POPULAR

Growth

Full-service hotel — F&B, housekeeping, inventory, procurement and messaging.

TZS 120,000 /month

INCLUDED FEATURES

✓ Reservations

✓ Rooms

✓ Guests

✓ Payments

✓ Booking Requests

✓ Staff Management

✓ Profile

✓ Reports

✓ Housekeepin

Enterprise

Multi-hotel chain — full platform with owner portal, analytics and all features.

TZS 300,000 /month

INCLUDED FEATURES

✓ Reservations

✓ Rooms

✓ Guests

✓ Payments

✓ Booking Requests

✓ Staff Management

✓ Profile

✓ Reports

✓ Housekeeping

✓ F&B Orders

Public pricing page (`/portal/pricing``) — SaaS tiers rendered from the ``plans`` database table.

Page 89 of 95



PricingSign InGet Started



Create your account

Start managing your hotel today

Hotel name

Full name

Email address

Phone number

City

Country

LEGAL & TAX REGISTRATION

TIN number (Tax Identification Number)

VRN number (VAT Registration, if applicable)

Business Registration Number

Country of registration

Self-service registration (`/portal/register``) — Google-style form with legal registration fields.



PricingSign InGet Started



Sign in

Use your TSCL account to continue

Email


Password

Continue

Forgot password?

Don't have an account? Create account

Customer login (`/portal/login``) — Google-style minimal form.



Customer dashboard (`/portal`) — trial banner, KPI cards, quick actions, account info.

13. SaaS Self-Service Portal

13.1 Architecture

The customer portal (`/portal`) is a separate entry point for hotels that sign up via the public pricing page. It uses two layouts:

- **MarketingLayout** — TSCL-branded public pages: pricing, registration, customer login
- **CustomerLayout** — superadmin-style panel for managing subscription, hotel details, staff, and payments

Self-service tenants are identified by the `self_service` boolean on the `tenants` table. The auth guard routes self-service users to `/portal` instead of `/app`.

13.2 Plans & pricing

Plans are stored in the `plans` database table and managed by the superadmin. The `config/plans.php` file is the seed source only.

Key model: `App\Models\Plan`

Column	Type	Description
<code>slug</code>	string (unique)	Plan identifier (e.g. <code>starter</code> , <code>growth</code> , <code>enterprise</code>)

Column	Type	Description
label	string	Display name
price_monthly	integer	Monthly price in TZS
price_yearly	integer	Yearly price (defaults to 10× monthly)
trial_days	integer	Free trial duration (default 14)
client_tier	enum	small , medium , large
features	json array	Feature keys included in this plan
is_active	boolean	Whether plan is available for new signups

API routes:

Method	Endpoint	Auth	Description
GET	/api/v1/public/plans	None	Public pricing (no-cache headers)
GET	/api/v1/plans	Superadmin	List all plans
POST	/api/v1/plans	Superadmin	Create plan
PUT	/api/v1/plans/{slug}	Superadmin	Update plan
DELETE	/api/v1/plans/{slug}	Superadmin	Delete plan (blocks if tenants assigned)

13.3 Registration flow

1. User visits /portal/pricing → selects a plan → clicks "Get Started"
2. Redirected to /portal/register?plan=starter (Google-style form, no cards)
3. Form collects: hotel name, contact, email, phone, city, country, TIN, VRN, business registration number, country of registration, password
4. Backend creates tenant with self_service = true , status = pending , subscription_status = trial , trial_ends_at = now + plan.trial_days
5. Subdomain auto-generated from hotel name (unique)
6. Success → redirect to /portal/login

13.4 Self-service payment flow

Customers can pay via mobile money (ClickPesa) or bank transfer:

Method	Provider	Flow
Mobile Money	M-Pesa, Tigo Pesa, Airtel Money, HaloPesa, EzyPesa	ClickPesa USSD push → customer confirms on phone
Bank Transfer	CRDB, NMB, Stanbic, ABSA, NCBA, Equity	Records payment as pending → TSCL admin confirms

API routes (portal):

Method	Endpoint	Auth	Description
GET	/api/v1/portal/subscription	Hotel admin	Show current plan and trial info
PUT	/api/v1/portal/subscription	Hotel admin	Change plan (upgrade/downgrade)
GET	/api/v1/portal/payments	Hotel admin	List payments (paginated, searchable)
POST	/api/v1/portal/payments/initiate	Hotel admin	Initiate ClickPesa or record bank transfer
GET	/api/v1/portal/payments/options	Hotel admin	Payment methods/providers

13.5 Feature gating

The `EnsureFeatureEnabled` middleware checks `Tenant::hasFeature($key)` against the plan's feature list. Features not in the plan are disabled for that tenant. Superadmin can override per-tenant via `TenantDetailPage`.

13.6 Layouts

Layout	Used by	Branding
<code>MarketingLayout.vue</code>	/portal/pricing , /portal/login , /portal/register	TSCL cloud logo, nav, footer
<code>CustomerLayout.vue</code>	/portal , /portal/hotel , /portal/subscription , /portal/staff , /portal/payments	Same style as superadmin sidebar
<code>StoreLayout.vue</code>	/app/* (hotel staff panel)	MRK Hotels branding (untouched)

14. i18n (Internationalization)**14.1 Locale files**

File	Language	Keys
src/locales/en.json	English	~2,200 keys
src/locales/sw.json	Swahili	~2,200 keys

14.2 Convention

All user-facing strings are wrapped in `$t('namespace.key')` or `t('namespace.key')` (script). The `useI18n()` composable is imported in `<script setup>` for script-level strings.

Key namespaces: - `superadmin.*` — superadmin panel (tenant management, plans, reports, features) - `common.*` — shared labels (search, loading, save, cancel, etc.) - `auth.*` — login/register forms - `nav.*` — navigation labels - `reservations.*`, `rooms.*`, `payments.*`, etc. — hotel panel modules

14.3 Adding a new string

1. Add the key to both `en.json` and `sw.json` under the appropriate namespace
2. Reference it in templates: `{{ $t('namespace.key') }}` or `:placeholder="$t('namespace.key')"`
3. Reference it in scripts: `t('namespace.key')` after `const { t } = useI18n()`

Changelog

v1.6 (21 August 2026)

- **SaaS self-service portal:** Customer registration, login, dashboard, subscription management, payments (ClickPesa mobile money + bank transfer)
- **Public pricing page:** DB-backed plans rendered from `plans` table with no-cache headers
- **Plan management:** Superadmin CRUD for plans with inline editing (price, trial days, features), dynamic plan filters from DB
- **Google-style auth:** Login and registration pages redesigned with minimal white background, password eye/slash toggle
- **Legal registration:** Registration collects TIN, VRN, business registration number, country of registration (replaces subdomain)
- **Portal payments:** `PortalPaymentController` with ClickPesa mobile money (M-Pesa, Tigo Pesa, Airtel Money, HaloPesa, EzyPesa) and bank transfer recording
- **i18n:** 55+ new keys in `en.json` and `sw.json` — all hardcoded strings in `ReportsPage`, `PlansPage`, `TenantListPage`, `TenantDetailPage` now dynamic
- **Superadmin integration dashboard:** Read-only view of Booking.com/QuickBooks connection status per hotel
- **Self-service tenant visibility:** Self-service tenants appear in superadmin panel with "Self Service" and "Trial" badges

v1.5 (18 August 2026)

- **Mobile app:** NativePHP Mobile 4.2 Android app with 8 pages (Login, Dashboard, Attendance, Housekeeping, Rooms, Reservations, Orders, Profile)
- **Soft-delete:** Reservations and guests now use `SoftDeletes` — data is archived, not destroyed

- **Security hardening:** ForceHTTPS middleware, CORS lockdown (env-driven), password policy (`mixedCase()` -> `numbers()` -> `uncompromised()`), payment refund gated to manager+
- **Infrastructure:** `docker-compose.yml` , `netlify.toml` , `.env.example` (both apps), GitHub Actions CI
- **Catastrophic fixes:** Vue 3.5.41 stable (downgraded from Vue 4 RC), 87 frontend tests (418 total)
- **API fixes:** `OrderController::update()` no longer auto-sets `paid` , `HousekeepingController::update()` strips `status` / `assigned_to`
- **Developer docs:** Updated to v1.5 with mobile app section

v1.4 (15 August 2026)

- Initial developer documentation
- Hotel code format: `{PREFIX}-{CODE}-{YYYY}-{SEQ}{CHECK}`
- HMAC-SHA256 check character system

End of developer documentation — © MRK Hotels.