EXPERIMENT – 1

ARDUINO UNO-BASED SMART HOME SAFETY AND OCCUPANCY MONITORING SYSTEM USING GAS, PIR AND ULTRASONIC SENSORS

Code:

```
#define GAS_PIN A0
#define PIR_PIN 2
#define TRIG_PIN 8
#define ECHO_PIN 9
#define BUZZER 10
#define LED 11

void setup()
{
  Serial.begin(9600);

  pinMode(PIR_PIN, INPUT);
  pinMode(TRIG_PIN, OUTPUT);
  pinMode(ECHO_PIN, INPUT);
  pinMode(BUZZER, OUTPUT);
  pinMode(LED, OUTPUT);
}

void loop()
{
  int gas = analogRead(GAS_PIN);
  int motion =
  digitalRead(PIR_PIN);

  digitalWrite(TRIG_PIN, LOW);
  delayMicroseconds(2);
```

```
digitalWrite(TRIG_PIN, HIGH);
delayMicroseconds(10);

digitalWrite(TRIG_PIN, LOW);

long duration = pulseIn(ECHO_PIN,
HIGH); float distance = duration * 0.0343 /
2;

if (gas > 500)
digitalWrite(BUZZER, HIGH);
else
  digitalWrite(BUZZER, LOW);

digitalWrite(LED, motion);

Serial.print("Gas Level: ");
Serial.println(gas);

Serial.print("Motion: ");

if (motion)
Serial.println("DETECTED");
else
  Serial.println("NOT DETECTED");

Serial.print("Distance: ");
Serial.print(distance, 1);
Serial.println(" cm");


if (gas > 500)
Serial.println("GAS ALERT!");
else if (motion)
```


```
  Serial.println("OCCUPANCY DETECTED");
 else
  Serial.println("SYSTEM SAFE");

 Serial.println("                    ");

 delay(1000);
}
```

Output





Reflection

Through this experiment, I learned how to acquire temperature data using an ADC and control fan speed using PWM generated by timer interrupts. I understood how temperature readings can be used to adjust the fan speed automatically in an industrial HVAC system. This experiment helped me gain practical knowledge of ADC, timers, interrupts, and PWM control, which are important for efficient temperature regulation
and energy saving.