




കേരള സ്റ്റേറ്റ് റൂട്രോണിക്സ്

**Faculty Development
Program - Day**

03

Organised by Groware Education
Solutions, Principal Affiliate of
Kerala State Rutronix






String Functions

- **replace(old, new [,max])** – Returns a copy of the string with all the occurrences of substring old is replaced by new. The max is optional and if it is specified, the first occurrences specified in max are replaced.

Example Program

```
# Demo of replace(old, new[,max])  
s="This is very new. This is good"  
print(s.replace('is', 'was'))  
print(s.replace('is', 'was', 2))
```



String Functions

- **count(str,beg=0,end=len(string))** – Returns the number of occurrences of str in the range beg and end.

Example Program

```
# Demo of count(str,beg=0,end=len(string))  
s="This is Python Programming"  
print(s.count('i',0,10))  
print(s.count('i',0,25))
```



String Functions

- **`index(str,beg=0,end=len(string))`** – Finds the index position of the item.

Example Program

```
# Demo of index(str,beg=0,end=len(string))  
s="This is Python Programming"  
print(s.index('thon',0,25))  
print(s.index('thy'))
```





String Functions

- **startswith(substring, beg=0, end=len(string))**- It returns True if the string begins with the specified substring, otherwise return False.

Example Program

```
# Demo of  
    startswith(substring,beg=0,end=len(string))  
s="Python programming is fun"  
print(s.startswith('is',10,21))  
s="Python programming is fun"  
print(s.startswith('is',19,25))
```



String Functions

- **endswith(substring, beg=0,end=len(string))-** It returns True if the string ends with the specified suffix, otherwise return False.

Example Program

```
# Demo of  
endswith(substring,beg=0,end=len(string))  
s="Python programming is fun"  
print(s.endswith('is',10,21))  
s="Python programming is fun"  
print(s.endswith('is',0,25))
```



String Functions

- **isalpha()** – Returns true if string has at least 1 character and all characters are alphabetic and false otherwise.

Example Program

```
# Demo of isalpha()
s="This is Python1234"
print(s.isalpha())
s="Python"
print(s.isalpha())
```



String Functions

- **isdigit()** – Returns true if string contains only digits and false otherwise.

Example Program

```
# Demo of isdigit()  
s="***Python1234"  
print(s.isdigit())  
s="123456"  
print(s.isdigit())
```




String Functions

- **isalnum()**- Returns true if string has at least 1 character and all characters are alphanumeric and false otherwise.

Example Program

```
# Demo of isalnum()  
s="***Python1234"  
print(s.isalnum())  
s="Python1234"  
print(s.isalnum())
```



String Functions

- **islower()** – Returns true if string has at least 1 cased character and all cased characters are in lowercase and false otherwise.

Example Program

```
# Demo of islower()  
s="Python Programming"  
print(s.islower())  
s="python programming"  
print(s.islower())
```



String Functions

- **isupper()** – Returns true if string has at least one cased character and all cased characters are in uppercase and false otherwise.

Example Program

```
# Demo of isupper()
s="Python Programming"
print(s.isupper())
s="PYTHON PROGRAMMING"
print(s.isupper())
```



String Functions

- **join(seq)** - Returns a string in which the string elements of sequence have been joined by a separator.

Example Program

```
# Demo of join(seq)
```

```
s="-"
```


```
seq=("Python", "Programming")
```

```
print(s.join(seq))
```

```
s="*"
```

```
seq=("Python", "Programming")
```

```
print(s.join(seq))
```



String Functions

- **split()** - Returns a **list** of all the words in the string, using str as the separator (splits on all whitespace if left unspecified).
- **Example Program**

```
s="Python programming is fun"
```

```
print(s.split(' '))
```

```
s="Python*programming*is*fun"
```

```
print(s.split('*'))
```

```
s="Python*programming*is*fun"
```

```
print(s.split('*',2))
```