

# ViennaMath 1.0.0

---

User Manual



Institute for Microelectronics  
Gußhausstraße 27-29 / E360  
A-1040 Vienna, Austria/Europe



Institute for Analysis and Scientific Computing  
Wiedner Hauptstraße 8-10 / E101  
A-1040 Vienna, Austria/Europe



*Author and Project Head:*

Karl Rupp

Institute for Microelectronics  
Vienna University of Technology  
Gußhausstraße 27-29 / E360  
A-1040 Vienna, Austria/Europe

Phone   +43-1-58801-36001  
FAX     +43-1-58801-36099  
Web     <http://www.iue.tuwien.ac.at>

Institute for Analysis and Scientific Computing  
Vienna University of Technology  
Wiedner Hauptstraße 8-10 / E101  
A-1040 Vienna, Austria/Europe

Phone   +43-1-58801-10101  
Web     <http://www.asc.tuwien.ac.at>

# Contents

<b>Introduction</b>	<b>1</b>
<b>1 Installation</b>	<b>2</b>
1.1 Dependencies . . . . .	2
1.2 Generic Installation of ViennaMath . . . . .	2
1.3 Building the Examples and Tutorials . . . . .	2
<b>2 Basic Types</b>	<b>5</b>
2.1 Types Evaluated at Runtime . . . . .	5
2.2 Types Evaluated at Compiletime . . . . .	8
<b>3 Expression Manipulation</b>	<b>9</b>
3.1 Evaluation . . . . .	9
3.2 Substitution . . . . .	9
3.3 Expansion . . . . .	9
3.4 Simplification . . . . .	9
3.5 Differentiation . . . . .	9
3.6 Integration . . . . .	9
3.7 Extract Coefficient . . . . .	9
3.8 Drop Dependent Terms . . . . .	9
<b>4 Advanced Features</b>	<b>10</b>
4.1 Function Symbols . . . . .	10
4.2 Integration Symbols . . . . .	10
4.3 $\text{\LaTeX}$ Output . . . . .	10
<b>5 Benchmark Results</b>	<b>11</b>
<b>Change Logs</b>	<b>12</b>
<b>License</b>	<b>13</b>



# Introduction

The beginning of the computing era is inherently linked with the use of computing devices for numerical algorithms. While the first implementations had been carried out in assembly language, the FORTRAN language then provided a means for efficiently abstracting the underlying hardware. This approach to programming is still common for the implementation of numerical algorithms today: Mathematical primitives such as polynomials or functions are in one way or another represented as an array of numbers already in user code. The mathematical meaning of these numbers is, if at all, only implicitly deducible for a programmer.

Abstraction facilities provided by modern programming languages such as C++ are much more powerful and mature compared to an abstraction at an array level. However, implementation guidelines in numerical textbooks written in the past cannot reflect the current state-of-the-art in programming, thus algorithms are often still implemented without making use of additional abstraction mechanisms. One of the reasons is that first attempts of using object-oriented programming have reported poor performance due to additional indirections at runtime. However, this issue (and several others) have been addressed by language improvements and/or programming techniques.

The aim of `ViennaMath` is to show by example that preserving the mathematical abstraction by means of a symbolic math engine can make code much more readable without sacrificing performance. Even though `ViennaMath` makes use of object-oriented programming, certain calculations and optimizations can already be carried out already at compile time, thus eliminating many expensive indirections at runtime. Consequently, the process of hand-tuning code, i.e. the use of information already available at compile time, is shifted from the user to the compiler. This increases productivity without reducing performance.

# Chapter 1

## Installation

This chapter shows how `ViennaMath` can be integrated into a project and how the examples are built. The necessary steps are outlined for several different platforms, but we could not check every possible combination of hardware, operating system, and compiler. If you experience any trouble, please write to the mailing list at

`viennamath-support@lists.sourceforge.net`

### 1.1 Dependencies

- A recent C++ compiler (e.g. GCC version 4.2.x or above and Visual C++ 2008 are known to work)
- CMake [1] as build system (optional, but recommended for building the examples)

### 1.2 Generic Installation of ViennaMath

Since `ViennaMath` is a header-only library, it is sufficient to copy the `viennamath/` folder either into your project folder or to your global system include path. On Unix based systems, this is often `/usr/include/` or `/usr/local/include/`.

On Windows, the situation strongly depends on your development environment. Please consult the documentation of your compiler or development environment on how to set the include path correctly. The include paths in Visual Studio are usually something like `C:\Program Files\Microsoft Visual Studio 9.0\VC\include` and can be set in `Tools -> Options -> Projects and Solutions -> VC++-Directories`.

### 1.3 Building the Examples and Tutorials

An overview of available examples and their purpose is given Tab. 1.1. For building the examples, we suppose that CMake is properly set up on your system. In the following, instructions on how to build the examples on different platforms are given.

File	Purpose
<code>basic.cpp</code>	Basic handling of ViennaMath expressions
<code>latex_output.cpp</code>	How to use and customize the $\text{\LaTeX}$ translator
<code>model_benchmark.cpp</code>	An example of how ViennaMath can eliminate dependencies in an expression
<code>newton_solve.cpp</code>	A Newton solver using ViennaMath expressions
<code>traversal.cpp</code>	How to traverse a ViennaMath expressions
<code>substitute.cpp</code>	Substitute terms in a ViennaMath expressions
<code>vector_expr.cpp</code>	Explains the use of vector expressions

Table 1.1: Overview of the examples in the `examples/` folder

### 1.3.1 Linux

To build the examples, open a terminal and change to:

```
$> cd /your-ViennaMath-path/build/
```

Execute

```
$> cmake ..
```

to obtain a Makefile and type

```
$> make
```

to build the examples. If desired, one can build each example separately instead:

```
$> make basic           #builds the 'basic' tutorial
$> make substitute      #builds the 'substitute' tutorial
```

Speed up the building process by using jobs, e.g. `make -j4`.



### 1.3.2 Mac OS X

The tools mentioned in Section 1.1 are available on Macintosh platforms too. For the GCC compiler the Xcode [2] package has to be installed. To install CMake, external portation tools such as Fink [3], DarwinPorts [4], or MacPorts [5] have to be used.

The build process of ViennaMath is similar to Linux.

### 1.3.3 Windows

In the following the procedure is outlined for Visual Studio: Assuming that an OpenCL SDK and CMake is already installed, Visual Studio solution and project files can be created using CMake:

- Open the CMake GUI.
- Set the ViennaMath base directory as source directory.

- Set the `build/` directory as build directory.
- Click on 'Configure' and select the appropriate generator (e.g. Visual Studio 9 2008).
- Click on 'Configure' again.
- Click on 'Generate' in order to let CMake generate the project files for you.
- The project files can now be found in the `ViennaMath` build directory, where they can be opened and compiled with Visual Studio (provided that the include and library paths are set correctly, see Sec. 1.2).



# Chapter 2

## Basic Types

Since C++ is a statically typed language [CITE], the basic mathematical building blocks such as constants or variables are represented as types. The possibility of manipulations at compiletime or runtime is accomplished by essentially two different implementations of these primitives. Basic types for runtime evaluations are discussed first, since their interface and handling is potentially more familiar to average C++ programmers. Sec. 2.2 then provides an overview of the basic types used for compiletime manipulations.

Note that all types reside in namespace `viennamath`. The namespace is not written explicitly in the following, thus either `viennamath::` prefixes or certain `using` declarations need to be added by the user in order to make the code valid.



### 2.1 Types Evaluated at Runtime

Common to all types represented at runtime is that they inherit from the same abstract base class and can thus be accessed and manipulated using a pointer to that interface. The interface is not fixed a-priori and can be adjusted via a template parameter, which is in the following called `InterfaceType`. Library users should use the expression wrapper objects discussed next, because it provides an automatic memory management and does not involve complicated pointer manipulation.

#### 2.1.1 Expression Wrapper `expr`

The main expression wrapper type in `ViennaMath` is `rt_expr<InterfaceType>`. The prefix `rt` refers to *runtime* and aids in distinguishing between types processed at runtime, and types processed at compiletime. In most cases, the default parameter for the runtime interface `InterfaceType` is used, in which case users would have to write

```
rt_expr<> my_expression = /* any expression here */;
```

for instantiating an expression wrapper object `my_expression`. In order to avoid users from having to write the `rt_` and the lower-than and greater-than signs, there is a convenience shortcut `expr` provided. The previous code line thus becomes

```
expr my_expression = /* any expression here */;
```

The `expr`-type can be evaluated and manipulated using operator overloads. For example, the addition of two expressions is accomplished by

```
expr ex1 = /* any expression here */;
expr ex2 = /* any expression here */;
expr result = ex1 + ex2;
```

The initialization of expression objects is accomplished by any of the fundamental types discussed in the next subsections. Note that objects of type `expr` are default-constructible, yet they can only be used after an expression has been assigned to them.

## 2.1.2 Constant

Constants in C++ have their own types `double`, `long`, etc. These types can be used with `ViennaMath` directly. In order to also represent constants using a pointer to the runtime interface, a separate class `rt_constant<NumericT, InterfaceType>` is provided. The template parameter `NumericT` denotes the underlying numerical type such as `double`, `long`, or high precision types. There is again a convenience shortcut `constant` provided for the case of the commonly used `rt_constant<double>`, hence a user can write code such as

```
constant pi = 3.1415;
constant pi_squared = pi * pi;
```

An exemplary use with the expression wrapper `expr` is

```
constant pi = 3.1415;
expr pi_squared = pi * pi;
expr result = pi + pi_squared;
```

## 2.1.3 Variable

A mathematical variable in `ViennaMath` is modeled by `rt_variable<InterfaceType>`. and refers to the mapping

$$(x_0, x_1, \dots, x_{N-1}) \mapsto x_j,$$

where the value of  $j$  is provided to the constructor of the variable. By default, the index  $j = 0$  is used. Any vector type offering access to its values using `operator[]` such as `std::vector<T>` can be used for an evaluation of the variable or a compounded expression.

A simple example leading to the mapping  $(x, y) \mapsto x(y + \pi)$  using the types introduced so far is as follows:

```
constant pi = 3.1415;
variable x(0);
variable y(1);
expr f = x * (y + pi);
```

An evaluation of `f` at  $(1, 2)$  can be accomplished by using evaluation overload the parenthesis operator and the `ViennaMath` helper function `make_vector()`, which conveniently creates a suitable vector for evaluation.

```
std::cout << f( make_vector(1,2) ) << std::endl; //prints 5.1415
```

### 2.1.4 Unary Expression

Mappings of the form  $x \mapsto \sin(x)$  are modeled by the `rt_unary_expr<InterfaceType>` class. Thus, they represent a unary function acting on a constant, a variable or an expression. The following unary functions are provided:

Name	ViennaMath Function	Name	ViennaMath Function
Exponential	<code>exp()</code>	Modulus	<code>fabs()</code>
Sine	<code>sin()</code>	Square Root	<code>sqrt()</code>
Cosine	<code>cos()</code>	Natural Logarithm	<code>log()</code>
Tangent	<code>tan()</code>	Logarithm, Base 10	<code>log10()</code>

Function names are intentionally chosen such that they coincide with the standard functions for floating point types. When calling these functions with floating point types, compilation might fail due to ambiguity. In such case the namespace should be specified explicitly.



Typically, unary expressions are not instantiated explicitly by the library user. Instead, they are generated implicitly by one of the unary functions and then assigned to an object of type `expr` as in the following example:

```
variable x;  
expr g = sin(2.0 * x); // wraps a unary expression into 'g'
```

### 2.1.5 Binary Expression

Similar to unary expressions, binary expressions at runtime are mostly handled in the background only. They are created whenever one of the operator overloads for addition, subtraction, multiplication, or division is triggered. In particular, the argument `2.0 * x` to `sin()` in

```
expr g = sin(2.0 * x);
```

is a binary expression. Binary expressions are central for compile time evaluations in Sec. 2.2.

### 2.1.6 Expression Vector

For the cases where a vector-valued expression is required, a user can either instantiate a vector of `expr`, which allows for storing multiple scalar-valued function only, or use the `rt_vector_expr<InterfaceType>` class provided by ViennaMath. A convenience shortcut `vector_expr` is provided. The benefit of using the `vector_expr` class is that it provides the usual operator overloads directly:

```
variable x(0), y(1);  
vector_expr vec(3); vec[0] = x; vec[1] = y; vec[2] = x + y;  
vector_expr vec2 = x * vec + y * vec;
```

The dot-product of two vector-valued expressions is provided as well:

```
expr h = vec * vec2;
```

## **2.2 Types Evaluated at Compiletime**

### **2.2.1 Constant**

### **2.2.2 Variable**

### **2.2.3 Unary Expression**

### **2.2.4 Binary Expression**

### **2.2.5 Expression Vector**

## **Chapter 3**

# **Expression Manipulation**

**3.1 Evaluation**

**3.2 Substitution**

**3.3 Expansion**

**3.4 Simplification**

**3.5 Differentiation**

**3.6 Integration**

**3.7 Extract Coefficient**

**3.8 Drop Dependent Terms**

## **Chapter 4**

# **Advanced Features**

### **4.1 Function Symbols**

### **4.2 Integration Symbols**

### **4.3 L<sup>A</sup>T<sub>E</sub>X Output**

## **Chapter 5**

# **Benchmark Results**

Give an idea of compile time performance.

# Change Logs

## **Version 1.0.0**

First release



# License

Copyright (c) 2012, Institute for Microelectronics and Institute for Analysis and Scientific Computing, TU Wien

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

# Bibliography

- [1] “CMake.” [Online]. Available: <http://www.cmake.org/>
- [2] “Xcode Developer Tools.” [Online]. Available: <http://developer.apple.com/technologies/tools/xcode.html>
- [3] “Fink.” [Online]. Available: <http://www.finkproject.org/>
- [4] “DarwinPorts.” [Online]. Available: <http://darwinports.com/>
- [5] “MacPorts.” [Online]. Available: <http://www.macports.org/>