

Escaneo de una red y un host con NMAP

Primero escaneamos la red en busca de hosts.

```
(victor@victor)-[~]
$ sudo nmap -sn 192.168.100.0/24
Starting Nmap 7.95 ( https://nmap.org ) at 2025-10-27 09:08 CET
Nmap scan report for 192.168.100.1
Host is up (0.0012s latency).
MAC Address: 00:50:56:C0:00:13 (VMware)
Nmap scan report for 192.168.100.130
Host is up (0.00065s latency).
MAC Address: 00:0C:29:63:9E:B3 (VMware)
Nmap scan report for 192.168.100.254
Host is up (0.00063s latency).
MAC Address: 00:50:56:F5:BC:1E (VMware)
Nmap scan report for 192.168.100.129
Host is up.
Nmap done: 256 IP addresses (4 hosts up) scanned in 27.91 seconds
```

Encontramos un host activo con la IP 192.168.100.130.

Escaneamos el host descubierto para ver que puertos tiene abiertos.

```
(victor@victor)-[~]
$ nmap 192.168.100.130
Starting Nmap 7.95 ( https://nmap.org ) at 2025-10-27 09:09 CET
Nmap scan report for 192.168.100.130
Host is up (0.0024s latency).
Not shown: 977 closed tcp ports (reset)
PORT      STATE SERVICE
21/tcp    open  ftp
22/tcp    open  ssh
23/tcp    open  telnet
25/tcp    open  smtp
53/tcp    open  domain
80/tcp    open  http
111/tcp   open  rpcbind
139/tcp   open  netbios-ssn
445/tcp   open  microsoft-ds
512/tcp   open  exec
513/tcp   open  login
514/tcp   open  shell
1099/tcp  open  rmiregistry
1524/tcp  open  ingreslock
2049/tcp  open  nfs
2121/tcp  open  ccproxy-ftp
3306/tcp  open  mysql
5432/tcp  open  postgresql
5900/tcp  open  vnc
6000/tcp  open  X11
6667/tcp  open  irc
8009/tcp  open  ajp13
8180/tcp  open  unknown
MAC Address: 00:0C:29:63:9E:B3 (VMware)

Nmap done: 1 IP address (1 host up) scanned in 13.25 seconds
```

PORT	STATE	SERVICE
21/tcp	open	ftp
22/tcp	open	ssh
23/tcp	open	telnet
25/tcp	open	smtp
53/tcp	open	domain
80/tcp	open	http
111/tcp	open	rpcbind
139/tcp	open	netbios-ssn
445/tcp	open	microsoft-ds
512/tcp	open	exec
513/tcp	open	login
514/tcp	open	shell
1099/tcp	open	rmiregistry
1524/tcp	open	ingreslock
2049/tcp	open	nfs
2121/tcp	open	ccproxy-ftp
3306/tcp	open	mysql
5432/tcp	open	postgresql
5900/tcp	open	vnc
6000/tcp	open	X11
6667/tcp	open	irc
8009/tcp	open	ajp13
8180/tcp	open	unknown

Hacemos un scan de sus servicios y versiones de los mismos.

```
(victor@victor)-[~]
$ sudo nmap -sV 192.168.100.130
Starting Nmap 7.95 ( https://nmap.org ) at 2025-10-27 09:12 CET
Nmap scan report for 192.168.100.130
Host is up (0.0027s latency).
Not shown: 977 closed tcp ports (reset)
PORT      STATE SERVICE      VERSION
21/tcp    open  ftp          vsftpd 2.3.4
22/tcp    open  ssh          OpenSSH 4.7p1 Debian 8ubuntu1 (protocol 2.0)
23/tcp    open  telnet       Linux telnetd
25/tcp    open  smtp         Postfix smtpd
53/tcp    open  domain       ISC BIND 9.4.2
80/tcp    open  http         Apache httpd 2.2.8 ((Ubuntu) DAV/2)
111/tcp   open  rpcbind      2 (RPC #100000)
139/tcp   open  netbios-ssn  Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
445/tcp   open  netbios-ssn  Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
512/tcp   open  exec         netkit-rsh rexecd
513/tcp   open  login?
514/tcp   open  shell        Netkit rshd
1099/tcp  open  java-rmi     GNU Classpath grmiregistry
1524/tcp  open  bindshell    Metasploitable root shell
2049/tcp  open  nfs          2-4 (RPC #100003)
2121/tcp  open  ftp          ProFTPD 1.3.1
3306/tcp  open  mysql        MySQL 5.0.51a-3ubuntu5
5432/tcp  open  postgresql   PostgreSQL DB 8.3.0 - 8.3.7
5900/tcp  open  vnc          VNC (protocol 3.3)
6000/tcp  open  X11          (access denied)
6667/tcp  open  irc          UnrealIRCd
8009/tcp  open  ajp13        Apache Jserv (Protocol v1.3)
8180/tcp  open  http         Apache Tomcat/Coyote JSP engine 1.1
MAC Address: 00:0C:29:63:9E:B3 (VMware)
Service Info: Hosts: metasploitable.localdomain, irc.Metasploitable.LAN; OSs: Unix, Linux; CPE: cpe:/o:linux:linux_kernel

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 65.69 seconds
```

21/tcp	open	ftp	vsftpd 2.3.4
--------	------	-----	--------------

22/tcp	open	ssh	OpenSSH 4.7p1 Debian 8ubuntu1 (protocol 2.0)
23/tcp	open	telnet	Linux telnetd
25/tcp	open	smtp	Postfix smtpd
53/tcp	open	domain	ISC BIND 9.4.2
80/tcp	open	http	Apache httpd 2.2.8 ((Ubuntu) DAV/2)
111/tcp	open	rpcbind	2 (RPC #100000)
139/tcp	open	netbios-ssn	Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
445/tcp	open	netbios-ssn	Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
512/tcp	open	exec	netkit-rsh rexecd
513/tcp	open	login?	
514/tcp	open	shell	Netkit rshd
1099/tcp	open	java-rmi	GNU Classpath grmiregistry
1524/tcp	open	bindshell	Metasploitable root shell
2049/tcp	open	nfs	2-4 (RPC #100003)
2121/tcp	open	ftp	ProFTPD 1.3.1
3306/tcp	open	mysql	MySQL 5.0.51a-3ubuntu5
5432/tcp	open	postgresql	PostgreSQL DB 8.3.0 - 8.3.7
5900/tcp	open	vnc	VNC (protocol 3.3)
6000/tcp	open	X11	(access denied)
6667/tcp	open	irc	UnrealIRCd
8009/tcp	open	ajp13	Apache Jserv (Protocol v1.3)
8180/tcp	open	http	Apache Tomcat/Coyote JSP engine 1.1

Escaneamos una vez más para ver sus sistema operativo y versión.

```
(victor@victor)-[~]
$ sudo nmap -O 192.168.100.130
Starting Nmap 7.95 ( https://nmap.org ) at 2025-10-27 09:10 CET
Nmap scan report for 192.168.100.130
Host is up (0.00067s latency).
Not shown: 977 closed tcp ports (reset)
PORT      STATE SERVICE
21/tcp    open  ftp
22/tcp    open  ssh
23/tcp    open  telnet
25/tcp    open  smtp
53/tcp    open  domain
80/tcp    open  http
111/tcp   open  rpcbind
139/tcp   open  netbios-ssn
445/tcp   open  microsoft-ds
512/tcp   open  exec
513/tcp   open  login
514/tcp   open  shell
1099/tcp  open  rmiregistry
1524/tcp  open  ingreslock
2049/tcp  open  nfs
2121/tcp  open  ccproxy-ftp
3306/tcp  open  mysql
5432/tcp  open  postgresql
5900/tcp  open  vnc
6000/tcp  open  X11
6667/tcp  open  irc
8009/tcp  open  ajp13
8180/tcp  open  unknown
MAC Address: 00:0C:29:63:9E:B3 (VMware)
Device type: general purpose
Running: Linux 2.6.X
OS CPE: cpe:/o:linux:linux_kernel:2.6
OS details: Linux 2.6.9 - 2.6.33
Network Distance: 1 hop

OS detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 14.61 seconds
```

Esta corriendo Linux con kernel 2.6.

Escaneamos vulnerabilidades en la maquina.

```
(victor@victor)-[~]
$ sudo nmap --script vuln 192.168.100.130
Starting Nmap 7.95 ( https://nmap.org ) at 2025-10-27 09:17 CET
Stats: 0:04:49 elapsed; 0 hosts completed (1 up), 1 undergoing Script Scan
NSE Timing: About 99.86% done; ETC: 09:22 (0:00:00 remaining)
Nmap scan report for 192.168.100.130
Host is up (0.0036s latency).
Not shown: 977 closed tcp ports (reset)
PORT      STATE SERVICE
21/tcp    open  ftp
| ftp-vsftpd-backdoor:
|   VULNERABLE:
|     vsFTPD version 2.3.4 backdoor
|       State: VULNERABLE (Exploitable)
|       IDs:  CVE:CVE-2011-2523  BID:48539
|         vsFTPD version 2.3.4 backdoor, this was reported on 2011-07-04.
|       Disclosure date: 2011-07-03
|       Exploit results:
|         Shell command: id
|         Results: uid=0(root) gid=0(root)
|       References:
|         https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2011-2523
|         https://github.com/rapid7/metasploit-framework/blob/master/modules/exploits/unix/ftp/vsftpd_234_backdoor.rb
|         http://scarybeastsecurity.blogspot.com/2011/07/alert-vsftpd-download-backdoored.html
|         https://www.securityfocus.com/bid/48539
|_
22/tcp    open  ssh
23/tcp    open  telnet
25/tcp    open  smtp
| smtp-vuln-cve2010-4344:
|_ The SMTP server is not Exim: NOT VULNERABLE
53/tcp    open  domain
80/tcp    open  http
| http-slowloris-check:
|   VULNERABLE:
|     Slowloris DOS attack
|       State: LIKELY VULNERABLE
|       IDs:  CVE:CVE-2007-6750
|         Slowloris tries to keep many connections to the target web server open and hold
|         them open as long as possible. It accomplishes this by opening connections to
|         the target web server and sending a partial request. By doing so, it starves
|         the http server's resources causing Denial Of Service.
|
|       Disclosure date: 2009-09-17
|       References:
|         http://ha.ckers.org/slowloris/
|         https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-6750
|_ http-trace: TRACE is enabled
```

Encontramos numerosas vulnerabilidades. Una de ellas en está en el puerto 21 FTP, se trata de un backdoor en el servicio vsFTPd version 2.3.4 que se puede explotar por parte de los atacantes.