

# Check-point

## Session 6: HTML/CSS/Layout

1) In a HTML file, create 2 `<p>` tags with content of your choice. Use CSS to change the text color of the tags into red.

2) In a HTML file, create 2 `<div>` tags with content of your choice. Use CSS to change only the second tag's background color to `#00FF00`

3) In a HTML file, create one `<p>` tag, one `<h1>` tag and one `<h2>` tag with arbitrary content. Use CSS to change font-size of `<p>` tag and `<h2>` tag to 24px

4) Given the following code: <https://codepen.io/mindxvn/pen/gOYrWwr>. **Without changing any CSS and do not change the property of the current CSS**, turn the page into this

I'm div

I'm p

5) Given the following code: <https://codepen.io/mindxvn/pen/XWrdRpx>. **Without changing any HTML**, turn the page into this

**I'm Mr.Black**

**I'm Mrs.Blue**

6) In a HTML file, add 2 `<a>` tags with different hrefs, no classes, no id. One with `target="_blank"` and one does not, change the text of `<a>` tag with `target="_blank"` color into yellow

7) In a HTML file, add an `<ul>` tag, inside this `<ul>` tag add 3 `<li>` tags, add an `<ol>` tag, inside this `<ol>` tag add 4 `<li>` tags. Without adding classes nor ids, change the font-weight of the `li` inside `ul` tag to bold

9) Giving the following HTML code

```
<div class="item">
```

```
<span>Title 1</span>
```

```
<div>
```

```
<span>Content 1</span>
```

```
<div>
```

```
</div>
```

```
<div class="item">
```

```
<span>Title 2</span>
```

```
<div>
```

```
<span>Content 2</span>
```

```
</div>
```

```
</div>
```

Without adding any HTML, inside **each `div.item`**, change the first span's font-size into 18px, change the second span font-style into italic

*Hint:*

*The child selectors or direct child selector can be cascaded. For example:*

```
ul li span { ... }
```

```
ul > li > a { ... }
```

-