Lecture 1
Introduction

Computer Networks

The slides are made by J.F Kurose and K.W. Ross,
adapted by Phuong Vo and Tan Le

Instructor: Le Duy Tan, Ph.D.

Email: tg_leduytan_cntt@tdtu.edu.vn

Contents

Contents

“Fun” internet appliances

IP picture frame
http://www.ceiva.com/

Web-enabled toaster +
weather forecaster

Tweet-a-watt:
monitor energy use

Internet
refrigerator

Slingbox: watch,
control cable TV remotely

Internet phones

WHAT IS THE INTERNET?

What's the Internet: "nuts and bolts" view

- millions of connected computing devices:
  - *hosts* = *end systems*
  - running *network apps*
- *communication links*
  - fiber, copper, radio, satellite
  - transmission rate: *bandwidth*
- *Packet switches:* forward packets (chunks of data)
  - *routers* and *switches*



What's the Internet?

- *Internet:* "network of networks"
  - Interconnected ISPs
- *protocols* control sending, receiving of msgs
  - e.g., TCP, IP, HTTP, Skype, 802.11
- *Internet standards*
  - RFC: Request for comments
  - IETF: Internet Engineering Task Force



ANYTHING ELSE?

What's a protocol?

human protocols:

- "what's the time?"
- "I have a question"
- introductions

… specific msgs sent

… specific actions taken when msgs received, or other events

network protocols:

- machines rather than humans
- all communication activity in Internet governed by protocols

protocols define format, order of msgs sent and received among network entities, and actions taken on msg transmission, receipt

What's a protocol?

a human protocol and a computer network protocol:



Contents

A closer look at network structure:

- *network edge:*
  - hosts (end-system): clients and servers
  - servers often in data centers
- *access networks, physical media:* wired, wireless communication links
- *network core:*
  - interconnected routers
  - network of networks



Access networks and physical media

Q: How to connect end systems to edge router?

- residential access nets
- institutional access networks (school, company)
- mobile access networks



Access net: home network



Enterprise access networks (Ethernet)



- typically used in companies, universities, etc
- 10 Mbps, 100Mbps, 1Gbps, 10Gbps transmission rates
- today, end systems typically connect into Ethernet switch

Wireless access networks

- shared *wireless* access network connects end system to router
  - via base station aka "access point"

wireless LANs:

- within building (100 ft)
- 802.11b/g /n(WiFi): 11M, 54,M 72M~150M transmission rate



wide-area wireless access

- provided by telco (cellular) operator, 10's km
- between 1 and 10 Mbps
- 3G, 4G: LTE

Physical media

- bit: propagates between transmitter/receiver pairs
- physical link: what lies between transmitter & receiver
- guided media:
  - signals propagate in solid media: copper, fiber, coax
- unguided media:
  - signals propagate freely, e.g., radio



twisted pair (TP)

- two insulated copper wires
  - Category 5: 100 Mbps, 1 Gpbs Ethernet
  - Category 6: 10Gbps

Physical media: coax, fiber

coaxial cable:

- two concentric copper conductors
- bidirectional
- broadband:
  - multiple channels on cable
  - HFC



fiber optic cable:

- glass fiber carrying light pulses, each pulse a bit
- high-speed operation:
  - high-speed point-to-point transmission (e.g., 10' s-100' s Gpbs transmission rate)
- low error rate:
  - repeaters spaced far apart
  - immune to electromagnetic noise



Physical media: radio

- signal carried in electromagnetic spectrum
- no physical "wire"
- bidirectional
- propagation environment effects:
  - reflection
  - obstruction by objects
  - interference

radio link types:

- terrestrial microwave
  - e.g. up to 45 Mbps channels
- LAN (e.g., WiFi)
  - 11Mbps, 54 Mbps, 72~150 Mbps
- wide-area (e.g., cellular)
  - 3G cellular: ~ few Mbps
- satellite
  - Kbps to 45Mbps channel (or multiple smaller channels)
  - 270 msec end-end delay
  - geosynchronous versus low altitude

Contents

1.1 what *is* the Internet?

1.2 network edge

- end systems, access networks, links

1.3 network core

- packet switching, circuit switching, network structure

1.4 delay, loss, throughput in networks

1.5 protocol layers, service models

The network core

- mesh of interconnected routers
- packet-switching: hosts break application-layer messages into *packets*
  - forward packets from one router to the next, across links on path from source to destination
  - each packet transmitted at full link capacity



Packet-switching: store-and-forward



- takes *L/R* seconds to transmit (push out) *L*-bit packet into link at *R* bps
- *store and forward:* entire packet must arrive at router before it can be transmitted on next link
- end-end delay = 2*L*/*R* (assuming zero propagation delay)

more on delay shortly …

one-hop numerical example:

- L = 7.5 Mbits
- R = 1.5 Mbps
- one-hop transmission delay = 5 sec

Packet Switching: queueing delay, loss



queuing and loss:

- If arrival rate (in bits) to link exceeds transmission rate of link for a period of time:
  - packets will queue, wait to be transmitted on link
  - packets can be dropped (lost) if memory (buffer) fills up

Problem 24

Suppose you would like to urgently deliver 40 terabytes data from Ha Noi to Ho Chi Minh. You have available a 100 Mbps dedicated link for data transfer.

Would you prefer to transmit the data via this link or instead use Viettel Post overnight delivery? Explain.

Problem 24 - answer

- L = 40 terabytes = $40 * 10^{12} * 8$ bits
- R = 100 Mbps = $100 * 10^6$ bit/s
- So, if using the dedicated link, it will take

  L/R = $40 * 10^{12} * 8 / (100 * 10^6)$ =3.200.000 seconds

  = 37 days.
- But with Viettel Post overnight delivery, you can guarantee the data arrives in one day.

Bit rates			
Name	**Symbol**	**Multiple**	
bit per second	bit/s	1	1
Decimal prefixes (SI)			
kilobit per second	kbit/s	10^3	1000^1
megabit per second	Mbit/s	10^6	1000^2
gigabit per second	Gbit/s	10^9	1000^3
terabit per second	Tbit/s	10^{12}	1000^4

Two key network-core functions

routing: determines source-destination route taken by packets

- *routing algorithms*

forwarding: move packets from router's input to appropriate router output



Alternative core: circuit switching

end-end resources allocated to, reserved for "call" between source & dest:

- In diagram, each link has four circuits.
  - call gets 2nd circuit in top link and 1st circuit in right link.
- dedicated resources: no sharing
  - circuit-like (guaranteed) performance
- circuit segment idle if not used by call *(no sharing)*
- Commonly used in traditional telephone networks



Circuit switching: FDM versus TDM

Example:

4 users 

Frequency-Division Multiplexing
FDM



Time-Division Multiplexing
TDM



Packet switching versus circuit switching

packet switching allows more users to use network!

example:

- 1 Mb/s link
- each user:
  - 100 kb/s when "active"
  - active 10% of time



- *circuit-switching:*
  - 10 users
- *packet switching:*
  - with 35 users, probability > 10 active at same time is less than .0004

Q: how did we get value 0.0004?

(Binomial distribution)

Q: what happens if > 35 users ?

Packet switching versus circuit switching

Packet switching:

- Pros:
  - great for bursty data
  - resource sharing
  - simpler, no call setup
- Cons:
  - excessive congestion possible: packet delay and loss
  - protocols needed for reliable data transfer, congestion control
- *Q*: How to provide circuit-like behavior?
  - bandwidth guarantees needed for audio/video apps

Internet structure: network of networks

- End systems connect to Internet via access ISPs (Internet Service Providers)
  - residential, company and university ISPs
- Access ISPs in turn must be interconnected
  - so that any two hosts can send packets to each other
- Resulting network of networks is very complex
  - evolution was driven by economics and national policies
- Let's take a stepwise approach to describe current Internet structure

Internet structure: network of networks

Question: given *millions* of access ISPs, how to connect them together?



Internet structure: network of networks

Option: connect each access ISP to every other access ISP?



connecting each access ISP to each other directly *doesn't scale:* O(N^2) connections.

Internet structure: network of networks

Option: connect each access ISP to one global transit ISP?
Customer and provider ISPs have economic agreement.



Internet structure: network of networks

But if one global ISP is viable business, there will be competitors ….



Internet structure: network of networks

But if one global ISP is viable business, there will be competitors …. which must be interconnected



Internet structure: network of networks

… and regional networks may arise to connect access nets to ISPS



Internet structure: network of networks

… and content provider networks (e.g., Google, Microsoft, Akamai) may run their own network, to bring services, content close to end users



Internet structure: network of networks



- at center: small # of well-connected large networks
  - "tier-1" commercial ISPs (e.g., Level 3, Sprint, AT&T, NTT), national & international coverage
  - content provider network (e.g., Google): private network that connects it data centers to Internet, often bypassing tier-1, regional ISPs

Read “Tier-1 network” from Wikipedia.

1. Which kind of ISPs does not pay for transit traffic? Which one does?

Contents

How do loss and delay occur?

packets *queue* in router buffers

- packet arrival rate to link (temporarily) exceeds output link capacity
- packets queue, wait for turn



Four sources of packet delay



$$d_{\text{nodal}} = d_{\text{proc}} + d_{\text{queue}} + d_{\text{trans}} + d_{\text{prop}}$$

d_{proc}: nodal processing

- check bit errors
- determine output link
- typically < msec

d_{queue}: queueing delay

- time waiting at output link for transmission
- depends on congestion level of router

Four sources of packet delay



$$d_{\text{nodal}} = d_{\text{proc}} + d_{\text{queue}} + d_{\text{trans}} + d_{\text{prop}}$$

d_{trans}: transmission delay:

- *L*: packet length (bits)
- *R*: link *bandwidth (bps)*
- $d_{trans} = L/R$

d_{prop}: propagation delay:

- *d*: length of physical link (meters)
- *s*: propagation speed in medium ($\sim 2 \times 10^8$ m/sec)
- $d_{prop} = d/s$

d_{trans} and d_{prop} *very* different

* Check out the Java applet for an interactive animation on trans vs. prop delay

Caravan analogy



- cars "propagate" at 100 km/hr
- toll booth takes 12 sec to service car (bit transmission time)
- car~bit; caravan ~ packet
- *Q:* How long until caravan is lined up before 2nd toll booth?

- time to "push" entire caravan through toll booth onto highway = 12*10 = 120 sec (d_{trans})

=> transmission delay in a router

- time for last car to propagate from 1st to 2nd toll booth: 100km/(100km/hr)= 1 hr (d_{prop})

=> propagation delay

- *A:* $d_{trans} + d_{prop}$ = 62 minutes

Caravan analogy (more)



- suppose cars now "propagate" at 1000 km/hr
- and suppose toll booth now takes one min to service a car
- *Q:* Will cars arrive to 2nd booth before all cars serviced at first booth?
  - *A: Yes!* after 7 min, 1st car arrives at second booth; three cars still at 1st booth.

Problem 25

Suppose two hosts, A and B, are separated by 20,000 kilometers and are connected by a direct link of R = 2 Mbps. Suppose the propagation speed over the link is $2.5*10^8$ meters/sec.

a. Calculate the bandwidth-delay product, $R*d_{prop}$. Provide an interpretation of the bandwidth-delay product.

b. Consider sending a file of 800,000 bits from Host A to Host B. Suppose the file is sent continuously as one large message. What is the maximum number of bits that will be in the link at any given time?

Problem 25 (Answer)

The distance (Distance) between two hosts A and B = 20,000 km

a)

The distance (Distance) between two hosts A and B = 20,000 km

$= 2 \times 10^7 meters\,(since 1km = 10^3 m)$

Trasmission rate(R) of the direct link between A and B =2Mbps

$= 2 \times 10^6 bps\,(1Mbps = 10^6 bps)$

Propagation Speed(S) of the link between A and B $= 2.5 \times 10^8 meters/sec$

Calculate the propagation delay:

$$d_{prog} = \frac{Distance}{Speed} = \frac{2 \times 10^7}{2.5 \times 10^8} = 0.08 sec$$

Calculate the band-width delay product:

$$R \times d_{prog} = 2 \times 10^6 \times 0.08 = 16 \times 10^4 bits$$

Therefore, band-with delay product is 160000bits

The bandwidth-delay product of a link is the maximum number of bits that can be in the link.

Problem 25 (Answer)

b)

Size of the file =800000 bits $= 8 \times 10^5 bits$

Trasmission rate(R) of the direct link between A and B =2Mbps

$= 2 \times 10^6 bps \left(1Mbps = 10^6 bps\right)$

The band-width delay product:

$$R \times d_{prog} = 2 \times 10^6 \times 0.08 = 16 \times 10^4 bits$$

Therefore, the maximum number of bits at a given time will be 160000bits.

Queueing delay (revisited)

- *R:* link bandwidth (bps)
- *L:* packet length (bits)
- a: average packet arrival rate (packets/sec)



- *La/R* ~ 0: avg. queueing delay small
- *La/R* -> 1: avg. queueing delay large
- *La/R* > 1: more "work" arriving than can be serviced, average delay infinite!

La/R ~ 0

La/R -> 1

* Check out the Java applet for an interactive animation on queuing and loss

"Real" Internet delays and routes

- what do "real" Internet delay & loss look like?
- `traceroute` program: provides delay measurement from source to router along end-end Internet path towards destination. For all *i*:
  - sends three packets that will reach router *i* on path towards destination
  - router *i* will return packets to sender
  - sender times interval between transmission and reply.



"Real" Internet delays, routes

traceroute: gaia.cs.umass.edu to www.eurecom.fr

3 delay measurements from
gaia.cs.umass.edu to cs-gw.cs.umass.edu

```
1  cs-gw (128.119.240.254)  1 ms  1 ms  2 ms
2  border1-rt-fa5-1-0.gw.umass.edu (128.119.3.145)  1 ms  1 ms  2 ms
3  cht-vbns.gw.umass.edu (128.119.3.130)  6 ms 5 ms 5 ms
4  jn1-at1-0-0-19.wor.vbns.net (204.147.132.129)  16 ms 11 ms 13 ms
5  jn1-so7-0-0-0.wae.vbns.net (204.147.136.136)  21 ms 18 ms 18 ms
6  abilene-vbns.abilene.ucaid.edu (198.32.11.9)  22 ms  18 ms  22 ms
7  nycm-wash.abilene.ucaid.edu (198.32.8.46)  22 ms  22 ms  22 ms
8  62.40.103.253 (62.40.103.253)  104 ms 109 ms 106 ms
9  de2-1.de1.de.geant.net (62.40.96.129)  109 ms 102 ms 104 ms
10  de.fr1.fr.geant.net (62.40.96.50)  113 ms 121 ms 114 ms
11  renater-gw.fr1.fr.geant.net (62.40.103.54)  112 ms  114 ms  112 ms
12  nio-n2.cssi.renater.fr (193.51.206.13)  111 ms  114 ms  116 ms
13  nice.cssi.renater.fr (195.220.98.102)  123 ms  125 ms  124 ms
14  r3t2-nice.cssi.renater.fr (195.220.98.110)  126 ms  126 ms  124 ms
15  eurecom-valbonne.r3t2.ft.net (193.48.50.54)  135 ms  128 ms  133 ms
16  194.214.211.25 (194.214.211.25)  126 ms  128 ms  126 ms
17  * * *
18  * * *
19  fantasia.eurecom.fr (193.55.113.142)  132 ms  128 ms  136 ms
```

trans-oceanic link

* means no response (probe lost, router not replying)

Packet loss

- queue (aka buffer) preceding link in buffer has finite capacity
- packet arriving to full queue dropped (aka lost)
- lost packet may be retransmitted by previous node, by source end system, or not at all



rate control / congestion control at the sender

* Check out the Java applet for an interactive animation on queuing and loss

Throughput

- *throughput:* rate (bits/time unit) at which bits transferred between sender/receiver
  - *instantaneous:* rate at given point in time
  - *average:* rate over longer period of time



Throughput (more)

- $R_s < R_c$ What is average end-end throughput?



- $R_s > R_c$ What is average end-end throughput?



bottleneck link

link on end-end path that constrains end-end throughput

Throughput: Internet scenario

- per-connection end-end throughput: min(R_c,R_s,R/10)
- in practice: R_c or R_s is often bottleneck



10 connections (fairly) share backbone bottleneck link R bits/sec

Contents

Protocol "layers"

Networks are complex,
with many "pieces":

- hosts
- routers
- links of various media
- applications
- protocols
- hardware, software

Question:

is there any hope of *organizing* structure of network?

…. or at least our discussion of networks?

Organization of air travel



- a series of steps

Layering of airline functionality



layers: each layer implements a service

- via its own internal-layer actions
- relying on services provided by layer below

Why layering?

dealing with complex systems:

- explicit structure allows identification, relationship of complex system's pieces
  - layered *reference model* for discussion
- modularization eases maintenance, updating of system
  - change of implementation of layer's service transparent to rest of system
  - e.g., change in gate procedure doesn't affect rest of system

Internet protocol stack

- *application:* supporting network applications
  - FTP, SMTP, HTTP
- *transport:* process-process data transfer
  - TCP, UDP
- *network:* routing of datagrams from source to destination
  - IP, routing protocols
- *link:* data transfer between neighboring network elements
  - Ethernet, 802.11 (WiFi), PPP
- *physical:* bits "on the wire"



ISO/OSI reference model

- *presentation:* allow applications to interpret meaning of data, e.g., encryption, compression, machine-specific conventions
- *session:* synchronization, checkpointing, recovery of data exchange
- Internet stack "missing" these layers!
  - these services, *if needed*, must be implemented in application
  - needed?



Encapsulation



Introduction: summary

covered a "ton" of material!

- Internet overview
- what's a protocol?
- network edge, core, access network
  - packet-switching versus circuit-switching
  - Internet structure
- performance: loss, delay, throughput
- layering, service models