# VIEWS

## Delivery Note

### Nine Deep-Learning Forecast Models

— ◇ —

| | |
|---|---|
| **Identifier** | `r2darts2-pgm-global-calibration-2026-10` |
| **Checksum** | `60597598` |
| **Date** | 10-10-2026 |
| **Author** | Simon Polichinel von der Maase |

***Scope*** *what the data is*

| | |
|---|---|
| **Partition** | Calibration |
| **Spatial resolution** | PRIO-GRID cell |
| **Spatial extent** | Global land — 64,818 cells |
| **Temporal resolution** | Month |
| **Temporal extent** | Forecasts Jan 2018 to Dec 2021; trained on Jan 1990 to Dec 2017 |
| **Forecast structure** | 13 rolling origins, each forecasting 36 months |
| **Targets** | State-based, non-state and one-sided fatalities |

***Provenance*** *what produced it*

| | |
|---|---|
| **Model library** | views-r2darts2 0.2.4, wrapping Darts (`unit8co/darts`) |
| **Framework** | views-pipeline-core 3.3.4 |
| **Data backend** | views-datafactory 1.13.0 |
| **Source commit** | `views-models@be7b7b6` |
| **Computed on** | Rented cloud GPUs (RunPod) |

*PRIO – Oslo*

VIEWS
PREDICTING CONFLICT & HUMANITARIAN IMPACTS

PRIO

# 1 Context

This Delivery Note accompanies `r2darts2-pgm-global-calibration-2026-10`, a set of conflict forecasts produced by nine deep-learning models on the calibration partition at global PRIO-GRID month. It is the authoritative description of what was handed over: the data itself carries no documentation, and the folder is not self-explanatory.

The purpose of this note is to:

- record what was delivered, in enough detail to identify it again later;
- describe the models that produced it, and what distinguishes them from one another;
- state how the files are organised and how they are intended to be consumed; and
- set out what is *not* in the delivery, and what is not yet known about it.

This note covers:

- the nine models, their architectures, and the published work they come from (Sections 2–3);
- the transformations applied to the data and undone again (Section 4);
- the objective functions they were trained on, including one written in-house (Section 5);
- the file layout, schema and units of the delivered forecasts (Section 6); and
- what the delivery excludes, and the caveats that bear on using it (Sections 7–8).

This note explicitly does *not* cover:

- **any evaluation of the models.** Nothing here has been scored, ranked or compared. No metric has been computed beyond a check that the files are not corrupt;
- any recommendation as to which models to prefer, or whether to use them at all;
- the validation or forecasting partitions, or any live forecast; and
- the internal machinery that produced the run — what it took to compute these forecasts is recorded separately, in `reports/postmortem_darts_calibration_2026-10.md`.

The delivery is a fixed artefact. It is identified by the identifier and checksum on the title page — quote both — and is not revised in place: any correction is issued as a new delivery with a new identifier and a new checksum.

# 2 The Models

All nine are **off-the-shelf deep-learning models for time series**, taken from the Python library **Darts** (`unit8co/darts`). The architectures are the library's, unmodified — each is a published model used as Darts implements it. What we supply is the data, the configuration, and for six of the nine a loss function of our own (Section 5).

They are *global* models in the forecasting sense: a single set of parameters is pooled across all 64,818 cells. The closest familiar analogue is a pooled panel estimator — a cell with almost no conflict history is still forecast using structure learned from the whole grid. Each cell's own level and scale are restored separately, by the normalisation described in Section 4.

Table 1: The nine delivered models.

| Model | Type | Loss | Predictors | Hyperparameters | Features |
|---|---|---|---|---|---|
| dark_river | N-BEATS | MSE | Outcomes only | link | link |
| old_rules | N-BEATS | Spotlight | Outcomes only | link | link |
| blue_ocean | N-BEATS | Spotlight | + 69 covariates | link | link |
| silent_fox | TSMixer | MSE | Outcomes only | link | link |
| dancing_monkey | TSMixer | Spotlight | Outcomes only | link | link |
| brave_heart | TSMixer | Spotlight | + 69 covariates | link | link |
| red_hawk | TiDE | MSE | Outcomes only | link | link |
| dark_necessities | TiDE | Spotlight | Outcomes only | link | link |
| golden_eagle | TiDE | Spotlight | + 69 covariates | link | link |

The link columns open each model's configuration files on GitHub, fixed at the delivery commit on the title page: **Hyperparameters** is `config_hyperparameters.py`, which sets the architecture, the loss and the training schedule; **Features** is `config_queryset.py`, which declares the predictors the model was given.

The names are arbitrary labels, assigned according to the `adjective_noun` convention used across views-models, and carry no meaning.

**Within each block of three, exactly two settings vary** — the loss function, and whether the model sees covariates. Everything else is identical: layer widths, depth, training epochs, learning rate, early stopping. So inside a block, each row differs from the one above it in a single setting. Across blocks the architecture changes and the comparison is a different one.

- **Outcomes only** — the model's inputs are the past values of the three outcomes and nothing else. Purely autoregressive. Six models: the first two rows of each block.
- **+ 69 covariates** — the same three histories plus 69 predictors: ACLED event and fatality counts, land cover shares, population and built-up area, infant and child mortality, V-Dem governance indices, SHDI development indices, travel time to cities, mineral and petroleum deposits, growing season and harvested area, and terrain. Three models: the third row of each block.

Note that the two splits are not the same split. Six models are outcomes-only and six use the Spotlight loss, but they are different sixes: `blue_ocean`, `brave_heart` and `golden_eagle` have covariates *and* Spotlight, while `dark_river`, `silent_fox` and `red_hawk` have neither.

**There is no model combining MSE with the covariates.** Three configurations exist, not four.

### Covariate Preparation

Covariates are prepared in two stages, by different parties and to different standards.

Within the datafactory, preparation is specified. Annual sources are extended across their twelve months by per-source rules; values outside a source's observed range are manufactured, zero before the first observation and the last value held after it; absent coverage is filled with zeros rather than nulls; raster and polygon sources are attached to grid cells by aggregation and spatial join. Feature engineering is excluded by design, cross-feature derivation being assigned to the model layer. Each of these is a recorded decision with an architecture decision record behind it — ADR-014, ADR-042, ADR-047 and ADR-052 in the datafactory repository, with a documentation card per source. That is the authoritative account and this note does not restate it.

Preparation after the fetch is set in the model configuration, and is documented only by the configuration itself. Two operations apply here: the selection of which covariates each model receives, and the transformations described in Section 4. Both are visible in the files linked in Table 1. Neither carries a decision record or a written rationale, and whether either is warranted is not established by this note.

### Covariate Coverage

The datafactory publishes, for each source, the month range in which its observations are real. Values outside that range exist but are manufactured. Checked against this delivery's partition, four of the five sources cover it fully and one does not.

Table 2: Source coverage against the calibration partition.

| **Source** | **Observed from** | **Training 1990–2017** | **Test 2018–2021** |
|---|---|---|---|
| ACLED (7 covariates) | January 2020 | **none — all zeros** | real from January 2020 |
| V-Dem | January 1989 | real | real |
| SHDI | January 1989 | real | real |
| Population | January 1989 | real | real |
| Built-up surface | January 1989 | real | real |

The seven ACLED covariates are therefore zero for every month these models were fitted on, and become non-zero partway through the forecast window. This is a sharper problem than an absent feature: a predictor that is constant in training and varies in test is one the model has learned to disregard. Nor is it visible in the data, since manufactured and observed zeros are written identically.

The coverage bounds are published so that manufactured values can be identified, and were available when these models were configured; the omission is downstream of the datafactory, not within it. Three models are affected — `blue_ocean`, `brave_heart` and `golden_eagle`. The six outcomes-only models use no covariates.

# 3 Model Architectures

All three are feed-forward neural networks built from ordinary dense layers. None uses recurrence, convolution or attention.

### N-BEATS

A deep stack of fully connected layers with backward and forward residual links. It builds the forecast as a sum of learned basis functions, which is what makes it partly interpretable. Designed for univariate point forecasting and benchmarked on the M3, M4 and TOURISM competition datasets.

> Darts: `NBEATSModel`
> Paper cited there: Oreshkin, B. N., Carpov, D., Chapados, N. & Bengio, Y. (2020), *N-BEATS: Neural basis expansion analysis for interpretable time series forecasting*, ICLR 2020. arXiv:1905.10437

### TSMixer

Dense layers only, applied alternately along the time axis and across the predictor variables, so the model mixes temporal structure and cross-variable structure in turn. Built for the multivariate case.

> Darts: `TSMixerModel`
> Paper cited there: Chen, S.-A., Li, C.-L., Yoder, N., Arik, S. O. & Pfister, T. (2023), *TSMixer: An All-MLP Architecture for Time Series Forecasting*, Transactions on Machine Learning Research. arXiv:2303.06053

### TiDE

An encoder–decoder, again dense layers only. It compresses the history and the predictors into a single code, then decodes the whole 36-month path from it in one pass.

> Darts: `TiDEModel`
> Paper cited there: Das, A., Kong, W., Leach, A., Mathur, S., Sen, R. & Yu, R. (2023), *Long-term Forecasting with TiDE: Time-series Dense Encoder*. arXiv:2304.08424

# 4 Transformations

Two transformations are applied between the data and the model, and both are reversible. No others are used: the configurations declare no logarithm, no min–max or standard scaling, no winsorising and no clipping of values.

**An `asinh` transform, declared in the model configuration.** All nine models apply it to the three outcomes. The three covariate-using models apply it to their inputs as well, so for those every one of the 72 columns is transformed. The inverse hyperbolic sine is used rather than a logarithm because it is defined at zero, which matters at this resolution: **99.6%** of observed cell-

months in this window are exactly zero. It is set by `target_scaler` and `feature_scaler_map` in the files linked in Table 1, and it is inverted on the model's output before predictions are written.

**Reversible instance normalisation, inside the network.** Each cell's series is standardised before the network sees it and the standardisation is undone on the way out. This is what returns a cell's own level and scale after the pooling described in Section 2, and it is applied by all nine models.

> Kim, T., Kim, J., Tae, Y., Park, C., Choi, J.-H. & Choo, J. (2022), *Reversible Instance Normalization for Accurate Time-Series Forecasting against Distribution Shift*, ICLR 2022.

Both inversions happen before the delivered files are written, so **every column in this delivery is intended to be on the original count scale** and no back-transformation should be applied to it.

That is an intention supported by a check rather than a proof. The largest delivered value is of the order of a few hundred fatalities, which is plausible as a count and would be absurd on the transformed scale — `asinh` of a few hundred corresponds to a number with over a hundred digits. Totals are within the same order of magnitude as the observed field. Nothing in the delivery verifies the inversion formally, and the check described in Section 8 is the extent of what was done.

## Scope, and Points for Future Examination

Whether `asinh` is a prudent choice here, what assumptions it imposes, and what follows for the delivered numbers are questions this note does not answer and is not responsible for answering. It records what was applied. The following are offered to whoever does examine it, and are arithmetic or configuration facts rather than findings.

**On this field, `asinh` is `log1p` shifted by a constant.** For non-negative values the two converge rapidly to a fixed offset of $\ln 2 \approx 0.693$ — already 0.68 at $x = 100$. What distinguishes `asinh` is its symmetric treatment of negative values, and fatality counts have none. Any claim that the choice between them matters materially here would need evidence, and none is offered in this delivery.

**The transform acts weakly where the data actually is.** $\text{asinh}(1) = 0.88$ and $\text{asinh}(2) = 1.44$: close to linear across the small counts where nearly all non-zero mass sits. Compression engages only in the tail. On a field that is 99.6% zero, "a variance-stabilising transform was applied" claims less than it may appear to.

**Inverting a point estimate is biased low, and these models deliver point estimates.** A model fitted to minimise error on a transformed scale estimates the transformed quantity; applying a convex inverse to that estimate does not recover the conditional mean. Collapsing draws in count space avoids this, but there are no draws here — all nine models produce a single value per cell (Section 8), so the inverse is necessarily applied to a point. The mechanism is therefore present by construction. Its magnitude depends on the conditional dispersion and has

not been quantified for these models. Whether the delivered totals are depressed relative to observed totals is measurable today, without refitting, and is the first thing worth checking.

**One failure mode was checked and is absent.** A consumer that applies a hardcoded inverse belonging to a different transform — `expm1`, assuming `log1p` — would return silently wrong counts, and this has occurred elsewhere on the platform. Neither the converter that produced these files nor the ensemble-construction tool applies any transform; the converter refuses to. What remains unverified is the count of inversion sites along the whole path: a value inverted twice, or not at all, would not be distinguished by the magnitude check described above, because on a sparse field of small counts an un-inverted column looks almost right. A round-trip assertion on the delivered columns would settle it.

**The transform and the objective are coupled.** The Spotlight threshold separating event from quiet cells is defined *on the transformed scale*, at $\text{asinh}(1) \approx 0.88$. Changing the transform would silently change what that threshold means; the two cannot be reconsidered independently.

**A different choice was made elsewhere on the same data, and reasoned.** Another model family on this platform uses `log1p` throughout and, for count-likelihood heads, rejects `asinh` at configuration load rather than permitting it. The reasoning is recorded in that repository (ADR-067, and C-198 in its risk register) and is the natural starting point for anyone examining this one. No head-to-head comparison of the two transforms has been run on either side.

One risk does *not* apply here. Repeated inversion can amplify modest drift into implausible counts where forecasts are fed back as inputs; these models forecast all 36 months directly in a single pass rather than recursively, so that path does not arise.

## 5 Loss Functions

**MSE** — ordinary squared error, every cell-month weighted equally. The library's own implementation, a thin wrapper around PyTorch's. Used by `dark_river`, `silent_fox` and `red_hawk`.

**Spotlight** (`SpotlightLossLogcosh`) — in-house, not off the shelf. A three-part objective computed after an `asinh` transform. It scores the *shape* of the error only in cells where the observation or the forecast exceeds one fatality; separately penalises the *level* in cells whose observation exceeds one fatality; and separately penalises forecasting conflict in cells that stayed below it. It uses `log cosh` rather than squared error, so a single very large observation does not dominate the gradient. Used by the other six.

### Development and Validation Status

Spotlight is not a one-off function but the production member of a sustained line of work. The first variant was committed in March 2026 and the one used here at the end of April; development continued into late August. The family now comprises six Spotlight variants and three related objectives — roughly 2,250 lines across nine modules — attracting some 216 commits over six months. The library's own documentation sets out five earlier generations of the design, recording

for each what it addressed and what it exposed. By any ordinary measure this represents a considerable investment of development effort.

Of the objective's two parameters, one is derived rather than fitted: the threshold separating event from quiet cells is $\operatorname{asinh}(1) \approx 0.88$, exactly one fatality on the transformed scale. The other, a weight on a spectral term, is set by hyperparameter sweep.

What the record does not contain is any formal account of it. No citation appears in the source, its documentation, the commit history or the architecture decision records; two other objectives in the same library do cite published work, so the omission is particular to this family rather than a habit of the codebase. Neither is it covered by tests. The library's suite exercises eight of its objectives and this is not among them, so nothing checks its gradients, compares it against a reference implementation, or establishes that the code computes what the written account describes — this for the objective on which 37 of the platform's 42 darts models are trained.

Six months of concentrated development across five successive generations is not the profile of an untried design, and the written account of its construction is detailed. It is reasonable to infer that the objective has been exercised extensively, if informally, during that period. Informal exercise is not validation, however, and the distinction is what this note is obliged to record: what is absent is not the work but the evidence of it. A derivation a third party can follow, and tests that fail when the implementation is wrong, remain outstanding and should be produced for an objective in production use at this scale.

On that basis this note takes no position on whether the objective is sound. It may be excellent, adequate, or quietly wrong, and nothing in the available record distinguishes those possibilities. Six of the nine delivered models were trained on it and three on ordinary squared error, which bears on how much weight a comparison between those two groups can carry.

## 6 The Delivered Files

**One folder per model.** Inside each: thirteen Parquet files, `..._00` through `..._12`, and a short text file recording when the model ran, which version of the software produced it, and which configuration it used.

**The thirteen files are thirteen forecast origins**, stepping forward one month at a time. An origin is the last month the model was allowed to see; from there it forecasts the next 36 months.

Table 3: The thirteen forecast origins.

| File | Last month seen | Months forecast |
|---|---|---|
| `..._00` | December 2017 | January 2018 – December 2020 |
| `..._01` | January 2018 | February 2018 – January 2021 |
| | ... | |
| `..._12` | December 2018 | January 2019 – December 2021 |

Within every file the earliest month is horizon 1 and the latest horizon 36, so a given target

month sits at a different horizon in each file containing it. Metrics computed per origin keep those apart; metrics pooled across origins mix them.

**Each file holds 2,333,448 rows** — 36 months × 64,818 cells — and five columns.

Table 4: Columns in every file.

| Column | Contents |
|---|---|
| `month_id` | Month |
| `priogrid_id` | Grid cell |
| `pred_lr_ged_sb` | Forecast state-based fatalities |
| `pred_lr_ged_ns` | Forecast non-state fatalities |
| `pred_lr_ged_os` | Forecast one-sided fatalities |

**Units are fatality counts.** A value of 2.4 means 2.4 fatalities; values are continuous rather than integer. The transformations applied during fitting are inverted before these files are written (Section 4), so no back-transformation should be applied to them.

**Observed values are not included, and are not needed from here.** Evaluation joins these forecasts to observed fatalities on `month_id` and `priogrid_id`; the ensemble-construction tool retrieves those itself, and they are otherwise available from the datafactory. The file naming used here already matches what that tool expects.

Nine models × thirteen origins = **117 files, about 2 GB** in total.

## 7 Not Included in This Delivery

Table 5: Not included in this delivery.

| Item | Where it is instead, or why not |
|---|---|
| Observed values | Fetched by the ensemble tool, or from the datafactory (Section 6) |
| Evaluation metrics | None computed — see Section 8 |
| Training logs | Not shipped. `calibration_log.txt`, which the ensemble tool can optionally read to resolve run timestamps, is among them; timestamps can be passed explicitly instead |
| Other partitions | Calibration only — no validation partition, no true forecasts |
| Model artefacts | No weights, no checkpoints |

## 8 Caveats and Notes

**No model here has a predictive distribution.** These are point forecasts — one number per cell-month, no draws, no quantiles, no intervals. All nine are configured as deterministic predictors, so a different export would not recover a distribution; it was never produced. Nothing

that scores a *single model's* uncertainty — CRPS of its predictive density, interval coverage, density calibration — can be computed from these files.

One qualification, since it would otherwise look like a contradiction in the output: the ensemble tool can still produce a CRPS. It does so by treating the member models' point forecasts as an empirical sample and scoring the spread across models. That is a property of the ensemble, not of any model in it, and it is not the same quantity as a CRPS computed from a model's own posterior. Worth knowing before the two are compared.

**Nothing here has been evaluated.** I checked only that the files are not broken: no negatives, no missing values, no duplicate cell-months, the expected row counts, and totals within the same order of magnitude as observed. That rules out a failed back-transformation or a collapsed model and establishes nothing else.

**It is nine models, not eleven.** Two others were set up to draw 100 samples per forecast, making them probabilistic counterparts of `dancing_monkey` and `dark_necessities`. A point delivery needs one value per cell, and at one sample their configurations are byte-identical to those siblings — the same model twice. Running them as intended is blocked by memory: 100 samples for 64,818 cells across thirteen origins needs far more RAM than any machine we have.

**One observation will dominate any squared-error metric.** December 2021, cell 148759 has **113,395** observed fatalities; the next largest anywhere in the window is 5,395. That month falls in only one of the thirteen origins (`..._12`), where that single cell is about 41% of observed fatalities. I do not know whether it is a real event or a data error. Either way it is better settled before the numbers are produced than explained afterwards.

**The software is pinned; the data is not.** The title page records the three versions that determine the output — the model library, the framework and the data backend — along with the `views-models` commit the configurations were read at. Between them those fix the code. They do not fix the *input*: the data backend served this run from a live store with no snapshot identifier, and the provenance record written beside the fetched data shows drift detection did not run. So re-running these nine models at these versions would reproduce the method, and would not guarantee reproducing the numbers, because the underlying observations may have been revised in the meantime. Worth knowing before anyone treats a re-run as a check.

**Column naming.** These files use the canonical target names, `pred_lr_ged_sb` and its two siblings. The September delivery used `pred_lr_sb_best` instead, so the two are not directly comparable without a rename. Renaming either set takes minutes and needs no re-run.

**Comparison with the September delivery.** You were sent three variants per model then — a mean, a 95th percentile and a conditional mean — each computed from that model family's predictive distribution. These nine have no distribution, so only the mean has an equivalent here. If the evaluation work has been built on one of the other two, the two deliveries are not like-for-like. A correction while I am here: my September note said the full distributions had been retained so alternative summaries could be produced without re-running. They were not kept.