

Amazon Fine Food Reviews Analysis

Data Source: <https://www.kaggle.com/snap/amazon-fine-food-reviews>

EDA: <https://nycdatascience.com/blog/student-works/amazon-fine-foods-visualization/>

The Amazon Fine Food Reviews dataset consists of reviews of fine foods from Amazon.

Number of reviews: 568,454

Number of users: 256,059

Number of products: 74,258

Timespan: Oct 1999 - Oct 2012

Number of Attributes/Columns in data: 10

Attribute Information:

1. Id
2. ProductId - unique identifier for the product
3. UserId - unique identifier for the user
4. ProfileName
5. HelpfulnessNumerator - number of users who found the review helpful
6. HelpfulnessDenominator - number of users who indicated whether they found the review helpful or not
7. Score - rating between 1 and 5
8. Time - timestamp for the review
9. Summary - brief summary of the review
10. Text - text of the review

Objective:

Given a review, determine whether the review is positive (rating of 4 or 5) or negative (rating of 1 or 2).

[Q] How to determine if a review is positive or negative?

[Ans] We could use Score/Rating. A rating of 4 or 5 can be considered as a positive review. A rating of 1 or 2 can be considered as negative one. A review of rating 3 is considered neutral and such reviews are ignored from our analysis. This is an approximate and proxy way of determining the polarity (positivity/negativity) of a review.

[1]. Reading Data

[1.1] Loading the data

The dataset is available in two forms

1. .csv file
2. SQLite Database

In order to load the data, We have used the SQLITE dataset as it is easier to query the data and visualise the data efficiently.

Here as we only want to get the global sentiment of the recommendations (positive or negative), we will purposefully ignore all Scores equal to 3. If the score is above 3, then the recommendation will be set to "positive". Otherwise, it will be set to "negative".

```
In [1]: %matplotlib inline
import warnings
warnings.filterwarnings("ignore")

import sqlite3
import pandas as pd
import numpy as np
import nltk
import string
```

```

import matplotlib.pyplot as plt
import seaborn as sns
from sklearn.feature_extraction.text import TfidfTransformer
from sklearn.feature_extraction.text import TfidfVectorizer

from sklearn.feature_extraction.text import CountVectorizer
from sklearn.metrics import confusion_matrix
from sklearn import metrics
from sklearn.metrics import roc_curve, auc
from nltk.stem.porter import PorterStemmer

import re
# Tutorial about Python regular expressions: https://pymotw.com/2/re/
import string
from nltk.corpus import stopwords
from nltk.stem import PorterStemmer
from nltk.stem.wordnet import WordNetLemmatizer

from gensim.models import Word2Vec
from gensim.models import KeyedVectors
import pickle

from tqdm import tqdm
import os

```

```

C:\Users\user\Anaconda3\lib\site-packages\gensim\utils.py:1197: UserWarning: detected Windows; aliasing chunkize to chunkize_serial
  warnings.warn("detected Windows; aliasing chunkize to chunkize_serial")

```

```

In [2]: # using SQLite Table to read data.
con = sqlite3.connect('database.sqlite')

# filtering only positive and negative reviews i.e.
# not taking into consideration those reviews with Score=3
# SELECT * FROM Reviews WHERE Score != 3 LIMIT 500000, will give top 50
0000 data points
# you can change the number to any other number based on your computing
power

```

```

# filtered_data = pd.read_sql_query(""" SELECT * FROM Reviews WHERE Score
!= 3 LIMIT 500000""", con)
# for tsne assignment you can take 5k data points

filtered_data = pd.read_sql_query(""" SELECT * FROM Reviews WHERE Score
!= 3 LIMIT 100000""", con)

# Give reviews with Score>3 a positive rating(1), and reviews with a score<3 a negative rating(0).
def partition(x):
    if x < 3:
        return 0
    return 1

#changing reviews with score less than 3 to be positive and vice-versa
actualScore = filtered_data['Score']
positiveNegative = actualScore.map(partition)
filtered_data['Score'] = positiveNegative
print("Number of data points in our data", filtered_data.shape)
filtered_data.head(3)

```

Number of data points in our data (100000, 10)

Out[2]:

	Id	ProductId	UserId	ProfileName	HelpfulnessNumerator	HelpfulnessDenominator
0	1	B001E4KFG0	A3SGXH7AUHU8GW	delmartian	1	
1	2	B00813GRG4	A1D87F6ZCVE5NK	dll pa	0	

		Id	ProductId	UserId	ProfileName	HelpfulnessNumerator	HelpfulnessDenomin
2	3	B000LQOCH0	ABXLMWJIXXAIN	Natalia Corres	"Natalia Corres"	1	

```
In [3]: display = pd.read_sql_query("""
SELECT UserId, ProductId, ProfileName, Time, Score, Text, COUNT(*)
FROM Reviews
GROUP BY UserId
HAVING COUNT(*)>1
""", con)
```

```
In [4]: print(display.shape)
display.head()
```

(80668, 7)

Out[4]:

	UserId	ProductId	ProfileName	Time	Score	Text	COUNT(*)
0	#oc-R115TNMSPFT9I7	B007Y59HVM	Breyton	1331510400	2	Overall its just OK when considering the price...	2
1	#oc-R11D9D7SHXIJB9	B005HG9ET0	Louis E. Emory "hoppy"	1342396800	5	My wife has recurring extreme muscle spasms, u...	3
2	#oc-R11DNU2NBKQ23Z	B007Y59HVM	Kim Cieszykowski	1348531200	1	This coffee is horrible and unfortunately not ...	2
3	#oc-R11O5J5ZVQE25C	B005HG9ET0	Penguin Chick	1346889600	5	This will be the bottle that you grab from the...	3

	UserId	ProductId	ProfileName	Time	Score	Text	COUNT(*)
4	#oc-R12KPBODL2B5ZD	B007OSBE1U	Christopher P. Presta	1348617600	1	I didnt like this coffee. Instead of telling y...	2

In [5]: `display[display['UserId']=='AZY10LLTJ71NX']`

Out[5]:

	UserId	ProductId	ProfileName	Time	Score	Text	COUNT(*)
80638	AZY10LLTJ71NX	B006P7E5ZI	undertheshrine "undertheshrine"	1334707200	5	I was recommended to try green tea extract to ...	5

In [6]: `display['COUNT(*)'].sum()`

Out[6]: 393063

[2] Exploratory Data Analysis

[2.1] Data Cleaning: Deduplication

It is observed (as shown in the table below) that the reviews data had many duplicate entries. Hence it was necessary to remove duplicates in order to get unbiased results for the analysis of the data. Following is an example:

In [7]: `display= pd.read_sql_query("""
SELECT *
FROM Reviews
WHERE Score != 3 AND UserId="AR5J8UI46CURR"
ORDER BY ProductID`

```
""", con)
display.head()
```

Out[7]:

	Id	ProductId	UserId	ProfileName	HelpfulnessNumerator	HelpfulnessDenon
0	78445	B000HDL1RQ	AR5J8UI46CURR	Geetha Krishnan	2	
1	138317	B000HDOPYC	AR5J8UI46CURR	Geetha Krishnan	2	
2	138277	B000HDOPYM	AR5J8UI46CURR	Geetha Krishnan	2	
3	73791	B000HDOPZG	AR5J8UI46CURR	Geetha Krishnan	2	
4	155049	B000PAQ75C	AR5J8UI46CURR	Geetha Krishnan	2	

As it can be seen above that same user has multiple reviews with same values for HelpfulnessNumerator, HelpfulnessDenominator, Score, Time, Summary and Text and on doing analysis it was found that

ProductId=B000HDOPZG was Loacker Quadratini Vanilla Wafer Cookies, 8.82-Ounce Packages (Pack of 8)

ProductId=B000HDL1RQ was Loacker Quadratini Lemon Wafer Cookies, 8.82-Ounce Packages (Pack of 8) and so on

It was inferred after analysis that reviews with same parameters other than ProductId belonged to the same product just having different flavour or quantity. Hence in order to reduce redundancy it was decided to eliminate the rows having same parameters.

The method used for the same was that we first sort the data according to ProductId and then just keep the first similar product review and delete the others. for eg. in the above just the review for ProductId=B000HDL1RQ remains. This method ensures that there is only one representative for each product and deduplication without sorting would lead to possibility of different representatives still existing for the same product.

```
In [8]: #Sorting data according to ProductId in ascending order
sorted_data=filtered_data.sort_values('ProductId', axis=0, ascending=True,
inplace=False, kind='quicksort', na_position='last')
```

```
In [24]: #Deduplication of entries
final=sorted_data.drop_duplicates(subset={"UserId","ProfileName","Time",
"Text"}, keep='first', inplace=False)
final.shape
```

```
Out[24]: (87775, 10)
```

```
In [10]: #Checking to see how much % of data still remains
(final['Id'].size*1.0)/(filtered_data['Id'].size*1.0)*100
```

```
Out[10]: 87.775
```

Observation:- It was also seen that in two rows given below the value of HelpfulnessNumerator is greater than HelpfulnessDenominator which is not practically possible hence these two rows too are removed from calculations

```
In [11]: display= pd.read_sql_query("""
SELECT *
```



```

FROM Reviews
WHERE Score != 3 AND Id=44737 OR Id=64422
ORDER BY ProductID
""", con)

display.head()

```

Out[11]:

	Id	ProductId	UserId	ProfileName	HelpfulnessNumerator	HelpfulnessDenom
0	64422	B000MIDROQ	A161DK06JJMCYF	J. E. Stephens "Jeanne"	3	
1	44737	B001EQ55RW	A2V0I904FH7ABY	Ram	3	

In [12]: `final=final[final.HelpfulnessNumerator<=final.HelpfulnessDenominator]`

In [13]: *#Before starting the next phase of preprocessing lets see the number of entries left*
`print(final.shape)`
#How many positive and negative reviews are present in our dataset?
`final['Score'].value_counts()`
 (87773, 10)

Out[13]:

1	73592
0	14181

Name: Score, dtype: int64

[3] Preprocessing

[3.1]. Preprocessing Review Text

Now that we have finished deduplication our data requires some preprocessing before we go on further with analysis and making the prediction model.

Hence in the Preprocessing phase we do the following in the order below:-

1. Begin by removing the html tags
2. Remove any punctuations or limited set of special characters like , or . or # etc.
3. Check if the word is made up of english letters and is not alpha-numeric
4. Check to see if the length of the word is greater than 2 (as it was researched that there is no adjective in 2-letters)
5. Convert the word to lowercase
6. Remove Stopwords
7. Finally Snowball Stemming the word (it was observed to be better than Porter Stemming)

After which we collect the words used to describe positive and negative reviews

```
In [14]: # printing some random reviews
sent_0 = final['Text'].values[0]
print(sent_0)
print("="*50)

sent_1000 = final['Text'].values[1000]
print(sent_1000)
print("="*50)

sent_1500 = final['Text'].values[1500]
print(sent_1500)
print("="*50)

sent_4900 = final['Text'].values[4900]
```

```
print(sent_4900)
print("="*50)
```

My dogs loves this chicken but its a product from China, so we wont be buying it anymore. Its very hard to find any chicken products made in the USA but they are out there, but this one isnt. Its too bad too bec ause its a good product but I wont take any chances till they know what is going on with the china imports.

=====

The Candy Blocks were a nice visual for the Lego Birthday party but the candy has little taste to it. Very little of the 2 lbs that I bought w ere eaten and I threw the rest away. I would not buy the candy again.

=====

was way to hot for my blood, took a bite and did a jig lol

=====

My dog LOVES these treats. They tend to have a very strong fish oil sme ll. So if you are afraid of the fishy smell, don't get it. But I think my dog likes it because of the smell. These treats are really small in size. They are great for training. You can give your dog several of the se without worrying about him over eating. Amazon's price was much more reasonable than any other retailer. You can buy a 1 pound bag on Amazon for almost the same price as a 6 ounce bag at other retailers. It's def initely worth it to buy a big bag if your dog eats them a lot.

=====

```
In [15]: # remove urls from text python: https://stackoverflow.com/a/40823105/40
84039
sent_0 = re.sub(r"http\S+", "", sent_0)
sent_1000 = re.sub(r"http\S+", "", sent_1000)
sent_150 = re.sub(r"http\S+", "", sent_1500)
sent_4900 = re.sub(r"http\S+", "", sent_4900)

print(sent_0)
```

My dogs loves this chicken but its a product from China, so we wont be buying it anymore. Its very hard to find any chicken products made in the USA but they are out there, but this one isnt. Its too bad too bec ause its a good product but I wont take any chances till they know what is going on with the china imports.

```
In [16]: # https://stackoverflow.com/questions/16206380/python-beautifulsoup-how
        -to-remove-all-tags-from-an-element
        from bs4 import BeautifulSoup

        soup = BeautifulSoup(sent_0, 'lxml')
        text = soup.get_text()
        print(text)
        print("="*50)

        soup = BeautifulSoup(sent_1000, 'lxml')
        text = soup.get_text()
        print(text)
        print("="*50)

        soup = BeautifulSoup(sent_1500, 'lxml')
        text = soup.get_text()
        print(text)
        print("="*50)

        soup = BeautifulSoup(sent_4900, 'lxml')
        text = soup.get_text()
        print(text)
```

My dogs loves this chicken but its a product from China, so we wont be buying it anymore. Its very hard to find any chicken products made in the USA but they are out there, but this one isnt. Its too bad too because its a good product but I wont take any chances till they know what is going on with the china imports.

=====

The Candy Blocks were a nice visual for the Lego Birthday party but the candy has little taste to it. Very little of the 2 lbs that I bought were eaten and I threw the rest away. I would not buy the candy again.

=====

was way to hot for my blood, took a bite and did a jig lol

=====

My dog LOVES these treats. They tend to have a very strong fish oil smell. So if you are afraid of the fishy smell, don't get it. But I think my dog likes it because of the smell. These treats are really small in size. They are great for training. You can give your dog several of the

se without worrying about him over eating. Amazon's price was much more reasonable than any other retailer. You can buy a 1 pound bag on Amazon for almost the same price as a 6 ounce bag at other retailers. It's definitely worth it to buy a big bag if your dog eats them a lot.

```
In [17]: # https://stackoverflow.com/a/47091490/4084039
import re

def decontracted(phrase):
    # specific
    phrase = re.sub(r"won't", "will not", phrase)
    phrase = re.sub(r"can't", "can not", phrase)

    # general
    phrase = re.sub(r"n't", " not", phrase)
    phrase = re.sub(r"\ 're", " are", phrase)
    phrase = re.sub(r"\ 's", " is", phrase)
    phrase = re.sub(r"\ 'd", " would", phrase)
    phrase = re.sub(r"\ 'll", " will", phrase)
    phrase = re.sub(r"\ 't", " not", phrase)
    phrase = re.sub(r"\ 've", " have", phrase)
    phrase = re.sub(r"\ 'm", " am", phrase)
    return phrase
```

```
In [18]: sent_1500 = decontracted(sent_1500)
print(sent_1500)
print("="*50)
```

```
was way to hot for my blood, took a bite and did a jig lol
=====
```

```
In [19]: #remove words with numbers python: https://stackoverflow.com/a/18082370/4084039
sent_0 = re.sub("\S*\d\S*", "", sent_0).strip()
print(sent_0)
```

```
My dogs loves this chicken but its a product from China, so we wont be
buying it anymore. Its very hard to find any chicken products made in
```

the USA but they are out there, but this one isnt. Its too bad too because its a good product but I wont take any chances till they know what is going on with the china imports.

```
In [20]: #remove spacial character: https://stackoverflow.com/a/5843547/4084039
sent_1500 = re.sub('[^A-Za-z0-9]+', ' ', sent_1500)
print(sent_1500)
```

was way to hot for my blood took a bite and did a jig lol

```
In [21]: # https://gist.github.com/sebleier/554280
# we are removing the words from the stop words list: 'no', 'nor', 'not'
# <br /><br /> ==> after the above steps, we are getting "br br"
# we are including them into stop words list
# instead of <br /> if we have <br/> these tags would have revmoved in the 1st step

stopwords= set(['br', 'the', 'i', 'me', 'my', 'myself', 'we', 'our', 'ours', 'ourselves', 'you', "you're", "you've", \
               "you'll", "you'd", 'your', 'yours', 'yourself', 'yourselves', 'he', 'him', 'his', 'himself', \
               'she', "she's", 'her', 'hers', 'herself', 'it', "it's", 'its', 'itself', 'they', 'them', 'their', \
               'theirs', 'themselves', 'what', 'which', 'who', 'whom', 'this', 'that', "that'll", 'these', 'those', \
               'am', 'is', 'are', 'was', 'were', 'be', 'been', 'being', 'have', 'has', 'had', 'having', 'do', 'does', \
               'did', 'doing', 'a', 'an', 'the', 'and', 'but', 'if', 'or', 'because', 'as', 'until', 'while', 'of', \
               'at', 'by', 'for', 'with', 'about', 'against', 'between', 'into', 'through', 'during', 'before', 'after', \
               'above', 'below', 'to', 'from', 'up', 'down', 'in', 'out', 'on', 'off', 'over', 'under', 'again', 'further', \
               'then', 'once', 'here', 'there', 'when', 'where', 'why', 'how', 'all', 'any', 'both', 'each', 'few', 'more', \
               'most', 'other', 'some', 'such', 'only', 'own', 'same', 'so', 'than', 'too', 'very', \
               's', 't', 'can', 'will', 'just', 'don', "don't", 'should',
```

```
"should've", 'now', 'd', 'll', 'm', 'o', 're', \
    've', 'y', 'ain', 'aren', "aren't", 'couldn', "couldn't",
'didn', "didn't", 'doesn', "doesn't", 'hadn', \
    "hadn't", 'hasn', "hasn't", 'haven', "haven't", 'isn', "is
n't", 'ma', 'mightn', "mightn't", 'mustn', \
    "mustn't", 'needn', "needn't", 'shan', "shan't", 'shouldn',
"shouldn't", 'wasn', "wasn't", 'weren', "weren't", \
    'won', "won't", 'wouldn', "wouldn't"])
```

```
In [35]: # Combining all the above students
from tqdm import tqdm
preprocessed_reviews = []
# tqdm is for printing the status bar
for sentence in tqdm(final['Text'].values):
    sentence = re.sub(r"http\S+", "", sentence)
    sentence = BeautifulSoup(sentence, 'lxml').get_text()
    sentence = decontracted(sentence)
    sentence = re.sub("\S*\d\S*", "", sentence).strip()
    sentence = re.sub('[^A-Za-z]+', ' ', sentence)
    # https://gist.github.com/sebleier/554280
    sentence = ' '.join(e.lower() for e in sentence.split() if e.lower()
    ) not in stopwords)
    preprocessed_reviews.append(sentence.strip())
```

```
100%|██████████| 87775/87775 [01:04<00:00, 1358.83it/s]
```

```
In [36]: preprocessed_reviews[1500]
```

```
Out[36]: 'way hot blood took bite jig lol'
```

```
In [39]: final['CleanedText'] = preprocessed_reviews
         final.head(5)
```

Out[39]:

Id	ProductId	UserId	ProfileName	HelpfulnessNumerator	HelpfulnessDenominator
----	-----------	--------	-------------	----------------------	------------------------

	Id	ProductId	UserId	ProfileName	HelpfulnessNumerator	HelpfulnessD
22620	24750	2734888454	A13ISQV0U9GZIC	Sandikaye	1	
22621	24751	2734888454	A1C298ITT645B6	Hugh G. Pritchard	0	
70677	76870	B00002N8SM	A19Q006CSFT011	Arielle	0	
70676	76869	B00002N8SM	A1FYH4S02BW7FN	wonderer	0	
70675	76868	B00002N8SM	AUE8TB5VHS6ZV	eyeofthestorm	0	

[3.2] Preprocessing Review Summary

In [0]: `## Similarly you can do preprocessing for review summary also.`

[4] Featurization

[4.1] BAG OF WORDS

```
In [0]: #Bow
count_vect = CountVectorizer() #in scikit-learn
count_vect.fit(preprocessed_reviews)
print("some feature names ", count_vect.get_feature_names()[:10])
print('='*50)

final_counts = count_vect.transform(preprocessed_reviews)
print("the type of count vectorizer ", type(final_counts))
print("the shape of out text BOW vectorizer ", final_counts.get_shape())
print("the number of unique words ", final_counts.get_shape()[1])

some feature names  ['aa', 'aahhs', 'aback', 'abandon', 'abates', 'abb
ott', 'abby', 'abdominal', 'abiding', 'ability']
=====
the type of count vectorizer  <class 'scipy.sparse.csr.csr_matrix'>
the shape of out text BOW vectorizer  (4986, 12997)
the number of unique words  12997
```

[4.2] Bi-Grams and n-Grams.

```
In [0]: #bi-gram, tri-gram and n-gram

#removing stop words like "not" should be avoided before building n-gra
ms
# count_vect = CountVectorizer(ngram_range=(1,2))
# please do read the CountVectorizer documentation http://scikit-learn.org/stable/modules/generated/sklearn.feature\_extraction.text.CountVectorizer.html

# you can choose these numebrs min_df=10, max_features=5000, of your ch
oice
count_vect = CountVectorizer(ngram_range=(1,2), min_df=10, max_features
=5000)
```

```

final_bigram_counts = count_vect.fit_transform(preprocessed_reviews)
print("the type of count vectorizer ",type(final_bigram_counts))
print("the shape of out text BOW vectorizer ",final_bigram_counts.get_shape())
print("the number of unique words including both unigrams and bigrams "
, final_bigram_counts.get_shape()[1])

```

```

the type of count vectorizer <class 'scipy.sparse.csr.csr_matrix'>
the shape of out text BOW vectorizer (4986, 3144)
the number of unique words including both unigrams and bigrams 3144

```

[4.3] TF-IDF

In [0]:

```

tf_idf_vect = TfidfVectorizer(ngram_range=(1,2), min_df=10)
tf_idf_vect.fit(preprocessed_reviews)
print("some sample features(unique words in the corpus)",tf_idf_vect.get_feature_names()[0:10])
print('='*50)

```

```

final_tf_idf = tf_idf_vect.transform(preprocessed_reviews)
print("the type of count vectorizer ",type(final_tf_idf))
print("the shape of out text TFIDF vectorizer ",final_tf_idf.get_shape())
print("the number of unique words including both unigrams and bigrams "
, final_tf_idf.get_shape()[1])

```

```

some sample features(unique words in the corpus) ['ability', 'able', 'able find', 'able get', 'absolute', 'absolutely', 'absolutely delicious', 'absolutely love', 'absolutely no', 'according']

```

```

=====

```

```

the type of count vectorizer <class 'scipy.sparse.csr.csr_matrix'>
the shape of out text TFIDF vectorizer (4986, 3144)
the number of unique words including both unigrams and bigrams 3144

```

[4.4] Word2Vec

```
In [0]: # Train your own Word2Vec model using your own text corpus
i=0
list_of_sentence=[]
for sentence in preprocessed_reviews:
    list_of_sentence.append(sentence.split())
```

```
In [0]: # Using Google News Word2Vectors

# in this project we are using a pretrained model by google
# its 3.3G file, once you load this into your memory
# it occupies ~9Gb, so please do this step only if you have >12G of ram
# we will provide a pickle file wich contains a dict ,
# and it contains all our courpus words as keys and model[word] as values
# To use this code-snippet, download "GoogleNews-vectors-negative300.bin"
# from https://drive.google.com/file/d/0B7XkCwpI5KDYNlNUTTlSS21pQmM/edit
# it's 1.9GB in size.

# http://kavita-ganesan.com/gensim-word2vec-tutorial-starter-code/#.W17SRFAzZPY
# you can comment this whole cell
# or change these variable according to your need

is_your_ram_gt_16g=False
want_to_use_google_w2v = False
want_to_train_w2v = True

if want_to_train_w2v:
    # min_count = 5 considers only words that occurred at least 5 times
    w2v_model=Word2Vec(list_of_sentence,min_count=5,size=50, workers=4)
    print(w2v_model.wv.most_similar('great'))
    print('='*50)
    print(w2v_model.wv.most_similar('worst'))

elif want_to_use_google_w2v and is_your_ram_gt_16g:
    if os.path.isfile('GoogleNews-vectors-negative300.bin'):
```

```
w2v_model=KeyedVectors.load_word2vec_format('GoogleNews-vectors
-negative300.bin', binary=True)
print(w2v_model.wv.most_similar('great'))
print(w2v_model.wv.most_similar('worst'))
else:
print("you don't have gogole's word2vec file, keep want_to_train_w2v = True, to train your own w2v ")
```

```
[('snack', 0.9951335191726685), ('calorie', 0.9946465492248535), ('wonderful', 0.9946032166481018), ('excellent', 0.9944332838058472), ('especially', 0.9941144585609436), ('baked', 0.9940600395202637), ('salted', 0.994047224521637), ('alternative', 0.9937226176261902), ('tasty', 0.9936816692352295), ('healthy', 0.9936649799346924)]
=====
[('varieties', 0.9994194507598877), ('become', 0.9992934465408325), ('popcorn', 0.9992750883102417), ('de', 0.9992610216140747), ('miss', 0.9992451071739197), ('melitta', 0.999218761920929), ('choice', 0.9992102384567261), ('american', 0.9991837739944458), ('beef', 0.9991780519485474), ('finish', 0.9991567134857178)]
```

```
In [0]: w2v_words = list(w2v_model.wv.vocab)
print("number of words that occurred minimum 5 times ", len(w2v_words))
print("sample words ", w2v_words[0:50])
```

```
number of words that occurred minimum 5 times 3817
sample words ['product', 'available', 'course', 'total', 'pretty', 'sticky', 'right', 'nearby', 'used', 'ca', 'not', 'beat', 'great', 'received', 'shipment', 'could', 'hardly', 'wait', 'try', 'love', 'call', 'instead', 'removed', 'easily', 'daughter', 'designed', 'printed', 'use', 'car', 'windows', 'beautifully', 'shop', 'program', 'going', 'lot', 'fun', 'everywhere', 'like', 'tv', 'computer', 'really', 'good', 'idea', 'final', 'outstanding', 'window', 'everybody', 'asks', 'bought', 'made']
```

[4.4.1] Converting text into vectors using Avg W2V, TFIDF-W2V

[4.4.1.1] Avg W2v

```
In [0]: # average Word2Vec
# compute average word2vec for each review.
sent_vectors = []; # the avg-w2v for each sentence/review is stored in
this list
for sent in tqdm(list_of_sentence): # for each review/sentence
    sent_vec = np.zeros(50) # as word vectors are of zero length 50, yo
u might need to change this to 300 if you use google's w2v
    cnt_words = 0; # num of words with a valid vector in the sentence/re
view
    for word in sent: # for each word in a review/sentence
        if word in w2v_words:
            vec = w2v_model.wv[word]
            sent_vec += vec
            cnt_words += 1
    if cnt_words != 0:
        sent_vec /= cnt_words
    sent_vectors.append(sent_vec)
print(len(sent_vectors))
print(len(sent_vectors[0]))
```

```
100%|████████████████████████████████████████████████████████████████████████████████| 4986/4986 [00:03<00:00, 1330.47it/s]
```

```
4986
50
```

[4.4.1.2] TFIDF weighted W2v

```
In [0]: # S = ["abc def pqr", "def def def abc", "pqr pqr def"]
model = TfidfVectorizer()
tf_idf_matrix = model.fit_transform(preprocessed_reviews)
# we are converting a dictionary with word as a key, and the idf as a v
alue
dictionary = dict(zip(model.get_feature_names(), list(model.idf_)))
```

```
100%|██████████| 4986/4986 [00:20<00:00, 245.63it/s]
```

2. The hyper paramter tuning(find best Alpha)

- Find the best hyper parameter which will give the maximum [AUC](#) value
- Consider a wide range of alpha values for hyperparameter tuning, start as low as 0.00001
- Find the best hyper paramter using k-fold cross validation or simple cross validation data
- Use gridsearch cv or randomsearch cv or you can also write your own for loops to do this task of hyperparameter tuning

3. Feature importance


- Find the top 10 features of positive class and top 10 features of negative class for both feature sets [Set 1](#) and [Set 2](#) using values of `feature_log_prob_` parameter of [MultinomialNB](#) and print their corresponding feature names


4. Feature engineering

- To increase the performance of your model, you can also experiment with with feature engineering like :
 - Taking length of reviews as another feature.
 - Considering some features from review summary as well.

5. Representation of results

- You need to plot the performance of model both on train data and cross validation data for each hyper parameter, like shown in the figure. Here on X-axis you will have alpha values, since they have a wide range, just to represent those alpha values on the graph, apply log function on those alpha values.

 Once after you found the best hyper parameter, you need to train your model with it, and find the AUC on test data and plot the ROC curve on both train and test.

 Along with plotting ROC curve, you need to print the [confusion matrix](#) with predicted and original labels of test data points. Please visualize your confusion matrices using [seaborn heatmaps](#).



6. Conclusion

- [You need to summarize the results at the end of the notebook, summarize it in the table format. To print out a table please refer to this prettytable library link](#)



Note: Data Leakage

1. There will be an issue of data-leakage if you vectorize the entire data and then split it into train/cv/test.
2. To avoid the issue of data-leakag, make sure to split your data first and then vectorize it.
3. While vectorizing your data, apply the method fit_transform() on you train data, and apply the method transform() on cv/test data.
4. For more details please go through this [link](#).

Applying Multinomial Naive Bayes

[5.1] Applying Naive Bayes on BOW, SET 1

```
In [0]: # Please write all the code with proper documentation
```

```
In [40]: X = final["CleanedText"]
print("shape of X:", X.shape)
```

shape of X: (87775,)

```
In [41]: y = final["Score"]
print("shape of y:", y.shape)
```

shape of y: (87775,)


```

In [42]: from sklearn.model_selection import train_test_split

# X_train, X_test, y_train, y_test = train_test_split(X, Y, test_size=
0.33, shuffle=False): this is for time series split
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.3
3) # this is random splitting
X_train, X_cv, y_train, y_cv = train_test_split(X_train, y_train, test_
size=0.33) # this is random splitting

print(X_train.shape, y_train.shape)
print(X_cv.shape, y_cv.shape)
print(X_test.shape, y_test.shape)

print("="*100)

from sklearn.feature_extraction.text import CountVectorizer
vectorizer = CountVectorizer()
vectorizer.fit(X_train) # fit has to happen only on train data

# we use the fitted CountVectorizer to convert the text to vector
X_train_bow = vectorizer.transform(X_train)
X_cv_bow = vectorizer.transform(X_cv)
X_test_bow = vectorizer.transform(X_test)

print("After vectorizations")
print(X_train_bow.shape, y_train.shape)
print(X_cv_bow.shape, y_cv.shape)
print(X_test_bow.shape, y_test.shape)
print("="*100)

(39402,) (39402,)
(19407,) (19407,)
(28966,) (28966,)
=====
=====
After vectorizations
(39402, 37005) (39402,)
(19407, 37005) (19407,)


```

```
(28966, 37005) (28966,)
```

```
=====
```

```
In [47]: from sklearn.naive_bayes import MultinomialNB
from sklearn.metrics import roc_auc_score
import matplotlib.pyplot as plt
train_auc = []
cv_auc = []
K = [0.00001, 0.0001, 0.001, 0.01, 0.1, 1, 10]
for i in K :
    MNB = MultinomialNB(alpha = i)
    MNB.fit(X_train_bow, y_train)
    # roc_auc_score(y_true, y_score) the 2nd parameter should be probab
    ility estimates of the positive class
    # not the predicted outputs
    y_train_pred = MNB.predict_proba(X_train_bow)[:,-1]
    y_cv_pred = MNB.predict_proba(X_cv_bow)[:,-1]

    train_auc.append(roc_auc_score(y_train,y_train_pred))
    cv_auc.append(roc_auc_score(y_cv, y_cv_pred))
plt.plot(K, train_auc, label='Train AUC')
plt.plot(K, cv_auc, label='CV AUC')
plt.legend()
plt.xlabel("K: hyperparameter")
plt.ylabel("AUC")
plt.title("ERROR PLOTS")
plt.show()
```



In [48]: `best_alpha=1.75`


In [49]: `from sklearn.metrics import roc_curve, auc`

```
MNB = MultinomialNB(alpha=best_alpha)
MNB.fit(X_train_bow, y_train)
# roc_auc_score(y_true, y_score) the 2nd parameter should be probability
# estimates of the positive class
# not the predicted outputs

train_fpr, train_tpr, thresholds = roc_curve(y_train, MNB.predict_proba(
X_train_bow)[: ,1])
test_fpr, test_tpr, thresholds = roc_curve(y_test, MNB.predict_proba(X_
test_bow)[: ,1])

plt.plot(train_fpr, train_tpr, label="train AUC =" + str(auc(train_fpr, t
rain_tpr)))
plt.plot(test_fpr, test_tpr, label="test AUC =" + str(auc(test_fpr, test_
tpr)))
plt.legend()
```

```
plt.xlabel("K: hyperparameter")
plt.ylabel("AUC")
plt.title("ERROR PLOTS")
plt.show()
```



```
In [50]: bow_features = vectorizer.get_feature_names()
```

```
In [51]: feat_count = MNB.feature_count_  
         feat_count.shape
```

```
Out[51]: (2, 37005)
```

```
In [52]: MNB.class_count_
```

```
Out[52]: array([ 6389., 33013.])
```

```
In [53]: log_prob = MNB.feature_log_prob_  
         log_prob
```

```
Out[53]: array([[ -11.71889178, -12.17087691, -12.17087691, ..., -12.17087691,  
                 -12.17087691, -12.17087691],
```

```
[-12.05502524, -12.78096224, -12.35351823, ..., -12.54457346,  
-13.09111717, -13.09111717]])
```

```
In [54]: feature_prob = pd.DataFrame(log_prob, columns = bow_features)  
feature_prob_tr = feature_prob.T  
feature_prob_tr.shape
```

```
Out[54]: (37005, 2)
```

```
In [55]: print("Top 10 Negative Features:-\n",feature_prob_tr[0].sort_values(asc  
ending = False)[0:10])  
print("\n\n Top 10 Positive Features:-\n",feature_prob_tr[1].sort_value  
s(ascending = False)[0:10])
```

```
Top 10 Negative Features:-
```

```
not      -3.464836  
like     -4.565485  
would    -4.854329  
taste    -4.884000  
product  -4.903351  
one      -5.096276  
good     -5.330636  
coffee  -5.359161  
no       -5.398941  
flavor   -5.441736  
Name: 0, dtype: float64
```


```
Top 10 Positive Features:-
```

```
not      -3.758664  
like     -4.573942  
good     -4.706583  
great    -4.788671  
one      -4.913525  
taste    -5.013783  
coffee  -5.031094  
flavor   -5.102636  
would    -5.107832
```

```
love      -5.129905  
Name: 1, dtype: float64
```

```
In [62]: from sklearn.metrics import confusion_matrix  
import seaborn as sns  
print("Train confusion matrix")  
cm=confusion_matrix(y_train, MNB.predict(X_train_bow))  
class_label = ["negative", "positive"]  
df_cm = pd.DataFrame(cm, index = class_label, columns = class_label)  
sns.heatmap(df_cm, annot = True, fmt = "d")  
plt.title("Confusion Matrix")  
plt.xlabel("Predicted Label")  
plt.ylabel("True Label")  
plt.show()
```


Train confusion matrix



```
In [63]: print("Test confusion matrix")  
cm=confusion_matrix(y_test, MNB.predict(X_test_bow))  
class_label = ["negative", "positive"]  
df_cm = pd.DataFrame(cm, index = class_label, columns = class_label)  
sns.heatmap(df_cm, annot = True, fmt = "d")
```

```
plt.title("Confusiion Matrix")
plt.xlabel("Predicted Label")
plt.ylabel("True Label")
plt.show()
```

Test confusion matrix



[5.1.1] Top 10 important features of positive class from SET 1

```
In [0]: # Please write all the code with proper documentation
```

```
In [64]: X = final["CleanedText"]
print("shape of X:", X.shape)
```

shape of X: (87775,)

```
In [65]: y = final["Score"]
print("shape of y:", y.shape)
```

shape of y: (87775,)

```

In [66]: from sklearn.model_selection import train_test_split

# X_train, X_test, y_train, y_test = train_test_split(X, Y, test_size=
0.33, shuffle=False): this is for time series split
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.3
3) # this is random splitting
X_train, X_cv, y_train, y_cv = train_test_split(X_train, y_train, test_
size=0.33) # this is random splitting

print(X_train.shape, y_train.shape)
print(X_cv.shape, y_cv.shape)
print(X_test.shape, y_test.shape)

print("="*100)

from sklearn.feature_extraction.text import TfidfVectorizer
vectorizer = TfidfVectorizer(ngram_range=(1,2))
vectorizer.fit(X_train) # fit has to happen only on train data

# we use the fitted CountVectorizer to convert the text to vector
X_train_tfidf = vectorizer.transform(X_train)
X_cv_tfidf = vectorizer.transform(X_cv)
X_test_tfidf = vectorizer.transform(X_test)

print("After vectorizations")
print(X_train_tfidf.shape, y_train.shape)
print(X_cv_tfidf.shape, y_cv.shape)
print(X_test_tfidf.shape, y_test.shape)
print("="*100)

(39402,) (39402,)
(19407,) (19407,)
(28966,) (28966,)
=====
=====
After vectorizations
(39402, 774328) (39402,)
(19407, 774328) (19407,)

```



```
(28966, 774328) (28966,)
```


```
=====
```

```
In [70]: from sklearn.naive_bayes import MultinomialNB
from sklearn.metrics import roc_auc_score
import matplotlib.pyplot as plt
train_auc = []
cv_auc = []

K = [0.00001, 0.0001, 0.001, 0.01, 0.1, 1, 10]
for i in K :
    MNB = MultinomialNB(alpha = i)
    MNB.fit(X_train_tfidf, y_train)
    # roc_auc_score(y_true, y_score) the 2nd parameter should be probab
    ility estimates of the positive class
    # not the predicted outputs
    y_train_pred = MNB.predict_proba(X_train_tfidf)[:,-1]
    y_cv_pred = MNB.predict_proba(X_cv_tfidf)[:,-1]

    train_auc.append(roc_auc_score(y_train,y_train_pred))
    cv_auc.append(roc_auc_score(y_cv, y_cv_pred))

plt.plot(K, train_auc, label='Train AUC')
plt.plot(K, cv_auc, label='CV AUC')
plt.legend()
plt.xlabel("K: hyperparameter")
plt.ylabel("AUC")
plt.title("ERROR PLOTS")
plt.show()
```



In [72]: `best_alpha=1`


In [73]: `from sklearn.metrics import roc_curve, auc`

```
MNB = MultinomialNB(alpha =best_alpha)
MNB.fit(X_train_tfidf, y_train)
# roc_auc_score(y_true, y_score) the 2nd parameter should be probability
# estimates of the positive class
# not the predicted outputs

train_fpr, train_tpr, thresholds = roc_curve(y_train, MNB.predict_proba(
X_train_tfidf)[: ,1])
test_fpr, test_tpr, thresholds = roc_curve(y_test, MNB.predict_proba(X_
test_tfidf)[: ,1])

plt.plot(train_fpr, train_tpr, label="train AUC =" +str(auc(train_fpr, t
rain_tpr)))
plt.plot(test_fpr, test_tpr, label="test AUC =" +str(auc(test_fpr, test_
tpr)))
plt.legend()
```

```
plt.xlabel("K: hyperparameter")
plt.ylabel("AUC")
plt.title("ERROR PLOTS")
plt.show()
```



```
In [74]: tfidf_features = vectorizer.get_feature_names()
```

```
In [75]: feat_count = MNB.feature_count_  
         feat_count.shape
```

```
Out[75]: (2, 774328)
```

```
In [76]: MNB.class_count_
```

```
Out[76]: array([ 6369., 33033.]
```

```
In [77]: log_prob = MNB.feature_log_prob_  
         log_prob
```

```
Out[77]: array([[ -13.44331986, -13.62109891, -13.62109891, ..., -13.62109891,  
                 -13.62109891, -13.62109891],
```

```
[-13.20737315, -13.63748125, -13.6956151 , ..., -13.76081361,  
-13.75334593, -13.75334593]])
```

```
In [78]: feature_prob = pd.DataFrame(log_prob, columns = tfidf_features)  
feature_prob_tr = feature_prob.T  
feature_prob_tr.shape
```

```
Out[78]: (774328, 2)
```

```
In [79]: print("Top 10 negative features:-\n",feature_prob_tr[0].sort_values(asc  
ending = False)[0:10])  
print("\n\n Top 10 positive features:-\n",feature_prob_tr[1].sort_value  
s(ascending = False)[0:10])
```

```
Top 10 negative features:-
```

```
not      -8.174450  
like     -8.970659  
taste    -9.091604  
would    -9.106226  
product  -9.108145  
coffee  -9.309711  
one      -9.423601  
flavor   -9.557258  
no       -9.567925  
good     -9.617312  
Name: 0, dtype: float64
```


```
Top 10 positive features:-
```

```
not      -7.335034  
great    -7.676431  
good     -7.744778  
like     -7.778422  
coffee  -7.779309  
love     -7.910020  
tea      -7.910410  
one      -8.028604  
taste    -8.029803
```

```
product    -8.049458  
Name: 1, dtype: float64
```

```
In [80]: from sklearn.metrics import confusion_matrix  
import seaborn as sns  
print("Train confusion matrix")  
cm=confusion_matrix(y_train, MNB.predict(X_train_tfidf))  
class_label = ["negative", "positive"]  
df_cm = pd.DataFrame(cm, index = class_label, columns = class_label)  
sns.heatmap(df_cm, annot = True, fmt = "d")  
plt.title("Confusion Matrix")  
plt.xlabel("Predicted Label")  
plt.ylabel("True Label")  
plt.show()
```


Train confusion matrix



```
In [81]: print("Test confusion matrix")  
cm=confusion_matrix(y_test, MNB.predict(X_test_tfidf))  
class_label = ["negative", "positive"]  
df_cm = pd.DataFrame(cm, index = class_label, columns = class_label)  
sns.heatmap(df_cm, annot = True, fmt = "d")
```

```
plt.title("Confusiion Matrix")
plt.xlabel("Predicted Label")
plt.ylabel("True Label")
plt.show()
```

Test confusion matrix



```
In [82]: models = pd.DataFrame({'vectorizer': ['NaiveBayes with Bow', "NaiveBayes with TFIDF"], 'Model' : ["MultinomialNB", "MultinomialNB"], 'Hyper Parameter(alpha)': [1.75,1], 'AUC': [.88,.78]}, columns = ["vectorizer", "Model", "Hyper Parameter(alpha)", "AUC"])
models
```

Out[82]:

	vectorizer	Model	Hyper Parameter(alpha)	AUC
0	NaiveBayes with Bow	MultinomialNB	1.75	0.88
1	NaiveBayes with TFIDF	MultinomialNB	1.00	0.78

In []:

[5.1.2] Top 10 important features of negative class from SET 1

```
In [0]: # Please write all the code with proper documentation
```

[5.2] Applying Naive Bayes on TFIDF, SET 2

```
In [0]: # Please write all the code with proper documentation
```

[5.2.1] Top 10 important features of positive class from SET 2

```
In [0]: # Please write all the code with proper documentation
```

[5.2.2] Top 10 important features of negative class from SET 2

```
In [0]: # Please write all the code with proper documentation
```

[6] Conclusions

```
In [0]: # Please compare all your models using Prettytable library
```