

Cisco Packet Tracer

File Edit Options View Tools Extensions Window Help

Logical Physical x: 768, y: 22

PC-PT PC0 10.0.0.10 10.0.0.1 2620XM Router0 20.0.0.1 PC-PT PC1 20.0.0.10

PC0

```
Packets: Sent = 4, Received = 3, Lost = 1 (25% loss),
Approximate round trip times in milli-seconds:
  Minimum = 1ms, Maximum = 10ms, Average = 4ms

C:\>ping 10.0.0.1

Pinging 10.0.0.1 with 32 bytes of data:

Reply from 10.0.0.1: bytes=32 time<1ms TTL=255
Reply from 10.0.0.1: bytes=32 time<1ms TTL=255
Reply from 10.0.0.1: bytes=32 time<1ms TTL=255
Reply from 10.0.0.1: bytes=32 time=1ms TTL=255

Ping statistics for 10.0.0.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
      Minimum = 0ms, Maximum = 1ms, Average = 0ms
```

PC1

```
Pinging 10.0.0.10 with 32 bytes of data:

Request timed out.
Request timed out.
Request timed out.
Request timed out.

Ping statistics for 10.0.0.10:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

C:\>
C:\>
C:\>ping 10.0.0.10

Pinging 10.0.0.10 with 32 bytes of data:

Reply from 10.0.0.10: bytes=32 time<1ms TTL=127
Reply from 10.0.0.10: bytes=32 time=1ms TTL=127
Reply from 10.0.0.10: bytes=32 time=2ms TTL=127
Reply from 10.0.0.10: bytes=32 time=1ms TTL=127
```

Router0

```
Router(config-if)#
Router(config-if)#
Router(config-if)#
Router(config-if)#do sh ip route
Codes: C - connected, S - static, I - IGRP, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2, S - EGP
       i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS inter area
       * - candidate default, U - per-user static route, o - ODR
       P - periodic downloaded static route

Gateway of last resort is not set

C    10.0.0.0/8 is directly connected, Ethernet1/0
C    20.0.0.0/8 is directly connected, Ethernet1/1

Router(config-if)#
```

Time: 00:32:14

Copy Paste

ENG IN 07:38 22-08-2026

Cisco Packet Tracer

File Edit Options View Tools Extensions Window Help

Logical Physical x: 782, y: 48

Root 07:04:00

PC-PT PC0 10.0.0.10 10.0.0.1 2620XM Router0 20.0.0.1 20.0.0.10 PC-PT PC1

PC0

Physical Config Desktop Programming Attributes

Command Prompt

```
Cisco Packet Tracer PC Command Line 1.0
C:\>
C:\>
C:\>
C:\>ping 20.0.0.10

Pinging 20.0.0.10 with 32 bytes of data:

Request timed out.
Reply from 20.0.0.10: bytes=32 time=1ms TTL=127
Reply from 20.0.0.10: bytes=32 time=1ms TTL=127
Reply from 20.0.0.10: bytes=32 time=10ms TTL=127

Ping statistics for 20.0.0.10:
    Packets: Sent = 4, Received = 3, Lost = 1 (25% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 1ms, Maximum = 10ms, Average = 4ms

C:\>
```

PC1

Physical Config Desktop Programming Attributes

Command Prompt

```
C:\>
C:\>
C:\>ping 10.0.0.10

Pinging 10.0.0.10 with 32 bytes of data:

Request timed out.
Request timed out.
Request timed out.
Request timed out.

Ping statistics for 10.0.0.10:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

C:\>
C:\>
C:\>ping 10.0.0.10

Pinging 10.0.0.10 with 32 bytes of data:

Reply from 10.0.0.10: bytes=32 time<1ms TTL=127
Reply from 10.0.0.10: bytes=32 time=1ms TTL=127
Reply from 10.0.0.10: bytes=32 time=2ms TTL=127
Reply from 10.0.0.10: bytes=32 time=1ms TTL=127
```

Scenario

New Delete

Toggle PDU List Window

ENG IN 07:20 22-08-2026