Status	Finished
Started	Wednesday, 28 October 2026, 5:06 PM
Completed	Wednesday, 28 October 2026, 5:17 PM
Duration	11 mins 12 secs
Grade	**12.00** out of 15.00 (**80**%)

Question **1**

Correct

Mark 1.00 out of 1.00

What will be printed when the following code executes?

```
a = ("Python Programming")
```

```
print type(a)
```

```
```

a. <class 'str'> ✓

b. <class 'tuple'>

c. str

d. <class 'int'>

Question **2**

Correct

Mark 1.00 out of 1.00

What will the below Python code do?

```
set1={2,3}

set2={3,2}

set3={2,1}

if(set1==set2):

    print("yes")

else:

    print("no")

if(set1==set3):

    print("yes")

else:

    print("no")
```

a. No, No

b. Yes, Yes

c. "==" is not supported for set in Python

d. Yes, No ✓

Question **3**

Correct

Mark 1.00 out of 1.00

What is the output of the following code

```
aSet = {1, 'rec', ('cse', 'ece'), True}
print(aSet)
```

a. {'rec', 1, ('cse', 'ece'),True}

b. {'rec', 1, ('cse', 'ece')} ✓

c. {'rec', True, ('cse', 'ece')}

d. Error

Question **4**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
aTuple = (10, 20, 30, 40, 50, 60, 70, 80)
print(aTuple[2:5], aTuple[:4], aTuple[3:])
```

a. (30, 40, 50) (10, 20, 30, 40)

b. (10, 20, 30, 40) (40, 50, 60, 70, 80)

c. (30, 40, 50) (10, 20, 30, 40) (40, 50, 60, 70, 80) ✓

d. (30, 40, 50)(40, 50, 60, 70, 80)

Question **5**

Correct

Mark 1.00 out of 1.00

Choose the correct option.

a. In Python, a tuple can contain both integers and strings as its elements. ✓

b. In Python, a tuple can contain only strings as its elements.

c. In Python, a tuple can contain only integers as its elements.

d. In Python, a tuple can contain either string or integer but not both at a time.

Question **6**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
set1={0,0,9}

print(set1)
```

a. {0,9} ✓

b. It will throw an error as there are two 0 while creating the set.

c. {0,0,9}

d. {9}

Question **7**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

t = (58, 47, 36, 25, 14, 3)

x = t[2:-1]

print(x)

- a. Error
- b. (3,14,25)
- c. (58,47,36,25)
- d. (36, 25, 14) ✓

Question **8**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
list1=[1,3,4,2]

x=list1.pop(2)

print(set([x]))
```

- a. {4} ✓
- b. {1,3,2}
- c. {1,3,4}
- d. {2}

Question **9**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
set1={2,5,3}

set2={3,1}

set3={}

set3=set1&set2

print(set3)
```

a. {2,5,1}

b. {3} ✓

c. {2,5,3,1}

d. {}

Question **10**

Incorrect

Mark 0.00 out of 1.00

What will set1|set2 do?

```
If set1={"a","b",3}
set2={3,7}
```

a. Elements of set2 will get appended to set1

b. A new set will be created with the unique elements of set1 and set2. ✗

c. A new set will be created with the elements of both set1 and set2

d. Elements of set1 will get appended to set2

Question **11**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

```
t1 = (1,2,3)
t2 = (4,5,6)
x = t1+t2
print(x)
```

- a. (1,2,3,4,5,6) ✓
- b. (1,2,3,3,2,1)
- c. Error
- d. (1,2,3)(4,5,6)

Question **12**

Incorrect

Mark 0.00 out of 1.00

What is printed when the following code is run?

```
tup = ('30', '3', '2', '8')
print(sorted(tup,reverse = True))
```

- a. ['2', '3', '30', '8']
- b. ['2', '3', '8', '30']
- c. ['30', '8', '3', '2'] ✗
- d. ['8', '30', '3', '2']

Question **13**

Incorrect

Mark 0.00 out of 1.00

Which of the following options will produce the same output?

```
t = (15, 83, 21, 49, 60,45,52,85,100)
# options i, ii, iii, or iv
print(t[:-1])
print(t[0:5])
print(t[0:8])
print(t[-7:])
```

- a. iii,iv ✗
- b. i,ii
- c. ii,iv
- d. i,iii

Question **14**

Correct

Mark 1.00 out of 1.00

Which of the following options will not result in an error when performed on tuples in Python where tupl=(5,2,7,0,3)?

a. tupl.sort()

b. tupl1=tupl+tupl ✓

c. tupl.append(2)

d. tupl[1]=2

Question **15**

Correct

Mark 1.00 out of 1.00

Which of the following Python code will create a set?

(i) set1=set((0,9,0))
(ii) set1=set([0,2,9])
(iii) set1={}

a. i,ii ✓

b. ii

c. All of the above

d. iii