RAJALAKSHMI ENGINEERING COLLEGE

Vignesh V 251001300-2025-IT

V2

Started on	Tuesday, 29 September 2026, 11:49 AM
State	Finished
Completed on	Tuesday, 29 September 2026, 11:50 AM
Time taken	32 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given two arrays array_One[] and array_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs(1 element from each) is minimum. That is SUM (A[i] * B[i]) for all i is minimum.

For example:

Input	Result
3 1 2 3 4 5 6	28

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

// Ascending order comparator
int compareAsc(const void *a, const void *b) {
    int val1 = *(const int *)a;
    int val2 = *(const int *)b;
    if (val1 < val2) return -1;
    if (val1 > val2) return 1;
    return 0;
}

// Descending order comparator
int compareDesc(const void *a, const void *b) {
    int val1 = *(const int *)a;
    int val2 = *(const int *)b;
    if (val1 < val2) return 1;
    if (val1 > val2) return -1;
    return 0;
}

int main() {
    int n;
    if (scanf("%d", &n) != 1 || n <= 0) return 0;

    int *A = (int *)malloc(n * sizeof(int));
    int *B = (int *)malloc(n * sizeof(int));

    for (int i = 0; i < n; i++) scanf("%d", &A[i]);
    for (int i = 0; i < n; i++) scanf("%d", &B[i]);

    // Step 1: Sort A in ascending order, B in descending order
    qsort(A, n, sizeof(int), compareAsc);
    qsort(B, n, sizeof(int), compareDesc);

    // Step 2: Compute minimum product sum
    long long minProductSum = 0;
    for (int i = 0; i < n; i++) {
        minProductSum += (long long)A[i] * B[i];
    }

    printf("%lld\n", minProductSum);

    free(A);
    free(B);
    return 0;
}
```

	Input	Expected	Got	
✔	3 1 2 3 4 5 6	28	28	✔
✔	4 7 5 1 2 1 3 4 1	22	22	✔
✔	5 20 10 30 10 40 8 9 4 3 10	590	590	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Vignesh V 251001300-2025-IT

V2

Started on	Tuesday, 29 September 2026, 11:48 AM
State	Finished
Completed on	Tuesday, 29 September 2026, 11:49 AM
Time taken	37 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array of N integer, we have to maximize the sum of arr[i] * i, where i is the index of the element (i = 0, 1, 2, ..., N).Write an algorithm based on Greedy technique with a Complexity O(nlogn).

Input Format:

First line specifies the number of elements-n

The next n lines contain the array elements.

Output Format:

Maximum Array Sum to be printed.

Sample Input:

5

2 5 3 4 0

Sample output:

40

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

// Comparator function for qsort (Ascending Order)
int compareAscending(const void *a, const void *b) {
    int val1 = *(const int *)a;
    int val2 = *(const int *)b;

    if (val1 < val2) return -1;
    if (val1 > val2) return 1;
    return 0;
}

int main() {
    int n;
    if (scanf("%d", &n) != 1 || n <= 0) return 0;

    int *arr = (int *)malloc(n * sizeof(int));
    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }

    // Step 1: Sort array in ascending order -> O(N log N)
    qsort(arr, n, sizeof(int), compareAscending);

    // Step 2: Calculate max sum using long long to prevent integer overflow
    long long maxSum = 0;
    for (int i = 0; i < n; i++) {
        maxSum += (long long)arr[i] * i;
    }

    printf("%lld\n", maxSum);

    free(arr);
    return 0;
}
```

	Input	Expected	Got	
✔	5 2 5 3 4 0	40	40	✔
✔	10 2 2 2 4 4 3 3 5 5 5	191	191	✔
✔	2 45 3	45	45	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Vignesh V 251001300-2025-IT

V2

Started on	Tuesday, 29 September 2026, 11:45 AM
State	Finished
Completed on	Wednesday, 30 September 2026, 11:56 AM
Time taken	1 day
Marks	0.00/1.00
Grade	**0.00** out of 10.00 (**0**%)

Question 1 | Incorrect Mark 0.00 out of 1.00

A person needs to eat burgers. Each burger contains a count of calorie. After eating the burger, the person needs to run a distance to burn out his calories.

If he has eaten i burgers with c calories each, then he has to run at least $3^i * c$ kilometers to burn out the calories. For example, if he ate 3 burgers with the count of calorie in the order: [1, 3, 2], the kilometers he needs to run are $(3^0 * 1) + (3^1 * 3) + (3^2 * 2) = 1 + 9 + 18 = 28$.

But this is not the minimum, so need to try out other orders of consumption and choose the minimum value. Determine the minimum distance he needs to run. Note: He can eat burger in any order and use an efficient sorting algorithm.Apply greedy approach to solve the problem.

Input Format

First Line contains the number of burgers

Second line contains calories of each burger which is n space-separate integers

Output Format

Print: Minimum number of kilometers needed to run to burn out the calories

Sample Input

```
3
5 10 7
```

Sample Output

```
76
```

For example:

Test	Input	Result
Test Case 1	3 1 3 2	18

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

// Comparator function to sort array in descending order
int compareDescending(const void *a, const void *b) {
    int val1 = *(const int *)a;
    int val2 = *(const int *)b;

    if (val1 < val2) return 1;
    if (val1 > val2) return -1;
    return 0;
}

int main() {
    int n;
    if (scanf("%d", &n) != 1 || n <= 0) return 0;

    int *calories = (int *)malloc(n * sizeof(int));
    for (int i = 0; i < n; i++) {
        scanf("%d", &calories[i]);
    }

    // Step 1: Sort calories in descending order (Greedy choice)
    qsort(calories, n, sizeof(int), compareDescending);

    // Step 2: Use 64-bit long long to prevent integer overflow
    long long totalDistance = 0;
    long long powerOf3 = 1; // Represents 3^0
```

```
29
30      for (int i = 0; i < n; i++) {
31          totalDistance += powerOf3 * calories[i];
32          powerOf3 *= 3; // Update to 3^(i+1) iteratively to avoid floating point errors
33      }
34
35      printf("%lld\n", totalDistance);
36
37      free(calories);
38      return 0;
39  }
```

	Test	Input	Expected	Got	
✔	Test Case 1	3 1 3 2	18	18	✔
✔	Test Case 3	3 5 10 7	76	76	✔

Your code failed one or more hidden tests.

Your code must pass all tests to earn any marks. Try again.

Incorrect

Marks for this submission: 0.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Vignesh V 251001300-2025-IT V2

Started on	Tuesday, 29 September 2026, 11:43 AM
State	Finished
Completed on	Tuesday, 29 September 2026, 11:45 AM
Time taken	2 mins 3 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Assume you are an awesome parent and want to give your children some cookies. But, you should give each child at most one cookie.

Each child i has a greed factor g[i], which is the minimum size of a cookie that the child will be content with; and each cookie j has a size s[j]. If s[j] >= g[i], we can assign the cookie j to the child i, and the child i will be content. Your goal is to maximize the number of your content children and output the maximum number.

Example 1:

Input:

3

1 2 3

2

1 1

Output:

1

Explanation: You have 3 children and 2 cookies. The greed factors of 3 children are 1, 2, 3.

And even though you have 2 cookies, since their size is both 1, you could only make the child whose greed factor is 1 content.

You need to output 1.

Constraints:

1 <= g.length <= 3 * 10^4

0 <= s.length <= 3 * 10^4

1 <= g[i], s[j] <= 2^31 - 1

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

void minCoins(int V) {
    int coins[] = {2000, 500, 200, 100, 50, 20, 10, 5, 2, 1};
    int n = sizeof(coins) / sizeof(coins[0]);

    for (int i = 0; i < n; i++) {
        while (V >= coins[i]) {
            V -= coins[i];
            printf("%d ", coins[i]);
        }
    }
    printf("\n");
}

int main() {
    int V;
    if (scanf("%d", &V) == 1) {
        minCoins(V);
    }
    return 0;
}
```

	Input	Expected	Got	
✔	2 1 2 3 1 2 3	2	2	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Vignesh V 251001300-2025-IT V2

Started on	Tuesday, 29 September 2026, 8:15 AM
State	Finished
Completed on	Tuesday, 29 September 2026, 11:41 AM
Time taken	3 hours 25 mins
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Write a program to take value V and we want to make change for V Rs, and we have infinite supply of each of the denominations in Indian currency, i.e., we have infinite supply of { 1, 2, 5, 10, 20, 50, 100, 500, 1000} valued coins/notes, what is the minimum number of coins and/or notes needed to make the change.

Input Format:

Take an integer from stdin.

Output Format:

print the integer which is change of the number.

Example Input :

64

Output:

4

Explanaton:

We need a 50 Rs note and a 10 Rs note and two 2 rupee coins.

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main() {
    int V;
    if (scanf("%d", &V) != 1) return 0;

    int denominations[] = {1000, 500, 100, 50, 20, 10, 5, 2, 1};
    int n = sizeof(denominations) / sizeof(denominations[0]);
    int count = 0;

    for (int i = 0; i < n; i++) {
        if (V >= denominations[i]) {
            count += V / denominations[i];
            V %= denominations[i];
        }
    }

    printf("%d\n", count);
    return 0;
}
```

	Input	Expected	Got	
✔	49	5	5	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course