(https://access.redhat.com/)





How to update a content of deployment overlay in EAP 6

⊘ SOLUTION VERIFIED - Updated June 27 2019 at 9:49 PM - English **▼**()

Environment

• Red Hat JBoss Enterprise Application Platform (EAP) 6.x

Issue

- How do I update a content of deployment overlay in EAP 6
- I'm using deployment overlay (https://access.redhat.com/solutions/383393) and would like to update the specified content. Can I update the specified original content directory?

Resolution

When you want to update the deployment-overlay content, please execute the following CLI to remove the existing config and upload new content:

```
deployment-overlay remove --name=myOverlay --content=/foo/bar.html
deployment-overlay upload --name=myOverlay --content=/foo/bar.html=/tmp/newfile.html --
redeploy-affected
```

Note that the deployment-overlay content configured with deployment overlay is copied and located under \$JBOSS_HOME/standalone/data/content/. For example, the following setting means that the deployment-overlay content is stored as

\$JBOSS_HOME/standalone/data/content/7d/91e92683856d8b018da09975d6cc8320553ccf/content:

So, updating the original file, which you specified in CLI, does not become effective. (And, it means that you can delete the original file after completing cofiguration.).

Product(s)

Red Hat JBoss Enterprise Application Platform (/taxonomy/products/red-hat-jboss-enterprise-application-platform)

Component jbossas (/components/jbossas) Category Learn more (/category/learn-more)

Tags eap (/tags/eap) jboss (/tags/jboss) jboss_eap (/tags/jboss_eap)

This solution is part of Red Hat's fast-track publication program, providing a huge library of solutions that Red Hat engineers have created while supporting our customers. To give you the knowledge you need the instant it becomes available, these articles may be presented in a raw and unedited form.

People who viewed this solution also viewed

Does deployment-overlay command support Wildcards?

Solution - Nov 1, 2016

What is a deployment overlay and how do I use it?

Solution - Oct 5, 2015

Deployment-overlay is not working for an ear file in JBoss EAP 6.

DOIULION - NOV 10, ZUIS



(https://access.redhat.com/)



Comments

All systems operational (https://status.redhat.com)

Privacy Statement (http://www.redhat.com/en/about/privacy-policy)

Customer Portal Terms of Use

(https://access.redhat.com/help/terms/)

All Policies and Guidelines

(http://www.redhat.com/en/about/all-policies-guidelines)

Cookie Preferences

Copyright © 2020 Red Hat, Inc.