



UNIVERSITÀ
DI SIENA
1240

DIPARTIMENTO DI INGEGNERIA DELL'INFORMAZIONE E SCIENZE

MATEMATICHE

Computer and Automation Engineering

ROBOTICS AND AUTOMATION

Handshake human-robot analysis

Professor:

D. Prattichizzo

Student:

Francesco Vigni

A.A. 2017-2018

Contents

1	The state of the Art	4
1.1	4
1.2	4
1.3	4
2	The Idea	5
3	Hardware setup	6
3.1	The Pisa/IIT qbhand	6
3.2	The Sensors	6
3.3	6
3.4	Ros	6

Introduction

The following work wants to explore the phases of the handshake between a human and a robot, reaching a consensus in the human-machine interaction. The handshake event can be divided in two steps: the approaching and handshaking. The consensus is a parameter that allow the human to evaluate a handshake mixing aspects like: duration of the event, dynamics, force exchanged etc.. The handshake is the most common human-human interaction and is extensively used worldwide in events like: greetings, introduction routine between human beings and agreements. This work focuses only on the latter handshake step, with the purpose of evaluating different algorithms. Many research teams focused on the the human-robot physical interaction, providing different solutions.

Chapter 1

The state of the Art

Develop a robot capable of performing a smooth human-like handshake is still a highly interested topic in the scientific literature. The industries are highly interested in robots since they can easily implement repetitive tasks and improve the business reducing failures in final products. [\[3\]](#) [\[1\]](#) [\[4\]](#) The robots are becoming more and more common in our daily lives, [\[2\]](#).

1.1

1.2

1.3

Chapter 2

The Idea

Chapter 3

Hardware setup

3.1 The Pisa/IIT qbhand

3.2 The Sensors

3.3

3.4 Ros

Conclusion

This project applies learning [?] techniques to MNIST handwritten dataset. As we can see in the previous confusion matrix the accuracy of the final work is 97.6%. The overall idea is to train *autoenc1*, *autoenc2* and *softmax1* once per time and to crop the nets in order to have coherent dimension between network interconnections. At the end of [?]this process we stack all the partial neural network together and the deep neural network come to life.

The satisfaction behind this project can be experimented by running the file "MNIST_drawsim.m" which is a matlab function that allows the user to draw a digit and returns the correct digit value 97,6 times over 100.

Bibliography

- [1] E. Knoop, M. Bächer, V. Wall, R. Deimel, O. Brock, and P. Beardsley. Handshakiness: Benchmarking for human-robot hand interactions. In *2017 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 4982–4989, Sept 2017.
- [2] D. Papageorgiou and Z. Doulgeri. A kinematic controller for human-robot handshaking using internal motion adaptation. In *2015 IEEE International Conference on Robotics and Automation (ICRA)*, pages 5622–5627, May 2015.
- [3] M. Y. Tsalamlal, J. C. Martin, M. Ammi, A. Tapus, and M. A. Amorim. Affective handshake with a humanoid robot: How do participants perceive and combine its facial and haptic expressions? In *2015 International Conference on Affective Computing and Intelligent Interaction (ACII)*, pages 334–340, Sept 2015.
- [4] Chao Zhai, Francesco Alderisio, Piotr Słowiński, Krasimira Tsaneva-Atanasova, and Mario Di Bernardo. Design of a virtual player for joint improvisation with humans in the mirror game. 11:e0154361, 04 2016.