Usage Scenario

1. Get the standard spec
2. Implement, using libVig
3. ???
4. VERIFIED

17

Usage Scenario

1. Get the standard spec
2. Implement, using libVig
3. ???
4. VERIFIED

Specification Example

```
from state import flow_emap, int_devices
EXP_TIME = 10 * 1000
EXT_DEVICE = 1

if a_packet_received:
    flow_emap.expire_all(now - EXP_TIME)

h3 = pop_header(tcpudp, on_mismatch=([],[]))
h2 = pop_header(ipv4, on_mismatch=([],[]))
h1 = pop_header(ether, on_mismatch=([],[]))

if received_on_port == EXT_DEVICE:
    internal_flow = FlowIdc(h3.dst_port, h3.src_port, h2.daddr, h2.saddr, h2.npid)
    if flow_emap.has(internal_flow):
        fl_id = flow_emap.get(internal_flow)
        flow_emap.refresh_idx(fl_id, now)
        out_port = vector_get(int_devices, fl_id)
        return ([out_port],[ether(h1, saddr=..., daddr=...), ipv4(h2, cksum=...), tcpudp(h3)])
    else:
        return ([],[])
else:
    internal_flow = FlowIdc(h3.src_port, h3.dst_port, h2.saddr, h2.daddr, h2.npid)
    if flow_emap.has(internal_flow):
        fl_id = flow_emap.get(internal_flow)
        flow_emap.refresh_idx(fl_id, now)
    else:
        if not flow_emap.full():
            fl_id = the_index_allocated
            flow_emap.add(internal_flow, fl_id, now)
            vector_set(int_devices, fl_id, received_on_port)
    return ([EXT_DEVICE],[ether(h1, saddr=..., daddr=...), ipv4(h2, cksum=...), tcpudp(h3)])
```