```
In [1]: import pandas as pd
        import numpy as np
        import matplotlib.pyplot as plt
        import seaborn as sns
        %matplotlib inline
        sns.set_style('whitegrid')
        sns.set_context('poster')
        sns.set_palette('Set2')
```

```
In [2]: df = pd.read_csv('Data_Train.csv')
        df.head()
```

```
Out[2]:
   Airline  Date_of_Journey  Source  Destination  Route  Dep_Time  Arrival_Time  Duration  Total_Stops  Additional_Info  Price
0  IndiGo   24/03/2019       Banglore  New Delhi  BLR → DEL  22:20  01:10 22 Mar  2h 50m  non-stop  No info  3897
1  Air India  1/05/2019      Kolkata  Banglore  CCU → IXR → BBI → BLR  05:50  13:15  7h 25m  2 stops  No info  7662
2  Jet Airways  9/06/2019    Delhi  Cochin  DEL → LKO → BOM → COK  09:25  04:25 10 Jun  19h  2 stops  No info  13882
3  IndiGo  12/05/2019        Kolkata  Banglore  CCU → NAG → BLR  18:05  23:30  5h 25m  1 stop  No info  6218
4  IndiGo  01/03/2019        Banglore  New Delhi  BLR → NAG → DEL  16:50  21:35  4h 45m  1 stop  No info  13302
```

```
In [3]: df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 10683 entries, 0 to 10682
Data columns (total 11 columns):
Airline            10683 non-null object
Date_of_Journey    10683 non-null object
Source             10683 non-null object
Destination        10683 non-null object
Route              10682 non-null object
Dep_Time           10683 non-null object
Arrival_Time       10683 non-null object
Duration           10683 non-null object
Total_Stops        10682 non-null object
Additional_Info    10683 non-null object
Price              10683 non-null int64
dtypes: int64(1), object(10)
memory usage: 918.2+ KB
```

```
In [4]: df.describe()
```

```
Out[4]:
              Price
count  10683.000000
mean    9087.064121
std     4611.359167
min     1759.000000
25%     5277.000000
50%     8372.000000
75%    12373.000000
max    79512.000000
```

```
In [5]: df.describe(include='object')
```

```
Out[5]:
       Airline  Date_of_Journey  Source  Destination  Route  Dep_Time  Arrival_Time  Duration  Total_Stops  Additional_Info
count  10683  10683  10683  10683  10682  10683  10683  10683  10682  10683
unique  12  44  5  6  128  222  1343  368  5  10
top  Jet Airways  18/05/2019  Delhi  Cochin  DEL → BOM → COK  17:30  19:00  2h 50m  1 stop  No info
freq  3849  504  4537  4537  2376  233  423  1196  5625  8345
```

```
In [6]: df.isnull().sum()
```

```
Out[6]:
Airline            0
Date_of_Journey    0
Source             0
Destination        0
Route              1
Dep_Time           0
Arrival_Time       0
Duration           0
Total_Stops        1
Additional_Info    0
Price              0
dtype: int64
```

```
In [7]: df[df['Route'].isnull()]
```

```
Out[7]:
   Airline  Date_of_Journey  Source  Destination  Route  Dep_Time  Arrival_Time  Duration  Total_Stops  Additional_Info  Price
9039  Air India  6/05/2019  Delhi  Cochin  NaN  09:45  09:25 07 May  23h 40m  NaN  No info  7480
```

```
In [8]: df[df['Total_Stops'].isnull()]
```

```
Out[8]:
   Airline  Date_of_Journey  Source  Destination  Route  Dep_Time  Arrival_Time  Duration  Total_Stops  Additional_Info  Price
9039  Air India  6/05/2019  Delhi  Cochin  NaN  09:45  09:25 07 May  23h 40m  NaN  No info  7480
```

```
In [9]: df.dropna(inplace=True)
```

```
In [10]: df.isnull().sum()
```

```
Out[10]:
Airline            0
Date_of_Journey    0
Source             0
Destination        0
Route              0
Dep_Time           0
Arrival_Time       0
Duration           0
Total_Stops        0
Additional_Info    0
Price              0
dtype: int64
```

```
In [11]: df['Journey_day'] = pd.to_datetime(df['Date_of_Journey'], format='%d/%m/%Y').dt.day
         df['Journey_month'] = pd.to_datetime(df['Date_of_Journey'], format='%d/%m/%Y').dt.month
         df.head()
```

```
Out[11]:
   Airline  Date_of_Journey  Source  Destination  Route  Dep_Time  Arrival_Time  Duration  Total_Stops  Additional_Info  Price  Journey_day  Journey_month
0  IndiGo  24/03/2019  Banglore  New Delhi  BLR → DEL  22:20  01:10 22 Mar  2h 50m  non-stop  No info  3897  24  3
1  Air India  1/05/2019  Kolkata  Banglore  CCU → IXR → BBI → BLR  05:50  13:15  7h 25m  2 stops  No info  7662  1  5
2  Jet Airways  9/06/2019  Delhi  Cochin  DEL → LKO → BOM → COK  09:25  04:25 10 Jun  19h  2 stops  No info  13882  9  6
3  IndiGo  12/05/2019  Kolkata  Banglore  CCU → NAG → BLR  18:05  23:30  5h 25m  1 stop  No info  6218  12  5
4  IndiGo  01/03/2019  Banglore  New Delhi  BLR → NAG → DEL  16:50  21:35  4h 45m  1 stop  No info  13302  1  3
```

```
In [12]: df.drop('Date_of_Journey', axis=1, inplace=True)
```

```
In [13]: df['Dep_hour'] = pd.to_datetime(df['Dep_Time']).dt.hour
         df['Dep_min'] = pd.to_datetime(df['Dep_Time']).dt.minute
         df.drop('Dep_Time', axis=1, inplace=True)
         df.head()
```

```
Out[13]:
   Airline  Source  Destination  Route  Arrival_Time  Duration  Total_Stops  Additional_Info  Price  Journey_day  Journey_month  Dep_hour  Dep_min
0  IndiGo  Banglore  New Delhi  BLR → DEL  01:10 22 Mar  2h 50m  non-stop  No info  3897  24  3  22  20
1  Air India  Kolkata  Banglore  CCU → IXR → BBI → BLR  13:15  7h 25m  2 stops  No info  7662  1  5  5  50
2  Jet Airways  Delhi  Cochin  DEL → LKO → BOM → COK  04:25 10 Jun  19h  2 stops  No info  13882  9  6  9  25
3  IndiGo  Kolkata  Banglore  CCU → NAG → BLR  23:30  5h 25m  1 stop  No info  6218  12  5  18  5
4  IndiGo  Banglore  New Delhi  BLR → NAG → DEL  21:35  4h 45m  1 stop  No info  13302  1  3  16  50
```

```
In [14]: df['Arrival_hour'] = pd.to_datetime(df['Arrival_Time']).dt.hour
         df['Arrival_min'] = pd.to_datetime(df['Arrival_Time']).dt.minute
         df.drop('Arrival_Time', axis=1, inplace=True)
         df.head()
```

```
Out[14]:
   Airline  Source  Destination  Route  Duration  Total_Stops  Additional_Info  Price  Journey_day  Journey_month  Dep_hour  Dep_min  Arrival_hour  Arrival_min
0  IndiGo  Banglore  New Delhi  BLR → DEL  2h 50m  non-stop  No info  3897  24  3  22  20  1  10
1  Air India  Kolkata  Banglore  CCU → IXR → BBI → BLR  7h 25m  2 stops  No info  7662  1  5  5  50  13  15
2  Jet Airways  Delhi  Cochin  DEL → LKO → BOM → COK  19h  2 stops  No info  13882  9  6  9  25  4  25
3  IndiGo  Kolkata  Banglore  CCU → NAG → BLR  5h 25m  1 stop  No info  6218  12  5  18  5  23  30
4  IndiGo  Banglore  New Delhi  BLR → NAG → DEL  4h 45m  1 stop  No info  13302  1  3  16  50  21  35
```

```
In [15]: duration = list(df['Duration'])
         for i in range(len(duration)):
             if len(duration[i].split()) != 2:
                 if 'h' in duration[i]:
                     duration[i] = duration[i] + ' 0m'
                 else:
                     duration[i] = '0h ' + duration[i]
         df['Duration'] = duration
         df.head()
```

```
Out[15]:
   Airline  Source  Destination  Route  Duration  Total_Stops  Additional_Info  Price  Journey_day  Journey_month  Dep_hour  Dep_min  Arrival_hour  Arrival_min
0  IndiGo  Banglore  New Delhi  BLR → DEL  2h 50m  non-stop  No info  3897  24  3  22  20  1  10
1  Air India  Kolkata  Banglore  CCU → IXR → BBI → BLR  7h 25m  2 stops  No info  7662  1  5  5  50  13  15
2  Jet Airways  Delhi  Cochin  DEL → LKO → BOM → COK  19h 0m  2 stops  No info  13882  9  6  9  25  4  25
3  IndiGo  Kolkata  Banglore  CCU → NAG → BLR  5h 25m  1 stop  No info  6218  12  5  18  5  23  30
4  IndiGo  Banglore  New Delhi  BLR → NAG → DEL  4h 45m  1 stop  No info  13302  1  3  16  50  21  35
```

```
In [16]: def hour(x):
             return x.split()[0][0:-1]
         def min(x):
             return x.split()[1][0:-1]
         df['Duration_hours'] = df['Duration'].apply(hour)
         df['Duration_mins'] = df['Duration'].apply(min)
         df.drop('Duration', axis=1, inplace=True)
         df.head()
```

```
Out[16]:
   Airline  Source  Destination  Route  Total_Stops  Additional_Info  Price  Journey_day  Journey_month  Dep_hour  Dep_min  Arrival_hour  Arrival_min  Duration_hours  Duration_mins
0  IndiGo  Banglore  New Delhi  BLR → DEL  non-stop  No info  3897  24  3  22  20  1  10  2  50
1  Air India  Kolkata  Banglore  CCU → IXR → BBI → BLR  2 stops  No info  7662  1  5  5  50  13  15  7  25
2  Jet Airways  Delhi  Cochin  DEL → LKO → BOM → COK  2 stops  No info  13882  9  6  9  25  4  25  19  0
3  IndiGo  Kolkata  Banglore  CCU → NAG → BLR  1 stop  No info  6218  12  5  18  5  23  30  5  25
4  IndiGo  Banglore  New Delhi  BLR → NAG → DEL  1 stop  No info  13302  1  3  16  50  21  35  4  45
```

```
In [17]: df['Duration_hours'] = df['Duration_hours'].astype(int)
         df['Duration_mins'] = df['Duration_mins'].astype(int)
         df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
Int64Index: 10682 entries, 0 to 10682
Data columns (total 14 columns):
Airline            10682 non-null object
Source             10682 non-null object
Destination        10682 non-null object
Route              10682 non-null object
Total_Stops        10682 non-null object
Additional_Info    10682 non-null object
Price              10682 non-null int64
Journey_day        10682 non-null int64
Journey_month      10682 non-null int64
Dep_hour           10682 non-null int64
Dep_min            10682 non-null int64
Arrival_hour       10682 non-null int64
Arrival_min        10682 non-null int64
Duration_hours     10682 non-null int32
Duration_mins      10682 non-null int32
dtypes: int32(2), int64(8), object(4)
memory usage: 1.2+ MB
```

```
In [18]: df['Airline'].value_counts()
```

```
Out[18]:
Jet Airways                          3849
IndiGo                               2053
Air India                            1751
Multiple carriers                    1196
SpiceJet                              818
Vistara                               479
Air Asia                              319
GoAir                                 194
Multiple carriers Premium economy      13
Jet Airways Business                    6
Vistara Premium economy                 3
Trujet                                  1
Name: Airline, dtype: int64
```

```
In [19]: sns.catplot(y='Price', x='Airline', data=df.sort_values('Price', ascending=False), kind='boxen', height=6, aspect=3)
```

```
Out[19]: <seaborn.axisgrid.FacetGrid at 0x1a1e1ed0f0>
```



```
In [20]: Airline = df[['Airline']]
         Airline = pd.get_dummies(Airline, drop_first=True)
         Airline.head()
```

```
Out[20]:
   Airline_Air India  Airline_GoAir  Airline_IndiGo  Airline_Jet Airways  Airline_Jet Airways Business  Airline_Multiple carriers  Airline_Multiple carriers Premium economy  Airline_SpiceJet  Airline_Trujet  Airline_Vistara  Airline_Vistara Premium economy
0  0  0  1  0  0  0  0  0  0  0  0
1  1  0  0  0  0  0  0  0  0  0  0
2  0  0  0  1  0  0  0  0  0  0  0
3  0  0  1  0  0  0  0  0  0  0  0
4  0  0  1  0  0  0  0  0  0  0  0
```

```
In [21]: df['Source'].value_counts()
```

```
Out[21]:
Delhi       4536
Kolkata     2871
Banglore    2197
Mumbai       697
Chennai      381
Name: Source, dtype: int64
```

```
In [22]: sns.catplot(y='Price', x='Source', data=df.sort_values('Price', ascending=False), kind='boxen', height=6, aspect=3)
```

```
Out[22]: <seaborn.axisgrid.FacetGrid at 0x1a1e1ed0f0>
```



```
In [23]: Source = df[['Source']]
         Source = pd.get_dummies(Source, drop_first=True)
         Source.head()
```

```
Out[23]:
   Source_Chennai  Source_Delhi  Source_Kolkata  Source_Mumbai
0  0  0  0  0
1  0  0  1  0
2  0  1  0  0
3  0  0  1  0
4  0  0  0  0
```

```
In [24]: df['Destination'].value_counts()
```

```
Out[24]:
Cochin       4536
Banglore     2871
Delhi        1265
New Delhi     932
Hyderabad     697
Kolkata       381
Name: Destination, dtype: int64
```

```
In [25]: Destination = df[['Destination']]
         Destination = pd.get_dummies(Destination, drop_first=True)
         Destination.head()
```

```
Out[25]:
   Destination_Cochin  Destination_Delhi  Destination_Hyderabad  Destination_Kolkata  Destination_New Delhi
0  0  0  0  0  1
1  0  0  0  0  0
2  1  0  0  0  0
3  0  0  0  0  0
4  0  0  0  0  1
```

```
In [26]: df['Route'].value_counts()
```

```
Out[26]:
DEL → BOM → COK             2376
BLR → DEL                   1552
CCU → BOM → BLR              979
CCU → BLR                    724
BOM → HYD                    621
                            ...
BOM → VNS → DEL                1
BOM → UDR → DEL                1
BOM → JDH → DEL                1
BOM → IDR → DEL                1
BLR → BOM → JDH → DEL          1
Name: Route, Length: 128, dtype: int64
```

```
In [27]: df['Total_Stops'].value_counts()
```

```
Out[27]:
1 stop      5625
non-stop    3491
2 stops     1520
3 stops       43
4 stops        3
Name: Total_Stops, dtype: int64
```

```
In [28]: df['Total_Stops'] = df['Total_Stops'].map({'non-stop':0, '1 stop':1, '2 stops':2, '3 stops':3, '4 stops':4})
         df.head()
```

```
Out[28]:
   Airline  Source  Destination  Route  Total_Stops  Additional_Info  Price  Journey_day  Journey_month  Dep_hour  Dep_min  Arrival_hour  Arrival_min  Duration_hours  Duration_mins
0  IndiGo  Banglore  New Delhi  BLR → DEL  0  No info  3897  24  3  22  20  1  10  2  50
1  Air India  Kolkata  Banglore  CCU → IXR → BBI → BLR  2  No info  7662  1  5  5  50  13  15  7  25
2  Jet Airways  Delhi  Cochin  DEL → LKO → BOM → COK  2  No info  13882  9  6  9  25  4  25  19  0
3  IndiGo  Kolkata  Banglore  CCU → NAG → BLR  1  No info  6218  12  5  18  5  23  30  5  25
4  IndiGo  Banglore  New Delhi  BLR → NAG → DEL  1  No info  13302  1  3  16  50  21  35  4  45
```

```
In [29]: df['Additional_Info'].value_counts()
```

```
Out[29]:
No info                         8344
In-flight meal not included     1982
No check-in baggage included     320
1 Long layover                    19
Change airports                    7
Business class                     4
No Info                            3
1 Short layover                    1
Red-eye flight                     1
2 Long layover                     1
Name: Additional_Info, dtype: int64
```

```
In [30]: df['Additional_Info'] = df['Additional_Info'].map({'No info':0, 'In-flight meal not included':1, 'No check-in baggage included':2, '1 Long layover':3, 'Change airports':4, 'Business class':5, 'No Info':6, '1 Short layover':7, 'Red-eye flight':8, '2 Long layover':9})
         df.head()
```

```
Out[30]:
   Airline  Source  Destination  Route  Total_Stops  Additional_Info  Price  Journey_day  Journey_month  Dep_hour  Dep_min  Arrival_hour  Arrival_min  Duration_hours  Duration_mins
0  IndiGo  Banglore  New Delhi  BLR → DEL  0  0  3897  24  3  22  20  1  10  2  50
1  Air India  Kolkata  Banglore  CCU → IXR → BBI → BLR  2  0  7662  1  5  5  50  13  15  7  25
2  Jet Airways  Delhi  Cochin  DEL → LKO → BOM → COK  2  0  13882  9  6  9  25  4  25  19  0
3  IndiGo  Kolkata  Banglore  CCU → NAG → BLR  1  0  6218  12  5  18  5  23  30  5  25
4  IndiGo  Banglore  New Delhi  BLR → NAG → DEL  1  0  13302  1  3  16  50  21  35  4  45
```

```
In [31]: df.drop('Route', axis=1, inplace=True)
```

```
In [32]: df = pd.concat([df, Airline, Source, Destination], axis=1)
         df.head()
```

```
Out[32]:
   Airline  Source  Destination  Total_Stops  Additional_Info  Price  Journey_day  Journey_month  Dep_hour  Dep_min  Arrival_hour  Arrival_min  Duration_hours  Duration_mins  Airline_Air India  Airline_GoAir  Airline_IndiGo  Airline_Jet Airways  Airline_Jet Airways Business  Airline_Multiple carriers  Airline_Multiple carriers Premium economy  Airline_SpiceJet  Airline_Trujet  Airline_Vistara  Airline_Vistara Premium economy  Source_Chennai  Source_Delhi  Source_Kolkata  Source_Mumbai  Destination_Cochin  Destination_Delhi  Destination_Hyderabad  Destination_Kolkata  Destination_New Delhi
0  IndiGo  Banglore  New Delhi  0  0  3897  24  3  22  20  1  10  2  50  0  0  1  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  1
1  Air India  Kolkata  Banglore  2  0  7662  1  5  5  50  13  15  7  25  1  0  0  0  0  0  0  0  0  0  0  0  1  0  0  0  0  0  0
2  Jet Airways  Delhi  Cochin  2  0  13882  9  6  9  25  4  25  19  0  0  0  0  1  0  0  0  0  0  0  0  0  1  0  0  1  0  0  0
3  IndiGo  Kolkata  Banglore  1  0  6218  12  5  18  5  23  30  5  25  0  0  1  0  0  0  0  0  0  0  0  0  1  0  0  0  0  0  0
4  IndiGo  Banglore  New Delhi  1  0  13302  1  3  16  50  21  35  4  45  0  0  1  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  1
```

```
In [33]: df.drop(['Airline', 'Source', 'Destination'], axis=1, inplace=True)
```

```
In [34]: df.head()
```

```
Out[34]:
   Total_Stops  Additional_Info  Price  Journey_day  Journey_month  Dep_hour  Dep_min  Arrival_hour  Arrival_min  Duration_hours  Duration_mins  Airline_Air India  Airline_GoAir  Airline_IndiGo  Airline_Jet Airways  Airline_Jet Airways Business  Airline_Multiple carriers  Airline_Multiple carriers Premium economy  Airline_SpiceJet  Airline_Trujet  Airline_Vistara  Airline_Vistara Premium economy  Source_Chennai  Source_Delhi  Source_Kolkata  Source_Mumbai  Destination_Cochin  Destination_Delhi  Destination_Hyderabad  Destination_Kolkata  Destination_New Delhi
0  0  0  3897  24  3  22  20  1  10  2  50  0  0  1  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  1
1  2  0  7662  1  5  5  50  13  15  7  25  1  0  0  0  0  0  0  0  0  0  0  0  1  0  0  0  0  0  0
2  2  0  13882  9  6  9  25  4  25  19  0  0  0  0  1  0  0  0  0  0  0  0  0  1  0  0  1  0  0  0
3  1  0  6218  12  5  18  5  23  30  5  25  0  0  1  0  0  0  0  0  0  0  0  0  1  0  0  0  0  0  0
4  1  0  13302  1  3  16  50  21  35  4  45  0  0  1  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  1
```

```
In [35]: plt.figure(figsize=(30,30))
         sns.heatmap(df.corr(), annot=True, cmap='RdYlGn')
```

```
Out[35]: <matplotlib.axes._subplots.AxesSubplot at 0x1a1e1ed0f0>
```



```
In [36]: from sklearn.ensemble import ExtraTreesRegressor
         selection = ExtraTreesRegressor()
         selection.fit(df.drop('Price', axis=1), df['Price'])
```

```
Out[36]:
ExtraTreesRegressor(bootstrap=False, criterion='mse', max_depth=None,
                    max_features='auto', max_leaf_nodes=None,
                    min_impurity_decrease=0.0, min_impurity_split=None,
                    min_samples_leaf=1, min_samples_split=2,
                    min_weight_fraction_leaf=0.0, n_estimators=10, n_jobs=None,
                    oob_score=False, random_state=None, verbose=0, warm_start=False)
```

```
In [37]: plt.figure(figsize=(12,8))
         feat_importances = pd.Series(selection.feature_importances_, index=df.drop('Price', axis=1).columns)
         feat_importances.nlargest(20).plot(kind='barh')
```

```
Out[37]: <matplotlib.axes._subplots.AxesSubplot at 0x1a1e1ed0f0>
```



```
In [38]: from sklearn.model_selection import train_test_split
         X = df.drop('Price', axis=1)
         y = df['Price']
         X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=42)
```

```
In [39]: from sklearn.metrics import r2_score
```

```
In [40]: from sklearn.ensemble import RandomForestRegressor
         rf = RandomForestRegressor()
         rf.fit(X_train, y_train)
```

```
Out[40]:
RandomForestRegressor(bootstrap=True, criterion='mse', max_depth=None,
                      max_features='auto', max_leaf_nodes=None,
                      min_impurity_decrease=0.0, min_impurity_split=None,
                      min_samples_leaf=1, min_samples_split=2,
                      min_weight_fraction_leaf=0.0, n_estimators=10, n_jobs=None,
                      oob_score=False, random_state=None, verbose=0, warm_start=False)
```

```
In [41]: y_pred = rf.predict(X_test)
```

```
In [42]: r2_score(y_test, y_pred)
```

```
Out[42]: 0.7988420116668173
```

```
In [43]: from sklearn.model_selection import RandomizedSearchCV
```

```
In [44]: n_estimators = [int(x) for x in np.linspace(start=100, stop=1200, num=12)]
         max_features = ['auto', 'sqrt']
         max_depth = [int(x) for x in np.linspace(5, 30, num=6)]
         min_samples_split = [2, 5, 10, 15, 100]
         min_samples_leaf = [1, 2, 5, 10]
```

```
In [45]: random_grid = {'n_estimators': n_estimators,
                        'max_features': max_features,
                        'max_depth': max_depth,
                        'min_samples_split': min_samples_split,
                        'min_samples_leaf': min_samples_leaf}
```

```
In [46]: rf = RandomForestRegressor()
```

```
In [47]: rf_random = RandomizedSearchCV(estimator=rf, param_distributions=random_grid, scoring='neg_mean_squared_error', n_iter=10, cv=5, verbose=2, random_state=42, n_jobs=1)
```

```
In [48]: rf_random.fit(X_train, y_train)
```

```
Fitting 5 folds for each of 10 candidates, totalling 50 fits
[CV] n_estimators=900, min_samples_split=5, min_samples_leaf=5, max_features=sqrt, max_depth=10 
[CV]  n_estimators=900, min_samples_split=5, min_samples_leaf=5, max_features=sqrt, max_depth=10, total=  11.1s
```