

Getting Started with Git and GitHub

Module 2 Cheat Sheet: Git Commands and Managing GitHub Projects

Package/Method	Description
git add	Used to move changes from the working directory to the staging area
git add .	Allows to move the changed files into the staging area on GitHub repositories
git am	Used to apply patches emailed to the repository
git branch	Allows to create an isolated environment within the repository to make changes
git checkout	Allows to see and change existing branches
git checkout main	Allows to switch to the main branch
git clone	Allows to create a copy of the remote repository
git commit	Allows you to take staged snapshots if changes and commit them to the project
git config --global user.email	Example 1: Sets a global email configuration for Git
	Example 2: Sets a global username configuration for Git
git daemon	Used to allow anonymous download from the repository

Code Example

```
1. 1
1. git add sample.md
```

Copied!

```
1. 1
1. git add .
```

Copied!

```
1. 1
1. git am < patchfile.patch
```

Copied!

```
1. 1
1. git branch <new-branch>
```

Copied!

```
1. 1
1. git checkout <existing-branch>
```

Copied!

```
1. 1
1. git checkout main
```

Copied!

```
1. 1
1. git clone <repository-url>
```

Copied!

```
1. 1
1. git commit -m "Your commit message here"
```

Copied!

Example 1:

```
1. 1
1. git config --global user.email "your.email@example.com"
```

Copied!

Example 2:

```
1. 1
1. git config --global user.name "Your Name"
```

Copied!

```
1. 1
```

Package/Method	Description	Code Example
		<pre>1. git daemon --reuseaddr --verbose</pre> <div>Copied!</div>
git diff	Helps others to review your code to identify and compare the changes	<pre>1. 1 1. git diff example.txt</pre> <div>Copied!</div>
git fetch	Used to transfer the changes from the remote repo to your local repo	<pre>1. 1 1. git fetch <options> <remote name> <branch name></pre> <div>Copied!</div>
git fetch upstream/master	Used to grab upstream branches	<pre>1. 1 1. git fetch upstream master:upstream-master</pre> <div>Copied!</div>
git format-patch	Generates or prepares e-mail submission if you adopt Linux kernel-style public forum workflow	<pre>1. 1 1. git format-patch -n <number_of_commits></pre> <div>Copied!</div>
git http-backend	Provides a server-side implementation of Git-over-HTTP, allowing both fetch and push services	<pre>1. 1 2. 2 3. 3 1. git clone --bare /path/to/repos/myrepo.git 2. cd myrepo.git 3. git update-server-info</pre> <div>Copied!</div>
git init	Used to clone an existing repository	<pre>1. 1 1. git init <directory></pre> <div>Copied!</div>
git instaweb	Allows to set up web front-end to Git repositories	<pre>1. 1 1. git instaweb -p 8080</pre> <div>Copied!</div>
git log	Enables to browse previous changes to a project	<pre>1. 1 1. git log -p filename</pre> <div>Copied!</div>
git merge	Used to merge changes in the active branch into another branch	<pre>1. 1 1. git merge feature_branch</pre> <div>Copied!</div>
git merge upstream/master	Merges changes from the 'upstream/master' branch to the current branch	<pre>1. 1 1. git merge upstream/master</pre> <div>Copied!</div>
git pull	Used to transfer the changes from the remote repo to your local repo, and merge them to a branch	<pre>1. 1 1. git pull origin main</pre> <div>Copied!</div>
git pull downstream	Pulls changes from a downstream repository, specifically from the master branch of that repository	<pre>1. 1 1. git pull downstream main</pre>

Package/Method	Description	Code Example
git pull upstream	Pulls changes from the "upstream" repository into the current branch	<div>Copied!</div> <pre>1. 1 1. git pull upstream main</pre>
git push	Used to push all the committed changes into the repository	<div>Copied!</div> <pre>1. 1 1. git push origin your_branch_name</pre>
git remote	A command to manage a set of tracked repositories	<div>Copied!</div> <pre>1. 1 1. git remote add upstream https://github.com/original/repo.git</pre>
git remote add origin <URL>	Adds a remote repository named "origin" with the specified URL	<div>Copied!</div> <pre>1. 1 1. git remote add origin https://github.com/yourusername/your-repo.git</pre>
git remote add upstream	Adds the original repository as a new remote repository labeled upstream	<div>Copied!</div> <pre>1. 1 1. git remote add upstream https://github.com/original/repo.git</pre>
git remote rename	The git remote rename command is followed by the name of the remote repository(origin) you want to rename and the new name(upstream) you want to give it	<div>Copied!</div> <pre>1. 1 1. git remote rename origin new-origin</pre>
git remote -v	Allows to view the remotes associated with the local repository	<div>Copied!</div> <pre>1. 1 1. git remote -v</pre> <p>Example 1:</p> <pre>1. 1 1. git request-pull origin/main your-branch</pre>
git request-pull	<p>Example 1: Creates a summary of changes for your upstream to pull</p> <p>Example 2: Generates a summary of pending changes for an email request</p>	<div>Copied!</div> <p>Example 2:</p> <pre>1. 1 1. git request-pull <base> <head> <repository></pre>
git rerere	Reuses recorded resolution of previously resolved merge conflicts	<div>Copied!</div> <pre>1. 1 2. 2 1. git rerere 2. git rerere diff</pre>
git reset	Undoes changes that were made to the files in your working directory	<div>Copied!</div> <pre>1. 1 1. git reset HEAD~1</pre>

Package/Method	Description	Code Example
git revert	Used to undo botched commits	<div>Copied!</div> <pre>1. 1 1. git revert HEAD</pre>
		<div>Copied!</div> <p>Example 1:</p> <pre>1. 1 2. 2 1. git send-email --to=recipient@example.com 2. path/to/patchfile.patch</pre>
git send-email	Example 1: Sends your email submission without corruption by your MUA	<div>Copied!</div>
	Example 2: Sends a collection of patches as emails	<p>Example 2:</p> <pre>1. 1 2. 2 1. git send-email --to recipient@example.com 2. patches/*.patch</pre>
git-shell	Used as a restricted login shell for shared central repository users	<div>Copied!</div> <pre>1. 1 1. sudo usermod -s /usr/bin/git-shell gituser</pre>
		<div>Copied!</div> <pre>1. 1 1. git status</pre>
git status	Allows to see the state of your working directory and the staged snapshot of the changes	<div>Copied!</div>
git version	Displays the current Git version installed on your system	<pre>1. 1 1. git --version</pre>
		<div>Copied!</div>
git web	Provides a web front-end to Git repositories	<pre>1. 1 1. git instaweb --port=8080</pre>
		<div>Copied!</div>



Skills Network