

Get your Zapier MCP URL

Sign up or log in at <https://zapier.com/mcp> and generate your **unique** MCP endpoint (it'll look like

`https://actions.zapier.com/mcp/<your-unique-id>/sse`

In the Zapier UI, scope which actions (tools) you want to expose—e.g. “send_email”, “create_event”, “search_email”

Install the MCP Python SDK

```
pip install mcp
```

Access the service by using the MCP Client APIs, via the MCP Server

Use following as a reference:

```
import asyncio

from mcp import ClientSession

from mcp.client.sse import sse_client

async def main():

    # Your Zapier MCP SSE endpoint (from zapier.com/mcp)

    mcp_url = "https://actions.zapier.com/mcp/<your-unique-id>/sse"


    # Connect to the MCP server over SSE

    streams_ctx = sse_client(url=mcp_url)

    streams = await streams_ctx.__aenter__()


    # Open an MCP session

    session_ctx = ClientSession(*streams)

    session = await session_ctx.__aenter__()

    await session.initialize()


    # List available tools

    tool_list = (await session.list_tools()).tools

    print("Available tools:", [t.name for t in tool_list])
```

```
# Call a tool (e.g. send_email) if it's enabled
if "send_email" in [t.name for t in tool_list]:
    response = await session.call_tool(
        "send_email",
        {
            "to": "alice@example.com",
            "subject": "Hello from MCP!",
            "body": "This email was sent via the Zapier MCP Server."
        }
    )
    print("send_email result:", response)

# Clean up
await session_ctx.__aexit__(None, None, None)
await streams_ctx.__aexit__(None, None, None)
asyncio.run(main())
```