

```
#include<stdio.h>
int main()
{
char i=010101;
printf("%x\n",i);
}
```

```
int counter(int i)
{ static int count=0;
  count=count+i;
  return(count); }

main()
{ int i,j;
  for(i=0;i<=5;i++)
  j=counter(i);
  printf("%d",j);
}
```

```
#include<stdio.h>
int main(){
    union u{
        int i;
        char c:4;
    }v={02345};
    union u *RCB=&v;
    printf("%d \n",v.c );
}
```

```
#define big(a,b) a > b ? a : b
#define swap(a,b) temp=a; a=b; b=temp;
void main()
{
    int a=3,b=5,temp=0;
    if ((3+big(a,b)) > b)
        swap(a,b);
    printf("%d %d",a,b);
}
```

```
#include<stdio.h>
int main()
{
    char RCB[21]="abcdefgh";
    short int *ptr=RCB;
    printf("%x %x",ptr[0],ptr[1]);
    return 0;
}
```

```
#define SQR(x) x*x
main()
{
    int a, b=3;
    a=SQR(b+2);
    printf("%d", a);
}
```

```
#include<stdio.h>
int cap(int);
int main()
{
    int n;
    n= cap(7);
    printf("%d \n",n);
    return 0;
}
int cap(int n)
{
    if(n<=1)
        return 1;
    else
        return(cap(n-4)+cap(n-2));
}
```

```
#include <stdio.h>
int main() {
    short int d = 499;
    unsigned char k=d;
    printf("%d \n", (char)k);
    return 0;
}
```



```
int main()
{
    char ch=-220;
    printf("%d\n",ch);
}
```

```
#include<stdio.h> main() { int arr[2][3][2]={{{2,4},{7,8},{3,4}},  
{{2,2},{2,3},{3,4}}}; printf("%d \n",**(*arr+2)+0+2); }
```

```
#include <stdio.h>
int main() {
    char f = 'f';
    printf("%x\n", f);
    return 0;
}
```

```
int main()
{
int a[5]={1,2,3,4,5};
char *p=a;
p=p+2;
printf("%d\n",*p);
}
```

```
int main()
{double *d=10;
printf("%d\n",d+3);}
```

When an enumerated value is passed through a function its formal parameter type should be _____.

```
#include<stdio.h>
int main()
{
    static int IPS=5;
    if(--IPS){
        main();
        printf("%d \n",IPS);
    }
    return 0;
}
```

```
main()
{
    struct bitfield
    {
        unsigned a:5;
        unsigned c:5;
        unsigned b:6;

    }bit;
    char *p;
    struct bitfield *ptr,bit1={1,3,3};
    p=&bit1;
    p++;
    printf("%d",*p);

}
```



```
int main()
```

```
{
```

```
    printf("hydvector\b\rblr\n");
```

```
}
```

```
#include<stdio.h>
int main(){
    static int k=0x1f;
    if(--k>27){
        main();
        printf("%d \n",k);
    }
    return 0;
}
```

```
#define int char
```

```
{  
    printf("%d  
",sizeof(i));  
}
```

```
main()
```

```
int i=65;
```

```
#include<stdio.h>
int main(){
    int k=04;
    char *p=&k;
    *++p=04;
    printf("%d\n",k);
    return 0;
}
```

The function used to position the file pointer in C is

```
#include<stdio.h>
int main()
{
    char *string="*vector*";
    printf("%ld\n",sizeof(*string));
    printf("%ld\n",sizeof(string[1]));
    return 0;
}
```

```
#include<stdio.h>
int main()
{
    extern char love;
    love=20;
    printf("%ld \n",sizeof(love));
    return 0;
}
```

```
#include<stdio.h>
int main(){
    int a[3]={11,22,33};
    int b[4]={2,4,6,8};
    int *p[2]={a,b};
    printf("%d \n",**++p);
    return 0;
}
```



```
#include<stdio.h>
int main(){
    int a[3]={11,22,33};
    int b[4]={2,4,6,8};
    int *p[2]={a,b};
    printf("%d \n",**++p);
    return 0;
}
```

```
#include <stdio.h>
int main() {
    int d = 3456 ,r=100 ;
    int k=d/r, p=d%10;
    printf("%d \n", k+p*r);
    return 0;
}
```

```
#include<stdio.h> main() { int i = 65; char ch = 'B'; switch(ch, i) {  
case 65: printf("Placement \n"); break; case 'B': printf("MNC  
company \n"); break; default: printf("Bye"); } }
```

```
#include <stdio.h>
int *m()
{
    int *p = 2000;
    return p;
}
int main()
{
    int *k = m();
    printf("%d \n", k);
    return 0;
}
```

```
#include<stdio.h>
int main(){
if(sizeof(double)> -1)
printf("CSK \n");
else
printf("RCB \n");
}
```

```
#include<stdio.h>
int main()
{
    unsigned char ch=-111;
    printf("%d\n",ch);
}
```

```
enum {false,true};
```

```
main()
{
    int i=1;
    do
    {
        printf("%d",i);
        i++;
        if(i < 15)
            continue;
    }while(false);
}
```

```
main(){  
    int a=5;  
    static int i=a+5;  
    printf("%d",i);  
}
```



```
#include <stdio.h>
int main() {
    int d = 2020 ,r=22 ;
    printf("%d \n", d/r);
    return 0;
}
```

```
#include<stdio.h>
int main(){
    int i=11,j=22,k=33;
    int *p[3]={&i ,&k ,&j};
    printf("%d \n",p[1][0]***p);
    return 0;
}
```

```
#include<stdio.h>
int main(){
    int a[3]={11,22,33};
    int b[4]={2,4,6,8};
    int *p[2]={a,b};
    printf("%d \n",*++*p+*b);
    return 0;
}
```

Which keyword make execution faster ?

```
#include<stdio.h>
```

```
int main(){
```

```
    char *p[3]={"cds","coding","sirji"};
```

```
    printf("%c \n",**p++);
```

```
    return 0;
```

```
}
```

```
main()
{
    union {
        struct {
            char c[2];
            char ch[2];
        }s;
        struct {
            short int i;
            short int j;
        }st;
    }u={ 12,1, 15,1};
    printf("%d %d",u.st.i, u.st.j);
}
```

```
int main()
{
    int i=2;
    do
    {
        printf("a");
    }while(i--);
}
```