

[OPERATOR]

1.

```
int main(){
int a=11,b=4,c;
c= b%a;
printf("%d \n",c);
}
```

2.

```
int main(){
int a=21,b=7,c;
c= b%a/3;
printf("%d \n",c);
}
```

3.

```
int main(){
int a=19,b=7,c;
c= -a+b;
printf("%d \n",c);
}
```

4.

```
int main(){
int a=37,b=7,c;
c= a%10*10;
printf("%d \n",c);
}
```

5.

```
int main(){
int a=-17,b=7,c;
c= a > -b;
printf("%d \n",c);
}
```

6.

```
int main(){
int a=17,b=77,c;
c= a>-b;
printf("%d \n",c);
}
```

7.

```
int main(){
int a=27,b=7,c;
c= -a>=b;
printf("%d \n",c);
}
```

8.
int main(){
int a=17,b=87,c;
c= 7%(-a>=b);
printf("%d \n",c);
}

9.
int main(){
int a=77,b=7,c;
c= a%(b-7);
printf("%d \n",c);
}

10.
int main(){
int a=-28,b=-7,c;
c= a%(b-7);
printf("%d \n",c);
}

11.
int main(){
int a=-1,b=7,c;
c= (a-b)*10;

printf("%d \n",c);
}

12.
int main(){
int a=17,b=7,c;
c= b<a/a+b;
printf("%d \n",c);
}

13.
int main(){
float a=9,b=56,c;
c= a%b+10;
printf("%f \n",c);
}

14.
int main(){
float a=05,b=7,c;
c= 35/10;
printf("%f \n",c);
}

```
15
int main(){
float a=17,b=7,c;
c= 'A'/10;
printf("%.3f \n",c);
}
```

```
16.
int main(){
float a=17,b=10,c;
c= 'a'/b;
printf("%.2f \n",c);
}
```

```
17.
int main(){
double a=17,b=10,c;
c= 'b'/b;
printf("%.1f \n",c);
}
```

```
18.
int main(){
double a=17,b=10,c;
c= 'b'% b;
```

```
printf("%.1f \n",c);
}
```

```
19.
int main(){
int a=0,b=20,c;
c= a||(b=0);
printf("%d %d\n",c,b);
}
```

```
20.
int main(){
int a=0,b=30,c;
c= (a==0)||(b=0);
printf("%d %d\n",c,b);
}
```

```
21.
int main(){
int a=00,b=40,c;
c= (a==0)&&(b=0);
printf("%d %d\n",c,b);
}
```

22.

```
int main(){
int a=0,b=70,c=40,d;
d= (a==0)&&(b=0)||(c=5);
printf("%d %d %d\n",b,c,d);
}
```

23.

```
int main(){
int a=0,b='A',c='4',d;
d= (a==0)&&(b=2)||(c=5);
printf("%d %d %d\n",b,c,d);
}
```

24.

```
int main(){
int a='A';
!a;
printf("%d \n",a);
}
```

25.

```
int main(){
int a=0,b=010,c=49,d;
```

```
d= (a==0)||(b=2)||(c=5);
printf("%d %d %d\n",b,c,d);
}
```

26.

```
int main(){
int a=0,b=020,c=-1,d;
d= (a==0)||(b=2)&&(c=5);
printf("%d %d %d\n",b,c,d);
}
```

27.

```
int main(){
int a=1,b=90,c=4,d;
d= (a==0)&&(b=2)&&(c=5);
printf("%d %d %d\n",b,c,d);
}
```

28.

```
int main(){
int vector=1=2;
printf("%d \n",vector);
}
```

29.

```
int main(){  
int  coding='2'+3;  
printf("%x\n",coding);  
}
```

30.

```
int main(){  
int  sirji=0x55;  
sirji= 0xAA+sirji;  
printf("%d\n",sirji);  
}
```

31.

```
int main(){  
int  pawan=0x1FF;  
pawan = 0x1AA+0777;  
printf("%d\n",pawan);  
printf("%x\n",pawan);  
printf("%o\n",pawan);  
}
```

-----\$ Pawan KY